Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Examples: Using the API with Tenants

You can use the Stellar Cyber API to perform the following tasks for tenants:

- Create a new tenant
- Delete an existing tenant
- Update an existing tenant's settings
- List all tenants
- Retrieve a tenant's information using its tenant ID

Refer to **Configuring API Authentication** for general requirements to use the API.

Tenants API Syntax

The tenants API is available at the following location:

`https://<DP url>/connect/api/v1/tenants`

The table below lists the available methods for the tenants API, along with the corresponding syntax. Following the table, separate sections provide the schema for each method along with a corresponding example.

Task	Method	Syntax
Get All Tenants	GET	/tenants
Get a Specific Tenant	GET	/tenants/{id}
Delete a Specific Tenant	DELETE	/tenants/{id}
Create a Tenant	POST	/tenants/
Update a Tenant's Configuration	PATCH	/tenants/{id}

Get All Tenants

The following example uses cURL with basic authentication to query for all tenants with a GET command using the following details:

- **Username:API Key** – ohtani:N-YrP02Xl6yHO-1HW1gi1nems2g319Q3wLNpOAxWx9_ttbMw3pyB5qPvSVl3qt9CmgvOhHhtDCuEs5KcIn6mWw
- **Stellar Cyber DP IP Address** –192.168.11.11

```
curl -k -u ohtani:N-YrP02Xl6yHO-1HW1gi1nems2g319Q3wLNpOAxWx9_ttbMw3pyB5qPvSVl3qt9CmgvOhHhtDCuEs5KcIn6mWw -i -H "Accept: application/json" -H "Content-Type: application/json" -X GET https://192.168.11.11/connect/api/v1/tenants
```

Values in bold are the values you must supply as part of a similar query.

Get a Specific Tenant

The following example uses cURL to query for a specific tenant with a GET command using the following details:

- **Username:API Key** – ohtani:N-YrP02Xl6yHO-1HW1gi1nems2g319Q3wLNpOAxWx9_ttbMw3pyB5qPvSVl3qt9CmgvOhHhtDCuEs5KcIn6mWw
- **Stellar Cyber DP IP Address** –192.168.11.11
- **Tenant ID** – e4241ed4714c43df93bce83e847dfa0e

> You can find the tenant ID in **System | ORGANIZATION MANAGEMENT | Tenants**. Select the in the **ID** column and use the **Copy to Clipboard** command in the context menu that appears to copy the Tenant ID.

```
curl -k -u ohtani:N-YrP02Xl6yHO-1HW1gi1nems2g319Q3wLNpOAxWx9_ttbMw3pyB5qPvSVl3qt9CmgvOhHhtDCuEs5KcIn6mWw -i -H "Accept: application/json" -H "Content-Type: application/json" -X GET https://192.168.11.11/connect/api/v1/tenants/e4241ed4714c43df93bce83e847dfa0e
```

In response, the API returns configuration details for the specified tenant, similar to the following:

```
{"data":
{"address":"","authentication_method":"system_default","contact":"","contact_email":"","contact_phone":"","cust_id":"f257fe53576a4dada621fcac940a9fb5","cust_name":"docs","ds_num":0,"info":"{}","ingestion_limit":"","mfa_enabled":false,"org_id":"default-organization","retention_group":"default","tgrp_name":"","ts_created":"1682412066","user_num":0}}
```

The `"field":"value"` pairs returned by the API are same options you set when creating a tenant manually in **System | ORGANIZATION MANAGEMENT | Tenants** and are described in the schema in **Create a Tenant**.

Delete a Specific Tenant

The following example uses cURL to delete a specific tenant with a DELETE command using the following details:

- **Username:API Key** – ohtani:N-YrP02Xl6yHO-1HW1gi1nems2g319Q3wLNpOAxWx9_ttbMw3pyB5qPvSVl3qt9CmgvOhHhtDCuEs5KcIn6mWw
- **Stellar Cyber DP IP Address** –192.168.11.11
- **Tenant ID** – 55e521cdc5be4374bd42df5cdae628e1

> You can find the tenant ID in **System | ORGANIZATION MANAGEMENT | Tenants**. Select the in the **ID** column and use the **Copy to Clipboard** command in the context menu that appears to copy the Tenant ID.

```
curl -k -u ohtani:N-YrP02Xl6yHO-1HW1gi1nems2g319Q3wLNpOAxWx9_ttbMw3pyB5qPvSVl3qt9CmgvOhHhtDCuEs5KcIn6mWw -i -H "Accept: application/json" -H "Content-Type: application/json" -X DELETE 'https://192.168.11.11/connect/api/v1/tenants/55e521cdc5be4374bd42df5cdae628e1'
```

In response, the API returns a success or failure message. Success messages appear as follows:

```
{"data":"Ok\n"}
```

> **Note:** If you use the API to delete the last tenant in a Tenant Group, both the tenant and the now-empty Tenant Group are deleted.

Create a Tenant

This section describes how to create a new tenant in the API. The schema for the tenants API lets you specify all of the same configuration details you would when creating a new tenant in the user interface. The only mandatory field is the Tenant Name (**cust_name**). The available fields are as follows:

```
{
  "cust_name": "string",
  "contact": "string",
  "contact_email": "string",
  "contact_phone": "string",
  "address": "string",
  "info": "string",
  "retention_group": "string",
  "mfa_enabled": true,
  "authentication_method": "sso_saml",
  "sso_config": {
    "allow_clock_skew": true,
    "idp_certificate": "string",
    "idp_metadata": "string",
    "idp_callback_type": "string",
    "issuer_url": "string",
    "sso_config_method": "metadata",
    "sso_entry_point": "string"
  },
  "ingestion_limit": 0
}
```

Your call must have the header and the `/connect/api/v1/tenants` path, and must have at least the **cust_name** field, in addition to any optional fields shown in the schema above.

Note that the **retention_group** field cannot be used with the managed (SaaS) version of Stellar Cyber. Managed versions of Stellar Cyber have version numbers ending in **s** (for example, **5.2.0s**).

Sample Create Tenant Script

Here is a sample Python script with arguments filled in. Note that any arguments that you don't supply values for are left at their default settings, as described in **Managing Tenants**

```
#!/usr/bin/env python
import json
import requests
headers={'Accept': 'application/json', 'Content-type': 'application/json'}
elastic_url ='https://192.168.11.11/connect/api/v1/tenants'
json_data = {
"cust_name": "My New API Tenant",
"contact": "Dev Ops",
"contact_email": "devops@fakecompany.com",
"contact_phone": "415-555-1212",
}
query = json.dumps(json_data)
response = requests.post(elastic_url, auth=('ohtani','N-YrP02Xl6yHO-
1HW1gi1nems2g319Q3wLNpOAxWx9_ttbMw3pyB5qPvSVl3qt9CmgvOhHhtDCuEs5KcIn6mWw'),
data=query, verify=False, headers = headers)
print (response.text)
```

This example performs a POST call as the user **ohtani**with the API key shown in the text. The call is to the Stellar Cyber server at **192.168.11.11**to create a tenant with the following fields:

- **cust_name** – My New API Tenant
- **contact**– Dev Ops
- **contact_email** – devops@fakecompany.com
- **contact_phone** – 415-555-1212

All other fields for the tenant are left at their default values.

Update a Tenant

This section describes how update the settings for an existing tenant. You can use a PATCH to the tenants API to change any of the configuration details available when creating a new tenant in the user interface. The only mandatory fields are the Tenant ID and the Tenant Name (**cust_name**). The available fields are as follows:

```
{
  "cust_name": "string",
  "contact": "string",
  "contact_email": "string",
  "contact_phone": "string",
  "address": "string",
  "info": "string",
  "retention_group": "string",
  "mfa_enabled": true,
  "authentication_method": "sso_saml",
  "sso_config": {
    "allow_clock_skew": true,
    "idp_certificate": "string",
    "idp_metadata": "string",
    "idp_callback_type": "string",
    "issuer_url": "string",
    "sso_config_method": "metadata",
    "sso_entry_point": "string"
  },
  "ingestion_limit": 0
}
```

Your call must have the header and the `/connect/api/v1/tenants/<tenant_id>` path, and must have at least the **cust_name** field, in addition to any optional fields shown in the schema above that you want to change.

Note that the **retention_group** field cannot be used with the managed (SaaS) version of Stellar Cyber. Managed versions of Stellar Cyber have version numbers ending in **s** (for example, **5.2.0s**).

Sample Update Tenant Script

This script takes the tenant we created in **Create a Tenant** and changes the contact name. Note that any arguments that you don't supply values for are left at their existing settings**Managing Tenants**

```
#!/usr/bin/env python
import json
import requests
headers={'Accept': 'application/json', 'Content-type': 'application/json'}
elastic_url
='https://192.168.11.11/connect/api/v1/tenants/046b8eeceac549a2aefa579a180dfb45'
json_data = {
"cust_name": "My New API Tenant",
"contact": "James Dean",
}
query = json.dumps(json_data)
response = requests.patch(elastic_url, auth=('ohtani','N-YrP02Xl6yHO-
1HWlgi1nems2g319Q3wLNpOAxWx9_ttbMw3pyB5qPvSVl3qt9CmgvOhHhtDCuEs5KcIn6mWw'),
data=query, verify=False, headers = headers)
print (response.text)
```

This example performs a PATCH as the user **ohtani**with the API key shown in the text. The call is to the Stellar Cyber server at **192.168.11.11**to patch the tenant's contact name to James Dean:

- **Tenant ID** – 046b8eeceac549a2aefa579a180dfb45

  The Tenant ID can be retrieved from **System | ORGANIZATION MANAGEMENT | Tenants** and included in the URL.

- **cust_name** – My New API Tenant
- **contact**– James Dean

All other fields for the tenant are left at their existing values.

© 2026 Stellar Cyber . All rights reserved.