Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Firewall Requirements

Several components in the Stellar Cyber product require certain ports and domains be accessible through your firewall. Use the legend and tables below to understand which are appropriate for your environment.

Also see: **Log Parser Ports**.

Legend

- **CM**: Configuration Manager (runs in the DL)
- **DA**: Data Analyzer*
- **DL**: Data Lake*
- **DP**: Data Processor
- **LAS**: Linux Server (Agent) Sensor
- **MS**: Modular Sensor
- **WAS**: Windows Server (Agent) Sensor

Although these are part of the DP, they have unique IP addresses so are listed independently in the tables below.

General Purpose Ports

Source	Destination	Port	Protocol	Required ?	Purpose
Stellar Cyber user's SSH client	LAS, MS	22	TCP	Optional	Management access
Sensors	DNS Server Environment specific	53	**UDP**	Required	Name service for: • Downloading third-party libraries • Support of customer configured Active Directory • CM communication (if CM is by name vs IP)
All sensors	NTP Server	123	UDP	Required	Performing time synchronization
Stellar Cyber user's web browser	DL	443	TCP	Required	Viewing the Stellar Cyber user interface
WAS, LAS, MS	<org>.stellarcyber.cloud dn-<org>.stellarcyber.cloud	443	HTTPS with TLS 1.2	Required	Communicating with the CM. The dn-<org>.stellarcyber.cloud port is used when fast path communications between sensors and the CM are enabled. This happens automatically when either a Sensor CLI session is initiated from the user interface or a response is configured on the sensor.
WAS, LAS, MS	receiver-<org>.stellarcyber.cloud	8889	TCP (HTTPS with TLS 1.2)	Required	Downloading software and files from the DP, including custom log parsers.
WAS, LAS, MS	receiver-<org>.stellarcyber.cloud	8889	TCP (HTTPS with TLS 1.2)	Required	Receiver ports for communicating with the DA
WAS, LAS, MS	MS with Aggregator Enabled	8080	HTTP Proxy	Required	Must be open for communications between sensor and aggregator.

Domains

All of the following domains are required.

Source	Destination	Port	Protocol	Purpose
MS	archive.ubuntu.com security.ubuntu.com esm.ubuntu.com ppa.launchpad.net	443 80	TCP	Software updates.
LAS	**For centos/redhat servers:**	Environment specific	TCP	Customer configured port for accessing the OS provider's server (repository) for application updates

Source	Destination	Port	Protocol	Purpose
	• domains included in the repository configuration files (/etc/yum.repo.d/.repo) • dl.fedoraproject.org • mirrors.fedoraproject.org			
LAS	**For SUSE servers:** • domains in the repository configuration files /etc/zypp/repos.d/*.repo	Environment specific	TCP	Customer configured port for accessing the OS provider's server (repository) for application updates
LAS	**For Ubuntu servers:** • hosts in the ubuntu /etc/apt/source.list	Environment specific	TCP	Customer configured port for accessing the OS provider's server (repository) for application updates
LAS	launchpadlibrarian.net	80	TCP	Software updates
LAS	http://download.webmin.com	80	TCP	Software updates
Stellar Cyber user's web browser	doc-server.stellarcyber.ai	443	TCP	Accessing online help on the Stellar Cyber documentation server
Stellar Cyber user's web browser	• https://clientsdk-ld.stellarcyber.ai • https://clientstream-ld.stellarcyber.ai • https://events-ld.stellarcyber.ai	443	TCP	Dynamically enabling Early Access Program functionality, features, and fixes in the Stellar Cyber Platform 5.4.0
WAS	live.sysinternals.com/sysmon.exe	443	TCP	Optional. Domain is required if the customer wants to install feature
MS	sandbox.stellarcyber.ai	443	TCP	(Optional) Domain is required if the customer wants Malware Sandbox capability
MS	Environment specific	Environment specific	TCP	(Optional) Customer configured host and port for Tenable vulnerability scanning support
Machine with User's Browser	*.oraclecloud.com	443	TCP	For download of upgrade packages from Oracle Cloud Infrastructure.

Connector/Parser-specific

In addition to the general requirements above, review the following for your specific connector and parser choices:

- For any connector, you must also allow access between the sensor (or DP if applicable) and the API hosts/URLs you specify during configuration.
- In most cases, connector communication is over port TCP 443. Connectors with unique requirements are shown below.
- The configuration of firewall rules for connector Collect and Respond functions depends on the deployment type:

  On-premises: For connectors running on the DP, configure the firewall with the DA IP address for Collect functions and the DL IP address for the Respond functions.

  SaaS: The egress IP address used for both Collect and Respond connector functions is unique to each SaaS instance. To add this address to an allow-list on your perimeter firewall, contact Stellar Cyber Support to confirm the egress IP address assigned to your SaaS environment.
- For the ports to open for sensors receiving logs from devices on your network see **Log Parser Ports** Also, refer to Using the Port Relay Feature to Minimize Open Ports for information on relaying traffic sent to the generic syslog port to its appropriate vendor-specific parser.

Source	Destination	Port	Protocol	Connector
MS	AD Server and domain specified in connector configuration	LDAP/S: 389 or 636 (TCP) Kerberos: 88 (if used) (TCP/UDP)	TCP/UDP	Active Directory
DP	api.barracudanetworks.com	443	TCP	Barracuda Email server

© 2026 Stellar Cyber . All rights reserved.