Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Integration of Third Party Native Alerts

Stellar Cyber's alerts are created from data pathways that leverage raw data collected from all forms of data sources, including third party services and Stellar Cyber's sensors. You can choose to allow Stellar Cyber's Machine Learning (ML) and Statistical Analysis (SA) to generate alerts based on raw data ingested from third party services. For certain services, you can additionally choose to ingest and integrate alerts that are natively created in *those* services.

This topic summarizes which third party services and products Stellar Cyber supports for native alert integration and how those alerts are mapped in Stellar Cyber.

Third Party Native Alert Mapping

Stellar Cyber handles each service and product in a custom manner, according to the nature of the incoming data, including third party native alerts and other security events. To view alerts and events from multiple sources in our unified, common platform, Stellar Cyber normalizes and enriches the third party native alerts and security events during the data ingestion process. With ingested, normalized, and enriched third party native alerts and security events, Stellar Cyber further applies ML/SA engines, a direct mapping, or a combination of the two, to create Stellar Cyber alerts mapped to the XDR Kill Chain with additional deduplication to reduce noise and alert fatigue.

Review the following to better understand the native third party alert mapping Stellar Cyber is doing to help you get to the decision points more efficiently:

- **Deduplication**: In mapping third-party native alerts and security events to the XDR Kill Chain, Stellar Cyber uses a variety of methods to identify and eliminate potential duplicates for each applicable alert or event type. In particular, Stellar Cyber identifies a combination of fields and values to be key characteristics and uses those to identify duplicates. An example method is to compare the values in that combination for each new third party native alert; if the same value set occurs within a time threshold, that record is considered a duplicate and only the original record is mapped. This process is a critical mechanism to eliminate noise and reduce alert fatigue.
- **Normalization**: A key benefit of Stellar Cyber is standardization of all incoming data sources to a common data model (Interflow record), that includes some fields based on the Elastic Common Schema (ECS). Values from the incoming raw data are mapped into standardized fields in Stellar Cyber. In some cases, the original data field is still saved with the Interflow record. This normalization allows Stellar Cyber Analytics and Machine Learning to perform complex analysis and identify related events from disparate ingestion sources. Here are examples of normalization:
  - `crowdstrike.event.LocalIP` is mapped to Stellar Cyber's `host.ip` field
  - `threatInfo.classification` is mapped to Stellar Cyber `threat` field
- **Enrichment**: Stellar Cyber's data framework requires certain fields to help identify the data source, the category of data, the type of event, to support scoring calculations and certain other activities. In some cases, the ingested data can be directly mapped into these fields. In other cases, Stellar Cyber generates that data. Examples of data enrichment are:
  - (No incoming source field) `msg_origin.source` is created and populated with the vendor name, such as `crowdstrike`
  - (No incoming source field) `msg_origin.category` is created and populated with the applicable category for the data type, such as `endpoint`
  - Incoming data source field `crowdstrike.metadata.eventType` field exists and its value (such as `crowdstrike_detection_summary`) is mapped to Stellar Cyber field `msg_class`
  - Incoming data source field `event.technique.name` field exists and its value is either mapped directly or algorithmically standardized to populate to Stellar Cyber field `xdr.event_name`.

- Populating the `xdr_event` structure is a key part of enrichment, with Stellar Cyber ensuring that a Tactic, Technique, and Procedure name, and importance scores, are present in every Alert record.

Supported Native Third Party Alerts

The table below lists all the services and products for which Stellar Cyber has developed direct integration of third party native alerts, which includes mapping to the Stellar Cyber XDR Kill Chain and adding those alerts to the Alert index. Data not directly mapped is still run through the Stellar Cyber ML/SA pipeline, where applicable. The third party native alerts that are not mapped are ingested and available for creating ATH rules for automatic actions and entry of the result into the Alert index.

Use the table below to identify the data applicable for direct alert mapping, the method of ingestion, and the nature of the mapping.



- In cases where a value is indicated as **Derived**, Stellar Cyber assigns a value based on other attributes in the ingested data.
- Where possible, links to the third party data type format are provided for reference.

For the **Key Fields** for Third Party Alerts, see Key Fields for Third Party Native Alert Types.

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
Abnormal Security Email Security	Abnormal Security Email Security Alerts	Abnormal Security Email Security Connector This connector ingests logs from Abnormal Security Email Security to get the raw alerts that are stored in the Syslog index. Select the Threats content type.	Stellar Cyber maps Abnormal Security Email Security alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid`, `email.message_id`, and `event.threat.name`.	• msg_origin.source: `abnormal_security_email_security` • msg_class: `abnormal_security_email_security_threat` • Event (Alert) Name: Abnormal Security Threat: with the assigned Technique, for example `Abnormal Security Threat: Unknown Sender`: • Severity: 45 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Acronis Cyber Protect Cloud	Acronis Cyber Protect Cloud Alerts	Acronis Cyber Protect Cloud Connector	Stellar Cyber maps Acronis Cyber Protect Cloud alerts. The alerts are read from the Syslog index, enriched with	• msg_origin.source: `acronis_cyber_protect` • msg_class: `acronis_cyber_protect_alert` • Event (Alert) Name: ◦ Acronis Cyber Protect: with the assigned Technique, for example `Acronis Cyber Protect Cloud: Phishing` ◦ Acronis Cyber Protect: with the assigned Technique, for example `Acronis Cyber Protect Cloud: XDR Anomaly` ◦ Acronis Cyber Protect: with the assigned Technique, for example `Acronis Cyber Protect Cloud: Hide Artifacts`

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		This connector ingests logs from Acronis Cyber Protect Cloud to get the raw alerts that are stored in the Syslog index. Select the Alerts content type.	Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. The following four alert types are supported: Email security, EDR, Antimalware protection, and URL filtering. Tactic and Technique are based on alert type. Deduplication is by `tenantid`, `event.threat.name`, `host.name`, `user.name`, `url`, `process.pid`, `file.hash.sha1`, `email.from.address`, and `acronis_cyber_protect.details.edrAlertId`.	◦ Acronis Cyber Protect: with the assigned Technique, for example `Acronis Cyber Protect Cloud: Drive-by Compromise` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Armis 6.0.0	Armis Alerts Armis alert integration supports Mobile and Industrial Control Systems (ICS) tactics, in addition to Enterprise.	Armis Connector This connector ingests logs from Armis to get the raw alerts that are stored in the Syslog index. Select the Alerts content type.	Stellar Cyber maps Armis alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid`, `armis.alertId`, and `host.ip`.	• msg_origin.source: `armis` • msg_class: `armis_alerts` • Event (Alert) Name: Armis: with their multiple TTPs, for example `Armis: [MITRE ATT&CK | ICS] T0886 | Initial Access, Lateral Movement | Remote Services...` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Avanan	Avanan Alerts The alert types are: • spam • phishing • suspicious_phishing • malware	Configure ingestion of HTTP JSON format	Avanan sends email data to the Stellar Cyber Syslog index, which maps Avanan alerts to the Alerts index.	• msg_origin.source: `avanan` • msg_class: `avanan` • Event (Alert) Name: ◦ Avanan (Delivered): with the assigned Technique, for example `Avanan (Delivered): Phishing` ◦ Avanan (Quarantined): with the assigned Technique, for example `Avanan (Quarantined): Spam` • Severity: Derived from Avanan severity • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	• shadow_it • dlp • alert • anomaly • malicious_url	logs to a Stellar Cyber sensor.	Deduplication is by `tenantid`, `email.sender.address`, and `email.from.address`. If neither `email.sender.address` or `email.from.address` exists, `file.name` is used for deduplication. To search the alerts in the Alerts index or to search the Original Records in the Syslog index, use the queries: • `msg_class: avanan AND event.action: Delivered` • `msg_class: avanan AND event.action: Quarantined`	
AWS GuardDuty	AWS GuardDuty Alerts Refer to Amazon GuardDuty.	AWS GuardDuty Connector This connector ingests logs from AWS GuardDuty to get the raw alerts that are stored in the Syslog index.	Stellar Cyber maps AWS GuardDuty alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `aws_guardduty_id`.	• msg_origin.source: `aws_guardduty` • msg_class: `aws_guardduty_finding` • Event (Alert) Name: AWS GuardDuty: with the assigned Technique, for example `AWS GuardDuty: Valid Accounts` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Bitdefender	**URL--based** Antiphishing Data Protection User Control / Content Control **IP-based** Firewall	Configure ingestion of Bitdefender's Push event for	Of the different record types you can configure to push to Stellar Cyber's httpjson parser, the 11 at left are normalized and enriched as they are added to	• msg_origin.source: `bitdefender` • msg_class: Several. See the Bitdefender connector information card for a full list. • Event (Alert) Name: Bitdefender: with the assigned Technique, for example `Bitdefender: Data Encrypted for Impact` • Severity: Derived from `event.type` • Fidelity: Is Severity by default • MITRE | ATT&CK Technique and Tactic values are assigned as follows: Advanced Threat Control (ATC) — XDR Malware; XDR Misc Malware Antiexploit Event

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	Ransomware activity detection **Threat-based** Advanced Threat Control (ATC) Antiexploit Event Antimalware Hyper Detect event Sandbox Analyzer Detection Storage Antimalware	JSON RPC messages to send data to a Stellar Cyber sensor configured to ingest httpjson (port 5200) over TLS.	the Syslog index. The records are evaluated against existing records in the Alert index--those that do not already exist are directly mapped to the Alert index and XDR Kill chain. The other records are run through the ML/SA pipeline, which may generate alerts based on those algorithms. The labels assigned to the alert groups at left refer simply to the nature of the key data points for those alerts. Specifically, these data are supplied with the relevant alert description (Bitdefender field in parenthesis): • **URL-based alerts**: event.type (module acronym), host.name (computer_fqdn), host.ip (computer_ip), url • **IP-based alerts**: event.type (module acronym), host.name (computer_fqdn), host.ip (computer_ip), srcip (attack source or source-ip) • **Threat-based alerts**: event.type (module acronym), host.name (computer_fqdn), host.ip (computer_ip), threatName, where threatName varies depending on the record type (malware_name, threatType, detection_threatName, attack_types, aph_type,	Antimalware Hyper Detect event Sandbox Analyzer Detection User Control/Content Control — Execution; Exploitation for Client Execution Data Protection Storage Antimalware Event — Impact; Data Manipulation Ransomware activity detection — Impact; Data Encrypted for Impact Antiphishing — Initial Access; Phishing Firewall — XDR NBA; XDR Firewall Anomaly

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
			exploit_type, or target_type) See the Bitdefender connector information card for more details on normalization of these and other Bitdefender records. Deduplication is by the following fields: • IP—`tenantid`, `event.type`, `host.name`, `host.ip`, and `srcip`. • Threat—`tenantid`, `event.type`, `host.name`, `host.ip`, and `event.threat.name`. • URL—`tenantid`, `event.type`, `host.name`, `host.ip`, and `url`.	
Blackberry CylancePROTECT and CylanceOPTICS	CylancePROTECT: Exploit Attempts, Script Control, Threats CylanceOPTICS: Detections	Forward log files to port 5177 (specific for handling Cylance logs) The Blackberry Cylance Connector is applicable only for response actions.	• For **CylancePROTECT**, three types of Cylance events are mapped to the XDR Kill Chain and Stellar Cyber's Alert index: Exploit Attempts, Script Control, and Threats. The other data (Audit Log, Device, Device Control, and Threat Classification) are ingested and mapped to the Syslog index (not Alerts index), and are not run through the ML/SA pipeline. • For **CylanceOPTICS**, Detection events are evaluated with Stellar Cyber time series analysis models to determine abnormality of the event before mapping.	**CylancePROTECT** • msg_origin.source: `cylance_protect` • msg_class: `cylance_protect_alert` • Event (Alert) Name: CylancePROTECT: with the assigned Technique, for example `CylancePROTECT: OS Credential Dumping` • Severity: Not present in incoming data; Derived • Fidelity: `cylance_score` unless blank, then is populated with the same value as Severity • Kill Chain & MITRE | ATT&CK values are derived from `event_type` and `violation_type/threat_classification` **CylanceOPTICS** • msg_origin.source: `cylance_optics` • msg_class: `cylance_optics_event` • Event (Alert) Name: CylanceOPTICS: with the assigned Technique, for example `CylanceOPTICS: XDR Anomaly` • Severity: `severity` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are assigned a value during processing of CylanceOPTICS in the ML/SA pipeline

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
			Deduplication is by `org_id`, `tenantid`, `event.type`, `host.name`, `host.ip`, `file_name`, `file_path`, and `process_name`.	
Broadcom SES 6.1.0	Broadcom Incidents	Broadcom SES Connector This connector ingests logs from Broadcom Symantec Endpoint Security (SES) to get the raw alerts that are stored in the Syslog index. Select the Incidents content type.	Stellar Cyber maps Broadcom SES incidents. The incidents are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `broadcom.incident_uid`.	• msg_origin.source: `broadcom_ses` • msg_class: `broadcom_ses_incidents` • Event (Alert) Name: Broadcom SES Incident: with the assigned Technique, for example `Broadcom SES Incident: Data Encrypted for Impact` • Severity: Derived from `event.severity`: ◦ Unknown: 1 ◦ Informational: 15 ◦ Warning: 30 ◦ Minor: 45 ◦ Major: 60 ◦ Critical: 75 ◦ Fatal: 90 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Cato Networks 6.2.0	Cato Networks events	Cato Networks Connector This connector ingests logs from Cato Networks to get the	Stellar Cyber maps Cato Networks events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `event_id`.	• msg_origin.source: `cato_networks` • msg_class: `cato_security` • Event (Alert) Name: Cato Networks: with the event subtype, for example `Cato Networks: NG Anti Malware` • Severity: Derived from `event.severity`: • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		raw alerts that are stored in the Syslog index. Select the Security content type.		
Check Point Harmony Email 6.5.0	Check Point Harmony Email events The alert types are: • spam • phishing. • anomaly • shadow_it • graymail	Check Point Harmony Email Connector This connector ingests logs from Check Point Harmony Email to get the raw alerts that are stored in the Syslog index. Select the Security Event content type.	Stellar Cyber maps Check Point Harmony Email events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `checkpoint_harmony.eventId`.	• msg_origin.source: `checkpoint_harmony` • msg_class: `checkpoint_harmony_security_event` • Event (Alert) Name: Check Point Harmony Email: with the checkpoint_harmony.type, for example `Check Point Harmony Email: Phishing` • Severity: Derived from `event.severity`: ◦ 4=Very High: 80 ◦ 5=Critical: 99 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
CrowdStrike 6.4.0	CrowdStrike events	CrowdStrike Connector This connector ingests logs from CrowdStrike to get the raw alerts that are stored in the Syslog index. Select the EppDetectionSummaryEvent content type or the `crowdstrike_{metadata.eventType}` (example: crowdstrike_XdrDetectionSummaryEvent) default content type.	Stellar Cyber maps CrowdStrike events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `crowdstrike.event.CompositeId`.	• msg_origin.source: `crowdstrike` • msg_class: `crowdstrike.metadata.eventType:EppDetectionSummaryEvent` or `crowdstrike_XdrDetectionSummaryEvent` • Event (Alert) Name: CrowdStrike: with the assigned Technique, for example `CrowdStrike: XDR Endpoint Indicator of Threat` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
CyberArk EPM 6.2.0	CyberArk EPM events The following threat detection categories are supported: • AttackAttempt • AttackBlock • Suspicious ActivityAttempt	CyberArk EPM Connector This connector ingests logs from CyberA	Stellar Cyber maps CyberArk EPM events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index.	• msg_origin.source: `cyberark_epm` • msg_class: `cyberark_epm_event` • Event (Alert) Name: CyberArk EPM : with the threat detection rule, for example `CyberArk EPM: Credential Theft From Windows Credential Manager` • Severity: 45, by default • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	• Suspicious ActivityBlock	rk EPM to get the raw alerts that are stored in the Syslog index. Select the Events content type.	Deduplication is by `tenantid`, `cyberark_epm.eventType`, `cyberark_epm.policyName`, `cyberark_epm.filePath`, and `cyberark_epm.userName`.	
Cybereason	MalOp	Cybereason Connector Select the MalOp content type.	Stellar Cyber can generate alerts based on the Cybereason sensor and MalOp data, however the MalOp records are most applicable for direct mapping. The value in `malopDetectionType` is reformatted and used for the alert name. Stellar Cyber has evaluated each possible alert and assigned a corresponding MITRE | ATT&CK Stage, Tactic and Technique. Deduplication is by `tenantid`, `user_list`, `threat`, `host_list`, `file.name`, and `process.name`.	• msg_origin.source: `cybereason_malops_all_types` • msg_class: `cybereason_malops_all_types` • Event (Alert) Name: Cybereason: with the assigned Technique, for example `Cybereason: Phishing` • Severity: Derived from `threat` and `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived from `malopDetectionType`
Cyble 6.3.0	Cyble alerts The following alert types are supported: • leaked_credentials • stealer_logs • darkweb_data_breaches • darkweb_marketplaces • suspicious_domains • vulnerability	Cyble Connector This connector ingests logs from Cyble to get the raw alerts	Stellar Cyber maps Cyble alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `cyble.id`.	• msg_origin.source: `cyble` • msg_class: `cyble_alerts` • Event (Alert) Name: Cyble: with the event.threat.name, for example `Cyble: leaked_credentials` • Severity: Derived from `event.severity_str`: ◦ HIGH: 60 ◦ MEDIUM: 45 ◦ LOW: 30 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	• new_vulnerability • ip_risk_score • ssl_expiry	that are stored in the Syslog index. Select the Alerts content type.		
Cynet	ADT Alerts NextGen Antivirus Alerts Threat Intelligence Alerts Memory Protection Alerts Network Activity Alerts AMSI Alerts Feature Alerts	Configure ingestion of CEF format logs to a Stellar Cyber sensor.	The collection of Cynet alerts listed here are read from the Syslog index, enriched and mapped (with deduplication) to the Alert index and Stellar Cyber Kill Chain. The Cynet alert type is mapped to Stellar Cyber's `event.threat.name`, which is shown in the key fields. Deduplication is by `tenantid`, `host.ip`, `event.threat.name`, and `file.name`. To search the alerts in the Alerts index or to search the Original Records in the Syslog index, use the query: • `msg_class: cynet_alert AND _exists_:event.threat.name AND NOT event.threat.name:Audit`	• msg_origin.source: `cynet` • msg_class: `cynet_alert` • Event (Alert) Name: Cynet: with the assigned Technique, for example `Cynet: Data Encrypted for Impact` • Severity: Derived from `event.threat.name` and `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are assigned based on the value in Cynet's alert type which is mapped to `event.threat.name`
Darktrace 6.5.0	Darktrace events	Configure ingestion of CEF format logs to a Stellar Cyber sensor.	Darktrace sends Syslog CEF events to Stellar Cyber, which maps Darktrace events to the Alerts index. Deduplication is by `tenantid` and `darktrace.externalid`.	• msg_origin.source: `darktrace` • msg_class: `darktrace` • Event (Alert) Name: Darktrace: with the event.threat.name, for example `Darktrace: Anomalous Connection/Download and Upload` • Severity: Derived from event.severity: CEF numeric severity (1-10) • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
			To search the alerts in the Alerts index or to search the Original Records in the Syslog index, use the query: • `msg_class:darktrace AND _exists_:event.threat.name`	

Deep Instinct	Events	Deep Instinct Connector
		The connector can be used for three data types but only **Events** are applicable for alert mapping.
		Select the Events content type.
			The Events record includes a MITRE | ATT&CK structure with values that support direct mapping to Stellar Cyber's XDR Kill Chain. If the incoming tactic or technique are blank, the following values are assigned in Stellar Cyber:
			`tactic_name = XDR Malware`
			`technique_name = XDR Miscellaneous Malware`
			Deduplication is by `tenantid`, `event.type`, `host.name`, `host.ip`, `file.path`, `file.file_hash`, and `deep_instinct.action`.
				• msg_origin.source: `deep_instinct`
				• msg_class: `deep_instinct_maliciousevent`
				• Event (Alert) Name: DeepInstinct: with the assigned Technique, for example `DeepInstinct: User Execution`
				• Severity: Derived from `event.threat.name` and `event.severity_str`
				• Fidelity: Is Severity by default
				• Kill Chain & MITRE | ATT&CK values:
				  ◦ Stage: Derived from `MitreClassifications.mitre_id`
				  ◦ Tactic: `MitreClassifications.tactic_name`
				  ◦ Technique: `MitreClassifications.technique_name`
				• See also:
				  ◦ `event.reason` contains `trigger`
				  ◦ `action` contains `act`

Duo Trust Monitor 6.3.0	Duo Trust Monitor events	Duo Security Connector This connector ingests logs from Duo Security to get the raw alerts	Stellar Cyber maps Duo Trust Monitor events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `duosecurity.sekey`.	• msg_origin.source: `duosecurity` • msg_class: `duosecurity_trust_monitor` • Event (Alert) Name: Duo Trust Monitor: with the event.threat.name, for example `Duo Trust Monitor: Bypass Status Enabled` • Severity: Derived from `event.severity_str`: ◦ duosecurity.priority_event:false: 45 ◦ duosecurity.priority_event:true: 60 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		that are stored in the Syslog index. Select the Trust Monitor content type.		
ESET Cloud Office Security (ECOS) 5.5.0	ESET Cloud Office Security Types of alerts: • malware • spam • phishing For the following apps: • Microsoft 365 (Exchange, OneDrive, SharePoint, and Teams) • Google Workspace (Gmail and Google Drive)	Configure ingestion of Syslog format logs to a Stellar Cyber sensor.	ECOS quarantines malicious emails and files when anything from Exchange, OneDrive, Teams, SharePoint, Gmail, and GoogleDrive are identified as malicious or suspicious. When such an event happens, a security event (malware, spam, or phishing) is generated and ingested by Stellar Cyber's Syslog-based parser. ECOS Detections and Quarantine events are mapped from Syslog to the Alerts index. Deduplication is by `tenantid`, `eset.ScanResult`, `eset.OperationId`, `eset.Service`, and `eset.Tenant`. To search the alerts in the Alerts index or to search the Original Records in the Syslog index, use the query: • `msg_origin.source: eset_cos AND eset.ScanResult: (Malware* OR Spam OR Phishing)`	• msg_origin.source: `eset_cos` • msg_class: `eset_cos_googledrive`, `eset_cos_gmail`, `eset_cos_team`, `eset_cos_exchange`, `eset_cos_sharepoint`, or `eset_cos_onedrive` • Event (Alert) Name: ESET Cloud Office Security: with the assigned Technique, for example `ESET Cloud Office Security: XDR Endpoint Indicator of Threat` • Severity: Derived from severity • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
ESET Protect	ESET Protect Alerts and Events The following types of alerts and events are supported: • Filtered Websites Event • Firewall Aggregated Event • ESET Inspect Alert • Threat Event Refer to Events exported to JSON format.	Configure ingestion of JSON format logs to a Stellar Cyber sensor.	Stellar Cyber maps ESET Protect alerts and events. The alerts and events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by the following fields: • ESET Protect (Filtered Websites Event)—`tenantid`, `eset.rule_id`, `host.name`, `file.hash.sha1`, `srcip`, and `dstip`. • ESET Protect (Firewall Aggregated Event)—`tenantid`, `event.threat.name`, `eset.source_uuid`, `srcip`, `dstip`, and `user.name`. • ESET Protect (ESET Inspect Alert)—`tenantid`, `eset.eialarmid`, and `eset.rulename`. • ESET Protect (Threat Event)—`tenantid`, `process.executable`, `host.ip`, and `file.hash.sha1`. To search the alerts in the Alerts index or to search the Original Records in the Syslog index, use the queries: • ESET Protect (Filtered Websites Event)—`msg_origin.source: eset_protect AND eset.event_type: \"FilteredWebsites_Event\"` • ESET Protect (Firewall Aggregated Event)—`msg_origi`	• msg_origin.source: `eset_protect` • msg_class: `eset_protect_filtered_websites`, `eset_protect_firewall_aggregated`, `eset_protect_enterprise_inspector`, and `eset_protect_threatevent` • Event (Alert) Name: ◦ ESET Protect (Filtered Websites Event): with the assigned Technique, for example `ESET Protect (Filtered Websites Event): Blocked by Internal IP blacklist` ◦ ESET Protect (Firewall Aggregated Event): with the assigned Technique, for example `ESET Protect (Firewall Aggregated Event): Security vulnerability exploitation attempt` ◦ ESET Protect (ESET Inspect Alert): with the assigned Technique, for example `ESET Protect (ESET Inspect Alert): Suspicious PowerShell script - Obfuscation` ◦ ESET Protect (Threat Event): with the assigned Technique, for example `ESET Protect (Threat Event): XDR Endpoint Indicator of Threat` • Severity: Derived from `event.severity_str` for ESET Protect event: ◦ HIGH: 75 ◦ FATAL: 75 ◦ Error: 75 ◦ MED: 55 ◦ Warning: 25 ◦ LOW: 25 ◦ Information: 10 ◦ DIAGNOSTIC: 10 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
			`n.source: eset_protect AND eset.event_type: \"FirewallAggregated_Event\"` • ESET Protect (ESET Inspect Alert)—`msg_origin.source: eset_protect AND eset.event_type: \"ESET Inspect Alert\"` • ESET Protect (Threat Event)—`msg_origin.source: eset_protect AND eset.event_type: Threat_Event`	
ExtraHop Reveal(x) 360 6.5.0	ExtraHop Reveal(x) 360 detection events	ExtraHop Reveal(x) 360 Connector This connector ingests logs from ExtraHop Reveal(x) 360 to get the raw alerts that are stored in the Syslog index. Select the Detections content type.	Stellar Cyber maps ExtraHop Reveal(x) 360 detection events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `extrahop.id`.	• msg_origin.source: `extrahop_reveal_x_360` • msg_class: `extrahop_reveal_x_360_detections` • Event (Alert) Name: ExtraHop Reveal(x) 360: with the extrahop.title, for example `ExtraHop Reveal(x) 360: Unusual Archive File Upload` • Severity: Derived from `event.severity` using risk score directly as severity score (0-99) • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
FortiEDR 6.5.0	FortiEDR events	FortiEDR Connector This connector	Stellar Cyber maps FortiEDR events. The events are read from the Syslog index, enriched with Stellar Cyber	• msg_origin.source: `fortinet_edr` • msg_class: `fortiedr_events` • Event (Alert) Name: FortiEDR: with the event.threat.name, for example `FortiEDR: Unconfirmed Executable` • Severity: Derived from `fortinet_edr.severity`: ◦ Malicious: 65 ◦ Suspicious: 55 ◦ Potentially Unwanted Program (PUP): 45 ◦ Inconclusive: 35 ◦ Likely Safe: 25

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		ingests logs from FortiEDR to get the raw alerts that are stored in the Syslog index. Select the Events content type.	fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `fortinet_edr.eventId`.	• Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Fortinet Lacework 6.0.0	Fortinet Lacework Alerts, which are ingested using the Generic S3 connector	Generic S3 Connector This connector pulls data sent to S3 for Fortinet Lacework to get the raw alerts that are stored in the Syslog index.	Stellar Cyber maps Fortinet Lacework alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `fortinet_lacework.EVENT_ID`.	• msg_origin.source: `s3` • msg_class: `generic_s3_fortinet_lacework_alert_details` • Event (Alert) Name: Lacework: with the assigned Technique, for example `Lacework: ApiFailedWithError` • Severity: 45, by default • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Google Workspace	Google Workspace Alerts The following are supported: • Gmail phishing • Google identity • User Changes • Access Approvals • Domain wide takeout • State Sponsored Attack • Mobile device management • Security Center rules	Google Workspace Connector This connector ingests alerts from Google Workspace to get the raw alerts that are stored	Stellar Cyber maps Google Workspace alerts. The alerts are read from the Linux Events index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `org_id`, `tenantid`, `metadata.customerId`, `source`, `type`, and `metadata.alertId`.	• msg_origin.source: `gsuite` • msg_class: `gsuite_alert` • Alert Subtype: `gsuite.type` or `type` • Event (Alert) Name: Google Workspace Alert: with the assigned Technique, for example `Google Workspace Alert: Phishing` • Severity: `metadata.severity` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are assigned

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	• Data Loss Prevention • Apps outage • Sensitive Admin Action • Customer abuse • Reporting Rule • Chrome • Google Mandatory Service Announcement • Google Operations • Google Voice • AppMaker Editor • App Settings Changed	in the Linux Events index. Select the Alert content type.		
Group IB 6.5.0	Group IB alerts The alert types are: • Generic Trojan • Covert Channel. • Exploit Kits • Malicious File • Suspicious Activity	Group-IB Connector This connector ingests logs from Group-IB to get the raw alerts that are stored in the Syslog index. Select the Alerts content type.	Stellar Cyber maps Group-IB alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `group_ib.ID`.	• msg_origin.source: `group_ib` • msg_class: `group_ib_alerts` • Event (Alert) Name: Group IB: with the event.threat.name, for example `Group IB: Generic Trojan` • Severity: Derived from `event.severity`: ◦ 5: 99 ◦ 4: 80 ◦ 3: 60 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Halcyon 6.4.0	Halcyon alerts	Halcyon Connector This connector ingests logs from Halcyon to get the raw alerts	Stellar Cyber maps Halcyon alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `halcyon.id`.	• msg_origin.source: `halcyon` • msg_class: `halcyon_alerts` • Event (Alert) Name: Halcyon: with the event.threat.name, for example `Halcyon: VulnerableDriver` • Severity: Derived from `halcyon.action`: ◦ Report: Informational/Low: 30 ◦ Block: Medium: 45 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		that are stored in the Syslog index. Select the Alerts content type.		
HoxHunt 6.3.0	HoxHunt events	Hoxhunt Connector This connector ingests logs from HoxHunt to get the raw alerts that are stored in the Syslog index. Select the Threats content type.	Stellar Cyber maps HoxHunt events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `email.from.address`, `email.to.addresses`, and `email.subject`.	• msg_origin.source: `hoxhunt` • msg_class: `hoxhunt_threats` • Event (Alert) Name: HoxHunt: with the event.threat.name, for example `HoxHunt: User Reported Malicious Email` • Severity: Derived from `event.severity_str`: ◦ COMPROMISED_EMAIL: 90 ◦ SPEAR: 80 ◦ PHISH: 75 ◦ SPAM: 60 ◦ INCONCLUSIVE: 45 ◦ FALSE_POSITIVE: 3 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Huntress	Huntress Incidents	Huntress Connector This connector ingests logs from Huntress to get the raw alerts that are stored in the Syslog index. Select the Incident	Stellar Cyber maps Huntress incidents. The incidents are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid`, `huntress_id`, `huntress.organization_id`, and `huntress.account_id`. Huntress has six indicator types for Tactic and Technique	• msg_origin.source: `huntress` • msg_class: `huntress_incident_report` ◦ Alert Subtype: `huntress.subject` • Event (Alert) Name: Huntress Incident: with the assigned Technique, for example `Huntress Incident: Event Triggered Execution` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		Reports content type.	mapping: monitored_files, process_detections, ransomware_canaries, footholds, managed_identity, and antivirus_detections. One incident could have as many as six indicators showing at the same time.	
HYAS Protect	HYAS Protect passthrough alerts The following are supported: • Domain tagged with Suspicious Registrar • Domain tagged as blocked by HYAS Engine • Domain tagged as Highly Suspicious	HYAS Protect Connector This connector ingests logs from HYAS Protect to get the raw alerts that are stored in the Syslog index. Select the DNS Log Reports content type.	Stellar Cyber maps HYAS Protect passthrough alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid`, `dns.question.name`. and `srcip`.	• msg_origin.source: `hyas_protect` • msg_class: `hyas_protect_dns_log_report` • Event (Alert) Name: HYAS Protect (passthrough alert): with the assigned Technique, for example: ◦ Domain tagged with Suspicious Registrar, for example: `HYAS Protect (Watch Engine): Valid Accounts` ◦ Tactic: Initial Access ◦ Technique: Valid Accounts ◦ Sub-technique: Domain Accounts ◦ Domain tagged as blocked by HYAS Engine, for example> `HYAS Protect (Block): Application Layer Protocol` ◦ Tactic: Command and Control ◦ Technique: Application Layer Protocol: DNS ◦ Domain tagged as Highly Suspicious, for example: `HYAS Protect (Highly Suspicious): Dynamic Resolution` ◦ Tactic: Command and Control ◦ Technique: Dynamic Resolution • Severity: Derived from `event.severity_str` for HYAS threat level: ◦ critical: 75 ◦ high: 55 ◦ medium: 35 ◦ low: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
LimaCharlie	LimaCharlie Alerts The following types of events for alerts collected by LimaCharlie's EDR sensors are supported: • Process Events • Logon Events • FIM Events Refer to Events.	LimaCharlie Connector This connector ingests logs from LimaCharlie to get the raw alerts that are	Stellar Cyber maps LimaCharlie alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `limacharlie.routing.event_id`. Tactic and Technique are	• msg_origin.source: `limacharlie` • msg_class: `limacharlie_alert` • Event (Alert) Name: LimaCharlie: with the assigned Technique, for example `LimaCharlie: Data Manipulation` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		stored in the Syslog index. Select the Alerts content type.	provided by the LimaCharlie raw alerts field `limacharlie.detect_mtd.tags`.	
Microsoft App Governance (Graph Security API) 6.6.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Windows Events index. Select the Alert content type.	Stellar Cyber maps Microsoft App Governance alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. Deduplication is by `tenantid` and `microsoft_graph_security_api.id`.	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `microsoft_app_governance_alerts` • Event (Alert) Name: Microsoft App Governance: with the event.threat.name, for example `Microsoft App Governance: OAuth App with suspicious Reply URL` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
Microsoft Data Loss Prevention (Graph Security API) 6.6.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Windows Events index. Select the Alert content type.	Stellar Cyber maps Microsoft Data Loss Prevention (DLP) alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. Deduplication is by `tenantid` and `microsoft_graph_security_api.id`.	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `microsoft_data_loss_prevention_alerts` • Event (Alert) Name: Microsoft Data Loss Prevention: with the event.threat.name, for example `Microsoft Data Loss Prevention: Exfiltration` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Microsoft Defender for Endpoint	Syslog	Microsoft Defender for Endpoint Connector This connector ingests logs from Microsoft Defender for Endpoint (connector). Select the Alerts	Stellar Cyber maps Microsoft Defender ATP alerts. Deduplication is by `tenantid`, `host.ip`, `host.name`, and `microsoft_defender.id`. The lastUpdateTime timestamp is used with the API to pull alerts/events. The alertCreationTime timestamp is not used. This may result in the old event being pulled	• msg_origin.source: `microsoft_defender` • msg_class: `microsoft_defender_alerts` • Alert Subtype: `microsoft_defender.title` • Event (Alert) Name: Microsoft Defender ATP: with the assigned Technique, for example `Microsoft Defender ATP: OS Credential Dumping` • Severity: Derived from `threat` and `event.severity_str` • Fidelity: Is Severity by default • Tactic: XDR Malware • Mitre TTP mappings are provided by the Microsoft ATP field `microsoft_defender.mitreTechniques`. When the field is empty, Stellar Cyber's own TTP mapping is used.

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		content type. This alert integration supports the following detection sources: WindowsDefenderAv and WindowsDefenderAtp. If you have integrated both Microsoft Defender for Endpoint (connector) and Windows Defender Antivirus (free version), there may be two data sources for third party native alerts. The integration of Microsoft Defender for Endpoint (connec	[redacted] again when an update happens on the event.	

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		tor) may stop the alert mapping for Windows Defender Antivirus (free version).		
Microsoft Defender for Endpoint (Graph Security API) 6.2.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Windows Events index. Select the Alert content type.	Stellar Cyber maps Microsoft Defender for Endpoint alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. There is no deduplication of alerts between Microsoft Defender ATP and Microsoft Defender for Endpoint (Graph Security API).	• msg_origin.source: `microsoft_graph_security_apif` • msg_class: `microsoft_defender_for_endpoint_alerts` • Event (Alert) Name: Microsoft Defender ATP: with the assigned Technique, for example `Microsoft Defender ATP: OS Credential Dumping` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Microsoft Defender for Cloud	Microsoft Defender for Cloud alerts Refer to Alerts.	Azure Event Hub Connector This connector ingests logs from	Stellar Cyber maps Microsoft Defender for Cloud alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index.	• msg_origin.source: `azure_eventhub` • msg_class: `microsoft_defender_cloud` • Event (Alert) Name: Microsoft Defender for Cloud: with the assigned Technique, for example `Microsoft Defender for Cloud: Traffic detected from IP addresses recommended for blocking` • Severity: Derived from original severity from Microsoft Defender for Cloud • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived from microsoft_defender_cloud.Intent: ◦ Probing, Reconnaissance ◦ PreAttack , Reconnaissance

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		the content type, Microsoft Defender for Cloud, to get the raw alerts that are stored in the Windows Events index.	Deduplication is by `tenantid` and `microsoft_defender_cloud.SystemAlertId`.	
Microsoft Defender for Cloud (Graph Security API) 6.2.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Windows Events index. Select the Alert content type.	Stellar Cyber maps Microsoft Defender for Cloud alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. There is no deduplication of alerts between Microsoft Defender for Cloud and Microsoft Defender for Cloud (Graph Security API).	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `microsoft_defender_for_cloud_alerts` • Event (Alert) Name: Microsoft Defender for Cloud: with the assigned Technique, for example `Microsoft Defender for Cloud: Traffic detected from IP addresses recommended for blocking` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Microsoft Defender for Cloud Apps	Microsoft Defender for Cloud Apps alerts The risk categories are: 0: THREAT_DETECT	Microsoft Defender for Cloud Apps Connector	Stellar Cyber maps Microsoft Defender for Cloud Apps alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber	• msg_origin.source: `ms_defender_for_cloud_apps` • msg_class: `microsoft_defender_for_cloud_apps_alerts` • Event (Alert) Name: Microsoft Defender for Cloud Apps: {microsoft_defender_for_cloud_apps.title}, for example `Microsoft Defender for Cloud Apps: Activity from a Tor IP address` • Severity: Derived from original severity from Microsoft Defender for Cloud Apps: ◦ 0: LOW ◦ 1: MEDIUM ◦ 2: HIGH ◦ 3: INFORMATIONAL • Fidelity: Is Severity by default

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	ION 1: PRIVILEGED_ACCOUNT_MONITORING 2: COMPLIANCE 3: DLP 4: DISCOVERY 5: SHARING_CONTROL 7: ACCESS_CONTROL 8: CONFIGURATION_MONITORING	This connector ingests logs from Microsoft Defender for Cloud Apps to get the raw alerts that are stored in the Windows Events index. Select the Alerts content type.	fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `microsoft_defender_for_cloud_apps._id`.	• Kill Chain & MITRE | ATT&CK values are derived from microsoft_defender_cloud.Intent: ◦ UNKNOWN, Reconnaissance ◦ PREATTACK , Reconnaissance
Microsoft Defender for Cloud Apps (Graph Security API) 6.2.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Windows Events index. Select the Alert	Stellar Cyber maps Microsoft Defender for Cloud Apps alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. There is no deduplication of alerts between Microsoft Defender for Cloud Apps and Microsoft Defender for Cloud Apps (Graph Security API).	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `microsoft_defender_for_cloud_apps_alerts` • Event (Alert) Name: Microsoft Defender for Cloud Apps: {microsoft_defender_for_cloud_apps.title}, for example `Microsoft Defender for Cloud Apps: Activity from a Tor IP address` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		content type.		
Microsoft Defender for Identity (Graph Security API) 6.6.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Windows Events index. Select the Alert content type.	Stellar Cyber maps Microsoft Defender for Identity alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. Deduplication is by `tenantid` and `microsoft_graph_security_api.id`.	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `microsoft_defender_for_identity_alerts` • Event (Alert) Name: Microsoft Defender for Identity: with the event.threat.name, for example `Microsoft Defender for Identity: Potential Credential Abuse in Entra ID Authentication` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Microsoft Defender for Office 365 (Graph Security API) 6.6.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Window	Stellar Cyber maps Microsoft Defender for Office 365 alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. Deduplication is by `tenantid` and `microsoft_graph_security_api.id`.	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `microsoft_defender_for_office365_alerts` • Event (Alert) Name: Microsoft Defender for Office 365: with the event.threat.name, for example `Microsoft Defender for Office 365: Email messages removed after delivery` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		s Events index. Select the Alert content type.		
Microsoft Defender XDR 6.1.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Syslog index. Select the Alert content type.	Stellar Cyber maps Microsoft Defender XDR alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication uses the `microsoft_graph_security_api.id` field.	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `microsoft_graph_defender_xdr_alert` • Event (Alert) Name: Microsoft Defender XDR: with the microsoft_graph_security_api.title, for example `Microsoft Defender XDR: Activity Outside of U.S.` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Microsoft Entra ID (formerly Azure AD)	riskDetections>riskEvents The integration does not include alerts of "riskEventType": "generic".	Microsoft Entra ID (formerly Azure AD) Connector This connector ingests several log types from Microsoft Entra ID to	The value in the fields for the data type noted at left are mapped to Stellar Cyber's XDR Alert index. These alerts are suitable for MITRE | ATT&CK classification, but do not contain tactic and technique values. Stellar Cyber has evaluated each possible alert and assigned a corresponding MITRE | ATT&CK	• msg_origin.source: `azure_ad` • msg_class: `azure_ad_risk_detection` • Event (Alert) Name: Microsoft Entra RiskDetection: with the assigned Technique, for example `Microsoft Entra RiskDetection: Valid Accounts` • Severity: Derived from `riskLevel` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		get the raw alerts that are stored in the Windows Events index. Only **Risk Detection** logs are relevant to alert mapping. Select the Risk Detection Collection content type.  When both the Microsoft Entra ID (formerly Azure A	Stage, Tactic and Technique. Deduplication is by `tenantid`, `riskEventType`, `riskLevel`, `userDisplayName`, and `ipAddress`.	

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		D) connector and the Microsoft Graph Security API connector are enabled for the same tenant		

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		, the same underlying risk event will generate two alerts, one for each connector. It is recom		

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		m e n d e d t h a t w h e n y o u e n a b l e t h e M i c r o s o f t G r a p h S e c u r i t y A P I c o n n e c t o r , y o u d i s a b l e t h e M		

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		icrosoft Entra ID (formerly Azure AD) connector to avoid alert duplication.		
Microsoft Entra ID Protection (Graph Security API) 6.6.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from	Stellar Cyber maps Microsoft Entra ID Protection alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. Deduplication is by `tenantid` and `microsoft_graph`	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `azure_ad_identity_protection_alerts` • Event (Alert) Name: Microsoft Entra ID Protection: with the event.threat.name, for example `Microsoft Entra ID Protection: Sign-in from malicious IP address` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		Graph Security API to get the raw alerts that are stored in the Windows Events index. Select the Alert content type.  When both the Microsoft Graph Security API connector and the	`_security_api.id`.	

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		Microsoft Entra ID (formerly Azure AD) connector are enabled for the same tenant, the same un		

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		derlying risk event will generate two alerts, one for each connector. It is recommended that w		

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		henyouenablethe Microsoft Graph Security API connector, youdisablethe Microsoft Entral		

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		D(formerly Azure AD) connector to avoid alert duplication.		
Microsoft Office 365	Windows Events	Office 365 Connectors This connector ingests logs from Microsoft Office 365 to get the raw alerts that are stored in the Windows	Stellar Cyber maps Microsoft Office 365 alerts from the **AlertTriggered** operation. For the Audit General content type, Office 365 alerts contain events from the **AlertTriggered** operation, which are sent to the Alerts index. The source records may also include related events in the **AlertEntityGenerated** operation. Some information	• msg_origin.source:`office365` • msg_class: `office365_audit_general` • Alert Subtype: `event.threat.name` or `office365.Name` • Event (Alert) Name: Microsoft 365: with the assigned Technique and the assigned (Tactic), for example `Microsoft 365: Valid Accounts (Privilege Escalation)` • Fidelity: Is Severity by default • Severity: Derived from Office 365 alert policy Severity `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 • Kill Chain & MITRE | ATT&CK values are mapped to the Office 365 alert policies and the category to which each policy is assigned. You can also refer to the Microsoft documentation.

Click Here for Alert Details

Alerts	Tactic	Technique	Severity
High Severity Alerts:			
◦ A potentially malicious URL click was detected	Initial Access	Phishing	High
◦ A user clicked through to a potentially malicious URL	Initial Access	Phishing	High
◦ Activity from a password-spray associated IP address	Credential Access	Brute Force	High

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields			
		Events index. Select the Audit General content type. Only the **AlertTriggered** operation is relevant to alert mapping.	(AlertEntityId and EntityType) from the **AlertEntityGenerated** operation is merged with the **AlertTriggered** operation for the same Alert ID. The information (AlertEntityId and EntityType) is stored in the `event_summary` field. Deduplication is by `tenantid` and `AlertId`.	○ Activity from a Tor IP address	Command and Control	Proxy	High
				○ Data exfiltration to an app that is not sanctioned	Exfiltration	Exfiltration Over Web Service	High
				○ Data Leaks - Priority Users	Exfiltration	Exfiltration Over Web Service	High
				○ DataLossPrevention	Exfiltration	Exfiltration Over Web Service	High
				○ Elevation of administrative privilege	Privilege Escalation	Valid Accounts	High
				○ Form blocked due to potential phishing attempt	Lateral Movement	Internal Spearphishing	High
				○ Form flagged and confirmed as phishing	Initial Access	Phishing	High
				○ High Alert Forwarding Redirect	XDR UBA	XDR Anomaly	High
				○ Malware detection	Execution	User Execution	High
				○ Messages have been delayed	XDR NBA	XDR Rule Violation	High
				○ Potential nation-state activity	Initial Access	Valid Accounts	High
				○ Privilege Escalation - Office 365	Privilege Escalation	Valid Accounts	High
				○ Risky Action	XDR UBA	XDR Anomaly	High
				○ Suspicious connector activity	Initial Access	Phishing	High
				○ Suspicious email forwarding activity	Collection	Email Collection	High
				○ Suspicious impersonated activity	Defense Evasion	Masquerading	High
				○ Suspicious inbox forwarding rule	Collection	Email Collection	High
				○ Suspicious inbox manipulation rule	Collection	Email Collection	High
				○ Suspicious OAuth app file download activities	Persistence	Account Manipulation	High
				○ Suspicious tenant sending patterns observed	Privilege Escalation	Valid Accounts	High
				○ Tenant restricted from sending email	Privilege Escalation	Valid Accounts	High
				○ Tenant restricted from sending unprovisioned email	Initial Access	Valid Accounts	High
				○ Unusual addition of credentials to an OAuth app	Credential Access	Steal Application Access Token	High
				○ Unusual external user file activity	Impact/Exfiltration	Data Destruction, Exfiltration Over Web Service	High
				○ User restricted from sending email	Initial Access	Valid Accounts	High
				○ User restricted from sharing forms and collecting responses	Lateral Movement	Internal Spearphishing	High
				Medium Severity Alerts:			
				○ Access granted to a users mailbox	Initial Access	Valid Accounts	Medium
				○ AccessGovernance	Privilege Escalation	Valid Accounts	Medium

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields			
				○ Activities from suspicious user agents	Exfiltration	Exfiltration Over C2 Channel	Medium
				○ Activity from an anonymous proxy	Command and Control	Proxy	Medium
				○ Activity from infrequent country	Defense Evasion	Unused/Unsupported Cloud Regions	Medium
				○ Add or remove delegated permission	Collection	Email Collection	Medium
				○ Admin triggered user compromise investigation	XDR UBA	XDR Suspicious User	Medium
				○ Altum Capital Forward/Redirect Rule	Collection	Email Collection	Medium
				○ Colleague Global Login	Initial Access	Valid Accounts	Medium
				○ Data Leaks - General	Exfiltration	Exfiltration Over Web Service	Medium
				○ Delegate Permissions on Mailbox	Persistence	Account Manipulation	Medium
				○ Email sending limit exceeded	Initial Access	Valid Accounts	Medium
				○ External File Share Policy	Exfiltration	Exfiltration Over Web Service	Medium
				○ Forwarding	Collection	Email Collection	Medium
				○ Granted mailbox permission	Persistence	Account Manipulation	Medium
				○ Granted mailbox permissions	Persistence	Account Manipulation	Medium
				○ Impossible travel activity	XDR UBA	XDR Location Anomaly	Medium
				○ Inbox Rule Modification	Collection	Email Collection	Medium
				○ InsiderRiskManagement	XDR UBA	XDR Anomaly	Medium
				○ ISP for an OAuth App	Credential Access	Steal Application Access Token	Medium
				○ Mailbox Permission Change Alert	Collection	Email Collection	Medium
				○ MailFlow	XDR UBA	XDR Anomaly	Medium
				○ Mass delete	Impact	Data Destruction	Medium
				○ Mass download	Exfiltration	Data Transfer Size Limits	Medium
				○ Mass download by a single user	Exfiltration	Data Transfer Size Limits	Medium
				○ Messages containing malicious entity not removed after delivery	Initial Access	Phishing	Medium
				○ Multiple failed login attempts	Credential Access	Brute Force	Medium

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields

○ Multiple failed user log on attempts to an app	Credential Access	Brute Force	Medium
○ Multiple failed user logon attempts to a service	Credential Access	Brute Force	Medium
○ Suspicious Amount of files being moved	Impact	Data Destruction	Medium
○ Suspicious email deletion activity	Impact	Data Destruction	Medium
○ Suspicious email sending patterns detected	Initial Access	Valid Accounts	Medium
○ Suspicious Power BI report sharing	Persistence	Account Manipulation	Medium
○ ThreatManagement	XDR UBA	XDR Anomaly	Medium
○ Transom Forwarding/Redirect Rule	Collection	Email Collection	Medium
○ Unusual volume of external file sharing	Exfiltration	Exfiltration Over Web Service	Medium
○ Unusual volume of file deletion	Impact	Data Destruction	Medium
○ Users targeted by phish campaigns	Initial Access	Phishing	Medium
Low Severity Alerts:			
○ Alert when file is shared externally	Exfiltration	Exfiltration Over Web Service	Low
○ Block cut/copy and paste based on real-time content inspection	Persistence	Account Manipulation	Low
○ Block download on personal devices	Initial Access	Drive-by Compromise	Low
○ CC_User-reported messages	Initial Access	Phishing	Low
○ Compliance Manager Default Alert Policy	Initial Access	Phishing	Low
○ DataGovernance	Exfiltration	Exfiltration Over Web Service	Low
○ Elevation of Exchange admin privilege	Privilege Escalation	Valid Accounts	Low
○ Email Quarantined	Initial Access	Phishing	Low
○ Email reported by user as junk	Initial Access	Phishing	Low
○ Email reported by user as malware or phish	Initial Access	Phishing	Low
○ Email reported by user as not junk	Initial Access	Phishing	Low
○ Flextrade Billing account notification	XDR UBA	XDR Anomaly	Low
○ Mailbox access test Cloud App	Initial Access	Valid Accounts	Low
○ Other	XDR UBA	XDR Anomaly	Low
○ Repeat users contributing to incidents	Persistence	Valid Accounts	Low
○ Sharepoint File Deletion	Impact	Data Destruction	Low
Info Severity Alerts:			

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
				◦ Access Agreement Template Accessed — Privilege Escalation — Valid Accounts — Info ◦ Admin submission result completed — XDR UBA — XDR Anomaly — Info ◦ Admin triggered manual investigation of email — XDR UBA — XDR Anomaly — Info ◦ Administrative action submitted by an Administrator — XDR UBA — XDR Anomaly — Info ◦ Creation of forwarding/redirect rule — Collection — Email Collection — Info ◦ eDiscovery search started or exported — Discovery — Account Discovery — Info ◦ Email messages containing malicious file removed after delivery — Initial Access — Phishing — Info ◦ Email messages containing malicious URL removed after delivery — Initial Access — Phishing — Info ◦ Email messages containing malware removed after delivery — Initial Access — Phishing — Info ◦ Email messages containing phish URLs removed after delivery — Initial Access — Phishing — Info ◦ Email messages from a campaign removed after delivery — Initial Access — Phishing — Info ◦ Email messages removed after delivery — Initial Access — Phishing — Info ◦ Malware not zapped because ZAP is disabled — Initial Access — Phishing — Info ◦ Phish delivered because a user's Junk Mail folder is disabled — Initial Access — Phishing — Info ◦ Phish delivered due to an ETR override — Initial Access — Phishing — Info ◦ Phish delivered due to an IP allow policy — Initial Access — Phishing — Info ◦ Phish not zapped because ZAP is disabled — Initial Access — Phishing — Info ◦ Remediation action taken by admin on emails or URL or sender — Initial Access — Phishing — Info ◦ Removed an entry in Tenant Allow/Block List — Defense Evasion — Impair Defenses — Info ◦ Tenant Allow/Block List entry is about to expire — XDR UBA — XDR Policy Anomaly — Info ◦ User requested to release a quarantined message — Initial Access — Valid Accounts — Info
Microsoft Sentinel	Microsoft Sentinel incidents Refer to Incidents. The integration focuses exclusively on Microsoft Sentinel Incident data and only	Azure Event Hub Connector This connector ingests logs from the content type,	Stellar Cyber maps Microsoft Sentinel incidents. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `microsoft_senti`	• msg_origin.source: `azure_eventhub` • msg_class: `microsoft_sentinel` • Event (Alert) Name: Microsoft Sentinel Incident: with the assigned Technique, for example `Microsoft Sentinel Incident: Unfamiliar sign-in properties` • Severity: Derived from original severity from Microsoft Sentinel • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	[redacted] supports data transferred through Azure Event Hub.	Microsoft Sentinel, to get the raw alerts that are stored in the Syslog index.	`nel.IncidentName`.	
Microsoft Threat Intelligence (Graph Security API) 6.6.0	Graph Security API alerts	Microsoft Graph Security API Connector This connector ingests logs from Graph Security API to get the raw alerts that are stored in the Windows Events index. Select the Alert content type.	Stellar Cyber maps Microsoft Threat Intelligence alerts. The alerts are read from the Windows Events index, enriched with Stellar Cyber fields, and mapped to the Alerts index. Deduplication is by `tenantid` and `microsoft_graph_security_api.id`.	• msg_origin.source: `microsoft_graph_security_api` • msg_class: `microsoft_threat_intelligence_alerts` • Event (Alert) Name: Microsoft Threat Intelligence: with the event.threat.name, for example `Microsoft Threat Intelligence: Connection to known threat actor infrastructure` • Severity: Derived from `event.severity_str`: ◦ High: 75 ◦ Medium: 55 ◦ Low: 35 ◦ Informational: 15 ◦ Unknown: 15 ◦ Unknown future value: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Mimecast 6.0.0	Mimecast alerts There are the following types of alerts: • Mimecast Attachment Protect safeguards against spear phishing and other targeted attacks using email attachments • Mimecast AV/AntiVirus protects users by checking	Mimecast API 1.0 Connector Mimecast API 2.0 Connector This connector ingests	Stellar Cyber maps Mimecast alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication for Mimecast API 1.0 is by the following fields: • Attachment Protect and	• msg_origin.source: `mimecast_email` (for Mimecast API 1.0) and `mimecast2_email` (for Mimecast API 2.0) • msg_class by event log type: ◦ `mimecast_email_attachment_protect_log` for Mimecast Attachment Protect logs ◦ `mimecast_email_av_log` for Mimecast AV logs ◦ `mimecast_email_impersonation_protect_log` for Mimecast Impersonation Protect logs ◦ `mimecast_email_internal_email_protect_log` for Mimecast Internal Email Protect logs ◦ `mimecast_email` for Mimecast Malicious Receipt logs ◦ `mimecast_email_url_protect_log` for Mimecast URL Protect logs ◦ `mimecast2_email_mta_log` for other logs • Event (Alert) Name: Mimecast <event log type>: with the assigned Technique, for example `Mimecast Attachment Protect: Phishing` • Severity: 45, except for Mimecast URL Protect, which has Severity: 75 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	the content again for new malware released • Mimecast Impersonation Protect defends against emails that impersonate people and brands • Mimecast Internal Email Protect detects email-related security threats that originate from within an email system • Mimecast Malicious Receipt Log is Mail Transfer Agent (MTA) data that contains a virus found by Mimecast • Mimecast URL Protect blocks malicious URLs Refer to "Log Field Descriptions" in Understanding SIEM Logs: Targeted Threat Protection - Attachment Protect logs, AV logs, Targeted Threat Protection - Impersonation Protect logs, Target Threat Protection - Internal Email Protect logs, Receipt logs, Targeted Threat Protection - URL Protect logs	logs from Mimecast to get the raw alerts that are stored in the Syslog index. Select the MTA Log content type.	AV/AntiVirus—`tenantid`, `srcip`, `file.hash.md5`, `email.sender.address`, and `email.recipient.addresses`. • Impersonation Protect, Internal Email , and Malicious Receipt—`tenantid` and `mimecast.aCode`. • URL Protect—`tenantid`, `srcip`, `url`, `email.sender.address`, and `email.recipient.addresses`. Deduplication for Mimecast API 2.0 is by the following fields: • Impersonation Protect, Internal Email, and Malicious Receipt Log—`tenantid` and `mimecast.processingId`	
Netskope	Netskope Alerts The following types are supported: • Netskope Alert 5.5.0 • Netskope Alert (Breach) • Netskope Alert (Connection) • Netskope Alert (Malsite)	Netskope Connector This connector ingests logs from Netskope to get the	Stellar Cyber maps Netskope alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by the following fields: • All types—`tenantid`, `user.name`, `host.name`,	• msg_origin.source: `netskopewsg` • msg_class: `netskopewsg_alert` • Event (Alert) Name: ◦ Netskope Alert: with the assigned Technique, for example `Netskope Alert: DLP` or `Netskope Alert: uba` or `Netskope Alert: policy` or `Netskope Alert: ips` 5.5.0 ◦ Netskope Alert (Breach): with the assigned Technique, for example `Netskope Alert (Breach): Drive-by Compromise` ◦ Netskope Alert (Connection): with the assigned Technique, for example `Netskope Alert (Connection): Web Service` ◦ Netskope Alert (Malsite): with the assigned Technique, for example `Netskope Alert (Malsite): Cryptocurrency Mining` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		raw alerts that are stored in the Syslog index. Select the Alert content type.	and `netskopewsg._event_id`. 5.5.0 Breach—`tenantid`, `user.name`, and `netskopewsg.breach_id`. • Connection—`tenantid`, `user.name`, and `netskopewsg.connection_id`. • Malsite—`tenantid`, `user.name`, and `netskopewsg.malsite_id`.	
Oracle Cloud Infrastructure (OCI) Cloud Guard	OCI CloudGuard Alerts Refer to OCI CloudGuard.	OCI Streaming Connector This connector ingests logs from OCI to get the raw alerts that are stored in the Syslog index.	Stellar Cyber maps OCI CloudGuard alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid`, `oracle.data.additionalDetails.tenantId`, `event.threat.name`, and `cloud.resource.id`.	• msg_origin.source: `oracle_cloud_infrastructure` • msg_class: `oracle_cloud_guard` • Event (Alert) Name: OCI CloudGuard: with the assigned Technique, for example `OCI CloudGuard: Modify Cloud Compute` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Palo Alto Networks CORTEX XDR 6.1.0	Palo Alto Networks CORTEX XDR Alerts There are the following categories of alerts: • PAN NGFW • XDR Agent • XDR Analytics BIOC* • XDR BIOC* • XDR IOC * Behavioral Indicator of Compromise (BIOC)	Palo Alto Networks CORTEX XDR Connector This connector ingests logs from Palo Alto Networks CORTEX XDR to get	Stellar Cyber maps Palo Alto Networks CORTEX XDR alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `palo_alto_networks.alert_id`.	• msg_origin.source: `palo_alto_networks_cortex_xdr` • msg_class: `palo_alto_networks_cortex_xdr_alerts` • Event (Alert) Name: ◦ Palo Alto Networks Cortex XDR (PAN NGFW): with the palo_alto_networks.name, for example `Palo Alto Networks Cortex XDR (PAN NGFW): Generic Cryptominer Traffic Detection` ◦ Palo Alto Networks Cortex XDR (XDR Agent): with the palo_alto_networks.name, for example `Palo Alto Networks Cortex XDR (XDR Agent): Administrative Hash Exception` ◦ Palo Alto Networks Cortex XDR (XDR Analytics BIOC): with the palo_alto_networks.name, for example `Palo Alto Networks Cortex XDR (XDR Analytics BIOC): PowerShell runs suspicious base64-encoded commands` ◦ Palo Alto Networks Cortex XDR (XDR BIOC): with the palo_alto_networks.name, for example `Palo Alto Networks Cortex XDR (XDR BIOC): Process runs from the recycle bin` ◦ Palo Alto Networks Cortex XDR (XDR IOC): with the palo_alto_networks.name, for example `Palo Alto Networks Cortex XDR (XDR IOC): IOC (WinSCP.exe)` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		the raw alerts that are stored in the Syslog index. Select the Alerts content type.		
Palo Alto Networks Prisma Cloud 6.4.0	Palo Alto Networks Prisma Cloud alerts	Prisma Cloud Connector This connector ingests logs from Palo Alto Networks Prisma Cloud to get the raw alerts that are stored in the Syslog index. Select the Alert content type.	Stellar Cyber maps Palo Alto Networks Prisma Cloud alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid`, `.palo_alto_networks_prisma_cloud.type`, `palo_alto_networks_prisma_cloud.audit_id`, `palo_alto_networks_prisma_cloud.incident_id`.	• msg_origin.source: `palo_alto_networks_prisma_cloud` • msg_class: `palo_alto_networks_prisma_cloud` • Event (Alert) Name: Prisma Cloud: with the event.threat.name, for example `Prisma Cloud: Explicitly Denied File` • Severity: Derived from `event.severity_str`: ◦ critical: 60 ◦ high: 50 ◦ medium: 30 ◦ moderate: 30 ◦ low: 10 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Proofpoint Targeted Attack Protection (TAP)	Proofpoint TAP Alerts There are the following categories of alerts: • Phish: Phishing is when attackers send malicious emails designed to trick people into falling for a scam. Typically, the intent is to get users to reveal financial information,	Proofpoint TAP Connector This connector ingests logs from Proofpoint TAP to get the raw alerts that are	Stellar Cyber maps Proofpoint TAP alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `email.from.address` and `email.sender.address`.	• msg_origin.source: `proofpoint_tap` • msg_class: `proofpoint_tap_event` • Event (Alert) Name: Proofpoint TAP: with the event type and the assigned Technique, for example `Proofpoint TAP messageBlocked: Phishing` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
	system credentials or other sensitive data. • Imposter: A scammer sets up an email address that looks like it is from your company. Then the scammer sends out messages using that email address. This practice is called spoofing, and the scammer is what we call a business email imposter. • Malware: Malware is a common cyber attack and an umbrella term for various malicious programs delivered and installed on end-user systems and servers. These attacks are designed to cause harm to a computer, server, or computer network, and are used by cyber criminals to obtain data for financial gain • Toad (Telephone-Oriented Attack Delivery): Toad is a type of social engineering attack that lures potential victims to contact fraudulent call centers managed by threat actors in attempts to steal credentials or install malware onto their systems. • Spam: Email spam, also known as junk email, refers to unsolicited email messages, usually sent in bulk to a large list of recipients.	stored in the Syslog index. Select the Events content type.	There are the following event types: • Proofpoint TAP messageBlocked • Proofpoint TAP messageDelivered • Proofpoint TAP clickBlocked • Proofpoint TAP clickDelivered	

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
Recorded Future 6.1.0	Recorded Future Alerts and Playbook Alerts For Playbook Alert, there are the following categories of alerts: • Domain Abuse • Novel Identity Exposure • Data Leakage on Code Repository • Cyber Vulnerability • Third Party Risk	Recorded Future Connector This connector ingests logs from Recorded Future to get the raw alerts that are stored in the Syslog index. Select the Alert and Playbook Alert content types.	Stellar Cyber maps Recorded Future alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by the following fields: • Alert—`tenantid` and `recorded_future.id`. • Playbook Alert—`tenantid` and `recorded_future.playbook_alert_id`.	• msg_origin.source: `recorded_future` • msg_class: `recorded_future_alert` and `recorded_future_playbook_alert` • Event (Alert) Name: ◦ Recorded Future Alert: with the rule name, for example `Recorded Future Alert: Company Email on Code Repository` ◦ Recorded Future Playbook Alert: with the rule name, for example `Recorded Future Playbook Alert: Domain Abuse` • Severity: Derived from `recorded_future.panel_status.risk_score` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
SentinelOne Cloud	Threats	SentinelOne Connector This connector can ingest Hosts, Threats, and Vulnerabilities. Of these, only **Threats** are relevant for alert mapping. Select the Threats content type.	The threat dataset includes a variety of fields that enable Stellar Cyber to map the native SentinelOne alerts to the Stellar Cyber alert index. For example, `threatInfo.classification` describes the event (such as Trojan). That and other fields in the `threatInfo` record support direct mapping of SentinelOne's MITRE | ATT&CK Tactic and Technique fields to Stellar Cyber's XDR Kill Chain. Deduplication is by `org_id`, `tenantid`, `host.name`,	• msg_origin.source: `sentinelone_endpoint` • msg_class: `sentinelone_threat_detection` • Event (Alert) Name: SentinelOne: with the assigned Technique, for example `SentinelOne: User Execution` • Severity: Derived from `threat` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are mapped from the `indicators` field set. If more than one value is present in the Tactic and/or Technique fields, Stellar Cyber software determines which pair of values reflects the most severe position in the XDR Killchain and uses that pair for mapping. If those source fields are empty, the Tactic is set to **XDR Malware**, Technique set to **XDR Miscellaneous Malware**, and Stage is set to **Propagation**.

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		For related SentinelOne Deep Visibility events, see Related Events for Alert Types.	`host.ip`, `file.name`, `file.path`, and `process.parent.name`. SentinelOne alerts are also deduplicated, for example, if a previously created alert is updated. This type of deduplication avoids old alerts being resent.	
SentinelOne Singularity Identity 6.3.0	SentinelOne alerts	SentinelOne Connector This connector ingests logs from SentinelOne to get the raw alerts that are stored in the Syslog index. Select the Unified Alerts content type.	Stellar Cyber maps SentinelOne alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `sentinelone.external_id`.	• msg_origin.source: `sentinelone_endpoint` • msg_class: `sentinelone_unified_alerts` • Event (Alert) Name: SentinelOne Singularity Identity: with the event.threat.name, for example `SentinelOne Singularity Identity: LDAP - Domain Information Discovery Detected` • Severity: Derived from `event.severity_str`: ◦ CRITICAL: 75 ◦ HIGH: 60 ◦ MEDIUM: 45 ◦ LOW: 30 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
SOCRadar 6.3.0	SOCRadar incidents	SOCRadar Connector This connector ingests logs from SOCRadar to get the raw alerts that are	Stellar Cyber maps SOCRadar incidents. The incidents are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `socradar.consolidated_alarm_id`.	• msg_origin.source: `socradar` • msg_class: `socradar_incidents` • Event (Alert) Name: Socradar: with the socradar.alarm_notification_texts.alarm_title, for example `Socradar: Supply Chain Activity Detected in Dark Web` • Severity: Derived from `event.severity_str`: ◦ INFO 15 ◦ LOW: 30 ◦ MEDIUM: 45 ◦ HIGH: 60 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		stored in the Syslog index. Select the Incidents content type.		
SonicWall Endpoint Security 6.3.0	SonicWall Endpoint Security alerts	SonicWall Endpoint Security Connector This connector ingests logs from SonicWall Endpoint Security to get the raw alerts that are stored in the Syslog index. Select the Alerts content type.	Stellar Cyber maps SonicWall Endpoint Security alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `sonicwall_theron.alert_id`.	• msg_origin.source: `sonicwall_theron` • msg_class: `sonicwall_theron_alerts` • Event (Alert) Name: SonicWall Endpoint Security: with the sonicwall_theron.reason, for example `SonicWall Endpoint Security: OnDownload` • Severity: Derived from `event.severity_str`: ◦ 4: 60 ◦ 3: 45 ◦ 2: 30 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Sophos Central	Sophos Alerts and Sophos Events	Sophos Central Connector This connector ingests logs from Sophos Central to get the raw alerts	Stellar Cyber maps Sophos alerts and events. The alerts and events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `sophos.id`.	• msg_origin.source: `sophos_events` or `sophos_alerts` • msg_class: `sophos_events` or `sophos_alerts` • • Event (Alert) Name: Sophos Alert: or Sophos Event: with the assigned Technique, for example `Sophos Alert: Data Encrypted for Impact` or `Sophos Event: User Execution` • Alert Subtype: `event.type` and `event.threat.name`, for example, `Event::Endpoint::WebFilteringBlocked` • Severity: Derived from `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		that are stored in the Syslog index. Select the Alerts and Events content types.	The subtype uses `sophos.type`. Only Endpoint-related alerts and events are integrated.	
Trellix (FireEye) Endpoint Security	Alerts	Trellix (FireEye) Endpoint Security HX The connector can be used for three data types but only **Alerts** are applicable for alert mapping. Select the Alerts content type.	Stellar Cyber identifies the FireEye data logged into the **Syslog** index. Records of the type Alerts are then normalized, enriched, and mapped to the **Alerts** index. The following fields are included as part of the Stellar Cyber alert description: `indicator.name` and `agent.url`. Each relevant Syslog record is compared against existing records in the Alert index and not added to that index if the values in the following fields match those of an existing record logged in the previous 24 hours: `org_id`, `tenantid`, `user.name`, `host.ip`, `event.name`, `file.path`, `process.path`. The following four alert types are supported: IOC, MAL, AMSI, and PROCGUARD. Tactic and Technique are based on alert type.	• msg_origin.source: `fireeye_hx` • msg_class: `fireeye_alerts` • Alert Subtype: ◦ IOC: `event.name` ◦ MAL: `event.threat.name` ◦ AMSI: `event.threat.name` ◦ PROCGUARD: `event.threat.name` • Event (Alert) Name: ◦ Fireeye IOC: with the assigned Technique, for example: `Fireeye IOC: XDR Indicator of Compromise` ◦ Fireeye MAL: with the assigned Technique, for example: `Fireeye MAL: User Execution` ◦ Fireeye AMSI: with the assigned Technique, for example: `Fireeye AMSI: Windows Management Instrumentation` ◦ Fireeye PROCGUARD: with the assigned Technique, for example: `Fireeye PROCGUARD: OS Credential Dumping` • Severity: Derived from alert source and severity level `event.severity_str` • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are assigned

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
			Deduplication is by the following fields: • AMSI—`tenantid`, `host.ip`, `host.name`, `event.url`, and `event.threat.name`. • IOC—`tenantid`, `user.name`, `host.ip`, `host.name`, `event.name`, `file.path`, and `process.executable`. • MAL—`tenantid`, `host.ip`, `host.name`, `event.url`, and `file.path`. • PROCGUARD—`tenantid`, `host.ip`, `host.name`, `event.url`, and `event.threat.name`.	
Trellix MVISION 5.5.0	Trellix MVISION Alerts	Trellix MVISION Connector This connector ingests logs from Trellix MVISION to get the raw alerts that are stored in the Syslog index. Select the Alerts content type.	Stellar Cyber maps Trellix MVISION alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `trellix_mvision.id`.	• msg_origin.source: `trellix_mvision` • msg_class: `trellix_mvision_edr_alerts` • Event (Alert) Name: Trellix MVISION: with the assigned Technique, for example `Trellix MVISION: Threat Detected` • Severity: Derived from `event.severity_str` and mapped to severity score: ◦ s5: 85 ◦ s4: 75 ◦ s3: 60 ◦ s2: 45 ◦ s1: 30 ◦ s0: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Trend Micro Cloud App Security 6.4.0	Trend Micro Cloud App Security events	Trend Micro Cloud App Security Connector	Stellar Cyber maps Trend Micro Cloud App Security events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped	• msg_origin.source: `trendmicro_cloud_app_security` • msg_class: `trendmicro_cas_logs_exchange`, `trendmicro_cas_logs_onedrive`, `trendmicro_cas_logs_sharepoint`, and `trendmicro_cas_logs_teams` • Event (Alert) Name: Trend Micro Cloud App Security: with the event.threat.name, for example `Trend Micro Cloud App Security: Malicious URLs` • Severity: Derived from `event.severity_str`: ◦ Dangerous: 75 ◦ Highly suspicious: 60 ◦ Suspicious: 45 ◦ Untested: 15 ◦ High Risk: 60

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		This connector ingests logs from Trend Micro Cloud App Security to get the raw alerts that are stored in the Syslog index. Select the Exchange, OneDrive, Sharepoint Log, and Teams content types.	(with deduplication) to the Alerts index. Deduplication is by `trendmicro_cloud_app_security.log_item_id`.	◦ Medium Risk: 45 ◦ Low RIsk: 30 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Trend Micro Vision One	Trend Micro Vision One Alerts	Trend Micro Vision One Connector This connector ingests logs from Trend Micro Vision One to get the raw alerts that are stored in the Syslog index.	Stellar Cyber maps Trend Micro Vision One alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `trendmicro_visionone.workbenchId`. Tactic and Technique are provided by the Trend Micro Vision One raw alerts field `trendmicro_visionone.matchedRules`.	• msg_origin.source: `trendmicro_visionone` • msg_class: `trendmicro_visionone_alerts` • Event (Alert) Name: Trend Micro Vision One: with the Trend Micro alert type (Model name), for example `Trend Micro Vision One: Suspicious File Creation in Uncommon Folder` • Severity: Derived from `event.severity_str` and mapped to: ◦ Critical: 75 ◦ High: 55 ◦ Medium: 35 ◦ Low: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
Varonis DatAdvantage	Varonis Alerts • File system operation • Directory services operation	Select the Alerts content type. Configure ingestion of CEF format logs to a Stellar Cyber sensor.	Varonis sends Syslog CEF events to Stellar Cyber, which maps Varonis DatAdvantage alerts to the Alerts index. Deduplication is by `tenantid`, `user.name`, `file.name`, `file.path`, and `event.threat.name`. To search the alerts in the Alerts index or to search the Original Records in the Syslog index, use the query: • `msg_class: (varonis_datadvantage_file_system_operation or varonis_datadvantage_directory_services_operation)`	• msg_origin.source: `varonis_datadvantage` • msg_class: `varonis_datadvantage_file_system_operation` or `varonis_datadvantage_directory_services_operation` • Alert Subtype: `varonis.rulename` • Event (Alert) Name: Varonis DatAdvantage: with the assigned Technique, for example `Varonis DatAdvantage: File and Directory Discovery` • Severity: Derived from CEF severity • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
VMware Carbon Black Cloud	Alerts of type CB Analytics, Device Control, and Watchlist	VMware Carbon Black Cloud Connector Select the Alert content type.	VMware Carbon Black alerts are assigned a MITRE technique / tactic / procedure (TTP) which is reformatted but otherwise preserved during mapping, except as noted below. **CB Analytics and Device Control:** • Alerts with a threat_cause_threat_category of NON_MALWARE, NEW_MALWARE, and KNOWN_MALWARE are directly mapped to the Alerts	• msg_origin.source: `carbonblack_cloud` • msg_class: `carbonblack_alert` • Event (Alert) Name: Carbon Black: with the assigned Technique, for example `Carbon Black: OS Credential Dumping` • Severity: Assigned based on `threat_cause_threat_category`, values range from 20-55 • Fidelity: Is Severity by default, except Watchlist alerts and alerts with threat category of UNKNOWN which receive a computed value from the ML/SA pipeline • Kill Chain & MITRE | ATT&CK values are derived from the `ttps` field of the `threat_indicators` record. If those fields are empty or the `threat_type` is UNKNOWN, the Tactic is set to **XDR Malware**, Technique is set to **XDR Miscellaneous Malware**, and Stage is set to **Persistent Foothold**. ORIGINAL FIELDS: In addition to the mapping of fields to Stellar Cyber Interflow fields, all of the original fields for this alert type are included in the Interflow record.

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
			index. The kill_chain_status values (RECONNAISSANCE, WEAPONIZE, DELIVER_EXPLOIT, INSTALL_RUN, COMMAND_AND_CONTROL, EXECUTE_GOAL, BREACH) are preserved and mapped to the Stellar Cyber XDR Kill Chain. • Alerts with a threat category value of RISKY_PROGRAM are assigned a Tactic of XDR Malware and Techinque of XDR PUA. • Alerts with threat category value of UNKNOWN are run through Stellar Cyber's ML/SA pipeline, to better ascertain the nature of the alert before mapping it to the Alert index. This type is assigned an Tactic of XDR EBA and Technique of XDR Anomaly **Watchlist**: This type of alert is considered noisy (generates a large volume of hits), so it is routed through the ML/SA pipeline using our Time Series Analytic and Rare models, along with deduplication, before being mapped to the Alerts index. This type of alert is classified as Tactic: XDR EBA with Technique: XDR Anomaly.	

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
			Deduplication is by `org_id`, `tenantid`, `event.type`, `host.external_ip`, `host.ip`, `process.name`, `event.description_id`, and `file.name`. VMware Carbon Black alerts are also deduplicated, for example, if a previously created alert is updated. This type of deduplication avoids old alerts being resent.	
Windows Defender Antivirus (free version only)	Events	Windows Agent Detection Logs ingested from a Windows Agent	These events are ingested to the Stellar Cyber Windows Events index. As of the v4.3.2 release, they are also now processed into the Alerts index. In these logs, multiple events correlate to a single case, such as event_id 1116 (malware detected), one with event_id 1117 (means malware is quarantined). Stellar Cyber manages this, tracking the events to the related case during the mapping process. Deduplication is by `tenantid`, `event.ms_incident_id`, `threat`, and `file.path`. To search the events in the Alerts index or to search the Original Records in the Windows Events index, use the query:	• msg_origin.source: `windows_agent` • msg_class: `Microsoft-Windows-Windows Defender` • Event (Alert) Name: WindowsDefenderAntivirus: with the assigned Technique, for example `WindowsDefenderAntivirus: XDR Trojan` • Severity: Derived from threat name and severity level `event.severity_str` • Fidelity: Is Severity by default • Kill Chain values are derived (not displayed if values are blank) • See also: ◦ `event.ms_incident_id` contains `Detection ID` ◦ `threat` contains `Threat name`

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
			• `msg_class:\"Microsoft-Windows-Windows Defender\" AND _exists_:event.ms_incident_id.keyword"`	
WithSecure Elements 6.3.0	WithSecure Elements detections	WithSecure Elements Connector This connector ingests logs from WithSecure Elements to get the raw alerts that are stored in the Syslog index. Select the Detections content type.	Stellar Cyber maps WithSecure Elements detections. The detections are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid`, `event.threat.name`, `user.name`, `process.hash.sha1`, `withsecure_elements.detectionId`, and `withsecure_elements.description`.	• msg_origin.source: `withsecure_elements` • msg_class: `withsecure_elements_detection` • Event (Alert) Name: WithSecure: with the withsecure_elements.name, for example `WithSecure: Powershell Memorystream` • Severity: Derived from `event.severity_str`: ◦ critical: 75 ◦ high: 60 ◦ medium: 45 ◦ low: 30 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived
Wiz 6.4.0	Wiz events	Wiz Connector This connector ingests logs from Wiz to get the raw alerts that are stored in the Syslog index. Select the Issues	Stellar Cyber maps Wiz events. The events are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index. Deduplication is by `tenantid` and `wiz.id`.	• msg_origin.source: `wiz` • msg_class: `wiz_issues` • Event (Alert) Name: Wiz Cloud Security: with the assigned Technique, for example `Wiz Cloud Security: Exploitation for Defense Evasion` • Severity: Derived from `event.severity_str`: ◦ critical: 70 ◦ high: 60 ◦ medium: 45 ◦ low: 30 ◦ info: 15 • Fidelity: Is Severity by default • Kill Chain & MITRE | ATT&CK values are derived

Third Party Service	Third Party Data Type	Ingestion Method	Mapping of Native Alerts to Stellar Cyber Alerts	Notable Interflow Fields
		content type.		

© 2026 Stellar Cyber . All rights reserved.