Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

# Log Parser Ports

**Learn more at Stellar Cyber Academy.**

The following link takes you to a course on the Stellar Cyber Academy technical training portal where you can learn more about this topic by watching the suggested lesson.

M03 Modular Sensor Concepts and Configuration (08h:56m)

Parsers for Normalization Into Interflow (18m:00s)

Discover how parsers work to normalize telemetry and metadata into Interflow records. Learn how to interpret logs from diverse sources, identify key data fields, and understand their significance in threat analysis.

The first time you access a link on the portal during a session, you must log in to access content.

Sections in this topic:


**Choosing an Ingestion Port**

**Generic Log Parsers**

**Vendor-specific Log Parsers**

- **Vendor-Specific CEF Parsers Introduced by Release**
- **Parsers that Support Line Breaks in Messages Delivered over TCP**


To receive and parse logs from devices on your network, Stellar Cyber Modular Sensors require open inbound ports. These ports are already open on Modular Sensors by default. If there are any firewalls in the data path between the log sources and a modular sensor, you must also open the appropriate ports on the firewalls. This topic lists the supported log parsers and related details, including the port each parser uses. Log parsers are organized in the following categories:

- Generic
- Vendor-specific

Also see: **Firewall Requirements** and **Common Log Formats**

Unless otherwise noted, the ports listed are applicable for both UDP and TCP.

During installation, the timezone for sensors are automatically set to UTC+0. Since the logs for some security products might only include the local time without a timezone, Stellar Cyber recommends that you set the sensor timezone to the same timezone as your security product.

## Choosing an Ingestion Port

Modular Sensors listen on port 514 by default. They then analyze the logs to determine the source device. In some cases, Stellar Cyber has specific ports to process industry standard log formats, as well as specialized parsers to process vendor-specific logs in a more detailed manner. Identifying a more specific port for a log type than port 514 provides the following benefits:

- It speeds up data ingestion and log parsing and increases sensor performance because the sensor already knows the source device.
- It retains the correct log source when the sensor forwards normalized logs as Interflow records to the Stellar Cyber Open XDR platform.

Use the following as a guide:

- If the logs are in standard **Common Event Format (CEF)**, **Log Event Extended Format (LEEF)**, or **JavaScript Object Notation (JSON)** format, forward to the data to the port specific to that standard as listed in **Generic Log Parsers**.
- If the logs are in standard **Syslog** format use the port applicable for that vendor.
- If the logs are in a specialized format such as a **Syslog** and use regular expressions, key-value pairs, or comma-separated values (csv), use the Vendor-specific ports.

## Generic Log Parsers

This table includes all supported generic log parser formats, the required firewall port, device type, and the associated Stellar Cyber index.

Use the `msg_origin.source` field in the Interflow to find the logs when threat hunting in the specified index.

In the Interflow, there are also fields for `msg_origin.processor.type`, which is always `log_forwarder` for log parsers, and `msg_origin.processor.name`, which stores specific components of the parser, such as the parser type (`cef`, `leef`).

When the Stellar Cyber Platform processes logs, it decides the index based on the data in the logs. For example, in the table the **Index** for LEEF is **Traffic (srcip), Syslog (otherwise)**. This means that the index will be **Traffic** if a source IP address is detected, or **Syslog** if not, in that order.

Following are the firewall ports to open for generic log formats, along with other useful details.

| Standard | Port | msg_origin.source | Index | Comments |
|---|---|---|---|---|
| CEF | 5143 and 5870 (TCP) | cef_device_vendor | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise)<br><br>The following vendor records are also indexed in IDPS/Malware Sandbox Events, with the threat field being normalized from logs as indicated below:<br>• If cef_device_vendor: Check Point, then the threat field is normalized from attack_information.<br>• If cef_device_vendor: F5, then the threat field is normalized from attack_type<br>• If cef_device_vendor: SentinelOne, then the threat field is normalized from classification | Stellar Cyber recommends using CEF, if available.<br><br>TCP port 5870 is for CEF messages that use octet counting and port 5143 is for messages that don't. |
| CEF2 | 5175 | cef_device_vendor | Traffic (srcip), Syslog (otherwise) | - |
| Generic capture | 5201 and 5871 (TCP) | generic_capture | Syslog | TCP port 5871 is for log messages that use octet counting and port 5201 is for messages that don't. |
| Generic syslog | 514 | - | - | Use only if you must use a log forwarder. |

| Standard | Port | msg_origin.source | Index | Comments |
|---|---|---|---|---|
| log HTTP JSON | 5200 (TCP) | httpjson | Syslog | When you configure your log forwarding for the HTTP JSON parser on this port, you must append /**httpjson** at the end of the URL of the target sensor. Example: http://<sensor-ip>:5200/httpjson |
| JSON stream | 5142 | json | Syslog | |
| JSON beats | 5044 | beats | Syslog | - |
| LEEF | 5522 | vendor | Traffic (srcip), Syslog (otherwise) | LEEF is primarily useful for logs from QRadar, for which LEEF was developed. |
| Linux S | 5555 | linux_syslogs | Syslog | - |

| Standard | Port | msg_origin.source | Index | Comments |
|---|---|---|---|---|
| syslog RFC3164 | 5140 | syslog | Syslog | - |
| RFC5424 | 5141 | syslog | Syslog | - |
| RFC5424Enhanced | 5589 | syslog_rfc5424 | Syslog | - |

# Vendor-specific Log Parsers

This table includes all supported vendor-specific parsers, the port on which parsers listen for log messages, log formats, device types, message types, and their associated Stellar Cyber indices.

The **Log Format** column states the format that log sources use when sending data to Stellar Cyber modular sensors. For information about the common log formats that Stellar Cyber parsers support, see **Common Log Formats**.

The **msg_origin.source** column specifies the vendor's product. Use the field in the Interflow to find the logs when threat hunting in the specified index. The **msg_origin.category** column specifies the overall category. In the Interflow, there are also fields for `msg_origin.processor.type`, which is always `log_forwarder` for log parsers, and `msg_origin.processor.name`, which stores specific components of the parser, such as the parser name.

The **Index** column indicates the fields that must be present (and not null) for the logged data to be entered into the respective index. In some cases, no specific field is required, so just the index name is listed. For many parsers, the remaining data that is not mapped to a specific index is "otherwise" and mapped into the Syslog index. For example, for FortiAnalyzer logs received on port 5542, data is added to the IDPS/Malware Sandbox Events index if the incoming field `vendor.attack_name` is not `null`. Data is added to the Traffic index if `dstip` is not `null`. The remaining data is added to the Syslog index. Use the `dev_type` field in the Interflow to find logs when threat hunting in the specified index.

## ICMP/IGMP Sent to Traffic Index

When using the table below, keep in mind that ICMP and IGMP traffic operates at Layer 3 in the OSI model and does not include port numbers. Stellar Cyber treats this traffic as though it includes all five tuples (source/destination addresses, source/destination ports, and protocol) and sends it to the **Traffic** index.

Log Format Legend

| | |
|---|---|
| RFC 3164 = RFC 3164: The BSD Syslog Protocol | KVP = key-value pairs |
| RFC 5424 = RFC 5424: The Syslog Protocol | JSON = JavaScript Object Notation |
| CEF = Common Event Format | HTTP JSON = HTTP protocol headers followed by JSON content |
| LEEF = Log Event Extended Format (used primarily for QRadar) | ( ) = optional |
| regex = regular expressions* | + = and |

Example: The log format `RFC 3164 + (regex)` means that logs include syslog messages formatted as specified in *RFC 3164: The BSD Syslog Protocol* and that the parser can apply regular expressions if needed. Log messages formatted according to RFC 3164 have a priority value, which encodes facility and severity, a timestamp, a hostname, and the log message. Regular expressions might optionally be applied to the log message to perform additional operations such as parsing complex messages, filtering logs, and extracting specific fields.

**About regex*: In Stellar Cyber parser documentation, “regex” indicates that a parser uses regular expressions to extract fields from a log because the raw log is not in a fixed position or standard delimiter-based structure. This does not mean the device outputs logs in a “regex format”. The other elements in the format (such as CSV, KVP, JSON, RFC 3164, RFC 5424)

describe how the remaining portion of the log is structured when sent by the device. After parsing, all logs are converted to Stellar Cyber Interflow records in JSON format.

Here's an example for which the log format is `regex + KVP`, shown before and after parsing it using regex:

Raw log before parsing:

```
<134>1 1377449842.514782056 MX84 ids-alerts signature=129:4:1 priority=3
timestamp=1377449842.512569 direction=ingress protocol=tcp/ip src=74.125.140.132:80
```

Interflow record after parsing the log with regex:

```
priority: 134

version: 1

timestamp: 1377449842.514782056

hostname: MX84

log_type: ids-alerts

signature_id: 129:4:1

priority_level: 3

event_timestamp: 1377449842.512569

direction: ingress

protocol: tcp/ip

source_ip: 74.125.140.132

source_port: 80
```

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| (OpnSense) Zenarmor plugin logs | 5604 | Sunny Valley Networks custom format | sunny_valley_networks_zenarmor | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| A10 vThunder Application Delivery Controller (ADC) 5.5.0 | 5882 | RFC 3164 + A10-specific log header + message | a10_vthunder_adc | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| AAA - Core (CEF) | 514 3 or 5870 | CEF | netiq_advance_auth | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog otherwise |
| Absolute Secure Endpoint 6.4.0 | 6078 | Absolute custom RFC 5424 header + custom CEF payload | absolute_secure_endpoint | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog otherwise |
| Accops | 3 a 2 6 | Accops custom format | accops | vpn | Traffic (srcip), Syslog otherwise |
| Ahnlab AIPS | 5 6 4 7 | Custom Label (RFC 3164 or RFC 5424) | ahnlab_aip | ngfw | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ahnlab Cloud Protection Platform 5.3.0 | 5 7 5 5 | CEF | ahnlab_cp | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ahnlab EDR (Endpoint Detection and Response) 5.5.0 | 5 8 8 3 | CEF + JSON | ahnlab_edr | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), |

## Vend sers Introduced by Release

Stella support parsing logs in Common Event Format (CEF) using built-in par of CEF parsers:

- **Parsers**: Parses CEF logs from recognized vendors with for that vendor's formatting. Vendor-specific CEF parsers extraction, normalization, and mapping into targeted Interflow the semantics of the vendor's log structure.
- Parses CEF logs from any device that does not match a known are normalized into general-purpose Interflow record fields e pair (KVP) mappings found in the CEF header and extension. CEF logs from unknown vendors.

When F parser is introduced in a sensor release, logs from that vendor —pre neric CEF parser—are reclassified and parsed using the new vendo esult in changes to field values in Interflow records, including `msg_c` in.vendor, `msg_class`, and others.

Such the following features behave:

- `msg_origin.source` or similar fields
- ion logic
- eports, or threat hunting views

To en fter a sensor upgrade, refer to the table below for a list of vendor-specif or updated in each release. For full parsing behavior changes, follow ease notes.

| Version | Name | ...sors Introduced or Updated | | | Link to Release Notes | | |
|---|---|---|---|---|---|---|---|
| | | t | | | | y | |
| | | | | | Notes | | Syslog (otherwise) |
| 6.5.0 | | Wall-1 (CEF) | | | Stellar Cyber 6.5.0s Release Notes | | |
| | EMS | 5 6 ) 5 7 | regex + KVP | ahnlab_ems | | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| | | his is the modular parser in Parser | | | | | |
| | | se Server (CEF) | | | | | |
| | EPP | 5 6 4 0 | regex + JSON | ahnlab_epp | | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| | | al (CEF) | | | | | |
| | | very Email Inspector (CEF) | | | | | |
| 6.4.0 | Policy Center | 5 t 5 ) 1 | AhnLab custom format | ahnlab_policy_center | Stellar Cyber 6.4.0s Release Notes | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| | | ole (CEF) | | | | | |
| | | nse (CEF) | | | | | |
| 6.3.0 | TrusGuard | 5 5 5 8 | grave accent-separated ( ` ) KVP | ahnlab_trusguard | Stellar Cyber 6.3.0s Release Notes | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| 6.2.0 | | | | | Stellar Cyber 6.2.0s Release Notes | | |
| | LOUD WAF 6.1.0 | 5 9 3 3 | PSV (pipe-separated-values) | aioncloud_waf | | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| | | Secura (CEF) | | | | | |

## Pars e Breaks in Messages Delivered over TCP

Most ... TCP use ASCII LF (represented as \n) as a TRAILER character to terr... s within the larger transmission. (This is the non-transparent-framir... ction 3.4.2 in RFC 6587 - Transmission of Syslog Messages over T... log uses LF (\n) as a line break within a message, parsers recog... as a TRAILER character and split it into multiple parts, depending on the number of line breaks involved. This results in the erroneous creation of multiple “messages” that are really just parts of one single message.

There with
LF (\ln which
the pa

| Versio | Name | sors Introduced or Updated | | | Link to Release Notes | |
|---|---|---|---|---|---|---|
| | | t | | | y | |
| | Ransomware Kill Switch | 5 6 0 | AirGap custom format | airgap_ran somware_k ill_switch | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| 6.0.0 | | 2 | | | Stellar Cyber 6.0.0s Release Notes | |
| | h | 5 1 4 3 or 5 8 7 0 | CEF | airwatch | iot | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| 5.5.0 | | 5 5 2 3 | | aix | Stellar Cyber 5.5.0s Release Notes | Traffic (event_time: time format of hour:minute: second), Syslog (otherwise) |
| 5.4.0 | WAF 6.3.0 | 6 0 6 0 | CEF | akamai_wa f_ecs | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| | _ucent Switch | 5 6 7 7 | Alcatel-Lucent custom format | alcatel_luc ent_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| 5.3.0 | Minerva Labs | | | | Stellar Cyber 5.3.0s Release Notes | |

sight on port 5621

port 5519

iance (ESA)

tion Firewall on port 5582

35

on port 6082

er on port 5188

cation on port 5751

ity Manager (ESM) / Nitro SIEM

rity on port 5610

ON parsers that listen on TCP 5200 also support LF line breaks

oduct is sending logs to TCP 5200 on a sensor, the URL doesn't
e product name to identify it. However, when there is more than
to differentiate them, include the product name. Example for

/sensor_ip_addr>:5200/httpjson or
_ip_addr>:5200/httpjson_avanan

pjson or httpjson_avanan

httpjson or httpjson_bitdefender_multiple_event

– httpjson or httpjson_ecs or httpjson_ecs_suricata

– httpjson or httpjson_ecs or httpjson_ecs_windows

json or httpjson_egnyte

– httpjson or httpjson_exium_sase

emetry – httpjson or httpjson_fs_telemetry_streaming

httpjson or httpjson_kubernetes

ZeroTrust EPP – httpjson or
reat_locker_zero_trust_epp

er supports HTTP JSON on other ports besides 5200. The
eceive logs formatted for HTTP JSON that contain LF line
essages.

ocker Zero Trust on port 5754

- HTTP Winlogbeat on port 5752

In add… 1 in RFC … ctet count… ined in this R…

The F… rt 5542 supports TCP multi-line messages in <PRI> key-value forma… (\n) trailer separation, the parser identifies a new message by detec… er followed by a key-value string. Older line-delimited TCP variar…

The F… so supports octet-counted framing as well as non-transparent framir… cter in a frame to determine which method is being used. If a log sent t… rser on TCP port 5517 contains an LF (\n) line break, then the octet-… used. Otherwise, either method works.

In sur… ted above can process logs that include \n and are sent over TCP. … nt over UDP because a UDP datagram contains just one syslog messa… ers don't need to separate multiple syslog messages from a single…

| Name | Version | Users Introduced or Updated | Link to Release Notes | | |
|---|---|---|---|---|---|
| AliCloud | 5.2.0 | 5 4 5 | RFC 3164 or RFC 5424 + regex | aliyun | paas | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Amazon Web Services WAF | 5.3.0 | 5 7 3 5 | RFC 3164 + Logstash header + JSON | aws_waf | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Android | | 5 6 0 5 | Google custom format for Android | android | unixlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Antaira Switch | 5.5.0 | 5 8 9 5 | RFC 5424 + regex | antaira_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Apache HTTP Server (HTTPD) | | 5 6 6 3 | RFC 3164 + custom header + regex | apache_httpd | weblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |


© 2026 Stellar Cyber . All rights reserved.

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| AQTRONiX WebKnight | 5658 | AQTRONiX custom format | aqtronix_webknight | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Aqua Cloud Native Application Protection Platform (CNAPP 2022.4) | 5656 | RFC 3164 + regex + KVP | aquasecurity_cnapp | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Arbor Peakflow SP | 5598 | Arbor Networks custom format | arbor_peakflow_sp | traffic | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Arcon PAM 5.5.0 | 5887 | JSON | arcon_pam | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Arista Networks Data Center Switch Router 5.2.0 | 5747 | RFC 3164 (with time zone and year in timestamp) | arista_data_center_switch_router | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Array Networks APV Series Load Balancing & App Delivery | 5680 | regex (specific to log_id) | array_networks_apv | netlogs | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | proto), Syslog (otherwise) |
| Array Networks ASF 1800 | 5675 | regex + KVP | array_networks_asf_1800 | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Array Networks Secure Access Gateway | 5537 | RFC 3164 | array_sag | vpn | Traffic (srcip), Syslog (otherwise) |
| Aruba ClearPass Policy Manager (CEF) | 5143 or 5870 | CEF | aruba_clear_pass | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Aruba Switch | 5577 | RFC 3164 or RFC 5424 + KVP | aruba_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Attrelogix EaziCloud 5.5.0 | 5905 | RFC 3164 | attrelogix_eazicloud | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Automox | 51 | Automox custom format | automox | patch | Syslog |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 83 | | | | |
| Avanan | 5681 | RFC 5424 + custom regex | avanan | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Avanan (HTTP JSON) | 52000 (TCP only) | HTTP JSON | avanan | email | Syslog |
| Avaya IP Office 6.6.0 | 6099 | RFC 3164 | avaya_ip_office | voip | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Avaya Switch | 5607 | Avaya custom format | avaya_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Aviatrix Firewall 5.3.0 | 5762 | RFC 3164 | aviatrix_firewall | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| AWS CloudWatch 6.4.0 | 6071 | JSON | aws_cloudwatch | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| AWS WAF (HTTP JSON) | 52000 (TCP only) | HTTP JSON | aws_waf | waf | Syslog |
| AXGATE Next Generation Firewall | 5703 | RFC 3164 + KVP | axgate_ngfw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Azure ATP (CEF) | 51443 or 58700 | CEF | azure_atp | iam | Traffic (srcip, srcport, dstip, dstports, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Azure MFA | 5528 | custom RFC 3164 | azure_mfa | iam | Traffic (srcip), Syslog (otherwise) |
| Barracuda email | 5559 | JSON | barracuda_email | email | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Barracuda firewall | 5524 | Barracuda Networks custom format | barracuda_fw | firewall | IDPS/Malware Sandbox Events (sub_dev_type: fw_threat or fw_av), Traffic (srcip), Syslog (otherwise) |
| Barracuda WAF | 5524 | Barracuda Networks custom format | barracuda_waf | waf | IDPS/Malware Sandbox Events (sub_dev_type: fw_threat or fw_av), Traffic (srcip), Syslog (otherwise) |
| Barracuda WAF 5.5.0 | 5880 | RFC 5424 + regex | barracuda_waf | waf | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| BeyondTrust BeyondInsight | 5621 | regex + KVP | beyondtrust_beyondinsight | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| BeyondTrust PasswordSafe | 5692 | RFC 3164 + KVP | beyondtrust_passwordsafe | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| BIO-key PortalGuard 6.2.0 | 5954 | RFC 5424 + regex | bio_key_portalguard | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Bitdefender (HTTP JSON) (Syslog JSON) Click here to configure log ingestion | 5200 (TCP only) 5142 | HTTP JSON or syslog JSON | bitdefender | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| BlackBerry CylancePROTECT & CylanceOPTICS | 51 | KVP | cylance cylance_op | endpoint | Traffic (srcip), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 77 | | tics cylance_protect | | Syslog (otherwise) |
| BlueCoat Proxy SG | 5576 | Broadcom custom format | bluecoat_proxysg | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Brocade switch (system & admin logs) | 5548 | RFC 3164 + regex | brocade_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| BullWall RansomCare 6.1.0 | 5928 | Timestamp + regex + HTML | bullwall_ransomcare | siem | Traffic (srcip, srcport, dstip, dstport, proto), Syslog (otherwise) |
| Calyptix UTM | 5161 | KVP | calyptix | firewall | IDPS/Malware Sandbox Events (ids.signature), Traffic (srcip), Syslog (otherwise) |
| Cato Networks Cato Security 6.5.0 | 6094 | Cato Networks custom JSON | cato_networks_cato_security | cloudsec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Centos Audit | 5673 | KVP | centos_audit | unixlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Centrify | 5165 | KVP | centrify | iam | Syslog |
| Cerberus FTP Logs | 5635 | regex | cerverus_ftp | unixlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Check Point - Application Control (CEF) | 5143 or 5870 | CEF | fw_checkpoint | firewall | IDPS/Malware Sandbox Events (threat, normalized from attack_information), Traffic (srcip, srcport,dstip, dstport, and proto), Syslog (otherwise) |
| Check Point - SmartConsole (CEF) 6.4.0 | 5143 or 58 | CEF | checkpoint_smart_console | netmgmt | IDPS/Malware Sandbox Events (threat_normalized from attack_information), Traffic (srcip, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 70 | | | | srcport, dstip, dstport, proto), Syslog (otherwise) |
| Check Point - Smart Defense (CEF) 6.4.0 | 5143 or 5870 | CEF | checkpoint_smart_defense | idps | IDPS/Malware Sandbox Events (threat_normalized from attack_information), Traffic (srcip, srcport, dstip, dstport, proto), Syslog (otherwise) |
| Check Point - URL Filtering (CEF) | 5143 or 5870 | CEF | fw_checkpoint | firewall | IDPS/Malware Sandbox Events (threat, normalized from attack_information), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Check Point Harmony Mobile | 6067 | priority + KVP | checkpoint_harmony_mobile | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| Check Point Quantum 6.0.0 | 5920 | Check Point custom syslog | checkpoint_quantum | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Check Point SandBlast Appliance 6.0.0 | 5915 | Check Point custom syslog | check_point_sandblast_appliance | idps | IDPS/Malware Sandbox Events (threat or ips), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| CheckPoint appliance | 5174 | KVP | fw_checkpoint_appliance | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| CheckPoint firewall | 5519 | RFC 5424 + KVP inside structured data (SD) | fw_checkpoint | firewall | Traffic (srcip), Syslog (otherwise) |
| CheckPoint Harmony Email & Collaboration 5.5.0 | 5879 | checkpoint-specific RFC 5425-like syslog | checkpoint_harmony_email_collaboration | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| CheckPoint Harmony EP | 5618 | regex + KVP | checkpoint_harmony_ep | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| CheckPoint SmartCenter 5.2.0 | 5741 | RFC 5424 | checkpoint_smartcenter | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| CheckPoint VPN-1 & FireWall-1 (CEF) | 514 3 or 5870 | CEF | fw_checkpoint | firewall | IDPS/Malware Sandbox Events (threat, normalized from attack_information), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco ACI | 5717 | two log formats | cisco_aci | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco ASA | 5518 | Cisco Systems custom format | fw_cisco_asa | firewall | Traffic (srcip), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Cisco Catalyst Firewal l | 5702 | regex + description | cisco_catalyst_fw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco Catalyst SD-WAN 5.2.0 | 5746 | NetFlow v9 | cisco_sd_wan | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco CUCM | 5532 | syslog + regex | cisco_cucm | voip | Syslog |
| Cisco ESA | 5562 | Cisco Systems custom format | cisco_esa | email | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco ESA | 5164 (deprecated) | Cisco Systems custom format | openldap_style | email | Syslog |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Cisco Firepower | 5168 | KVP | ips_fire_power | firewall | Traffic (srcip), Syslog (otherwise) |
| Cisco IKE | 5176 | KVP | ciscovpn | vpn | Syslog |
| Cisco IronPort | 5163 | Cisco Systems custom format | cisco_ironport | email | Syslog |
| Cisco IronPort (CEF) 5.5.0 | 5143 or 5870 | CEF | cisco_ironport | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco ISE | 5157 | KVP | ciscoise | asset | Syslog |
| Cisco MDS | 5563 | RFC 3164 + regex | cisco_mds | netlogs | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco Meraki | 5172 | syslog + regex | meraki | firewall | Traffic (srcip, srcport, dstip, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | dstport, and proto)<br>IDPS/Malware Sandbox Events (threat, or device_event_category, msg, signature, and event_severity),<br>Syslog (otherwise) |
| Cisco Meraki 6.1.0 | 5931 | Custom Cisco Meraki syslog format | cisco_meraki | firewall | Traffic (src_ip, src_port, dst_ip, dst_port, protocol), Syslog (otherwise)<br>IDPS/Malware Sandbox Events (threat, or device_event_category, msg, signature, and event_severity)<br>Syslog (otherwise) |
| Cisco NetFlow | 2055 | NetFlow v5 and v9 | netflow | traffic | Traffic |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 5 (UDP only) | | | | |
| Cisco routers and switches | 5158 | Cisco Systems custom format | cisco_router_switch | netlogs | Syslog |
| Cisco Secure Network Analytics (Stealthwatch) | 5719 | RFC 3164 + KVP | cisco_secure_network_analytics | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco UCS | 5579 | RFC 5424 + (regex) | cisco_ucs | unixlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cisco Umbrella | 5521 | CSV | cisco_umbrella | dnssec | Syslog |
| Cisco VPN | 5156 | Cisco Systems custom format | ciscovpn | vpn | Syslog |
| Cisco WLC | 5531 | syslog (regex) | cisco_wlc | wireless | Syslog |
| Cisco WSA 6.4.0 | 60 | RFC 3164 | cisco_wsa | web | Traffic (srcip, srcport, dstip, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 74 | | | | dstport, and proto), Syslog (otherwise) |
| Citrix ADC 6.5.0 | 6095 | RFC 5424 | citrix_adc | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Citrix Access Gateway | 5688 | Citrix Systems custom format | citrix_access_gateway | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Citrix NetScaler | 5166 | KVP | netscaler | netmgmt | Syslog |
| Citrix NetScaler (CEF) | 5143 or 5870 | CEF | netscaler | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Citrix XenServer 5.2.0 | 5732 | RFC 3164 + regex | citrix_xenserver | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Clavister NetWall 5.3.0 | 5760 | regex + KVP | clavister_netwall | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cloudflare 6.2.0 | 5945 | Custom syslog + JSON | cloudflare | cloudsec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cohesity 6.1.0 | 5942 | RFC 3164 header with RFC 5424 timestamp | cohesity | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ColorTokens 5.5.0 | 5884 | JSON | • colortokens (if the product_name field is empty or an unsupported value)<br>• colortokens_xshield (if product_name is xshield) | • misc (if the product_name field is empty or an unsupported value)<br>• firewall (if product_name is xshield)<br>• endpoint (if | • For Xshield: Traffic (if srcip, dstip, dstport, and proto contain data) Syslog (otherwise)<br>• For all others (Gatekeeper, Xprotect, or unidentified source): |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | • colortokens_gatekeeper (if product_name is gatekeeper)<br>• colortokens_xprotect (if product_name is xprotect) | product_name is gatekeeper)<br>• xdr (if product_name is xprotect) | Traffic (if srcip, srcport, dstip, dstport, and proto contain data)<br>Syslog (otherwise) |
| Commvault Commserve<br>5.3.0 | 574<br>0 | regex + KVP | commvault_commserve | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Commvault Metallic ThreatWise<br>5.2.0 | 573<br>6 | RFC 3164 + regex | commvault_metallic_threatwise | mdr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Comodo- CIS CCS (CEF) | 514<br>3<br>or<br>58 | CEF | comodo | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 70 | | | | |
| ConnectWise ScreenConnect 5.2.0 | 5744 | RFC 5424 (with custom structured data using KVP) | connectwise_screenconnect | remote_access | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Coraza WAF (HAProxy SPOA) 6.0.0 | 5913 | RFC 3164 | coraza_waf_spoa | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| CoreLight Sensor Click here to configure log ingestion | 5575 | JSON | corelight_sensor | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| CoSoSys Endpoint Protection | 5654 | RFC 5424 + custom KVP | cososys | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cowrie SSH/Telnet Honeypot 6.6.0 | 6206 | JSON | cowrie_ssh_telnet_honeypot | honeypot | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cribl default (Syslog JSON) | 51 | JSON | json | xdr | Traffic (srcip, srcport, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 42 | | | | dstip, dstport, and proto), Syslog (otherwise) |
| Cribl / NXLog (log -> NXLog ->Cribl) (Syslog JSON) | 5142 | JSON | microsoft | endpoint | Windows Events |
| CrowdStrike (Beats) | 5044 | JSON | crowdstrike | endpoint | Syslog |
| CrowdStrike (CEF) | 5143 or 5870 | CEF | crowd_strike_falcon_host | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| CTM360 Data Leakage Protection 6.4.0 | 6084 | RFC 5424 | ctm360_data_leakage_protection | dlp | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Custom Application JumpTo 6.6.0 | 6098 | JSON | custom_application_jumpto | miscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| CyberArk PTA (CEF) | 51 | CEF | cyberark | iam | Traffic (srcip, srcport, |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Click here to configure log ingestion | 43 or 5870 | | | | dstip, dstport, and proto), Syslog (otherwise) |
| Cygna Labs Cygna Auditor | 5718 | RFC 5424 + JSON | cygna_labs_cygna_auditor | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cynerio 5.2.0 | 5727 | RFC 5424 with syslog messages in structured data (SD) | cynerio | iot | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Cynet (CEF) | 514 3 or 5870 | CEF | cynet | xdr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| D-Link | 5189 | D-Link custom format | dlink | wireless | Traffic (srcip), Syslog (otherwise) |
| Darktrace - DCIP (CEF) 6.4.0 | 514 3 or | CEF | darktrace | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 5870 | | | | Syslog (otherwise) |
| Datto AP (Datto Wi-Fi) 6.4.0 | 60075 | RFC 3164 | datto_ap | wireless | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| DBSafer | 51881 | CSV | dbsafer | dlp | Syslog |
| Deep Instinct | 56288 | regex + KVP | deep_instinct | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| DefensX - DefensX (CEF) 6.5.0 | 51443 | CEF | defensx | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Dell EMC Data Domain 5.4.0 | 58744 | Modified RFC 3164 header + regex-parsable message | dell_emc_data_domain | unixlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Dell EMC PowerScale Isilon 6.1.0 | 5937 | PSV (pipe-separated-values) | dell_emc_powerscale_isilon | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Dell EMC Powerstore | 5683 | RFC 3164 + local header (RFC 5424) + message | dell_powerstore | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Dell iDRAC | 5566 | RFC 5424 + KVP | dell_idrac | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Dell Switch | 5578 | Dell Technologies custom format | dell_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Devolutions Remote Desktop Manager 6.5.0 | 6087 | Devolutions custom format + JSON | devolutions_remote_desktop_manager | remote_access | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| DHCP (Beats) | 5044 | JSON | dhcp | netmgmt | Traffic (srcmac), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| DHCPD (ISC DHCP) | 5554 | RFC 3164 + regex | dhcpd | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| DNSVault RPZdb | 5639 | regex + JSON | dnsvault_rpzdb | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Dragos (CEF) | 5539 | CEF | dragos | otsec | Traffic (srcip), Syslog (otherwise) |
| DrayTek Firewall | 5593 | DrayTek custom format | draytek_fw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ECS Suricata (HTTP JSON) | 52000 (TCP only) | HTTP JSON | suricata | ndr | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ECS Windows (HTTP JSON) | 52000 | HTTP JSON | microsoft_windows | endpoint | Windows Events (winlogevent) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | (TCP only) | | | | |
| eDictionary - eDictionary (CEF) | 514 3 or 5870 | CEF | edictionary | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| EfficientIP SOLIDserver DDI 5.3.0 | 5761 | RFC 3164 (hostname) | efficient_ip_solidserver | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Egnyte (Syslog JSON) (HTTP JSON) | 514 2 5200 (TCP only) | syslog JSON or HTTP JSON | egnyte | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Elastic Stack 6.2.0 | 59 | (RFC 3164 header) + JSON | elastic_stack | log_processing | Traffic (srcip, srcport, dstip, |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 50 | | | | dstport, and proto), Syslog (otherwise) |
| Ericom ZTEdge | 5603 | Ericom Software custom format | ericom_ztedge | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ericcson Cradlepoint Router 5.5.0 | 5886 | RFC 3164 | ericsson_cradlepoint_router | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ESET Cloud Office Security (COS) 5.5.0 | 5893 | RFC 5424 + JSON | eset_cos | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ESET PROTECT | 5655 | RFC 5424 + JSON | eset_protect | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Exium SASE (HTTP JSON) | 52000 (TCP | HTTP JSON | exium_sase | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | only) | | | | |
| ExtraHop (CEF) | 5143 or 5870 | CEF | extrahop | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Extreme AirDefense | 5612 | regex + KVP | extreme_airdefense | idps | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Extreme Controller | 5666 | RFC 3164 | extreme_controller | wireless | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ExtremeCloud IQ Site Engine | 5614 | regex + KVP | extreme_site_engine | asset | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Extreme Networks X690 | 5699 | regex | extreme_x690 | asset | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| F5 - ASM (CEF) | 514 3 or 587 0 | CEF | f5 | waf | IDPS/Malware Sandbox Events (threat, normalized from attack_type), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| F5 BIG-IP | 516 2 | F5 custom format | f5_big_ip | firewall | IDPS/Malware Sandbox Events (IDS signature), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| F5 Big-IP ASM 6.0.0 | 592 3 | CEF or KVP | f5_big_ip_asm | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| F5 BIG-IP LTM (Local Traffic Manager) 5.4.0 | 5765 | regex + KVP | f5_ltm | weblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| F5 BIG-IP Telemetry (HTTP JSON) | 52000 (TCP only) | HTTP JSON | f5_big_ip | firewall | Syslog |
| F5 Big-IP Virtual Edition 6.0.0 | 59222 | CSV + F5 custom format | f5_big_ip_virtual_edition | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| F5 IPI | 5536 | three log formats | f5_threat_intelligence | firewall | IDPS/Malware Sandbox Events (dev_type: /threat/), Traffic (dstip), Syslog (otherwise) |
| F5 iRule | 5536 | three log formats | f5_irule | firewall | IDPS/Malware Sandbox Events (dev_type: /threat/), Traffic (dstip), |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| F5 L7 DDoS | 5536 | three log formats | f5_l7ddos | firewall | IDPS/Malware Sandbox Events (dev_type: /threat/), Traffic (dstip), Syslog (otherwise) |
| F5 Mitigation | 5536 | three log formats | f5_ddos | firewall | IDPS/Malware Sandbox Events (dev_type: /threat/), Traffic (dstip), Syslog (otherwise) |
| F5 NGINX | 5151 | F5 custom format | nginx | weblogs | Syslog |
| F5 Silverline | 5536 | three log formats | f5_silverline | firewall | IDPS/Malware Sandbox Events (dev_type: /threat/), Traffic (dstip), Syslog (otherwise) |
| F5 VPN | 51887 | CSV | f5_vpn | vpn | Syslog |
| F5 WAAP 6.1.0 | 2834 | JSON | f4_waap | websec | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | proto), Syslog (otherwise) |
| F5 WAF | 5536 | three log formats | f5_waf | waf | IDPS/Malware Sandbox Events (dev_type: /threat/), Traffic (dstip), Syslog (otherwise) |
| FatPipe Networks SD-WAN | 5583 | FatPipe Networks custom format | fatpipe_sd_wan | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Firepower Management Center 5.3.0 | 5759 | RFC 3164 + regex | firepower_management_center | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Forcepoint - DLP (CEF) | 51443 or 58700 | CEF | forcepoint_dlp | dlp | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Forcepoint - Firewall (CEF) | 51443 | CEF | forcepoint | firewall | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | or 5870 | | | | proto), Syslog (otherwise) |
| Forcepoint Next-Generation Firewall (NGFW) 5.5.0 | 5891 | (syslog priority) + JSON | forcepoint_ngfw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Forcepoint Security (CEF) | 5143 or 5870 | CEF | forcepoint | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Forcepoint Web Security (Filebeat) 6.6.0 | 6101-62001 | RFC 5424 | beats_forcepoint_web_security | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Forescout | 5154 | Forescout Technologies custom format | forescout | asset | Syslog |
| Fortanix DSM (Data Security Manager) 5.5.0 | 5906 | RFC 5424 (description + fixed KVP) | fortanix_dsm | dlp | Traffic (srcip, srcport, dstip, dstport, proto), |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| FortiADC 5.2.0 | 5725 | syslog priority + KVP | fortinet_fortiadc | netlogs | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fortinet FortiAnalyzer | 5542 (UDP or TCP) | KVP | forti_analyzer | ndr | IDPS/Malware Sandbox Events (vendor.attack_name), Traffic (dstip), Syslog (otherwise) |
| Fortinet FortiAuthenticator | 5671 | RFC 3164 | fortinet_fortiauthenticator | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fortinet FortiEDR | 5661 | RFC 5424 + KVP | fortinet_fortiedr | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Fortinet Forticloud FortiClient EMS Cloud Endpoint Management Services | 5682 | regex + KVP | fortinet_forticlient_ems | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fortinet FortiDeceptor 6.1.0 | 5944 | KVP | fortinet_fortideceptor | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fortinet FortiGate | 5517 | KVP | fw_fortigate | firewall | Traffic (action), Syslog (otherwise) |
| Fortinet Fortigate 6.5.0<br>Note: Requires EAP participation to use. | 8517 (default) | RFC 5424, or RFC3164, or only a priority header with KVP | fortinet_fortigate | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), IDPS/Malware Sandbox Events (threat), Syslog (otherwise) |
| Fortinet Fortigate (CEF) | 5143 or 5870 | CEF | fw_fortigate | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Fortinet Fortigate Firewall (Filebeat) 6.3.0 | 5957 (5957–60057) | Beats (message contains syslog + KVP) | fw_fortigate | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fortinet FortiMail | 5616 | regex + KVP, or CEF | forti_mail | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fortinet FortiManager 5.5.0 | 5894 | syslog priority + KVP | fortinet_fortimanager | siem | Syslog |
| Fortinet FortiSandbox | 5648 | Fortinet custom format | fortinet_fortisandbox | asset | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fortinet Fortiswitch 5.5.0 | 5904 | Syslog + KVP | fortinet_fortiswitch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Fortinet FortiWeb | 5642 | sylog priority + KVP | fortinet_fortiweb | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fortra GoAnywhere MFT 6.5.0 | 6091 | Fortra custom format + RFC 5424 | fortra_goanywhere_mft | miscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| FreeRADIUS 5.3.0 | 5750 | RFC 3164 + regex | freeradius | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Fudo PAM 6.6.0 | 6096 | RFC 3164 | fudo_pam | pam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| FutureSystems WeGuardia SSL plus (SSL VPN) | 5651 | regex + pipe-separated ( \| ) KVP | future_systems_weguardia_ssl_plus | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| GHX Exchange 6.1.0 | 5932 | RFC 3164 + regex | ghx_exchange | saas | Threat (threat or ips, ids), Traffic (srcip, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | srcport, dstip, dstport, and proto), Syslog (otherwise) |
| GHX Vendormate 6.2.0 | 5947 | RFC 2164 + regex | ghx_vendormate | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Gigamon 6.1.0 | 5929 | CEF | gigamon | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Graylog | 5569 | (RFC 3164) regex (for Graylog format) | graylog | endpoint | Windows Events (winlogevent), IDPS/Malware Sandbox (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| GTB DLP 6.2.0 | 5951 | RFC 3164 + regex | gtb_dlp | dlp | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| Guardicore (CEF) | 514 3 or 587 0 | CEF | guardicore | cloudsec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HanDreamnet VIPM | 5676 | regex + KVP | handreamnet_vipm | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HAProxy | 5713 | RFC 5424 + JSON | haproxy | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HarfangLab EDR 6.4.0 | 6066 | RFC 3164 + JSON or RFC 5424 | harfanglab_edr | endpoint | IDPS/Malware Sandbox Events (threat, threat_id), Traffic (srcip, srcport, dstip, dstport, proto), Syslog (otherwise)s |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Hewlett Packard UNIX | 5585 | regex + KVP | hp-ux | unixlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Hillstone | 5514 | Hillstone Networks custom format | fw_hillstone | firewall | IDPS/Malware Sandbox Events log_type: threat), Traffic (log_type: traffic), Syslog (otherwise) |
| Hillstone NIPS 6.2.0 | 5949 | Custom StoneOS remote syslog | hillstone_nips | idps | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) or Traffic (hillstone_nips.log_type), Syslog (otherwise) |
| Hisun Global Core banking 6.3.0 | 60058 | Hisun custom header + { readable message or JSON } | hisun_global_core_banking | finance | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Hisun Global E-banking 5.4.0 | 5764 | Hisun custom header + readable message, or { Hisun custom header + JSON } | hisun_global_ebanking | finance | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| HPE Alletra 6.4.0 | 6079 | RFC 3164 + regex | hpe_alletra | storage | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| HPE iLO Amplifier Pack 6.4.0 | 6080 | RFC 3164 | hpe_ilo_amplifier_pack | it_mgmt | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| HPE Nimble Storage 5.2.0 | 5731 | RFC 3164 + KVP | hpe_nimble | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HPE Switch | 5595 | Hewlett Packard Enterprise custom format for switches | hpe_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HTTP Datto EDR 6.1.0 | 5927 | JSON | http_datto_edr | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| HTTP Google Cloud Armor 5.5.0 | 5896 | JSON | google_cloud_armor | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HTTP Google Kubernetes Engine 5.5.0 | 5907 | JSON | http_google_kubernetes_engine | cloudsec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HTTP Scx SmartEDR 5.5.0 | 5901 | JSON | scx_smart_edr | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HTTP ThreatLocker Zero Trust EPP 5.3.0 | 5754 | HTTP JSON (in an array) | threat_locker_zero_trust | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| HTTP Winlogbeat 5.3.0 | 5752 | HTTP JSON | winlogbeat | endpoint | Winlogevent (winlogevent), Syslog (otherwise) |
| IBM AS400 | 5632 | two log formats | ibm_i | ibm_os_logs | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| IBM WinCollect 5.4.0 | 5869 | RFC 3164 + (regex) | microsoft_windows_eventlog | endpoint | Winlogevent (winlogevent), Syslog (otherwise) |
| IIJ SWG 6.5.0 | 6086 | Internet Initiative Japan custom format | iij_swg | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Impero ContentKeeper | 5670 | syslog priority + JSON | impero_contentkeeper | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Imperva - SecureSphere 6.4.0 | 6065 | Imperva cusom CEF | imperva_secure_sphere | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Imperva - SecureSphere (CEF) | 51443 or 58700 | CEF | imperva_secure_sphere | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Incapsula SIEM Integration (CEF) | 511 | CEF | incapsula | waf | Traffic (srcip, srcport, |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 43 or 5870 | | | | dstip, dstport, and proto), Syslog (otherwise) |
| Indusface Web Application Firewall | 5582 | JSON | indusface_waf | waf | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Infoblox Data Connector (CEF) | 51443 or 5870 | CEF | infoblox | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Infoblox Network Identity OS (NIOS) | 5587 | Infoblox custom format | infoblox_nios | dnssec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Infocyte HUNT (CEF) | 51443 or | CEF | infocyte | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 5870 | | | | Syslog (otherwise) |
| Intrusion ATI (Applied Threat Intelligence) 5.4.0 | 5868 | RFC 3164 + (regex) | intrusion_ati | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| IPFIX | 4739 (UDP only) | NetFlow v5, v9, v10 | ipfix | traffic | Traffic |
| IRONSCALES (CEF) | 5143 or 5870 | CEF | ironscales_irontraps | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| IronWhale Eguard 6.2.0 | 5953 | RFC 3164 | ironwhale_eguard | miscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ISC BIND 6.0.0 | 59 | RFC 3164 + KVP | isc_bind | dnssec | Traffic (srcip, srcport, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 16 | | | | dstip, dstport, and proto), Syslog (otherwise) |
| Ivanti Connect Secure 5.3.0 | 5756 | RFC 5424 + regex | ivanti_connect_secure | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ivanti Endpoint Manager 5.3.0 | 5757 | RFC 5424 + regex | ivanti_endpoint_manager | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ivanti Pulse Secure | 5712 | RFC 5424 + JSON, or Ivanti custom format | ivanti_pulse_secure | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Jsonar Database Security Tool | 5586 | JSON | jsonar_db_security_tool | dblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Judy Security Email Protection 6.0.0 | 5919 | CEF | judy_security_email_protection | email | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| Judy Security Password Manager 6.0.0 | 5917 | JSON | judy_security_password_manager | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Juniper SRX | 5173 | KVP | fw_juniper_srx | firewall | Traffic (srcip), Syslog (otherwise) |
| Juniper SSG | 5516 | Juniper Networks custom format | fw_juniper_ssg | firewall | Traffic (srcip), Syslog (otherwise) |
| Juniper Switch | 5591 | Juniper Networks custom format | juniper_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| KasperskyLab (CEF) | 5143 or 5870 | CEF | kasperskylab | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Kaspersky Secure Mail Gateway 6.6.0 | 6205 | RFC 3164 | kaspersky_secure_mail_gateway | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Kaspersky Security Center | 5723 | RFC 5424 + KVP | kaspersky_security_center | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| KeeperSecurity Enterprise | 5710 | RFC5425 + JSON | keeper_security_enterprise | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Kemp Technologies Load Master LB | 5695 | RFC 5424 + Description | kemp_technologies_load_master_lb | weblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Keycloak | 5653 | RFC 5424 + KVP (values can be JSON) | keycloak | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Kubernetes (HTTP JSON) | 52000 (TCP only) | JSON | kubernetes | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| KVH CommBox Edge Gateway 6.3.0 | 6059 | KVP | kvh_commbox_edge_gateway | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Lancope - StealthWatch (LEEF) | 5522 | LEEF | lancope_stealthwatch | firewall | Traffic (srcip), Syslog (otherwise) |
| LanScope Cat | 5588 | MOTEX custom format | lanscope_cat | endpoint | Syslog |
| Lepide | 5607 | Lepide Software custom parser | lepide | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Libraesva Email Security Gateway (ESG) 5.2.0 | 5742 | RFC 3164 + regex | libraesva_esg | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise |
| Link11 WAAP 6.1.0 | 5934 | RFC 5424 + regex | link11_waap | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Linux Audit | 56 | Linux Audit custom format | linux_audit | unixlogs | Traffic (srcip, srcport, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 97 | | | | dstip, dstport, and proto), Syslog (otherwise) |
| Linux Syslog | 5555 | RFC 3164 or RFC 5424 + regex | linux_syslog | unixlogs | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| LiquidFiles 5.3.0 | 5753 | RFC 3164 + JSON | liquid_files | miscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Logstash Suricata | 5629 | regex + KVP (JSON values) | logstash_suricata | ndr | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Mage Data Platform | 6085 | Mage Data custom format | mage_data_platform | dlp | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Mailboarder Agent | 5580 | RFC 3164 + regex | mailboarder_agent | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Mako Networks firewall | 5547 | RFC 3164 + regex | mako_fw | firewall | Traffic (dstip), Syslog (otherwise) |
| ManageEngine ADAudit Plus | 5679 | regex + KVP | manageengine_adaudit_plus | iam | Windows Events |
| ManageEngine ADAuditPlus (CEF) | 5143 or 5870 | CEF | manageengine | iam | Windows Events |
| ManageEngine Endpoint Central 6.6.0 | 6203 | RFC 5424 | manageengine_endpoint_central | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| ManageEngine OpManager Plus 6.5.0 | 6090 | RFC 5424 | manageengine_opmanager_plus | it_mgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ManageEngine PAM360 6.3.0 | 6062 | RFC 3164 + regex | manageengine_pam360 | pam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ManageEngine Site24x7 6.2.0 | 5948 | JSON | manageengine_site_24x7 | it_mgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| McAfee (CEF) | 5143 or 5870 | CEF | If **Web Gateway** is in the product name, dev_type is set to: mcafee_web_gateway<br>Otherwise the value is determined from the CEF vendor field | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| McAfee Advanced Threat Defense | 55 | JSON | mcafee_atd | ndr | Traffic (srcip, srcport, |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 84 | | | | dstip, dstport, and proto), Syslog (otherwise) |
| McAfee ePolicy Orchestrator | 5533 | RFC 5424 + XML | mcafee_epo | endpoint | Traffic (srcip), Syslog (otherwise) |
| McAfee - ESM / Nitro SIEM (CEF) 6.0.0 | 5143 or 5870 | CEF | mcafee_nitro | siem | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| McAfee Firewall | 5169 | KVP | mcafee_firewall | firewall | Traffic (srcip), Syslog (otherwise) |
| McAfee Network Security | 5527 | McAfee custom format | mcafee_ns | ipds | Traffic (srcip), Syslog (otherwise) |
| McAfee Proxy 5.2.0 | 5739 | RFC 3164 + KVP | mcafee_proxy | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| MCAS SIEM Agent (CEF) | 5143 or 58 | CEF | mcas | firewall | Windows Events |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 70 | | | | |
| Medigate | 5631 | RFC 5424 + regex + JSON; or RFC 3164 + regex + JSON | medigate | iotsec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Melapress WordPress | 5714 | custom log format | melapress_wordpress | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Menlo Security MS-XL50M | 5630 | regex (RFC 5424) + KVP | menlo | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Microsoft Exchange Server 5.4.0 | 5876 | RFC 3164 + syslog, or RFC 3164 + CSV | microsoft_exchange | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Microsoft IIS | 5636 | SSV | microsoft_iis | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Microsoft IIS (Syslog JSON) | 5142 | syslog + JSON | json | weblogs | Syslog |
| Microsoft Office 365 | 5627 | JSON | office365 | office_suite | Windows Events |
| Microsoft RDWebAccess 6.4.0 | 6068 | JSON | microsoft_rdwebaccess | remote_access | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Microsoft Windows Event | 5646 | regex + XML | microsoft_windows_event | endpoint | Windows Events (winlogevent), Syslog (otherwise) |
| Microsoft Windows via Graylog | 5569 | (syslog header) + regex or JSON | microsoft_windows | endpoint | Windows Events (winlogevent) |
| MicroWorld eScan | 5645 | regex + KVP | microworld_escan | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| MikroTik firewall and router | 5553 | RFC 3164 + regex | mikrotik | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Minerva Labs (CEF) 5.3.0 | 514 3 or 5870 | CEF | minerva_labs | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| MONITORAPP AI WAF 4.1 | 5613 | MONITORAPP custom format | monitorapp_ai_waf | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| MONITORAPP WAF 1.0 | 5535 | syslog (regex) | monitor_app | websec | Traffic (srcip), Syslog (otherwise) |
| Nasuni | 5592 | Nasuni custom format | nasuni | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| NetApp | 5608 | NetApp custom format | netapp | dblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| NetApp (Fabric Attached Storage) 6.0.0 | 5908 | RFC 3164 + ONTAP description | netapp_fas | storage | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| Netfilter | 5544 | RFC 3164 + KVP | netfilter | netlogs | Traffic (dstip), Syslog (otherwise) |
| Netgear Full Managed Switches M4300 5.3.0 | 5749 | RFC 3164 + regex | netgear_full_managed_switches | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Netgear Smart Switch 6.4.0 | 6069 | RFC 3164 + regex | netgear_smart_switch | netlog | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| NetIQ - Identity Manager | 5143 or 5870 | CEF | netiq_identity_manager | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| NetIQ Access Manager | 5167 | JSON | access_manager | iam | Syslog |
| NetIQ SSO | 5171 | KVP | netiqsso | iam | Syslog |
| Netman Smart NAC | 56 | regex + pipe-separated ( \| ) values | netman_smart_nac | iam | Traffic (srcip, srcport, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 50 | | | | dstip, dstport, and proto), Syslog (otherwise) |
| NetMotion | 5641 | RFC 5424 | absolute_netmotion | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| NetScout Omnis 6.3.0 | 6063 | (syslog priority) CEF | netscout_omnis | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| NetScout Omnis 6.5.0<br>Note: Requires EAP participation to use. | 9063 (default) | (syslog priority) CEF | netscout_omnis | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Nextcloud 6.1.0 | 5935 | RFC 3164 + JSON | nextcloud | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Nippon Electric Company Indoor Unit 6.0.0 | 5921 | RFC-3164 header + NEC custom syslog | nec_idu | netlogs | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | proto), Syslog (otherwise) |
| Nutanix NX 5.2.0 | 5724 | RFC 3164 + vendor header + KVP | nutanix_nx | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| NVIDIA Mellanox Switch 5.2.0 | 5734 | NVIDIA custom format | nvidia_mellanox_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| NXLog<br>(Also see Cribl, above) | 5601 | JSON (regex) | nxlog | paas | Windows Events (winlogevent), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| OneLogin | 5581 | JSON | one_login | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ONV Switch 6.6.0 | 6100 | RFC 5424 | onv_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | proto), Syslog (otherwise) |
| OpenCanary | 5638 | regex + JSON | opencanary | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| OpenIAM 5.5.0 | 5889 | RFC 3164 + KVP | openiam | iam | Syslog |
| OpenLDAP<br>(for Cisco ESA, use 5562) | 5164 | OpenLDAP custom format | openldap_style | email | Syslog |
| OpenShift | 5573 | RFC 5424 + (regex, JSON values) | redhat_openshift | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| OpenText - Open Enterprise Server (CEF) 6.5.0 | 5143 or 5870 | CEF | opentext_oes | asset | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| OpenVPN | 5643 | OpenVPN custom format | openvpn | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| OPNsense | 5660 | RFC 3164 | opnsense | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Oracle Audit Trail 6.6.0 | 6204 | JSON | oracle_audit_trail | database | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Oracle DB | 5170 | CSV | oracle | dblogs | Traffic (srcip), Syslog (otherwise) |
| Oracle Solaris | 5664 | RFC 3164 or RFC 5424 + regex | oracle_solaris | unixlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ordr Connected Device Security | 5622 | syslog + regex + JSON | ordr_cds | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| PacketFence | 5686 | regex + description | packetfence | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| Palo Alto Networks Next Generation Firewall (LEEF) | 5522 | LEEF | fw_palo_alto | firewall | Traffic (srcip), Syslog (otherwise) |
| Palo Alto Networks - Traps Agent (CEF) | 5143 or 5870 | CEF | palo_alto_networks_traps_agent | xdr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Palo Alto Networks Next-Generation Firewall and Panorama (BSD syslog and CSV) | 5515 | BSD syslog + CSV | fw_palo_alto | firewall | Traffic (type: traffic), IDPS/Malware Sandbox Events (type: threat), Syslog (otherwise) |
| Palo Alto Networks Firewall via Graylog | 5569 | (syslog header) + regex or JSON | fw_palo_alto | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Palo Alto Networks - Prisma Access (LEEF) 6.5.0 | 5522 | LEEF | palo_alto_networks_prisma_access | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), IDPS/Malware Sandbox Events (cat: threat), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| Palo Alto Networks Prisma Cloud (Compute Edition) | 5720 | RFC 3164 (with RFC 5424 for timestamp) + KVP | palo_alto_networks_prisma_cloud | cloudsec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| PCI MVApp 6.3.0 | 6061 | RFC 5424 | pci_mvapp | miscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Penta Security WAPPLES WAF | 5560 | KVP | penta_security_wapples | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Pentera Appliance 5.2.0 | 5737 | regex + KVP | pentera_appliance | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Peplink XDR | 5665 | RFC 5424 + KVP | peplink_xdr | xdr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Perception Point X-Ray | 5667 | RFC 5424 + KVP | perception point_xray | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| pfSense Firewall | 5543 | RFC 3164 or RFC 5424 | pfsense_fw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog |
| PIOLINK WEBFRONT-K | 5617 | regex + KVP | piolink_webfront_k | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| PNPSECURE NODESAFER | 5711 | (syslog priority + version + timestamp + hostname) + JSON | pnpsecure_nodesafer | dblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| PostgreSQL 6.4.0 | 6083 | RFC 3164 | postgresql | database | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| PrintChaser | 5179 | CSV | printchaser | dlp | Syslog |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Pritunl 5.3.0 | 5748 | JSON | pritunl | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Privacy-i | 5178 | CSV | privacy | dlp | Syslog |
| Progress Kemp LoadMaster (CEF) 6.0.0 | 5143 or 5870 | CEF | progress_kemp_lm | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Proofpoint | 5596 (5160 is deprecated) | Proofpoint custom format | proofpoint | email | Syslog |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Prophaze WAF 5.2.0 | 5733 | RFC 3164 + RFC 5424 timestamp + JSON | prophaze_waf | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Pulse Secure | 5534 | RFC 5424 + (regex) | pulse_secure | vpn | Syslog |
| QNAP QTS 5.2.0 | 5726 | RFC 3164 + log type + KVP | qnap_qts | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| QSAN Storage 5.5.0 | 5898 | Syslog | qsan_storage | websec | Syslog |
| Qumulo Core | 5704 | RFC 5424 + CSV | qumulo_core | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Radware Alteon | 5700 | RFC 3164 or RFC 5424 + description | radware_alteon | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Radware Cyber Controller Plus 6.0.0 | 59 | RFC 3164 + CSV | radware_cybercontrol | idps | Traffic (srcip, srcport, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 14 | | ler_plus | | dstip, dstport, and proto), Syslog (otherwise) |
| Radware Defense Flow 6.4.0 | 6082 | RFC 3164 or RFC 5424 | radware_defense_flow | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Radware DefensePro | 5619 | Radware custom format | radware_defense_pro | idps | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Radware WAF 6.6.0 | 6208 | JSON | radware_waf | waf | Threat (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Rapid7 | 5153 | KVP | rapid7 | security_scan | Syslog |
| RazLeeSecurity - Audit (CEF) | 5143 or 58 | CEF | ibm_raz_lee_security | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 70 | | | | |
| Relianoid WAF 5.2.0 | 5730 | RFC 3164 + regex | relianoid_waf | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| RSA Authentication Manager | 5184 | CSV | rsa_auth | nsa | Syslog |
| Ruckus SmartZone Network Controller 5.4.0 | 5875 | RFC 3164 + KVP | ruckus_smartzone_network_controller | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ruckus ZoneDirector | 5662 | RFC 3164 or RFC 5424 | ruckus_zone_director | wireless | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| RuiJie Switch | 5689 | regex + (custom value) + timestamp + (hostname) + %facility-severity-mnemonic + description | ruijie_switch | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SafePC | 5180 | CSV | safepc | cloudsec | Syslog |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Safetica Data Loss Prevention 6.6.0 | 6202 | RFC 5424 | safetica_dlp | dlp | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Salt Security 6.5.0 | 6088 | RFC 5424 + CEF | salt_security | cloudsec | IDPS/Malware Sandbox Events (ids), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Sangfor EDR | 5701 | regex + (RFC 3164) + JSON | sangfor_edr | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Sangfor Internet Access Gateway (IAG) 5.5.0 | 5890 | syslog + RFC 3164 | sangfor_iag | websec | Syslog |
| Sangfor NDR 6.2.0 | 5952 | RFC 3614 + CEF | sangfor_ndr | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Sangfor NGAF | 56 | regex + (RFC 3164) + KVP | sangfor_ngaf | firewall | Traffic (srcip, srcport, dstip, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 37 | | | | dstport, and proto), Syslog (otherwise) |
| SAP Backup 5.5.0 | 5897 | custom syslog | custom_backup_app | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SAP Security Audit 5.5.0 | 5881 | RFC 3164 Time modified + CSV | sap_security_audit | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Sectona PAM | 5721 | regex + CSV | sectona_pam | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SECUi Bluemax NGF 6.1.0 | 5938 | regex (header) + CSV (payload) | secui_bluemax_ngf | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SECUi Firewall | 5561 | RFC 5424 + KVP | secui_fw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| SECUi MF2 Firewall | 5570 | RFC 5424 + (regex) | secui_mf2 | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SECUi MFD | 5611 | SECUi custom format | secui_mfd | idps | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Secureki APPM | 5693 | RFC 3164 + regex | secureki_appm | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Security Strategy Research (SSR) Metieye | 5572 | SSR custom format | ssr_metieye | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SecurityGen IDS 6.0.0 | 5911 | JSON<br>or<br>RFC 3164 (optional priority) + JSON<br>or<br>syslog_appname + syslog_procid + JSON | securitygen_ids | idps | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SecurityGen NGFW 6.0.0 | 59 | JSON<br>or | securitygen_ngfw | firewall | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 10 | RFC 3164 (optional priority) + JSON<br>or<br>syslog_appname + syslog_procid + JSON | | | proto), Syslog (otherwise) |
| Secuwiz Secuway SSLVPN (U v1.0 / M v3.0, v3.1) | 5652 | Secuwiz custom format | secuwiz_secuway_sslvpn | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SentinelOne (CEF2)<br>Click here to configure log ingestion | 51775 | CEF | cef_device_vendor | endpoint | Traffic (srcip), Syslog (otherwise) |
| SentinelOne Mgmt (CEF) | 51443 or 58700 | CEF | sentinelone_endpoint | endpoint | IDPS/Malware Sandbox Events (threat, normalized from classification), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SentinelOne Security Center (CEF) | 51443 or 58 | CEF | sentinelone_endpoint | endpoint | IDPS/Malware Sandbox Events (threat, normalized from classification), Traffic (srcip, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 70 | | | | srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SentinelOne Singularity Mobile | 5623 | syslog + regex + JSON | sentineone_sm | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Seqrite Endpoint Security 6.1.0 | 5943 | Custom CEF (missing last two fields) | seqrite_endpoint_security | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Segura (CEF) 6.2.0 | 514 3 or 5870 | CEF | segura | pam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ServiceNow Now Platform | 5668 | RFC 3164 + KVP | servicenow_nowplatform | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ShareTech Firewall | 5609 | ShareTech custom format or KVP | sharetech_fw | firewall | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | proto), Syslog (otherwise) |
| Skyhigh Secure Web Gateway 6.4.0 | 6076 | RFC 3164 | skyhigh_secure_web_gateway | websec | IDPS/Malware Sandbox Events (threat, ids), Traffic (srcip, srcport, dstip, dstport, proto), Syslog (otherwise) |
| Snare Agent | 5590 | Prophecy International Holdings custom format | snare_agent | paas | Windows Events (winlogevent), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Sniper IPS | 5182 | KVP | sniperips | idps | Traffic (srcip), Syslog (otherwise) |
| Snowflake (CEF) 5.4.0 | 5143 or 5870 | CEF | snowflake_ghx | mscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SOCRadar 5.4.0 | 58 | RFC 3614 + JSON | socradar | ndr | Traffic (srcip, srcport, |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 72 | | | | dstip, dstport, and proto), Syslog (otherwise) |
| SoftEther VPN Server 6.5.0 | 6089 | SoftEther custom format | softether_vpn_server | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SolarWinds Serv-U 6.0.0 | 5924 | SolarWinds | solarwinds_serv_u | weblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SonicWall Firewall | 5152 | syslog + KVP | sonicfw | firewall | IDPS/Malware Sandbox Events (IDS signature), Traffic (srcip), Syslog (otherwise) |
| SonicWall Firewall (Filebeat) 5.4.0 | 5767with5767_58 | Beats (message contains syslog + KVP) | sonicfw | firewall | Threat (IDS), Threat (threat), Traffic (src IP), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 67 reserved | | | | |
| SonicWall NSa | 6064 | SonicWall custom CEF | sonicwall_nsa | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SonicWall - NSA 2400 (CEF) | 5143 or 58700 | CEF | sonicwall_nsa | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| SonicWall VPN | 5556 | RFC 3164 + regex | sonicwall_vpn | vpn | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Sophos (CEF) | 5143 or 58700 | CEF | sophos | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Sophos endpoint | 5565 | regex + KVP | endpoint_sophos | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Sophos endpoint (beats) | 5044 | JSON (Beats) | endpoint_sophos | endpoint | Traffic (srcip), Syslog (otherwise) |
| Sophos firewall | 5520 | KVP | fw_sophos | firewall | Data goes to the indicated index based on the log_type:<br>• If Firewall, then Traffic index<br>• If any one of IDP, Anti-Virus, Anti-Spam, or Content Filter it goes to IDPS/Malware Sandbox Events Index<br>• For any other log_type, if srcip exists then it goes to the Traffic Index |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | • All other data goes to the Syslog index |
| Sophos Switch 5.5.0 | 5888 | RFC 3164 + syslog | sophos_switch | netlogs | Syslog |
| Sophos Web Appliance | 5626 | Sophos custom format or KVP | sophos_web_app | websec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Spica Access Control 6.5.0 | 6092 | Spica custom format + JSON | spica_access_control | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Splashtop | 5698 | regex + JSON | splashtop | asset | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Splunk Heavy Forwarder | 5188 | Splunk custom format | splunk_forwarder | netmgmt | Syslog |
| Stormshield Net Security Firewall | 5625 | Stormshield custom format or KVP | stormshield_fw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| Symantec Endpoint Protection | 5525 | Symantec custom format | symantec_ep | endpoint | Traffic (dstip), Syslog (otherwise) |
| Symantec Firewal | 5155 | Symantec custom format | symantec | firewall | Syslog |
| Symantec Messaging Gateway | 5567 | Symantec custom format | symantec_messaging_gateway | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Symantec DLP (CEF) | 5143 or 5870 | CEF | symantec | symantec_dlp | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Synology Directory Server | 5597 | Synology custom format | synology_directory_server | asset | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Synology DiskStation Manager (DSM) 6.4.0 | 6072 | RFC 3164 | synology_dsm | storage | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Syslog4Net | 5715 | syslog (regex) | syslog4net | log_processing | Windows Events (winlogevent), Syslog (otherwise) |
| Tait Communications P25 Base Station 6.0.0 | 5912 | Tait Communications custom syslog | taitcommunications_p25_basestation | miscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Tait Communications RFSS Controller 6.1.0 | 5941 | RFC 3164 | taitcommunications_rfss_controller | miscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Tait Communications Tait Dynamic Analysis 6.1.0 | 5940 | RFC 5424 | taitcommunications_tait_dynamic_analysis | miscs | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| Tait Communications Tait EnableFleet 6.4.0 | 6081 | RFC 5424 | taitcommunications_tait_enable_fleet | netmgmt | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Tait Communications Tait EnableProtect 6.4.0 | 6077 | RFC 5424 | taitcommunications_tait_enable_protect | iam | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| Tenable AD 6.3.0 | 5955 | RFC 3164 + regex | tenable_ad | iam | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| Teramind CEF 5.4.0 | 5143 or 5870 | CEF | teramind | saas | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| Thales Group CipherTrust Manager | 5674 | RFC 3164 + local header + CEF header + message with JSON | thales_cipher_trust_manager | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| threatER Enforce 6.4.0 | 6073 | RFC 5424 | threater_enforce | threat_intel | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| ThreatLocker Zero Trust EPP | 5200 | JSON (in an array) | threat_locker_zero_trust_epp | endpoint | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | (TCP only) | | | | proto), Syslog (otherwise) |
| ThreatX 6.4.0 | 6070 | regex + JSON | threatx | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| TmaxSoft WebtoB 5.4.0 | 5877 | JSON | tmaxsoft_webtob | weblogs | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| Trellix EPO 5.5.0 | 5902 | RFC 5424 + XML | trellix_epo | endpoint | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| Trellix ESM (Enterprise Security Manager) 5.4.0 | 5873 | RFC 3164 + syslog | trellix_esm | siem | Traffic (src IP, src port, dst IP, dst port, and proto), Syslog (otherwise) |
| Trellix FireEye - CMS (CEF) 5.3.0 | 5143 or 58 | CEF | fireeye_cms trellix_cms | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 70 | | | | |
| Trellix FireEye - eMPS (CEF) 5.4.0 | 514 3 or 5870 | CEF | fireeye_emps trellix_emps | mdr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trellix FireEye - ETP (CEF) 5.4.0 | 514 3 or 5870 | CEF | fireeye_cms trellix_cms | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trellix FireEye - fMPS (CEF) 5.4.0 | 514 3 or 5870 | CEF | fireeye_fmps trellix_fmps | mdr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trellix FireEye HX | 5644 | CEF + regex | fireeye_hx | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trellix FireEye - HX (CEF) 5.4.0 | 514 | CEF | fireeye_hx trellix_hx | paas | Traffic (srcip, srcport, dstip, |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 3 or 5870 | | | | dstport, and proto), Syslog (otherwise) |
| Trellix FireEye - MAS (CEF) 5.4.0 | 5143 or 5870 | CEF | fireeye_mas trellix_mas | xdr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trellix FireEye - MPS (CEF) 5.3.0 | 5143 or 5870 | CEF | fireeye_mps | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trend Micro Apex Central (CEF) | 5143 or 5870 | CEF | trendmicro_apex_central | endpoint | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Trend Micro - Deep Discovery Email Inspector (CEF) 6.5.0 | 514 3 or 5870 | CEF | trendmicro_deep_discovery_email | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trend Micro Deep Security 6.3.0 | 5956 | LEEF (custom Trend Micro format) | trendmicro_deep_security | endpoint, asset, miscs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trend Micro - Deep Security Agent (LEEF) | 5522 | LEEF | trendmicro_dsa | endpoint | Traffic (srcip), Syslog (otherwise) |
| Trend Micro Interscan Messaging | 5678 | TSV | trend_micro_interscan_messaging | saas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Trend Micro Proxy | 5540 | syslog (regex) | trendmicro_proxy | websec | Traffic (dstip), Syslog (otherwise) |
| Trend Micro TippingPoint | 5672 | syslog priority + syslog timestamp + TSV | trend_micro_tippingpoint | idps | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Trend Micro Worry-Free Business Security Service Parser 6.6.0 | 6209 | Custom header + CEF | trend_micro_worry_free_business_security_service | endpoint | Threat (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Tripwire Enterprise | 5186 | KVP | tripwire | endpoint | Syslog |
| Ubika WAF 6.6.0 | 6097 | RFC 5424 | ubika_waf | waf | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ubiquiti UAP-AC-Pro | 5552 | RFC 3164 (with hostname) + regex | ubiquiti | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ubiquiti UDM Pro 6.1.0 | 5926 | RFC 3164 + regex + KVP | ubiquiti_udm_pro | cloudsec | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Ubiquiti UniFi Security Gateway 5.5.0 | 5900 | RFC 3164 + regex + KVP | ubiquiti_usg | netlogs | Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| UMV WSS (Web Server Safeguard) 5.2.0 | 5709 | RFC 3164 + regex | umv_wss | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Unix | 5633 | (RFC 3164) + regex | unix | unixlogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Untangle Firewall (Syslog JSON) | 5142 | syslog + JSON | json | firewall | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Varonis DatAdvantage (CEF) | 5143 or 5870 | CEF | varonis_datadvantage | dlp | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Vectra AI Platform 5.2.0 | 57 | RFC 3164 + KVP | vectra_ai_platform | xdr | IDPS/Malware Sandbox Events |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 38 | | | | (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Veeam Backup & Replication 5.3.0 | 5751 | RFC 5424 + regex, RFC 5424 + KVP | veeam_backup_replication | dlp | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Versa Networks Firewall | 5568 | RFC 3164 or RFC 5424 + KVP | versa_networks_fw | firewall | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Versa Networks Unified SASE Platform 5.4.0 | 5766 | CEF | versa_networks_sase | sase | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| VMware - Carbon Black (LEEF) | 5522 | LEEF | vmware_cb | endpoint | Traffic (srcip), Syslog (otherwise) |
| VMware | 56 | VMware custom format | vmware | unixlogs | Syslog |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 00 | | | | |
| VMware ESXi 5.5.0 | 5878 | Modified RFC 5424 + plain text or JSON | vmware_esxi | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| VMware Horizon | 5687 | RFC 5424 + description | vmware_horizon | paas | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| VMware NSX Edge Firewall 5.3.0 | 5758 | RFC 3164 + KVP (with Netfilter logs) | vmware_nsx_edge_firewall | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| VMware NSX-T Data Center | 5574 | regex + KVP (with JSON values) | vmware_nsx_t | endpoint (unless log type is dfwpktlogs, then category is firewall) | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| VMware UAG | 5620 | VMware custom format | vmware_uag | iam | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| VMware Vcenter | 56 | VMware custom format | vmware_vcenter | itsm | Traffic (srcip, srcport, dstip, |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | 15 | | | | dstport, and proto), Syslog (otherwise) |
| VMware VeloCloud SD-WAN | 5685 | regex + KVP or message | vmware_velocloud_sdwan | netmgmt | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Wallix Bastion 6.2.0 | 5948 | RFC 5424 | wallix_bastion | pan | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| WatchGuard - XTM | 5522 | LEEF | watchguard_fw | firewall | Traffic (srcip), Syslog (otherwise) |
| WatchGuard firewall security appliance | 5557 | RFC 3164 + regex | watchguard_fw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Wazuh SIEM | 5634 | (regex) + JSON | wazuh_siem | endpoint | Windows Events (winlogevent) , Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Windows DNS Server | 5599 | Microsoft custom format | windows_dns_server | weblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Windows Event NXLog<br>Click here to configure HostIP | 5601 | regex or JSON | microsoft_windows | endpoint | Windows Events (winlogevent), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Windows System Security | 5610 | Microsoft custom format | windows_system_security | endpoint | Windows Events (winlogevent), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Wins IPS ONE-1 / Wins DDX | 5538 | syslog with Splunk header + (regex) | winsips | idps | IDPS/Malware Sandbox Events (vendor.attack_name), Syslog (otherwise) |
| WINS Sniper NGFW | 5649 | regex + KVP | wins_sniper_ngfw | firewall | Traffic (srcip, srcport, dstip, dstport, and |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | proto), Syslog (otherwise) |
| WordPress 6.5.0 | 6093 | KVP | wordpress | weblogs | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Zecurion - DLP (CEF) 6.5.0 | 5143 | CEF | zecurion_dlp | dlp | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Zeek (NXLog method) | 5142 | JSON | json | json | Syslog |
| Zimbra Email 5.5.0 | 5899 | RFC 3164 + syslog | zimbra_email | email | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Zix Mail | 5185 | Zix custom format | zix_mail | email | Traffic (srcip), Syslog (otherwise) |
| Zscaler Deception 5.5.0 | 5909 | RFC 5424 + JSON | zscaler_deception | ndr | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |

| Parser Name | Pt | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| Zscaler NSSWeblog (CEF) | 514 3 or 587 0 | CEF | zscaler | websec | Syslog |
| Zscaler ZIA Firewall | 5549 | JSON | zscaler_zia_fw | firewall | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Zscaler ZIA Web | 5550 | JSON | zscaler_zia_web | weblogs | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |
| Zscaler ZPA | 5551 | JSON | zscaler_zpa | vpn | IDPS/Malware Sandbox Events (threat), Traffic (srcip, srcport, dstip, dstport, and proto), |

| Parser Name | Port | Log Format | msg_origin.source | msg_origin.category | Index |
|---|---|---|---|---|---|
| | | | | | Syslog (otherwise) |
| Zyxel Firewall | 5594 | regex + KVP | zyxel_fw | firewall | Traffic (srcip, srcport, dstip, dstport, and proto), Syslog (otherwise) |