Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Metadata Dictionary Subset

Stellar Cyber monitors your network to collect and respond to data reported from multiple sources such as network packets, endpoint telemetry, cloud logs, and threat intelligence feeds. Each type of data is handled differently before being populated into a standardized set of fields referred to as metadata. Where applicable, and based on your configuration and the type of content, the data may be de-duplicated, normalized, and enriched as it passes through sensors and the data processor, on its way to becoming part of an Interflow record.

The following tables list the metadata dictionary field names in the Stellar Cyber Interflow record, their description, and data type.

You can use these fields as part of your searches or queries that you build, along with vendor specific fields and values.

Alerts

Click here for table of Alert field names

Field Name	Description	Data Type
_id2	Elasticsearch ID of the earlier of two login records	string
_index2	Elasticsearch index of the earlier of two login records	string
accumulated_anomalous_failures	Score value of TRW model, showing the degree of abnormal activities	integer
actual	Real value input for machine learning (ML) to process	integer
actual_range	Actual login time range	string
anomaly_id	Elasticsearch ID of the data that caused the anomaly	string
days_silent	Time intervals between latest two appearances	integer
detected_field	Identification field of the detection	string
detected_fields	Identification field of the detection	list

Field Name	Description	Data Type
detected_value	Identification field's value of the detection	string
detected_values	Identification field's value of the detection	list
detector_index	Detector index in ML detections	integer
distance_deviation	Distance deviation between two login geo locations	float
diversity	Metric of a parent node's unique child nodes, the higher value, the more unique child nodes it has	integer
end_bucket_time	End timestamp of the data that caused the anomaly, combines with start_bucket_time to form a time range of data	timestamp
event_name	Event name for the job	string
event_score	Event score, combination of severity, fidelity, and threat_score	float
event_status	Current status of a given event record	string
event_summary	Namespace for summarized data points from records contributing to an alert	object
fidelity	How confident that machine learning thinks the attack is happening	float
last_login_time	Login time of the earlier of two login records	timestamp
login_failure_rate	Rate of login failures per minutes in a fixed period	float
num_failed	Number of fail in current bucket	integer
num_successful	Number of success in current bucket	integer
orig_id	Elasticsearch ID of the data that caused the anomaly	string
orig_index	Elasticsearch index of the data that caused the anomaly	string
percent_failed	Fail percentage = num_fail / (num_failed + num_successful)	float
possible_breached_ips	List of source IP addresses that have suspicious activities	list
query_count	Number of DNS queries in a tunnel	integer
severity	How serious is the event when it occurs	integer
srcip_geo2	Geo location of the earlier of two login records	object

Field Name	Description	Data Type
stability	Update frequen a parent node's number of child nodes, the higher value, the lower frequency	integer
start_bucket_time	Start timestamp of the data that caused the anomaly	timestamp
stellar.alert_time	Time the anomaly was detected	timestamp
stellar.confidence	Prediction output from the SVM classifier	float
stellar.detection_time	Original write_time - new write_time from pipeline, indicating the total time from the Original Records being written to ES to the time of alert creation	timestamp
stellar_index_id	Indicates the Stellar Cyber index from which the alert was generated. Can be used together with the **stellar_uuid** to identify an alert uniquely.	string
stellar.nearest_geo	Previous login location nearest to the alerted login location	object
stellar.nearest_geo_info	Count and frequency of logins from the nearest login location	object
stellar.rule_id	Identifier of the rule triggering an alert	string
stellar.threshold	Threshold used for detection	float
stellar_uuid	Universally unique identifier for the alert, assigned by Stellar. Can be used together with the **stellar_index_id** to identify an alert uniquely.	string
suspicious_ips	List of suspicious IP addresses that could do credential stuffing to a cloud service	list
time_deviation	Time deviation between two login times	float
total_entropy	Total entropy of DNS queries in a tunnel	float
travel_speed	Travel speed between two login locations	float
typical	Typical value that machine learning calculated	integer
typical_range	Typical login time range	string
unknown_users_rate	Rate of unknown login usernames per minutes in a fixed period	float
unknown_users_to_login_failures	Ratio of unknown usernames in login failures in a fixed period	float
xdr_event	XDR kill chain info of each alert, such as kill chain stage, tactic, technique, and so on	object

Traffic

Click here for table of Traffic field names

Field Name	Description	Data Type
action	Action to be taken	string
aella_tuples	Concatenated field of srcip+dstip+dstport+appid	string
appid	ID of an application (>3,000 apps) identified by DPI engine	long
appid_family	Name of the application family to which the application belongs	string
appid_name	Name of an application (>3,000 apps) identified by DPI engine	string
appid_stdport	Indicates if application is using the standard port	string
appid_tags	Tags of the application	list
direction	Direction of maltrace event	string
domain_list	List of domain	list_of_string
domain_reputation	Encoded string of a list of domain reputation separated by commas	string
dscp_name	Name describing the commonly used DSCP values in RFC 2475	string
dstip	Destination IP address of the session	ip
dstip_aella_flag	Flag to indicate how the IP address will be processed in following pipeline	integer
dstip_domain_creation	Creation time of the domains associated with the IP address	date
dstip_geo	Geo location information for the destination IP address	object
dstip_geo_point	Geo point of the destination IP address	string
dstip_host	Hostname or DNS name for the destination IP address	string
dstip_sig_id	Signature ID concatenated with dstip	string
dstip_tag	Asset tag associated with the destination IP address	string
dstip_type	Type of the destination IP address	string
dstip_username	Username associated with the destination IP address	string
dstip_usersid	User ID associated with the destination IP address, for windows, windows SID is used	string
dstip_version	Indicates if the destination IP address is IPv4 or IPv6	string
dstmac	Destination MAC address	string

Field Name	Description	Data Type
dstport	Layer 4 destination port	integer
duration	Session duration in milliseconds	integer
end_reason	Reason the session ended	integer
hostip	IP address the endpoint is using	ip
hostip_assetid	Asset ID associated with the IP address	string
hostip_domain_creation	Creation time of the domains associated with the IP address	date
hostip_geo	Geo location information for the host IP address	object
hostip_geo_point	Geo point of the host IP address	string
hostip_host	Host name of the host IP address	string
hostip_reputation	Reputation of the IP address	string
hostip_reputation_source	Source of the reputation data	string
hostip_sig_id	Signature ID concatenated with hostip	string
hostip_tag	Asset tag associated with the IP address	string
hostip_type	Type of the host IP address	string
hostip_username	Username associated with the IP address	string
hostip_usersid	User ID associated with the IP address, for windows, windows SID is used	string
hostip_version	Indicates if the IP address is IPv4 or IPv6	string
icmp_type	ICMP message type	string
in_bytes_delta	Same as inbytes_delta	integer
in_bytes_total	Same as inbytes_total	integer
in_rate	Incoming traffic rate, which is in_bytes_delta / <stats update time interval>	float
inbytes_delta	Number of bytes received by client from the server since last update time	integer
inbytes_total	Number of bytes received by client from the server during the whole session	integer

Field Name	Description	Data Type
inpkts_delta	Number of packets received by client from the server since last update time	integer
inpkts_total	Number of packets received by client from the server during the whole session	integer
mac	List of MAC addresses associated with the host, also from scan result	list
netid_name	Name of a network ID	string
out_bytes_delta	Same as outbytes_delta	integer
out_bytes_total	Same as outbytes_total	integer
out_rate	Outgoing traffic rate, which is out_bytes_delta / <stats update time interval>	float
outbytes_delta	Number of bytes sent to the server by client since last update time	integer
outbytes_total	Number of bytes sent by client to the server during the whole session	integer
outpkts_delta	Number of packets sent to the server by client since last update time	integer
outpkts_total	Number of packets sent to the server by client during the whole session	integer
remote_ip	IP address of the remote entity involved in an event	ip
remote_ip_domain_creation	Creation time of the domains associated with the IP address	date
remote_ip_geo	Geo location information for the remote IP address	object
remote_ip_geo_point	Geo point of the remote IP address	string
remote_ip_reputation	Reputation of the remote IP address	string
remote_ip_reputation_source	Source of the reputation data	string
remote_ip_type	Type of the remote IP address	string
remote_ip_username	Username associated with the remote IP address	string
remote_ip_usersid	User ID associated with the IP address, for windows, windows SID is used	string
remote_ip_version	Indicates if the IP address is IPv4 or IPv6	string
remote_port	Port of a remote entity involved in an event	integer
srcip	Source IP address of the session	ip

Field Name	Description	Data Type
srcip_assetid	Asset ID associated with the source IP address	string
srcip_domain_creation	Creation time of the domains associated with the source IP address	date
srcip_geo	Geo location information for the source IP address	object
srcip_geo_point	Geo point of the source IP address	string
srcip_geo2	Geo location of the earlier of two login records	object
srcip_host	Hostname or DNS name for the source IP address	string
srcip_reputation	Reputation of the source IP address identified by Threat Intelligence	string
srcip_reputation_source	Source of the reputation data	string
srcip_sig_id	Signature ID concatenated with srcip	string
srcip_tag	Asset tag associated with the source IP address	string
srcip_type	Type of the source IP address	string
srcip_username	Username associated with the source IP address	string
srcip_usersid	User ID associated with the source IP address, for windows, windows SID is used	string
srcip_version	Indicates if the source IP address is IPv4 or IPv6	string
srcmac	Source MAC address	string
srcport	Layer 4 source port	integer
state	Current state of the session	string
suspicious_ips	List of suspicious IP addresses that could do credential stuffing to a cloud service	list
tos	Type of Service (ToS) value in IP header	integer
total_entropy	Total entropy of DNS queries in a tunnel	float
totalbytes	Number of total bytes received and sent by client for the whole session	integer
totalpackets	Number of total packets received and sent by client for the whole session	integer

Vulnerabilities

Click here for table of Vulnerability field names

Field Name	Description	Data Type
info	Host IP and MAC addresses for asset tracking	object
scan_end	Timestamp of when the security scan ends	date
scan_start	Timestamp of when the security scan starts	date
vuln_count	Count of vulnerabilities	integer
vulnerabilities	List of vulnerabilities	list_of_object
vulnerability	Vulnerability information	object

Assets

Click here for table of Asset field names

Field Name	Description	Index	Data Type
data_sources	Integrations that discover or report the asset	Assets	array
desc	Description (likely unused or used by the end user)	Assets	string
device_class	Host and OS related info from a vulnerability scanner	Assets	string
device_desc	Host and OS related info from a vulnerability scanner	Assets	string
engid	ID of the sensor that discovers the asset	Assets	string
engid_name	Name of sensor	Assets	string
geoip	Geo location	Assets	string
geo_point	Coordinates of the Geo location	Assets	string
hostname	Hostname of asset	Assets	array
id	Asset ID	Assets	string
ip	IP address	Assets	array
iphistory	List of IP addresses previously used by the current asset	Assets	object (ip, time)
last_seen	Last time the asset is reported or updated	Assets	timestamp
locid	Location of the data sensor if the location is assigned by the user from the GUI	Assets	string
mac	MAC address	Assets	string
name	Name of the asset	Assets	string
os	OS-related info	Assets	string
os_version	OS-related info	Assets	string
reputation	IP reputation of the asset	Assets	string
risk_score	Asset risk score	Assets	integer
risk_score_hist	Asset risk score history	Assets	array
start_time	Timestamp the current asset was first reported	Assets	timestamp
state	State of the asset: new, approved, unapproved	Assets	string
subtype	Asset type: router, server, client	Assets	string
tag	Asset tag	Assets	string
tenantid	Tenant ID	Assets	string
tenant_name	Tenant name	Assets	string

Field Name	Description	Index	Data Type
timestamp	Last_seen of the ass[illegible]ed as timestamp in daily snapshot in ES	Assets	timestamp
user_sid	Usersid in asset or user tracking	Assets	string
vendor	Vendor of the asset, calculated from the MAC address	Assets	string
vuln_score	Vulnerability score, calculated from vulnerabilities reported on the asset	Assets	integer

Users

Click here for table of User field names

Field Name	Description	Index	Data Type
data_sources	Integrations that discover or report the user	Users	array
desc	Description (likely unused or used by the end user)	Users	string
engid	ID of the sensor that discovers the user	Users	string
last_seen	Last time the asset is reported or updated	Users	timestamp
last_seen_srcs	Last time the asset is reported or updated with the data source from which it is reported or updated	Users	object {"azure_ad": }
last_updated	Last time the asset is reported or updated	Users	timestamp
name	User name	Users	string
name_srcs	User name with the data source from which the name is reported	Users	ojbect {"azure_ad":}
profile	User profile from the data source	Users	object
risk_score	User risk score	Users	integer
risk_score_hist	User risk score history	Users	array
search_key	Combination of username, sid, and other info for search optimization	Users	string
sid	User Sid	Users	array
tag	User tag	Users	string
tag_srcs	User tag with the data source on which the tag is applied	Users	object {"azure_ad":}

Field Name	Description	Index	Data Type
tenantid	Tenant ID	Users	string
tenant_name	Tenant name	Users	string
timestamp	Last_seen of the asset, used as timestamp in daily snapshot in ES	Users	timestamp

© 2026 Stellar Cyber . All rights reserved.