Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Configuring Microsoft Entra ID (formerly Azure Active Directory) Connectors 6.4.0

This connector allows Stellar Cyber to collect data from external sources and add the records to the data lake and, optionally, to issue response actions.

Microsoft Entra ID (formerly Azure Active Directory) integration with Stellar Cyber provides advanced identity and access management capabilities, enabling organizations to manage user access and security policies across their network, and providing enhanced security controls and compliance features.

The user information from Microsoft Entra ID (formerly Azure AD) enriches event Interflow records and provides user profile details for User Behavior Analytics. You can also disable (and re-enable) users for applicable events, confirm a compromised user, dismiss the risk of a user, remove a user from a group, and revoke sign-in sessions.

If you have more than one Microsoft Entra ID, you must create one connector for each of them.

Stellar Cyber connectors with the Collect function (collectors) may skip collecting some data when the ingestion volume is large, which potentially can lead to data loss. This can happen when the processing capacity of the collector is exceeded.

Connector Overview: Microsoft Entra ID

Capabilities

- Collect: **Yes**
- Respond: **Yes**
- Native Alerts Mapped: **Yes**
- Runs on: **DP**
- Interval: **Configurable**

Collected Data

Content Type	Index	Locating Records

Audit Log Collection 
Sign-in Logs Collection
Risk Detection Collection
Risky User Collection
User Profile
Service Principal Sign-in Logs Collection
6.3.0
	Windows Events	msg_class:
		`azure_ad_audit`
		`azure_ad_signin`
		`azure_ad_risk_detection`
		`azure_ad_risky_user`
		`user_profile`
		`azure_ad_service_principal_sign_in`
		6.3.0
		
		msg_origin.source:
		`azure_ad`
		
		msg_origin.vendor:
		`azure_ad`
		
		msg_origin.category:
		`iam`

Domain

https://graph.microsoft.com/

Response Actions

Action	Required Fields
Disable User	`userPrincipalName` The Disable User action requires User.EnableDisableAccount.All and User.ReadWrite.All permissions.
Confirm Compromised	The conditions for creating the Confirm Compromised and Dismiss Risk actions are as follows:

Action	Required Fields	
	msg_class of Content Type	**User ID on Which to Perform Action**
Dismiss Risk	`azure_ad_audit`	`initiatedBy.user.id`
	`azure_ad_signin`	`userId`
	`azure_ad_risk_detection`	`userId`
	`azure_ad_risky_user`	`azure_ad.id`
	`user_profile`	`user_profile.id`
	The Confirm Compromised and Dismiss Risk actions use the riskyUsers API, which requires an Microsoft Entra ID P2 license and IdentityRiskyUser.ReadWrite.All permissions.	
Revoke Existing Sign-In Sessions 6.2.0	`userPrincipalName`	
	The Revoke Existing Sign-In Sessions action requires User.RevokeSessions.All permission.	
Remove User from Group 6.2.0	`user_id` and `group_id`	
	The Remove User from Group action requires GroupMember.ReadWrite.All permission.	
Add User to Group 6.4.0	`user_id` and `group_id`	
	The Add User to Group action requires GroupMember.ReadWrite.All permission.	

There are two other ways to disable the Microsoft Entra ID user:

- Navigate to **Automation | Action History** and choose the **User Actions** tab. See Create a Disable User Action.
- Navigate to **Assets | User Behavior Analytics** and choose the **Users** tab. See Disable a User Action.

Third Party Native Alert Integration Details

This connector can ingest several log types, but only **Risk Detection** logs are relevant to alert mapping. Select the Risk Detection Collection content type.

Deduplication is by `tenantid`, `riskEventType`, `riskLevel`, `userDisplayName`, and `ipAddress`.

For details, see Integration of Third Party Native Alerts.

For full alert integration of Microsoft Entra ID, the following license is required:

- Microsoft Entra ID P2 (some non-premium detections do not require P2)

The integration does not include alerts of "riskEventType": "generic".

Required Credentials and Configurations

- Application (client) ID, Directory (tenant) ID, Secret Key (password), and Microsoft Entra ID Subscription Plan

Locating Records

To search the alerts in the Alerts index or to search the Original Records in the Windows Events index, use the query: `msg_class: azure_ad_risk_detection AND NOT riskEventType: generic`

Adding the Microsoft Entra ID Connector

To add the Microsoft Entra ID connector:

1. Register an application
2. Configure the application
3. Add the connector in Stellar Cyber
4. Test the connector
5. Verify ingestion

Registering an Application


Follow the instructions below to register an application and configure Microsoft Entra ID portal. During the process, make note of the following values for use when you create the connector later:

- **Application (client) ID**
- **Directory (tenant) ID**
- **Secret Key (password)**


1. With an administrative account, log in to the portal you use for Microsoft Entra ID administration of the Microsoft subscription (tenant) in which you want to register the Stellar Cyber application. (Example portals are: https://go.microsoft.com, portal.azure.com, and https://admin.microsoft.com/adminportal). If your account gives you access to more than one tenant, select your account icon and then the Microsoft Entra ID tenant that you want.

   The **Dashboard** appears.


2. Select **Microsoft Entra ID** from the left navigation pane.
3. In the navigation pane, select **App registrations**. A pane for adding and managing **App registrations** is displayed.



4. Click **New registration**. A pane is opened for your new parameters.



5. Enter a **Name**.
6. Choose a supported a[redacted]unt type. **Accounts in this organizational directory only** is typical.
7. The **Redirect URI** setting is not required.
8. Click **Register**. The registration is created and a summary of it is displayed.




9. Copy the following details to a file:
    - **Display Name**
    - **Application (client) ID**
    - **Directory (tenant) ID**

You are now ready to configure the application.

Configuring the Application


1. To set the access to the application, under **App registrations** in the navigation pane under **Manage**, select **Manifest**.



    a. In the **Microsoft Graph App Manifest (New)**, locate the field for **isFallbackPublicClient** and set it to **true**.

    b. Click **Save**.

2. To create your secret key, in the navigation pane under **Manage**, select **Certificates & secrets**.




    a. Click **New client secret**. The **Add a client secret** pane is displayed.

    b. Enter a **Description**.


    c. Choose an expiration.

d. Click **Add**. The secret key is created and is now displayed in the **Client secrets** list.




e. Copy the **Value**. This is the **Password** you will use to add the connector in Stellar Cyber.

3. To set the **permissions** for your application, in the navigation pane under **Manage**, select **API Permissions**. The **API permissions** pane appears.




a. Click **Add a permission**. The **Request API permissions** pane appears.




b. Click **Microsoft Graph**. The pane updates to offer **Delegated permissions** or **Application permissions**.

c. Click **Application permissions**.



The pane updates to display options for setting permissions.



d. Set the following permissions for the logs you want to collect.


Logs	API Permission	License Required
Audit	AuditLog.Read.All	Microsoft Entra ID Free
Sign in	AuditLog.Read.All	Microsoft Entra ID P1 or P2
	Directory.Read.All	
Risk detection security reports	IdentityRiskEvent.Read.All	Microsoft Entra ID P1 or P2
Risky user security reports	IdentityRiskyUser.Read.All	Microsoft Entra ID P2
User profile	User.Read.All	None
Service principal sign-in	AuditLog.Read.All	Microsoft Entra ID P1 or P2
	Directory.Read.All	

e. Click **Add permissions**. The **API permissions** page redisplays with your added permissions.

f. If you are the super admin, grant the permissions. Select the checkmark to **Grant admin consent for <account name>**.


Otherwise, wait for the super admin to grant them.

Make sure that the permissions are granted. If you add the connector before permissions are granted, the process fails.



When the permissions are granted successfully, there will be a green checkmark in the **Status** column.

4. If your connector will be used for respond actions, the API must also be configured with application permissions. From the **API Permissions** pane, click **Add a permission** again.



a. In the **Request API permissions** pane, click **Microsoft Graph.**

b. Click **Application permissions**.

c. For the Disable User response action, enable **User.EnableDisableAccount.All** and **User.ReadWrite.All**.
For the Confirm Compromised and Dismiss Risk response actions, enable **IdentityRiskyUser.ReadWrite.All**.

For the Revoke Existing Sign-In Sessions action, enable **User.RevokeSessions.All**.
For the Remove User from Group action, enable **GroupMember.ReadWrite.All**.
For the Add User to Group action, enable **GroupMember.ReadWrite.All**.


d. Click **Add permissions**. The **API permissions** page re-displays with your added permissions.

The permissions can take up to two hours to propagate to historical data. We suggest you add the permissions at least two hours prior to adding the connector in Stellar Cyber, as Stellar Cyber will try to pull historical logs when first configured.


Adding the Connector in Stellar Cyber

With the application registered, permissions granted, and the access information handy, you can add the Microsoft Entra ID connector in Stellar Cyber:

1. Log in to Stellar Cyber.
2. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.




3. Click **Create** and select **Connector**.



The **General** tab of the **Add Connector** screen appears. The information on this tab cannot be changed after you add the connector.

4. Choose **SaaS** from the **Category** dropdown.
5. Choose **Microsoft Entra ID (formerly Azure Active Directory)** from the **Type** dropdown.




The asterisk (*) indicates a required field.

6. For **Function**, enable the **Collect** checkbox. If you would like to issue response actions, also enable **Respond**.
7. Enter a **Name**.

   Notes:
   - This field does not accept multibyte characters.
   - It is recommended that you follow a naming convention such as tenantname-connectortype.

8. Choose a **Tenant Name**. The Interflow records created by this connector include this tenant name.
9. Choose the device on which to run the connector.
10. (Optional) When the **Function** is **Collect**, you can apply **Log Filters**. For information, see Managing Log Filters.
11. Click **Next**. The **Configuration** tab appears.



   The asterisk (*) indicates a required field.

12. Enter the **Application ID** you noted above.
13. Enter the **Directory ID** you noted above.
14. Enter the **Password** you noted above.
15. Select the applicable **Microsoft Entra ID Subscription Plan** from the menu:
    - **Enterprise Plan**
    - **GCC Government Plan**
    - **GCC High Government Plan**
    - **DoD Government Plan**

    To learn about Microsoft Entra ID government plans, refer to the following Microsoft documentation: https://learn.microsoft.com/en-us/azure/security/fundamentals/feature-availability.

    The Government Plans do not support the Sign-in Logs content type.


16. Choose the **Interval (min)**. This is how often the logs are collected.
17. Choose the logs you want to collect. These must match the permissions you set in Microsoft Entra ID. None are collected by default, so you must select at least one log. Note the following:

Log	Required License	Required Permissions	Alert Integration
Audit Log	Microsoft Entra ID Free	AuditLog.Read.All	No
Sign-in Logs	Microsoft Entra ID P1 or P2	AuditLog.Read.All Directory.Read.All	No
Risk Detection	Microsoft Entra ID P1 or P2	Identity.RiskEvent.Read.All	Mapped to Stellar Cyber Alerts
Risky User	Microsoft Entra ID P2	Identity.RiskyUser.Read.All	Mapped to Stellar Cyber Alerts
User Profile	N/A	User.Read.All	No
Service Principal Sign-in Logs	Microsoft Entra ID P1 or P2	AuditLog.Read.All Directory.Read.All	No


When the new connector is first active, it will collect logs for the content types as follows:

Log	Log Collection for First Data Pull
Audit Log	1 hour
Sign-in Logs	1 hour
Risk Detection	15 days
Risky User	15 days
User Profile	from the beginning
Service Principal Sign-in Logs	1 hour

18. (Optional) Stellar Cyber allows you to customize the scope of the request the collector should request for the selected log type. For example, specifying 60 minutes specifies that when the collector requests data, the request should delay completion until a full 60 minutes of data has been collected. To override the default delays, check the box at the top of the page for **Advanced Settings**. Any of the logs you selected now display a configurable delay field.



19. Click **Next**. The final confirmation tab appears.



20. Click **Submit**.


The new connector is immediately active.

Testing the Connector

When you add (or edit) a connector, we recommend that you run a test to validate the connectivity parameters you entered. The test validates authentication and connectivity.

For connectors running on a sensor, Stellar Cyber recommends that you allow 30-60 seconds for new or modified configuration details to be propagated to the sensor before performing a test.

1. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.



2. Locate the connector by name that you added, or modified, or that you want to test.
3. Click **Test** at the right side of that row. The test runs immediately.

Note that you may run only one test at a time.

Stellar Cyber conducts a basic connectivity test for the connector and reports a success or failure result. A successful test indicates that you entered all of the connector information correctly.

To aid troubleshooting your connector, the dialog remains open until you explicitly close it by using the **X** button. If the test fails, you can select the button from the same row to review and correct issues.

The connector status is updated every five (5) minutes. A successful test clears the connector status, but if issues persist, the status reverts to failed after a minute.


Repeat the test as needed.

Display sample messages...


Success !



Failure with summary of issue:



Show More example detail:



If the test fails, the common HTTP status error codes are as follows:

HTTP Error Code	HTTP Standard Error Name	Explanation	Recommendation
400	Bad Request	This error occurs when there is an error in the connector configuration.	Did you configure the connector correctly?
401	Unauthorized	This error occurs when an authentication credential is invalid or when a user does not have sufficient privileges to access a specific API.	Did you enter your credentials correctly? Are your credentials expired? Are your credentials entitled or licensed for that specific resource?
403	Forbidden	This error occurs when the permission or scope is not correct in a valid credential.	Did you enter your credentials correctly? Do you have the required role or permissions for that credential?
404	Not Found	This error occurs when a URL path does not resolve to an entity.	Did you enter your API URL correctly?
429	Too Many Requests	This error occurs when the API server receives too much traffic or if a user's license or entitlement quota is exceeded.	The server or user license/quota will eventually recover. The connector will periodically retry the query. If this occurs unexpectedly or too often, work with your API provider to investigate the server limits, user licensing, or quotas.

For a full list of codes, refer to HTTP response status codes.

Verifying Ingestion

To verify ingestion:

1. Select **Threat Hunting**.

   The **Interflow Search** tab appears.

2. Change the **Indices** to **Windows Events**.

   The table immediately updates to show ingested Interflow records.

© 2026 Stellar Cyber . All rights reserved.

