Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Configuring MySQL Connectors

Connectors allow Stellar Cyber to collect data from external sources and add it to the data lake.

You can install a connector to the OpenDental MySQL database or another data source. There can be any number of MySQL connectors.

Stellar Cyber connectors with the Collect function (collectors) may skip collecting some data when the ingestion volume is large, which potentially can lead to data loss. This can happen when the processing capacity of the collector is exceeded.

Connector Overview: MySQL

Capabilities

- Collect: **Yes**
- Respond: **No**
- Native Alerts Mapped: **No**
- Runs on: **DP** or **Sensor** 6.2.0
- Interval: **Configurable**

Collected Data

Content Type	Index	Locating Records
SQL Result	Syslog	msg_class: `OpenDental` or, `<data_source>` for a provided **Data Source** msg_origin.source: `opendental` or, `<data_source>` for a provided **Data Source** msg_origin.vendor

Content Type	Index	Locating Records

		`OpenDental`
		or, for a provided **Data Source**:
		• `<data_source>` for root tenant
		• `<data_source>_<tenant_id>` for any non-root tenant
		
		msg_origin.category:
		`crm`

Domain

N/A

Response Actions

N/A

Third Party Native Alert Integration Details

N/A

Required Credentials and Configurations

- Server Hostname or IP, Username, Password, Database Name, Select Columns, From Table, Datetime Column, and Data Source

Adding a MySQL Connector


To add a MySQL connector:

1. Add the connector in Stellar Cyber
2. Test the connector
3. Verify ingestion


Adding the Connector in Stellar Cyber

To add a MySQL connector in Stellar Cyber:

1. Log in to Stellar Cyber.
2. Click **System** | **INTEGRATIONS** | **Connectors**. The **Connector Overview** appears.




3. Click **Create** and select **Connector**.



The **General** tab of the **Add Connector** screen appears. The information on this tab cannot be changed after you add the connector.

4. Choose **Database** from the **Category** dropdown.
5. Choose **MySQL** from the **Type** dropdown.




The asterisk (*) indicates a required field.

6. For this connector, the supported **Function** is **Collect**, which is enabled already.
7. Enter a **Name**.

Notes:

- This field does not accept multibyte characters.
- It is recommended that you follow a naming convention such as tenantname-connectortype.

8. Choose a **Tenant Name**. The Interflow records created by this connector include this tenant name.
9. Choose the device on which to run the connector.
10. (Optional) When the **Function** is **Collect**, you can apply **Log Filters**. For information, see Managing Log Filters.
11. Click **Next**. The **Configuration** tab appears.




The asterisk (*) indicates a required field.

12. Enter the **Server Hostname or IP**. This is the hostname or IP address of the MySQL server. If entering a hostname, do not include https.
13. Enter the **Username** of a user with read access to the database.

14. Enter the **Password** for that user.

    The password should not include non-ASCII special characters.

15. Enter the **Database Name**. This is the name of the database on the MySQL server.
16. Enter the **Select Columns** that you want to ingest. Separate column names with commas, or enter * for all columns.
17. Enter the **From Table**. This is the table name in the database.
18. (Optional) Enter the **Where Condition**. This is an optional query condition in MySQL syntax. If you do not want to use a condition, leave it blank.
19. Enter the **Datetime Column**. This is the column in the database containing the date and time information for the logs. The **Datetime Column** accepts epoch, mysql data type datetime, and timestamp.
20. Enter the **Data Source**. You can select **OpenDental** from the dropdown or enter another Data Source value, which should indicate where the data was from. The recommended format is <vendor>_<product>.
21. Choose the **Interval (min)**. This is how often the logs are collected.
22. (Optional) Enter the **Data Timezone**. This is the timezone for the data stored in the MySQL database.
23. Choose the **Content Type** you would like to collect. The logs for **SQL Result** are supported.
24. Click **Next**. The final confirmation tab appears.



25. Click **Submit**.


The new connector is immediately active.

Testing the Connector

When you add (or edit) a connector, we recommend that you run a test to validate the connectivity parameters you entered. The test validates authentication and connectivity.

For connectors running on a sensor, Stellar Cyber recommends that you allow 30-60 seconds for new or modified configuration details to be propagated to the sensor before performing a test.

1. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.



2. Locate the connector by name that you added, or modified, or that you want to test.
3. Click **Test** at the right side of that row. The test runs immediately.

Note that you may run only one test at a time.

Stellar Cyber conducts a basic connectivity test for the connector and reports a success or failure result. A successful test indicates that you entered all of the connector information correctly.

To aid troubleshooting your connector, the dialog remains open until you explicitly close it by using the **X** button. If the test fails, you can select the button from the same row to review and correct issues.

The connector status is updated every five (5) minutes. A successful test clears the connector status, but if issues persist, the status reverts to failed after a minute.


Repeat the test as needed.

Display sample messages...


Success !



Failure with summary of issue:



Show More example detail:



If the test fails, the common HTTP status error codes are as follows:

HTTP Error Code	HTTP Standard Error Name	Explanation	Recommendation
400	Bad Request	This error occurs when there is an error in the connector configuration.	Did you configure the connector correctly?
401	Unauthorized	This error occurs when an authentication credential is invalid or when a user does not have sufficient privileges to access a specific API.	Did you enter your credentials correctly? Are your credentials expired? Are your credentials entitled or licensed for that specific resource?

HTTP Error Code	HTTP Standard Error Name	Explanation	Recommendation
403	Forbidden	This error occurs when the permission or scope is not correct in a valid credential.	Did you enter your credentials correctly? Do you have the required role or permissions for that credential?
404	Not Found	This error occurs when a URL path does not resolve to an entity.	Did you enter your API URL correctly?
429	Too Many Requests	This error occurs when the API server receives too much traffic or if a user's license or entitlement quota is exceeded.	The server or user license/quota will eventually recover. The connector will periodically retry the query. If this occurs unexpectedly or too often, work with your API provider to investigate the server limits, user licensing, or quotas.

For a full list of codes, refer to HTTP response status codes.

Verifying Ingestion

To verify ingestion:

1. Select **Threat Hunting**.

   The **Interflow Search** tab appears.

2. Change the **Indices** to **Syslog**.

   The table immediately updates to show ingested Interflow records.

© 2026 Stellar Cyber . All rights reserved.