Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Physical Photon Sensor Specifications 6.4.0

This article describes both the performance you can expect from your physical Stellar Cyber Photon sensors, as well as details on their physical provisioning.

Photon Sensor Performance Specifications

The table below summarizes the performance you can expect from your physical Photon sensors.

New physical sensors are shipped as modular sensors on Ubuntu 22.04.

Sensor	Supported Monitoring Ports	Maximum Throughput (Nominal Config*)	Maximum Throughput (All Features Enabled*)	Log Forwarding (Events per Second)
Photon 160	1 GbE	Up to 2.0 Gbps	Up to 1.4 Gbps	3984
Photon 250	1 GbE	Up to 5.0 Gbps	Up to 2.5 Gbps	4789
Photon 400	10 GbE & 1 GbE	Up to 10.0 Gbps	Up to 7.0 Gbps	16206

Keep in mind that log forwarding is handled by the Management port, by default. The other sensor ports are used primarily for network capture, IDS, and Malware Sandbox purposes.

* About Sensor Throughput Performance

Sensor throughput performance corresponds directly to the features enabled in a sensor's profile, as well as the type and rate of traffic processed. Actual performance may vary depending on your environment and sensor configuration.

- **Maximum Throughput (Nominal Config)** shows maximum aggregate ingestion with a span port and local file assembly, packet forwarding, and log forwarding enabled. The **Network Traffic**, **Sandbox**, and **IDS** features are not enabled.
- **Maximum Throughput (All Features Enabled)** shows maximum aggregate ingestion with a span port and all features enabled, including **Network Traffic**, **Sandbox**, and

IDS.

Photon Sensor Physical Specifications

The table below provides details on the physical provisioning of Stellar Cyber Photon sensors:

	PHOTON-160	PHOTON-250	PHOTON-400
Maximum Throughput (Nominal Config)	Up to 2.0 Gbps	Up to 5.0 Gbps	Up to 10.0 Gbps
Maximum Throughput (All Features Enabled)	Up to 1.4 Gbps	Up to 2.5 Gbps	Up to 7.0 Gbps
Network Interfaces	6 x RJ45 (1Gbps)	4 x GbE RJ45 MAC 2 x GbE RJ45 2 x GbE SFP	6 x GbE RJ45 2 x 10G SFP+
CPUs	4 physical cores	16 physical cores	16 physical cores
Memory	16 GB (DDR4 2667 MHz)	64 GB (2 x 32 GB) (DDR4 2666 MHz)	64 GB (4 x 16 GB) (DDR4 3200 MHz)
Storage	238 GB	512 GB	480 GB
Console Access	RJ45 Console (COM) Port	RJ45 Console Port	VGA port and USB keyboard or iDRAC Virtual Console (when licensed from Dell)
Size	7.32" x 4.98" x 2.60"	9.10” x 7.87” x 1.73”	17.08” x 1.68” x 28.13”
Weight	3.025 lbs	2.65 lbs	38.9 lbs
Power	AC 100-240V DC 12V, 60W	AC 100-240V DC 12V, 60W	AC 100-240v DC 240v, 800W



Stellar Cyber has the discretion to modify external connectors, size, weight, and power of any model noted above to accommodate enhancements that do not impact performance.



© 2026 Stellar Cyber . All rights reserved.