Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

# Rule-Based Only Alert Types

This article contains only the rule-based alert types. They are listed alphabetically by their display name.

For the Machine Learning only alert types, see Machine Learning Only Alert Types.

For all the alert types, see All Alert Types Details.

## Abnormal Parent / Child Process

A process that typically launches a small, consistent number of child processes has launched a new child process. Investigate the new child process or the parent process to see if it is benign.

This alert type has the following subtype categories:

- Machine Learning Anomaly Detection
- Rule Based Detection

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: XDR EBA (XTA0001)
- Technique: XDR Process Relationship Anomaly (XT1002)
- Tags: [Process Anomaly]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `parent_child`.

### Severity

25

## Alert Subtype: Machine Learning Anomaly Detection

The `xdr_event.subtype.name` for this alert subtype in the Interflow data is `machine_learning_anomaly_detection`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- parent_proc_name

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `process_name` — name of the process
- `parent_proc_name` — name of the parent process
- `hostip` — host IP address
- `hostip_host` — host name
- `stability` — score measuring the time since the parent process launched the last child process
- `days_stable` — time since the parent process launched the last child process
- `diversity` — score measuring the number of child processes that the parent process spawned
- `child_count` — number of child processes that the parent process spawned

### Use Case with Data Points

Each pair of parent/child processes (`parent_proc_name` and `process_name`) is examined periodically. If a parent process (`parent_proc_name`) with a small number of child processes (`diversity`, `child_count`) has not launched a new child process (`process_name`) for a long time (`stability`, `days_stable`) launches a new child process from a host (`srcip_host`), an alert is triggered.

## Alert Subtype: Rule Based Detection

The Parent/Child Suspicious Process Creation rules are used to identify suspicious activity with parent/child relationships associated with process creation. Any one or more of these will trigger the Parent/Child Suspicious Process Creation alert types.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- hostip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Parent/Child Suspicious Process Creation Alert Type

## Account MFA Login Failure Anomaly

An anomalously large number of Multi-Factor Authentication (MFA) user login failures was observed for an account. Check with the user.

This alert type has the following subtypes:

- Machine Learning Anomaly
- Rule Based

## Alert Subtype: Machine Learning Anomaly

### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: [External] Credential Access (TA0006)
- Technique: Brute Force (T1110)
- Tags: [External; Identity Detection]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `cloud_account_login_failure_okta`.

### Severity

45

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip_usersid

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip_usersid` — cloud account user ID
- `srcip_username` — cloud account user name
- `event_summary.total_failed` — number of failed logins in the period
- `event_summary.total_successful` — number of successful logins in the period
- `event_summary.total_fail_ratio` — percent of failed logins in the period, which is: `event_summary.total_failed` / (`event_summary.total_failed` + `event_summary.total_successful`)
- `weighted_anomaly_score` — net score based on weighted rating of successful versus failed attempts (scanning, login, or other). Scores greater than the detection threshold will generate an alert.
- `srcip_host` — host name of corresponding source IP address
- `login_type` — type of login
- `srcip_reputation` — source reputation
- `userIdentity.userName` — user name of the account involved in the event
- `eventSource` — source of the event
- `eventName` — name of the event
- `eventType` — type of the event

### Use Case with Data Points

Multi-Factor Authentication login failures and successes are calculated periodically for every account (`srcip_usersid`). If the number of failures is significantly larger than the number of successes, an alert is triggered. A sample Interflow includes the login type (`login_type`), source host (srcip_host), and source reputation (`srcip_reputation`).

### Alert Subtype: Rule Based

The Suspicious AWS Login Failure rules are used to identify suspicious AWS account login failures. Any one or more of these will trigger the AWS Cloud Account Login Failure alert type.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

#### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

#### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS Login Failure

## AWS Default VPC Configuration 6.5.0

The AWS Default VPC Configuration rules are used to detect the use of AWS default VPC settings. Any one or more of these will trigger the AWS Default VPC Configuration alert type.

#### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: Initial Access (TA0001)
- Technique: Exploit Public-Facing Application (T1190)
- Tags: [AWS]

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_config_default_vpc`.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- aws.configurationItem  N
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `aws.configurationItem.resourceType` — resource type of the configuration item
- `aws.configurationItem.resourceName` — resource name of the configuration item
- `aws.configurationItem.ARN` — resource ARN, which is the Amazon Resource Name of the configuration item
- `aws.configurationItem.configurationItemStatus` — status of the configuration item
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to AWS Default VPC Configuration Alert Type

## AWS EC2 Security Group Deleted 6.5.0

The AWS EC2 Security Group Deleted rules are used to detect the deletion of an AWS EC2 security group. Any one or more of these will trigger the AWS EC2 Security Group Deleted alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Sub-technique: Disable or Modify Cloud Firewall (T1562.007)
- Tags: [AWS]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_ec2_security_group_deleted`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- aws.configurationItem.ARN
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `aws.configurationItem.resourceType` — resource type of the configuration item

- `aws.configurationItem.resourceName` — resource name of the configuration item
- `aws.configurationItem.ARN` — resource ARN, which is the Amazon Resource Name of the configuration item
- `aws.configurationItem.configurationItemStatus` — status of the configuration item
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to AWS EC2 Security Group Deleted Alert Type

## AWS High-Risk Ports Exposed to Internet 6.5.0

The AWS High-Risk Ports Exposed to Internet rules are used to detect AWS security group rules that expose high-risk ports to the Internet. Any one or more of these will trigger the AWS High-Risk Ports Exposed to Internet alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Sub-technique: Disable or Modify Cloud Firewall (T1562.007)
- Tags: [AWS]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_high_risk_ports_exposed`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- aws.configurationItem.ARN
- aws.configurationItem.configuration.ipPermissions.fromPort
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `stellar.config_risky_port` — port exposed to the Internet
- `aws.configurationItem.resourceType` — resource type of the configuration item
- `aws.configurationItem.resourceName` — resource name of the configuration item
- `aws.configurationItem.ARN` — resource ARN, which is the Amazon Resource Name of the configuration item
- `aws.configurationItem.configurationItemStatus` — status of the configuration item
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to AWS High-Risk Ports Exposed to Internet Alert Type

## AWS IAM Policy with Wildcard Privileges 6.5.0

The AWS IAM Policy with Wildcard Privileges rules are used to detect IAM policies granting excessive permissions via wildcards. Any one or more of these will trigger the AWS IAM Policy with Wildcard Privileges alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Privilege Escalation (TA0004)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [AWS]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_config_iam_wildcard_privileges`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- aws.configurationItem.ARN
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `aws.configurationItem.resourceType` — resource type of the configuration item
- `aws.configurationItem.resourceName` — resource name of the configuration item
- `aws.configurationItem.ARN` — resource ARN, which is the Amazon Resource Name of the configuration item
- `aws.configurationItem.configurationItemStatus` — status of the configuration item
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to AWS IAM Policy with Wildcard Privileges Alert Type

## AWS S3 Bucket Missing Server-Side Encryption 6.5.0

The AWS S3 Bucket Missing Server-Side Encryption rules are used to detect S3 buckets without server-side encryption. Any one or more of these will trigger the AWS S3 Bucket Missing Server-Side Encryption alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Collection (TA0 )
- Technique: Data from Cloud Storage Object (T1530 )
- Tags: [AWS]

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_s3_missing_server_side_encryption`.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- aws.configurationItem.ARN
- stellar.rule_id

#### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `aws.configurationItem.resourceType` — resource type of the configuration item
- `aws.configurationItem.resourceName` — resource name of the configuration item
- `aws.configurationItem.ARN` — resource ARN, which is the Amazon Resource Name of the configuration item
- `aws.configurationItem.configurationItemStatus` — status of the configuration item
- `stellar.rule_id` — Stellar Cyber rule ID

#### Link to Rule-Based Alert Types

Rules Contributing to AWS S3 Bucket Missing Server-Side Encryption Alert Type

### AWS S3 Bucket Policy with Public Access 6.5.0

The AWS S3 Bucket Policy with Public Access rules are used to detect S3 bucket policies that allow unauthorized public access. Any one or more of these will trigger the AWS S3 Bucket Policy with Public Access alert type.

#### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Collection (TA0009 )
- Technique: Data from Cloud Storage Object (T1530 )
- Tags: [AWS]

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_config_s3_policy_public_access`.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- aws.configurationItem.ARN
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `aws.configurationItem.resourceType` — resource type of the configuration item
- `aws.configurationItem.resourceName` — resource name of the configuration item
- `aws.configurationItem.ARN` — resource ARN, which is the Amazon Resource Name of the configuration item
- `aws.configurationItem.configurationItemStatus` — status of the configuration item
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to AWS S3 Bucket Policy with Public Access Alert Type

## Azure Application Gateway Changed 5.2.0 5.3.0

The Azure Application Gateway Changed rules are used to identify events when an Azure application's gateway is changed. Any one or more of these will trigger the Azure Application Gateway Changed alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: External Remote Services (T1133)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_application_gateway_changed`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity

- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Azure Application Gateway Changed Alert Type

## Azure DNS Zone Changed 5.2.0 5.3.0

The Azure DNS Zone Changed rules are used to identify events when an Azure DNS zone is changed. Any one or more of these will trigger the Azure DNS Zone Changed alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Command and Control (TA0011)
- Technique: Application Layer Protocol (T1071)
- Sub-technique: DNS (T1071.004)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_dns_zone_change`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved

- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Azure DNS Zone Changed Alert Type

## Azure New CloudShell Created 5.2.0 5.3.0

The Azure New CloudShell Created rules are used to identify events when an Azure new Cloud Shell is changed. Any one or more of these will trigger the Azure New CloudShell Created alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Execution (TA0002)
- Technique: Command and Scripting Interpreter (T1059)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_new_cloudshell_created`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Azure New CloudShell Created Alert Type

## Azure Security Configuration Changed 5.2.0 5.3.0

The Azure Security Configuration Changed rules are used to identify events when an Azure security configuration is changed. Any one or more of these will trigger the Azure Security Configuration Changed alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_security_config_changed`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Azure Security Configuration Changed Alert Type

## BloodHound Enumeration Activity 5.5.0

The BloodHound Enumeration Activity rules are used to identify potential domain enumeration activity from BloodHound or other Active Directory data collection tools. Any one or more of these will trigger the BloodHound Enumeration Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0)
- Technique: Permission Groups Discovery (T1069)
- Sub-technique: Domain Groups (T1069.002)
- Tags: [LDAP; Network Traffic Analysis]

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_bloodhound_enumeration_activity`.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

#### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `metadata.request.base_object` — baseObject field of the LDAP search request
- `metadata.request.scope` — scope field of the LDAP search request
- `metadata.request.filter` — filter field of the LDAP search request
- `stellar.rule_id` — Stellar Cyber rule ID

#### Link to Rule-Based Alert Types

Rules Contributing to BloodHound Enumeration Activity Alert Type

### certutil.exe Certificate Extraction 6.3.0

The certutil.exe Certificate Extraction rules are used to identify certutil.exe certificate extraction activity. Any one or more of these will trigger the certutil.exe Certificate Extraction alert type.

#### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: Steal or Forge Authentication Certificates (T1649)
- Tags: [Identity Detection]

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `certutil_exe_certificate_extraction`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- process_name
- event_data.CommandLine

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `computer_name` — host name
- `event_data.CommandLine` — command line
- `process_name` — process name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to certutil.exe Certificate Extraction Alert Type

## DCERPC SMB Spoolss Named Pipe 5.4.0

The DCERPC SMB Spoolss Named Pipe rules detect suspicious SMB traffic accessing Spoolss named pipes. Any one or more of these will trigger the DCERPC SMB Spoolss Named Pipe alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Lateral Movement (TA0008)
- Technique: Remote Services (T1021)
- Sub-technique: SMB/Windows Admin Shares (T1021.002)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_win_security_dce_rpc_smb_spoolss_named_pipe`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip

- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to DCERPC SMB Spoolss Named Pipe Alert Type

## DNS Query to Anonymous File Upload Domains 5.5.0

The DNS Query to Anonymous File Upload Domains rules are used to identify DNS queries to anonymous file upload platform domains often used for malicious purposes. Any one or more of these will trigger the DNS Query to Anonymous File Upload Domains alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Exfiltration (TA0010)
- Technique: Exfiltration Over Web Service (T1567)
- Sub-technique: Exfiltration to Cloud Storage (T1567.002)
- Tags: [DNS]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `dns_anonymous_file_upload_domains`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- dns.question.name
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip` — IP address sending DNS query to anonymous file upload platform domains
- `srcip_geo.countryName` — country of the source IP address
- `dstip` — IP address receiving the DNS query
- `dstip_geo.countryName` — country of the destination IP address
- `dns.question.name` — anonymous file upload platform domain being resolved

- `metadata.request.query` — anonymous file upload platform domain being resolved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to DNS Query to Anonymous File Upload Domains Alert Type

## DNS Query to External Service Interaction Domains 5.5.0

The DNS Query to External Service Interaction Domains rules are used to identify DNS queries to external service interaction domains often used for out-of-band interactions after successful RCE. Any one or more of these will trigger the DNS Query to External Service Interaction Domains alert type.

### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: Initial Access (TA0001)
- Technique: Exploit Public-Facing Application (T1190)
- Tags: [DNS]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `dns_external_service_interaction_domains`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- dns.question.name
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip` — IP address sending external service domain DNS query
- `srcip_geo.countryName` — country of the source IP address
- `dstip` — IP address receiving the DNS query
- `dstip_geo.countryName` — country of the destination IP address
- `dns.question.name` — external service domain being resolved
- `metadata.request.query` — external service domain being resolved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to DNS Query to External Service Interaction Domains Alert Type

## DNS Query to Monero Crypto Coin Mining Pool Domains 5.5.0

The DNS Query to Monero Crypto Coin Mining Pool Domains rules are used to identify DNS queries to Monero crypto coin mining pool domains. Any one or more of these will trigger the DNS Query to Monero Crypto Coin Mining Pool Domains alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Resource Hijacking (T1496)
- Tags: [DNS]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `dns_pua_cryptocoin_mining_xmr`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- dns.question.name
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip` — IP address sending DNS query to crypto coin mining pool domains
- `srcip_geo.countryName` — country of the source IP address
- `dstip` — IP address receiving the DNS query
- `dstip_geo.countryName` — country of the destination IP address
- `dns.question.name` — crypto coin mining pool domain being resolved
- `metadata.request.query` — crypto coin mining pool domain being resolved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to DNS Query to Monero Crypto Coin Mining Pool Domains Alert Type

## DNS Query to TOR Proxy Domain 5.2.0 5.3.0

The DNS Query to TOR Proxy Domain rules are used to identify DNS queries to onion domains and proxy domains for TOR network. Any one or more of these will trigger the DNS Query to TOR Proxy Domain alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Exfiltration (TA0010)
- Technique: Proxy (T1090)

- Sub-technique: Multi-hop Proxy (T1090.003)
- Tags: [DNS]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `dns_tor_proxy_domain`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- dns.question.name
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip` — IP address sending TOR network related DNS query
- `srcip_geo.countryName` — country of the source IP address
- `dstip` — IP address receiving the DNS query
- `dstip_geo.countryName` — country of the destination IP address
- `dns.question.name` — TOR network domain being resolved
- `metadata.request.query` — TOR network domain being resolved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to DNS Query to TOR Proxy Domain Alert Type

## Impacket PsExec Execution 5.4.0

The Impacket PsExec Execution rules detect suspicious SMB traffic related to Impacket PsExec execution. Any one or more of these will trigger the Impacket PsExec Execution alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Lateral Movement (TA0008)
- Technique: Remote Services (T1021)
- Sub-technique: SMB/Windows Admin Shares (T1021.002)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_win_security_impacket_psexec`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Impacket PsExec Execution Alert Type

## Microsoft Entra Application Configuration Changes 5.2.0

The Microsoft Entra Application Configuration Changes rules are used to identify suspicious Microsoft Entra application configuration changes. Any one or more of these will trigger the Microsoft Entra Application Configuration Changes alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_application_configuration_changes`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity

- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Application Configuration Changes Alert Type

## Microsoft Entra Application Deleted 5.2.0 5.3.0

The Microsoft Entra Application Deleted rules are used to identify events when a Microsoft Entra application is deleted. Any one or more of these will trigger the Microsoft Entra Application Deleted alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Service Stop (T1489)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `microsoft_entra_app_deleted`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Application Deleted Alert Type

## Microsoft Entra Application Permission Changes 5.2.0

The Microsoft Entra Application Permission Changes rules are used to identify suspicious Microsoft Entra application permission changes. Any one or more of these will trigger the Microsoft Entra Application Permission Changes alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Privilege Escalation (TA0004)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_application_permission_changes`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Application Permission Changes Alert Type

## Microsoft Entra Bitlocker Key Retrieval 5.2.0

The Microsoft Entra Bitlocker Key Retrieval rules are used to identify suspicious Microsoft Entra Bitlocker key retrieval activity. Any one or more of these will trigger the Microsoft Entra Bitlocker Key Retrieval alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: Credentials from Password Stores (T1555)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_bitlocker_key_retrieval`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra BitLocker Key Retrieval Alert Type

## Microsoft Entra Changes to Conditional Access Policy 5.2.0

The Microsoft Entra Changes to Conditional Access Policy rules are used to identify suspicious Microsoft Entra changes to conditional access policy. Any one or more of these will trigger the Microsoft Entra Changes to Conditional Access Policy alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)

- Technique: Modify Authentication Process (T1556)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_suspicious_changes_to_conditional_access_policy`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.user.id
- initiatedBy.app.servicePrincipalId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Changes to Conditional Access Policy Alert Type

## Microsoft Entra Changes to Device Registration Policy 5.2.0

The Microsoft Entra Changes to Device Registration Policy rules are used to identify suspicious Microsoft Entra changes to device registration policy. Any one or more of these will trigger the Microsoft Entra Changes to Device Registration Policy alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Domain Policy Modification (T1484)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_changes_to_device_registration_policy`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Changes to Device Registration Policy Alert Type

## Microsoft Entra Changes to Privileged Account 5.2.0

The Microsoft Entra Changes to Privileged Account rules are used to identify suspicious Microsoft Entra changes to privileged account. Any one or more of these will trigger the Microsoft Entra Changes to Privileged Account alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_changes_to_privileged_account`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id

- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Changes to Privileged Account Alert Type

## Microsoft Entra Changes to Privileged Role Assignment 5.2.0

The Microsoft Entra Changes to Privileged Role Assignment rules are used to identify suspicious Microsoft Entra changes to privileged role assignment. Any one or more of these will trigger the Microsoft Entra Changes to Privileged Role Assignment alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Privilege Escalation (TA0004)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_changes_to_privileged_role_assignment`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Changes to Privileged Role Assignment Alert Type

## Microsoft Entra Federation Modified 5.2.0

The Microsoft Entra Federation Modified rules are used to identify suspicious Microsoft Entra federation modified activity. Any one or more of these will trigger the Microsoft Entra Federation Modified alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Domain Policy Modification (T1484)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_federation_modified`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.user.id
- initiatedBy.app.servicePrincipalId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity

- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Type

Rules Contributing to Microsoft Entra Federation Modified Alert Type

## Microsoft Entra Guest User Invited by Non-Approved Inviters 5.2.0

The Microsoft Entra Guest User Invited by Non-Approved Inviters rules are used to identify suspicious Microsoft Entra guest user invited by non-approved inviters. Any one or more of these will trigger the Microsoft Entra Guest User Invited by Non-Approved Inviters alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_guest_user_invited_by_non_approved_inviters`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.user.id
- initiatedBy.app.servicePrincipalId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Guest User Invited by Non-Approved Inviters Alert Type

## Microsoft Entra Hybrid Health AD FS New Server 5.2.0 5.3.0

The Microsoft Entra Hybrid Health AD FS New Server rules are used to identify a new hybrid health AD FS server. Any one or more of these will trigger the Microsoft Entra Hybrid Health AD FS New Server alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0007)
- Technique: Account Discovery (T1087)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `microsoft_entra_hybrid_health_adfs_new_server`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Hybrid Health AD FS New Server Alert Type

## Microsoft Entra Hybrid Health AD FS Service Deleted 5.2.0 5.3.0

The Microsoft Entra Hybrid Health AD FS Service Deleted rules are used to identify events when a hybrid health AD FS server is deleted. Any one or more of these will trigger the Microsoft Entra Hybrid Health AD FS Service Deleted alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold

- Tactic: Defense Evasion (TA0005)
- Technique: Modify Cloud Compute Infrastructure (T1578)
- Sub-technique: Delete Cloud Instance (T1578.003)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `microsoft_entra_hybrid_health_adfs_service_deleted`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Hybrid Health AD FS Service Deleted Alert Type

## Microsoft Entra ID Discovery Using AzureHound 5.2.0

The Microsoft Entra ID Discovery Using AzureHound rules are used to identify Microsoft Entra ID discovery using Azurehound. Any one or more of these will trigger the Microsoft Entra ID Discovery Using Azurehound alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0007)
- Technique: Account Discovery (T1087)
- Sub-technique: Cloud Account (T1087.004)

- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_discovery_using_azurehound`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip_username
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip_username` — user name of the account involved in the event
- `srcip` — IP address of the login client
- `srcip_host` — host name of the login client
- `UserAgent` — user agent string of the login client
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra ID Discovery Using Azurehound Alert Type

## Microsoft Entra ID MFA Disabled 5.2.0 5.3.0

The Microsoft Entra ID MFA Disabled rules are used to identify events when a Microsoft Entra ID multi-factor authentication is disabled. Any one or more of these will trigger the Microsoft Entra ID MFA Disabled alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Modify Authentication Process (T1556)
- Sub-technique: Multi-Factor Authentication (T1556.006)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_mfa_disabled`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra ID MFA Disabled Alert Type

## Microsoft Entra Owner Removed from Application 5.2.0 5.3.0

The Microsoft Entra Owner Removed from Application rules are used to identify events when a Microsoft Entra owner is removed from an application. Any one or more of these will trigger the Microsoft Entra Owner Removed from Application alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Indicator Removal (T1070)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `microsoft_entra_owner_removed_from_app`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity

- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Owner Removed from Application Alert Type

## Microsoft Entra PIM Setting Changed 5.2.0

The Microsoft Entra PIM Setting Changed rules are used to identify suspicious Microsoft Entra PIM setting changed. Any one or more of these will trigger the Microsoft Entra PIM Setting Changed alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Privilege Escalation (TA0004)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_pim_setting_changed`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra PIM Setting Changed Alert Type

## Microsoft Entra Privileged Account Assignment or Elevation 5.2.0

The Microsoft Entra Privileged Account Assignment or Elevation rules are used to identify suspicious Microsoft Entra privileged account assignment or elevation. Any one or more of these will trigger the Microsoft Entra Privileged Account Assignment or Elevation alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Privilege Escalation (TA0004)
- Technique: Valid Accounts (T1078)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_privileged_account_assignment_or_elevation`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Privileged Account Assignment or Elevation Alert Type

## Microsoft Entra Sign-in Failure 5.2.0

The Microsoft Entra Sign-in Failure rules are used to identify suspicious Microsoft Entra sign-in failures. Any one or more of these will trigger the Microsoft Entra Sign-in Failure alert type.

### XDR Kill Chain

- Kill Chain Stage: Prop ion
- Tactic: [Internal] Credential Access (TA0006)
- Technique: Brute Force (T1110)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_sign_in_failures`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip_username
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip_username` — user name of the account involved in the event
- `srcip` — IP address of the login client
- `srcip_host` — host name of the login client
- `login_result` — login result of user login events
- `azure_ad.status.failureReason` — reason for the login failure
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft Entra Sign-in Failure Alert Type

## Microsoft Entra Suspicious Sign-in Activity 5.2.0

The Microsoft Entra Suspicious Sign-in Activity rules are used to identify suspicious Microsoft Entra sign-in activity. Any one or more of these will trigger the Microsoft Entra Suspicious Sign-in Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: Initial Access (TA0001)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `azure_suspicious_sign_in_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip_username
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip_username` — user name of the account involved in the event
- `srcip` — IP address of the login client
- `srcip_host` — host name of the login client
- `login_result` — login result of user login events
- `azure_ad.status.failureReason` — reason for the login failure
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Microsoft Entra Sign-In Activity Alert Type

## OCI Discovery Activity 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The OCI Discovery Activity rules are used to identify suspicious discovery activity in OCI. Any one or more of these will trigger the OCI Discovery Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0007)
- Technique: Cloud Infrastructure Discovery (T1580)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `oci_discovery_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.definedTags.Oracle-Tags.CreatedBy
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event

- `oracle.data.definedTags.Oracle-Tags.CreatedBy` — name of the user or service principal that created the resource
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to OCI Discovery Activity Alert Type

## OCI Insecure Metadata Endpoint 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The OCI Insecure Metadata Endpoint rules are used to identify potentially insecure metadata endpoints in OCI. Any one or more of these will trigger the OCI Insecure Metadata Endpoint alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0007)
- Technique: Permission Groups Discovery (T1069)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `oci_insecure_metadata_endpoint`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.request.headers.oci-original-url
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.request.headers.oci-original-url` — endpoint URL requested
- `oracle.data.response.status` — status of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to OCI Insecure Metadata Endpoint Alert Type

## OCI Insecure NFS Export Configuration 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The OCI Insecure NFS Export Configuration rules are used to identify insecure NFS export configuration in OCI. Any one or more of these will trigger the OCI Insecure NFS Export Configuration alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0007)
- Technique: Cloud Infrastructure Discovery (T1580)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `oci_insecure_nfs_export_configuration`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `oracle.data.stateChange.current.exportOptions.source` — clients (either single IPv4 address or single IPv4 CIDR block) to which these options should apply
- `oracle.data.stateChange.current.exportOptions.access` — type of access to grant clients using the file system through this export
- `oracle.data.stateChange.current.exportOptions.identitySquash` — used when clients accessing the file system through this export have their UID and GID remapped to `anonymousUid` and `anonymousGid`
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to OCI Insecure NFS Export Configuration Alert Type

## OCI Instance Metadata Access 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The OCI Instance Metadata Access rules are used to identify suspicious metadata access of OCI instances. Any one or more of these will trigger the OCI Instance Metadata Access alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration

- Tactic: Discovery (TA0007)
- Technique: Permission Groups Discovery (T1069)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `oci_instance_metadata_access`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip` — source IP address of the connection
- `dstip` — destination IP address of the connection
- `action` — decision made by the security lists to accept or reject traffic
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to OCI Instance Metadata Access Alert Type

## OCI Unexpected User Agent 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The OCI Unexpected User Agent rules are used to identify unexpected user agents in OCI. Any one or more of these will trigger the OCI Unexpected User Agent alert type.

### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: Initial Access (TA0001)
- Technique: Exploit Public-Facing Application (T1190)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `oci_unexpected_user_agent`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.identity.userAgent

- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.identity.userAgent` — original user agent string from a web request
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to OCI Unexpected User Agent Alert Type

## Office365 Rare Operations 6.2.0

The Office365 Rare Operations rules are used to identify rare and suspicious Microsoft 365 mailbox operations. Any one or more of these will trigger the Microsoft 365 Rare Operations alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: [Office 365; Identity Detection]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `office365_rare_operations`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- office365.Operation
- user.name

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `office365.Operation` — name of the mail operation
- `user.name` — username of the Office 365 account
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Microsoft 365 Rare Operations Alert Type

## Password Reset By User Account 5.4.0

The Password Reset By User Account rules are used to identify events when a password is reset by a user account. Any one or more of these will trigger the Password Reset By User Account alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `password_reset_by_user_account`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `user.name` — user name of the account involved in the activity
- `azure_ad.activityDisplayName` — name of the activity
- `azure_ad.category` — category of the activity
- `azure_ad.result` — result of the activity
- `azure_ad.resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Password Reset By User Account Alert Type

## Persistence and Execution at Scale via GPO Scheduled Task 5.4.0

The Persistence and Execution at Scale via GPO Scheduled Task rules detect suspicious SMB traffic related to GPO scheduled task creation/access. Any one or more of these will trigger the Persistence and Execution at Scale via GPO Scheduled Task alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Scheduled Task/Job (T1053)
- Sub-technique: Scheduled Task (T1053.005)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_win_security_gpo_scheduledtasks`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Persistence and Execution at Scale via GPO Scheduled Task Alert Type

## Phishing Domain with File Extension TLD 5.2.0 5.3.0

The Phishing Domain with File Extension TLD rules are used to identify DNS queries to Top-Level Domains (TLDs) that resemble file extensions. Any one or more of these will trigger the Phishing Domain with File Extension TLD alert type.

### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: Initial Access (TA0001)
- Technique: Phishing (T1566)
- Tags: [DNS]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `dns_phishing_file_extension_tld`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- dns.question.name
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip` — IP address sending possible phishing domain DNS query
- `srcip_geo.countryName` — country of the source IP address
- `dstip` — IP address receiving the DNS query
- `dstip_geo.countryName` — country of the destination IP address
- `dns.question.name` — possible phishing domain being resolved
- `metadata.request.query` — possible phishing domain being resolved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Phishing Domain with File Extension TLD Alert Type

## Possible Impacket SecretDump Remote Activity 5.4.0

The Possible Impacket SecretDump Remote Activity rules detect suspicious SMB traffic related to credential dumping using Impacket. Any one or more of these will trigger the Possible Impacket SecretDump Remote Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: OS Credential Dumping (T1003)
- Tags: [Internal; SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_impacket_secretdump`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Possible Impacket SecretDump Remote Activity Alert Type

## Possible PetitPotam Coerce Authentication Attempt 5.4.0

The Possible Impacket SecretDump Remote Activity rules detect suspicious SMB traffic related to credential dumping using Impacket. Any one or more of these will trigger the Possible Impacket SecretDump Remote Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: Forced Authentication (T1187)
- Tags: [Internal; SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_petitpotam_network_share`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Possible PetitPotam Coerce Authentication Attempt Alert Type

## Potentially Malicious AWS Activity

The Potentially Malicious AWS Activity rules are used to identify suspicious activity within AWS logs. Any one or more of these will trigger the Potentially Malicious AWS Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)

- Technique: Impair Defenses (T1562)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_malicious_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- errorCode
- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Potentially Malicious AWS Activity Alert Type

## Potentially Malicious Windows Event

The Potentially Malicious Windows Event rules are used to identify suspicious activity with Windows events. This is a generic rule name. Any one or more of these will trigger the Potentially Malicious Windows Event alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Sub-technique: Indicator Blocking (T1562.006)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_malicious_event`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.TargetUserName
- event_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Potentially Malicious Event Alert Type

## Protected Storage Service Access 5.4.0

The Protected Storage Service Access rules detect suspicious SMB traffic accessing protected storage services. Any one or more of these will trigger the Protected Storage Service Access alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Lateral Movement (TA0008)
- Technique: Remote Services (T1021)
- Sub-technique: SMB/Windows Admin Shares (T1021.002)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_protected_storage_service_access`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Protected Storage Service Access Alert Type

## Remote Service Activity via SVCCTL Named Pipe 5.4.0

The Remote Service Activity via SVCCTL Named Pipe rules detect suspicious SMB traffic accessing SVCCTL named pipes. Any one or more of these will trigger the Remote Service Activity via SVCCTL Named Pipe alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Lateral Movement (TA0008)
- Technique: Remote Services (T1021)
- Sub-technique: SMB/Windows Admin Shares (T1021.002)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_win_security_svcctl_remote_service`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Remote Service Activity via SVCCTL Named Pipe Alert Type

## Remote Task Creation via ATSVC Named Pipe 5.4.0

The Remote Task Creation via ATSVC Named Pipe rules detect suspicious SMB traffic accessing ATSVC named pipes. Any one or more of these will trigger the Remote Task Creation via ATSVC Named Pipe alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Scheduled Task/Job (T1053)
- Sub-technique: At (Windows) (T1053.002)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_win_security_atsvc_task`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Remote Task Creation via ATSVC Named Pipe Alert Type

## Sensitive Windows Active Directory Attribute Modification

The Sensitive Windows Active Directory Attribute Modification rules are used to identify suspicious activity with sensitive Windows Active Directory attribute modification. Any one or more of these will trigger the Sensitive Windows Active Directory Attribute Modification alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)

- Technique: Domain Policy Modification (T1484)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_ad_sensitive_attribute_modification`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Sensitive Windows Active Directory Attribute Modification Alert Type

## Sensitive Windows Network Share File or Folder Accessed

The Sensitive Windows Network Share File or Folder Accessed rules are used to identify suspicious activity with Windows network share file or folder access. Any one or more of these will trigger the Sensitive Windows Network Share File or Folder Accessed alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Lateral Movement (TA0008)
- Technique: Remote Services (T1021)
- Sub-technique: SMB/Windows Admin Shares (T1021.002)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_sensitive_networkshare`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name

- event_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Sensitive Windows Network Share File or Folder Accessed Alert Type

## Startup/Logon Script Added to Group Policy Object 5.4.0

The Startup/Logon Script Added to Group Policy Object rules detect suspicious SMB traffic related to GPO script modifications. Any one or more of these will trigger the Startup/Logon Script Added to Group Policy Object alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Boot or Logon Autostart Execution (T1547)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_win_group_policy_iniscript`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Startup/L Script Added to Group Policy Object Alert Type

## Steal or Forge Kerberos Tickets 5.2.0

The Steal or Forge Kerberos Tickets rules are used to identify suspicious activity to steal or forge Kerberos tickets. Any one or more of these will trigger the Steal or Forge Kerberos Tickets alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: Steal or Forge Kerberos Tickets (T1558)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_steal_or_forge_kerberos_tickets`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.IpAddress
- event_data.ServiceName
- event_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `hostip_host` — host name
- `wineventlog_user` — Windows user who executed the script
- `event_data.ScriptBlockText` — Powershell script block text
- `event_id` — Windows event ID associated with the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Steal or Forge Kerberos Tickets Alert Type

## Suspicious Access Attempt to Windows Object

The Suspicious Access Attempt to Windows Object rules are used to identify suspicious activity with access attempt to Windows objects. Any one or more of these will trigger the Suspicious Access Attempt to Windows Object alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_object_access_suspicious_attempt`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.ObjectName
- event_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Access Attempt to Windows Object Alert Type

## Suspicious Activity Related to Security-Enabled Group

The Suspicious Activity Related to Security-Enabled Group rules are used to identify suspicious activity related to security-enabled groups. Any one or more of these will trigger the Suspicious Activity Related to Security-Enabled Group alert types.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_suspicious_activity_related_to_security_enabled_group`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.SubjectDomainName
- event_data.SubjectUserSid
- event_data.TargetDomainName
- event_data.TargetUserSid
- event_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `event_data.SubjectUserName` — subject user name associated with the activity
- `event_data.SubjectUserSid` — subject user SID associated with the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Activity Related to Security-Enabled Group Alert Type

## Suspicious AD Machine Account Creation 6.2.0

The Suspicious AD Machine Account Creation rules are used to identify suspicious machine account creation activity in Active Directory. Any one or more of these will trigger the Suspicious AD Machine Account Creation alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Create Account (T1136)
- Tags: [Identity Detection]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_ad_machine_account_creation`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- event_data.SubjectUserName

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `event_data.SubjectUserName` — name of the user who created the account
- `event_data.TargetUserName` — name of the created machine account
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AD Machine Account Creation Alert Type

## Suspicious AWS Bucket Enumeration

The Suspicious AWS Bucket Enumeration rules are used to identify suspicious activity related to AWS Bucket enumeration. Any one or more of these will trigger the Suspicious AWS Bucket Enumeration alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0007)
- Technique: Cloud Infrastructure Discovery (T1580)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_bucket_enumeration`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS Bucket Enumeration Alert Type

## Suspicious AWS EBS Activity

The Suspicious AWS EBS Activity rules are used to identify suspicious AWS Elastic Block Store (EBS) activity. Any one or more of these will trigger the Suspicious AWS EBS Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Collection (TA0009)
- Technique: Data Staged (T1074)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_ebs_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS EBS Activity Alert Type

## Suspicious AWS EC2 Activity

The Suspicious AWS EC2 Activity rules are used to identify suspicious activity within AWS EC2 logs. Any one or more of these will trigger the Suspicious AWS EC2 Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold

- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_ec2_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS EC2 Activity Alert Type

## Suspicious AWS ELB Activity

The Suspicious AWS ELB Activity rules are used to identify suspicious activity with AWS ELB. Any one or more of these will trigger the Suspicious AWS ELB Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_elb_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS ELB Activity Alert Type

## Suspicious AWS IAM Activity

The Suspicious AWS IAM Activity rules are used to identify suspicious activity within AWS IAM logs. Any one or more of these will trigger the Suspicious AWS IAM Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_iam_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- errorCode
- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS IAM Activity Alert Type

## Suspicious AWS RDS Event

The Suspicious AWS RDS Event rules are used to identify suspicious activity related to AWS RDS events. Any one or more of these will trigger the Suspicious AWS RDS Event alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Create Account (T1136)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_rds_event`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS RDS Event Alert Type

## Suspicious AWS Root Account Activity

The Suspicious AWS Root Account Activity rules are used to identify suspicious activity with AWS Root Account. Any one or more of these will trigger the Suspicious AWS Root Account Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Valid Accounts (T1078)
- Sub-technique: Cloud Accounts (T1078.004)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_root_account_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS Root Account Activity Alert Type

## Suspicious AWS Route 53 Activity

The Suspicious AWS Route 53 Activity rules are used to identify suspicious activity within AWS Route 53 logs. Any one or more of these will trigger the Suspicious AWS Route 53 Activity alert

type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_route53_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS Route 53 Activity Alert Type

## Suspicious AWS SSL Certificate Activity

The Suspicious AWS SSL Certificate Activity rules are used to identify suspicious activity with AWS SSL certificates. Any one or more of these will trigger the Suspicious AWS SSL Certificate alert type.

### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: Resource Development (TA0042)
- Technique: Obtain Capabilities (T1588)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_ssl_certificate_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- errorCode
- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS SSL Certificate Activity Alert Type

## Suspicious AWS VPC Flow Logs Modification

The Suspicious AWS VPC Flow Logs Modification rules are used to identify suspicious modification of AWS VPC Flow logs. Any one or more of these will trigger the Suspicious AWS VPC Flow Logs Modification alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_vpc_flow_logs_modification`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS VPC Flow Logs Modification Alert Type

## Suspicious AWS VPC Mirror Session

The Suspicious AWS VPC Mirror Session rules are used to identify suspicious AWS VPC mirror session activity. Any one or more of these will trigger the Suspicious AWS VPC Mirror Session alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_vpc_mirror_session`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious AWS VPC Mirror Session Alert Type

## Suspicious Azure Account Permission Elevation 5.2.0 5.3.0

The Suspicious Azure Account Permission Elevation rules are used to identify suspicious Azure account permission elevation. Any one or more of these will trigger the Suspicious Azure Account Permission Elevation alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Privilege Escalation (TA0004)
- Technique: Account Manipulation (T1098)
- Sub-technique: Additional Cloud Roles (T1098.003)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_account_permission_elevation`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation

- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Account Permission Elevation Alert Type

## Suspicious Azure Deployment Activity 5.2.0 5.3.0

The Suspicious Azure Deployment Activity rules are used to identify suspicious Azure deployment activity. Any one or more of these will trigger the Suspicious Azure Deployment Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Resource Hijacking (T1496)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_deployment_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Deployment Activity Alert Type

## Suspicious Azure Firewall Activity 5.2.0 5.3.0

The Suspicious Azure Firewall Activity rules are used to identify suspicious Azure firewall activity. Any one or more of these will trigger the Suspicious Azure Firewall Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Sub-technique: Disable or Modify Cloud Firewall (T1562.007)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_firewall_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Firewall Activity Alert Type

## Suspicious Azure Key Vault Activity 5.2.0 5.3.0

The Suspicious Azure Key Vault Activity rules are used to identify suspicious Azure Key Vault activity. Any one or more of these will trigger the Suspicious Azure Key Vault Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: Credentials from Password Stores (T1555)
- Sub-technique: Cloud Secrets Management Stores (T1555.006)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_key_vault_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- aoperationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Key Vault Activity Alert Type

## Suspicious Azure Kubernetes Activity: Credential Access 5.2.0 5.3.0

The Suspicious Azure Kubernetes Activity: Credential Access rules are used to identify suspicious Azure Kubernetes activity usually in the credential access stage. Any one or more of these will trigger the Suspicious Azure Kubernetes Activity: Credential Access alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Crede Access (TA0006)
- Technique: Unsecured Credentials (T1552)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_kubernetes_activity_credential_access`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Kubernetes Activity: Credential Access Alert Type

## Suspicious Azure Kubernetes Activity: Defense Evasion 5.2.0 5.3.0

The Suspicious Azure Kubernetes Activity: Defense Evasion rules are used to identify suspicious Azure Kubernetes activity usually in the defense evasion stage. Any one or more of these will trigger the Suspicious Azure Kubernetes Activity: Defense Evasion alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Sub-technique: Disable or Modify Tools (T1562.001)

- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_kubernetes_activity_defense_evasion`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Kubernetes Activity: Defense Evasion Alert Type

### Detection Time

## Suspicious Azure Kubernetes Activity: Impact 5.2.0 5.3.0

The Suspicious Azure Kubernetes Activity: Impact rules are used to identify suspicious Azure Kubernetes activity usually in the impact stage. Any one or more of these will trigger the Suspicious Azure Kubernetes Activity: Impact alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Data Destruction (T1485)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_kubernetes_activity_impact`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Kubernetes Activity: Impact Alert Type

## Suspicious Azure Kubernetes Activity: Persistence 5.2.0 5.3.0

The Suspicious Azure Kubernetes Activity: Persistence rules are used to identify suspicious Azure Kubernetes activity usually in the persistence stage. Any one or more of these will trigger the Suspicious Azure Kubernetes Activity: Persistence alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Scheduled Task/Job (T1053)
- Sub-technique: Container Orchestration Job (T1053.007)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_kubernetes_activity_persistence`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Kubernetes Activity: Persistence Alert Type

## Suspicious Azure Kubernetes Activity: Privilege Escalation 5.2.0 5.3.0

The Suspicious Azure Kubernetes Activity: Privilege Escalation rules are used to identify suspicious Azure Kubernetes activity usually in the privilege escalation stage. Any one or more of these will trigger the Suspicious Azure Kubernetes Activity: Privilege Escalation alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Privilege Escalation (TA0004)
- Technique: Valid Accounts (T1078)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_kubernetes_activity_privilege_escalation`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity
- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Kubernetes Activity: Privilege Escalation Alert Type

## Suspicious Azure Network Activity 5.2.0 5.3.0

The Suspicious Azure Network Activity rules are used to identify suspicious Azure network activity. Any one or more of these will trigger the Suspicious Azure Network Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Network Denial of Service (T1498)
- Tags: [Azure]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_network_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- operationName
- resourceId
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `callerIpAddress` — IP address of the user who performed the activity
- `resourceId` — identifier of the resource involved
- `operationName` — name of the activity

- `category` — activity category
- `resultType` — result of the operation
- `identity.authorization.evidence.principalType` — type of the service principal involved
- `identity.authorization.evidence.principalId` — identifier of the service principal involved
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Azure Network Activity Alert Type

## Suspicious Configuration Change to OCI Network Security Group 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious Configuration Change to OCI Network Security Group rules are used to identify suspicious configuration changes to Network Security Groups in OCI. Any one or more of these will trigger the Suspicious OCI Configuration Change to Network Security Group alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_configuration_change_to_network_security_group`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Configuration Change to OCI Network Security Group Alert Type

## Suspicious Connection to Another Process

The Suspicious Connection to Another Process rules are used to identify suspicious connection to another process. Any one or more of these will trigger the Suspicious Connection to Another Process alert types.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Execution (TA0002)
- Technique: Command and Scripting Interpreter (T1059)
- Sub-technique: PowerShell (T1059.001)
- Tags: [PowerShell]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_suspicious_connection_process`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Connection to Another Process Alert Type

## Suspicious Handle Request to Sensitive Object

The Suspicious Handle Request to Sensitive Object rules are used to identify suspicious activity with handle requests to sensitive Windows objects. Any one or more of these will trigger the Suspicious Handle Request to Sensitive Object alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: OS Credential Dumping (T1003)

- Sub-technique: LSASS Memory (T1003.001)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_suspicious_handle_request`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.ObjectName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `event_data.ObjectType` — object type of the handle request
- `event_data.ObjectName` — object name of the handle request
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Handle Request to Sensitive Object Alert Type

## Suspicious Kerberos Authentication from Golden Certificate 6.2.0

The Suspicious Kerberos Authentication from Golden Certificate rules are used to identify suspicious Kerberos certificate-based authentication activity potentially resulting from Golden Certificate in Active Directory. Any one or more of these will trigger the Suspicious Kerberos Authentication from Golden Certificate alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: Steal or Forge Kerberos Tickets (T1558)
- Tags: [Identity Detection]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_kerberos_authentication_from_golden_certificate`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- event_data.CertIssuerName

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `event_data.CertIssuerName` — name of the CA certificate issuer
- `event_data.TargetUserName` — name of the user requesting the Kerberos authentication ticket
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Kerberos Authentication from Golden Certificate Alert Type

## Suspicious LSASS Process Access 5.2.0

The Suspicious LSASS Process Access rules are used to identify suspicious process access to or from the Local Security Authority Subsystem Service (LSASS). Any one or more of these will trigger the Suspicious LSASS Process Access alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Credential Access (TA0006)
- Technique: OS Credential Dumping (T1003)
- Sub-technique: LSASS Memory (T1003.001)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_process_access_lsass`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.ObjectName
- event_data.SourceImage
- event_data.TargetImage
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address

- `hostip_host` — host name
- `event_data.SourceImage` — source image path associated with the activity
- `event_data.TargetImage` — target image path associated with the activity
- `event_data.ObjectType` — object type of the handle request
- `event_data.ObjectName` — object name of the handle request
- `wineventlog_user` — user associated with the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious LSASS Process Access Alert Type

## Suspicious Microsoft Entra Device Activity 5.2.0 5.3.0

The Suspicious Microsoft Entra Device Activity rules are used to identify suspicious Microsoft Entra device activity. Any one or more of these will trigger the Suspicious Microsoft Entra Device Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Network Denial of Service (T1498)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_device_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Microsoft Entra Device Activity Alert Type

## Suspicious Microsoft Entra Service Principal Activity 5.2.0 5.3.0

The Suspicious Microsoft Entra Service Principal Activity rules are used to identify suspicious Microsoft Entra service principal activity. Any one or more of these will trigger the Suspicious Microsoft Entra Service Principal Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Modify Cloud Compute Infrastructure (T1578)
- Tags: [Microsoft Entra]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_azure_service_principal_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- initiatedBy.app.servicePrincipalId
- initiatedBy.user.id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `initiatedBy.user.id` — user ID who initiated the activity
- `initiatedBy.app.servicePrincipalId` — application and Service Principal ID that initiated the activity
- `user.name` — user name
- `activityDisplayName` — activity display name
- `category` — activity category
- `result` — result of the activity
- `resultReason` — result reason of the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Microsoft Entra Service Principal Activity Alert Type

## Suspicious Modification of AWS CloudTrail Logs

The Suspicious Modification of AWS CloudTrail Logs rules are used to identify suspicious activity within AWS CloudTrail logs. Any one or more of these will trigger the Suspicious Modification of

AWS CloudTrail Logs alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_cloudtrail_logs_modification`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Modification of AWS CloudTrail Logs Alert Type

## Suspicious Modification of AWS Route Table

The Suspicious Modification of AWS Route Table rules are used to identify suspicious activity related to modification of AWS route table. Any one or more of these will trigger the Suspicious Modification of AWS Route Table alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_modification_of_route_table`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event
- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Modification of AWS Route Table Alert Type

## Suspicious Modification of OCI Route Table 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious Modification of OCI Route Table rules are used to identify suspicious modification of route tables in OCI. Any one or more of these will trigger the Suspicious OCI Modification of Route Table alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_modification_of_route_table`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `oracle.data.response.status` — status of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Modification of OCI Route Table Alert Type

## Suspicious Modification of S3 Bucket

The Suspicious Modification of S3 Bucket rules are used to identify suspicious activity within S3 Bucket logs. Any one or more of these will trigger the Suspicious Modification of S3 Bucket alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005 )
- Technique: Impair Defenses (T1562 )
- Sub-technique: Disable Cloud Logs (T1562 .008 )
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `aws_suspicious_modification_of_s3_bucket`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- eventName
- eventSource
- service_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `eventSource` — source of event

- `eventName` — name of event
- `eventType` — type of event
- `userIdentity.accountId` — key ID for the account involved in the event
- `userIdentity.userName` — user name of the account involved in the event
- `userIdentity.type` — type of account involved in the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Modification of S3 Bucket Alert Type

## Suspicious OCI Bucket Enumeration 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Bucket Enumeration rules are used to identify suspicious bucket enumeration activity in OCI. Any one or more of these will trigger the Suspicious OCI Bucket Enumeration alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0007)
- Technique: Cloud Infrastructure Discovery (T1580)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_bucket_enumeration`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `oracle.data.identity.principalId` — Oracle Cloud Identifier (OCID) of the principal entity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Bucket Enumeration Alert Type

## Suspicious OCI Bucket Public Access Type Configuration 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Bucket Public Access Type Configuration rules are used to identify suspicious public access type configuration of OCI buckets. Any one or more of these will trigger the Suspicious OCI Bucket Public Access Type Configuration alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration
- Tactic: Discovery (TA0007)
- Technique: Cloud Infrastructure Discovery (T1580)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_bucket_public_access_type_configuration`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `oracle.data.additionalDetails.publicAccessType` — type of public access enabled on the bucket
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Bucket Public Access Type Configuration Alert Type

## Suspicious OCI Event Rule Deletion 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Event Rule Deletion rules are used to identify suspicious deletion activity of event rules in OCI. Any one or more of these will trigger the Suspicious OCI Event Rule Deletion alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Indicator Removal (T1070)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_event_rule_deletion`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Event Rule Deletion Alert Type

## Suspicious OCI IAM Activity: Impact 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI IAM Activity: Impact rules are used to identify suspicious OCI IAM activity usually in the impact stage. Any one or more of these will trigger the Suspicious OCI IAM Activity: Impact alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Account Access Removal (T1531)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_iam_activity_impact`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `oracle.data.response.status` — status of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI IAM Activity: Impact Alert Type

## Suspicious OCI IAM Activity: Persistence 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI IAM Activity: Persistence rules are used to identify suspicious OCI IAM activity usually in the persistence stage. Any one or more of these will trigger the Suspicious OCI IAM Activity: Persistence alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Account Manipulation (T1098)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_iam_activity_persistence`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `oracle.data.response.status` — status of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI IAM Activity: Persistence Alert Type

## Suspicious OCI Inbound SSH Connection 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Inbound SSH Connection rules are used to identify suspicious inbound SSH connection activity in OCI. Any one or more of these will trigger the Suspicious OCI Inbound SSH Connection alert type.

### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: Initial Access (TA0001)
- Technique: Exploit Public-Facing Application (T1190)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_inbound_ssh_connection`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip` — source IP address of the connection
- `dstip` — destination IP address of the connection
- `dstport` — destination port of the connection
- `action` — decision made by the security lists to accept or reject traffic
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Inbound SSH Connection Alert Type

## Suspicious OCI Instance Activity 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Instance Activity rules are used to identify suspicious instance activity in OCI. Any one or more of these will trigger the Suspicious OCI Instance Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Resource Hijacking (T1496)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_instance_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `srcip` — source IP address of the user or service making the API request
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Instance Activity Alert Type

## Suspicious OCI Instance Image Export 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Instance Image Export rules are used to identify suspicious instance image export activity in OCI. Any one or more of these will trigger the Suspicious OCI Instance Image Export alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Exfiltration (TA0010)
- Technique: Transfer Data to Cloud Account (T1537)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_instance_image_export`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `oracle.data.response.status` — status of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Instance Image Export Alert Type

## Suspicious OCI Kubernetes Activity 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Kubernetes Activity rules are used to identify suspicious Kubernetes activity in OCI. Any one or more of these will trigger the Suspicious OCI Kubernetes Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Data Destruction (T1485)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_kubernetes_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Kubernetes Activity Alert Type

## Suspicious OCI Logging Activity 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Logging Activity rules are used to identify suspicious logging activity in OCI. Any one or more of these will trigger the Suspicious OCI Logging Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact
- Tactic: Impact (TA0040)
- Technique: Data Destruction (T1485)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_logging_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Logging Activity Alert Type

## Suspicious OCI Object Storage Activity 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Object Storage Activity rules are used to identify suspicious object storage activity in OCI. Any one or more of these will trigger the Suspicious OCI Object Storage Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Sub-technique: Disable or Modify Cloud Logs (T1562.008)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_object_storage_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `oracle.data.response.status` — status of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Object Storage Activity Alert Type

## Suspicious OCI Scanning Activity 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Scanning Activity rules are used to identify suspicious scanning activity in OCI. Any one or more of these will trigger the Suspicious OCI Scanning Activity alert type.

### XDR Kill Chain

- Kill Chain Stage: Initial Attempts
- Tactic: Reconnaissance (TA0043)
- Technique: Active Scanning (T1595)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_scanning_activity`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- srcip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `srcip` — source IP address of the connection
- `dstip` — destination IP address of the connection
- `dstport` — destination port of the connection
- `action` — decision made by the security lists to accept or reject traffic
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Scanning Activity Alert Type

## Suspicious OCI Security Service Impairment 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The Suspicious OCI Security Service Impairment rules are used to identify suspicious impairment activity to security services in OCI. Any one or more of these will trigger the Suspicious OCI Security Service Impairment alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Impair Defenses (T1562)
- Sub-technique: Disable or Modify Tools (T1562.001)
- Tags: [OCI]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_oci_security_service_impairment`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- oracle.data.eventName
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `oracle.data.eventName` — name of the event
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious OCI Security Service Impairment Alert Type

## Suspicious Office365 Inbox Rule 6.2.0

The Suspicious Office365 Inbox Rule rules are used to identify suspicious Microsoft 365 inbox rules. Any one or more of these will trigger the Suspicious Microsoft 365 Inbox Rule alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Hide Artifacts (T1564)
- Sub-technique: Email Hiding Rules (T1564.008)
- Tags: [Office 365; Identity Detection]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_office365_inbox_rule`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- office365.Operation
- user.name

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `office365.Operation` — name of the mail operation
- `office365.ObjectId` — ID of the inbox rule
- `user.name` — username of the Office 365 account
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Microsoft 365 Inbox Rule Alert Type

## Suspicious Office365 Mail Transport Rule 6.2.0

The Suspicious Office365 Mail Transport Rule rules are used to identify suspicious Microsoft 365 mail transport rules. Any one or more of these will trigger the Suspicious Microsoft 365 Mail Transport Rule alert type.

### XDR Kill Chain

- Kill Chain Stage: Exploration

- Tactic: Collection (TA0009)
- Technique: Email Collection (T1114)
- Tags: [Office 365; Identity Detection]

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_office365_mail_transport_rule`.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- office365.Operation
- user.name

#### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `office365.Operation` — name of the mail operation
- `office365.ObjectId` — ID of the transport rule
- `office365.Name` — name of the transport rule
- `user.name` — username of the Office 365 account
- `stellar.rule_id` — Stellar Cyber rule ID

#### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Microsoft 365 Mail Transport Rule Alert Type

## Suspicious Powershell Script

The Suspicious PowerShell Script rules are used to identify suspicious activity relating to PowerShell scripts. Any one or more of these will trigger the Suspicious PowerShell Script alert types.

#### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Execution (TA0002)
- Technique: Command and Scripting Interpreter (T1059)
- Sub-technique: PowerShell (T1059.001)
- Tags: [PowerShell]

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_powershell_script`.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `hostip_host` — host name
- `wineventlog_user` — Windows user who executed the script
- `event_data.ScriptBlockText` — Powershell script block text
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious PowerShell Script Alert Type

## Suspicious Process Creation Commandline

The Suspicious Process Creation Commandline rules are used to identify suspicious activity relating to command-line process creation. Any one or more of these will trigger the Suspicious Process Creation Commandline alert types.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Execution (TA0002)
- Technique: Command and Scripting Interpreter (T1059)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_commandline`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.CommandLine
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `event_data.CommandLine` — process creation command line
- `hostip_host` — host name
- `wineventlog_user` — Windows user who executed the command
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Process Creation Commandline Alert Type

## Suspicious PsExec Execution 5.4.0

The Suspicious PsExec Execution rules detect suspicious SMB traffic related to PsExec Execution activities. Any one or more of these will trigger the Suspicious PsExec Execution alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Lateral Movement (TA0008)
- Technique: Remote Services (T1021)
- Sub-technique: SMB/Windows Admin Shares (T1021.002)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_win_security_susp_psexec`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious PsExec Execution Alert Type

## Suspicious Windows Active Directory Operation

The Suspicious Windows Active Directory Operation rules are used to identify suspicious activity with Windows Active Directory operation. Any one or more of these will trigger the Suspicious Windows Active Directory Operation alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: [Internal] Crede Access (TA0006)
- Technique: OS Credential Dumping (T1003)
- Tags: []

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_ad_suspicious_operation`.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_id
- stellar.rule_id

#### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

#### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Windows Active Directory Operation Alert Type

## Suspicious Windows Logon Event

The Suspicious Windows Logon Event rules are used to identify suspicious activity with Windows logons. Any one or more of these will trigger the Suspicious Windows Logon alert types.

#### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Valid Accounts (T1078)
- Tags: []

#### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_suspicious_logon_event`.

#### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name

- event_id
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Windows Logon Event Alert Type

## Suspicious Windows Network Connection 5.2.0

The Suspicious Windows Network Connection rules are used to identify suspicious Windows network connection activities. Any one or more of these will trigger the Suspicious Windows Network Connection alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Signed Binary Proxy Execution (T1218)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_windows_network_connection`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.Image
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `hostip_host` — host name
- `event_data.Image` — process associated with the activity
- `wineventlog_user` — user associated with the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Windows Network Connection Alert Type

## Suspicious Windows Process Creation

The Suspicious Windows Process Creation rules are used to identify suspicious activity associated with process creation. Any one or more of these will trigger the Suspicious Process Creation alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Defense Evasion (TA0005)
- Technique: Signed Binary Proxy Execution (T1218)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_suspicious_process_creation`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- process_name
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `process_name` — process associated with the activity
- `hostip_host` — host name
- `wineventlog_user` — Windows user associated with the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Windows Suspicious Process Creation Alert Type

## Suspicious Windows Registry Event: Impact 5.2.0

The Suspicious Windows Registry Event: Impact rules are used to identify suspicious Windows registry events usually in the impact stage. Any one or more of these will trigger the Suspicious Windows Registry Event: Impact alert type.

### XDR Kill Chain

- Kill Chain Stage: Exfiltration & Impact

- Tactic: Impact (TA0040)
- Technique: Defacement (T1491)
- Sub-technique: Internal Defacement (T1491.001)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_windows_registry_event_impact`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.TargetObject
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `hostip_host` — host name
- `event_data.Image` — process associated with the activity
- `event_data.TargetObject` — target registry
- `event_data.Details` — value set to the registry
- `wineventlog_user` — user associated with the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Windows Registry Event: Impact Alert Type

## Suspicious Windows Registry Event: Persistence 5.2.0

The Suspicious Windows Registry Event: Persistence rules are used to identify suspicious Windows registry events usually in the persistence stage. Any one or more of these will trigger the Suspicious Windows Registry Event: Persistence alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Office Application Startup (T1137)
- Sub-technique: Add-ins (T1137.006)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `suspicious_windows_registry_event_persistence`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_data.TargetObject
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `hostip` — host IP address
- `hostip_host` — host name
- `event_data.Image` — process associated with the activity
- `event_data.TargetObject` — target registry
- `event_data.Details` — value set to the registry
- `wineventlog_user` — user associated with the activity
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Windows Registry Event: Persistence Alert Type

## Suspicious Windows Service Installation

The Suspicious Windows Service Installation rules are used to identify suspicious activity with service installation. Any one or more of these will trigger the Suspicious Windows Service Installation alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Execution (TA0002)
- Technique: Command and Scripting Interpreter (T1059)
- Sub-technique: PowerShell (T1059.001)
- Tags: []

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `windows_security_suspicious_service_installation`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- computer_name
- event_id

- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `event_id` — Windows event ID associated with the activity
- `hostip` — host IP address
- `hostip_host` — host name
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Suspicious Windows Service Installation Alert Type

## T1047 Wmiprvse Wbemcomn DLL Hijack 5.4.0

The T1047 Wmiprvse Wbemcomn DLL Hijack rules detect suspicious SMB traffic related to WMI DLL Hijack activities. Any one or more of these will trigger the T1047 Wmiprvse Wbemcomn DLL Hijack alert type.

### XDR Kill Chain

- Kill Chain Stage: Propagation
- Tactic: Lateral Movement (TA0008)
- Technique: Remote Services (T1021)
- Sub-technique: SMB/Windows Admin Shares (T1021.002)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_win_security_wmiprvse_wbemcomn_dll_hijack`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to T1047 W[image_ref id="1" box="0.343,0.057,0.388,0.089"]vse Wbemcomn DLL Hijack Alert Type

## Windows Network Access Suspicious desktop.ini Action 5.4.0

The Windows Network Access Suspicious desktop.ini Action rules detect suspicious SMB traffic accessing desktop.ini files. Any one or more of these will trigger the Windows Network Access Suspicious desktop.ini Action alert type.

### XDR Kill Chain

- Kill Chain Stage: Persistent Foothold
- Tactic: Persistence (TA0003)
- Technique: Boot or Logon Autostart Execution (T1547)
- Sub-technique: Shortcut Modification (T1547.009)
- Tags: [SMB; Network Traffic Analysis]

### Event Name

The `xdr_event.name` for this alert type in the Interflow data is `network_security_net_share_obj_susp_desktop_ini`.

### Alert Suppression Fields

Alert suppression fields are attribute values that trigger deduplication of alerts sharing them.

- appid_name
- srcip
- dstip
- stellar.rule_id

### Key Fields and Relevant Data Points

Key fields are meaningful and human-readable data points representing observable(s) being detected.

- `appid_name` — network traffic protocol that triggered this detection
- `srcip` — source IP address
- `dstip` — destination IP address
- `stellar.rule_id` — Stellar Cyber rule ID

### Link to Rule-Based Alert Types

Rules Contributing to Windows Network Access Suspicious desktop.ini Action Alert Type


© 2026 Stellar Cyber . All rights reserved.