Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Rules Contributing to Potentially Malicious AWS Activity Alert

The following rules are used to identify suspicious activity within AWS logs. Any one or more of these will trigger a Potentially Malicious AWS Activity Alert. Details for each rule can be viewed by clicking the **More Details** link in the description.

Title	Description

SES Identity Has Been Deleted	Detects an instance of an SES identity being deleted via the "DeleteIdentity" event. This may be an indicator of an adversary removing the account that carried out suspicious or malicious activities
	
	More details
	
	Rule ID
	
	`aws_3`
	
	Query
	
	`{'selection': {'eventSource': 'ses.amazonaws.com', 'eventName': 'DeleteIdentity'}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber AWS configured for:
	
	• AWS Cloudtrail
	
	Rule Source
	
	SigmaHQ,20f754db-d025-4a8f-9d74-e0037e999a9a
	
	Author: Janantha Marasinghe
	
	Tactics, Techniques, and Procedures
	
	TA0005, T1070
	
	References
	
	• https://unit42.paloaltonetworks.com/compromised-cloud-compute-credentials/
	
	Severity
	
	50

Title	Description
	pression Logic Based On • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/12/13 **Risk Level**: medium **False Positives**: • Unknown

AWS GuardDuty Important Change	Detects updates of the GuardDuty list of trusted IPs, perhaps to disable security alerts against malicious IPs.
	More details
	Rule ID
	`aws_4`
	Query
	`{'selection_source': {'eventSource': 'guardduty.amazonaws.com', 'eventName': 'CreateIPSet'}, 'condition': 'selection_source'}`
	Log Source
	Stellar Cyber AWS configured for:
	• AWS Cloudtrail
	Rule Source
	SigmaHQ,6e61ee20-ce00-4f8d-8aee-bedd8216f7e3
	Author: faloker
	Tactics, Techniques, and Procedures
	TA0005, T1562.001
	References
	• https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/guardduty__whitelist_ip/main.py#L9
	Severity
	75
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	Additional Information
	Maturity: test
	Creation Date: 2020/02/11
	Risk Level: high
	False Positives:
	• Valid change in the GuardDuty (e.g. to ignore internal scanners)

AWS Glue Development Endpoint Activity	Detects possible suspicious glue development endpoint activity. More details **Rule ID** `aws_5`

Title	Description
	 **ry** `{'selection': {'eventSource': 'glue.amazonaws.com', 'eventName': ['CreateDevEndpoint', 'DeleteDevEndpoint', 'UpdateDevEndpoint']}, 'condition': 'selection'}` **Log Source** Stellar Cyber AWS configured for: • AWS Cloudtrail **Rule Source** SigmaHQ,4990c2e3-f4b8-45e3-bc3c-30b14ff0ed26 Author: Austin Songer @austinsonger **Tactics, Techniques, and Procedures** TA0004, T1078 **References** • https://rhinosecuritylabs.com/aws/aws-privilege-escalation-methods-mitigation/ • https://docs.aws.amazon.com/glue/latest/webapi/API_CreateDevEndpoint.html **Severity** 25 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2021/10/03 **Risk Level**: low **False Positives** • Glue Development Endpoint Activity may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • If known behavior is causing false positives, it can be exempted from the rule.

AWS ECS Backdoor Task Definition	Detects when an Elastic Container Service (ECS) Task Definition has been modified and run. This can indicate an adversary adding a backdoor to establish persistence or escalate privileges. This rule is based on examining events created upon execution of Rhino Security Lab's Pacu in a lab environment.
	More details
	Rule ID
	`aws_7`
	Query
	`{'selection': {'eventSource': 'ecs.amazonaws.com', 'eventName': ['DescribeTaskDefinition', 'RegisterTaskDefinition', 'RunTask'], 'requestParameters_containerDefinitions_command|contains|all': ['169.254', '$AWS_CONTAINER_CREDENTIALS']}, 'condition': 'selection'}`
	Log Source

Title	Description
	ar Cyber AWS configured for: • AWS Cloudtrail **Rule Source** SigmaHQ,b94bf91e-c2bf-4047-9c43-c6810f43baad Author: Darin Smith **Tactics, Techniques, and Procedures** TA0003, T1525 **References** • https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/ecs__backdoor_task_def/main.py • https://docs.aws.amazon.com/AmazonECS/latest/APIReference/API_RegisterTaskDefinition.html **Severity** 50 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/06/07 **Risk Level**: medium **False Positives** • Task Definition being modified to request credentials from the Task Metadata Service for valid reasons

AWS Attached Malicious Lambda Layer	Detects when an user attached a Lambda layer to an existing function to override a library that is in use by the function, where their malicious code could utilize the function's IAM role for AWS API calls. This would give an adversary access to the privileges associated with the Lambda service role that is attached to that function.
	More details
	Rule ID
	`aws_9`
	Query
	`{'selection': {'eventSource': 'lambda.amazonaws.com', 'eventName|startswith': 'UpdateFunctionConfiguration'}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber AWS configured for:
	• AWS Cloudtrail
	Rule Source
	SigmaHQ,97fbabf8-8e1b-47a2-b7d5-a418d2b95e3d
	Author: Austin Songer
	Tactics, Techniques, and Procedures
	TA0004, T1548
	References

Title	Description
	• https://docs.aws.amazon.com/lambda/latest/dg/API_UpdateFunctionConfiguration.html **Severity** 50 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2021/09/23 **Risk Level**: medium **False Positives**: • Lambda Layer being attached may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • Lambda Layer being attached from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS EKS Cluster Created or Deleted	Identifies when an EKS cluster is created or deleted.
	
	More details
	
	Rule ID
	
	`aws_10`
	
	Query
	
	`{'selection': {'eventSource': 'eks.amazonaws.com', 'eventName': ['CreateCluster', 'DeleteCluster']}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber AWS configured for:
	• AWS Cloudtrail
	
	Rule Source
	
	SigmaHQ,33d50d03-20ec-4b74-a74e-1e65a38af1c0
	
	Author: Austin Songer
	
	Tactics, Techniques, and Procedures
	
	TA0040, T1485
	
	References
	• https://any-api.com/amazonaws_com/eks/docs/API_Description
	
	Severity
	
	25
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information

Title	Description
	Security / **Creation Date** / **Risk Level** / **False Positives** test / 2021/08/16 / low • EKS Cluster being created or deleted may be performed by a system administrator. • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. • EKS Cluster created or deleted from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS SecurityHub Findings Evasion	Detects the modification of the findings on SecurityHub.
	
	More details
	
	Rule ID
	`aws_15`
	
	Query
	`{'selection': {'eventSource': 'securityhub.amazonaws.com', 'eventName': ['BatchUpdateFindings', 'DeleteInsight', 'UpdateFindings', 'UpdateInsight']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber AWS configured for:
	• AWS Cloudtrail
	
	Rule Source
	SigmaHQ,a607e1fe-74bf-4440-a3ec-b059b9103157
	
	Author: Sittikorn S
	
	Tactics, Techniques, and Procedures
	TA0005, T1562
	
	References
	• https://docs.aws.amazon.com/cli/latest/reference/securityhub/
	
	Severity
	75
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information
	Maturity / **Creation Date** / **Risk Level** / **False Positives**
	stable / 2021/06/28 / high
	• System or Network administrator behaviors
	• DEV, UAT, SAT environment. You should apply this rule with PROD environment only.

AWS GuardDuty Detector Deletion	Identifies the deletion of an Amazon GuardDuty detector. Upon deletion, GuardDuty stops monitoring the environment and all existing findings are lost. More details

Title	Description

	ID
	`aws_16`
	Query
	`{'selection1': {'eventSource': 'guardduty.amazonaws.com'}, 'selection2': {'eventName': 'DeleteDetector'}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber AWS configured.
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0005, T1562
	References
	N/A
	Severity
	75
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	Additional Information
	Maturity: production
	Creation Date: 2020/05/28
	Risk Level: high
	False Positives
	• The GuardDuty detector may be deleted by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Detector deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS ElastiCache Security Group Created	Identifies when an ElastiCache security group has been created.
	More details
	Rule ID
	`aws_22`
	Query
	`{'selection1': {'eventSource': 'elasticache.amazonaws.com'}, 'selection2': {'eventName': 'Create Cache Security Group'}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber AWS configured.
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0005, T1562,

Title	Description
	erences N/A **Severity** 25 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2021/07/19 **Risk Level**: low **False Positives**: • A ElastiCache security group may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Security group creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS IAM Password Recovery Requested	Identifies AWS IAM password recovery requests. An adversary may attempt to gain unauthorized AWS access by abusing password recovery mechanisms.
	
	More details
	
	Rule ID
	`aws_25`
	
	Query
	`{'selection1': {'eventSource': 'signin.amazonaws.com'}, 'selection2': {'eventName': 'PasswordRecoveryRequested'}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber AWS configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0003, T1078
	
	References
	N/A
	
	Severity
	25
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information

Title	Description
	Maturity: production **Creation Date:** 2020/07/02 **Risk Level:** low **False Positives:** • Verify whether the user identity, user agent, and/or hostname should be requesting changes in your environment. Password reset attempts from unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS EventBridge Rule Disabled or Deleted	Identifies when a user has disabled or deleted an EventBridge rule. This activity can result in an unintended loss of visibility in applications or a break in the flow with other AWS services.
	
	More details
	
	Rule ID
	`aws_27`
	
	Query
	`{'selection1': {'eventSource': 'eventbridge.amazonaws.com'}, 'selection2': {'eventName': ['DeleteRule', 'DisableRule']}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber AWS configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0040, T1489
	
	References
	N/A
	
	Severity
	25
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information
	Maturity: production
	Creation Date: 2021/10/17
	Risk Level: low
	False Positives:
	• EventBridge Rules could be deleted or disabled by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. EventBridge Rules being deleted or disabled by unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS CloudWatch Alarm Deletion	Identifies the deletion of an AWS CloudWatch alarm. An adversary may delete alarms in an attempt to evade defenses. More details **Rule ID**

Title	Description
	 _28 **Query** `{'selection1': {'eventSource': 'monitoring.amazonaws.com'}, 'selection2': {'eventName': 'DeleteAlarms'}, 'condition': 'selection1 and selection2'}` **Log Source** Stellar Cyber AWS configured. **Rule Source** Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0005, T1562 **References** N/A **Severity** 50 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2020/06/15 **Risk Level**: medium **False Positives** • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Alarm deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS Configuration Recorder Stopped	Identifies an AWS configuration change to stop recording a designated set of resources.
	More details
	Rule ID
	`aws_39`
	Query
	`{'selection1': {'eventSource': 'config.amazonaws.com'}, 'selection2': {'eventName': 'StopConfigurationRecorder'}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber AWS configured.
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0005, T1562
	References

Title	Description
	 **Severity** 75 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2020/06/16 **Risk Level**: high **False Positives** • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Recording changes from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS Config Resource Deletion	Identifies attempts to delete an AWS Config Service resource. An adversary may tamper with Config services in order to reduce visibility into the security posture of an account and / or its workload instances.
	More details
	Rule ID
	`aws_41`
	Query
	`{'selection1': {'eventSource': 'config.amazonaws.com'}, 'selection2': {'eventName': ['DeleteConfigRule', 'DeleteOrganizationConfigRule', 'DeleteConfigurationAggregator', 'DeleteConfigurationRecorder', 'DeleteConformancePack', 'DeleteOrganizationConformancePack', 'DeleteDeliveryChannel', 'DeleteRemediationConfiguration', 'DeleteRetentionConfiguration']}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber AWS configured.
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0005, T1562
	References
	N/A
	Severity
	25
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	Additional Information

Title	Description
	 **Maturity** / **Creation Date** / **Risk Level** / **False Positives** production / 2020/06/26 / low • Privileged IAM users with security responsibilities may be expected to make changes to the Config service in order to align with local security policies and requirements. Automation, orchestration, and security tools may also make changes to the Config service, where they are used to automate setup or configuration of AWS accounts. Other kinds of user or service contexts do not commonly make changes to this service.

AWS STS GetSessionToken Abuse	Identifies the suspicious use of GetSessionToken. Tokens could be created and used by attackers to move laterally and escalate privileges.
	
	More details
	
	Rule ID
	`aws_43`
	
	Query
	`{'selection1': {'eventSource': 'sts.amazonaws.com'}, 'selection2': {'eventName': 'GetSessionToken'}, 'selection3': {'userIdentity_type': 'IAMUser'}, 'condition': 'selection1 and selection2 and selection3'}`
	
	Log Source
	Stellar Cyber AWS configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0004, T1548, TA0008, T1550
	
	References
	N/A
	
	Severity
	25
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information
	Maturity / **Creation Date** / **Risk Level** / **False Positives**
	production / 2021/05/17 / low
	• GetSessionToken may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. GetSessionToken from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS WAF Rule or Rule Group Deletion	Identifies the deletion of a specified AWS Web Application Firewall (WAF) rule or rule group. More details

Title	Description

	ID
	`aws_46`
	Query
	`{'selection1': {'eventSource': ['waf.amazonaws.com', 'waf-regional.amazonaws.com', 'wafv2.amazonaws.com']}, 'selection2': {'eventName': ['DeleteRule', 'DeleteRuleGroup']}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber AWS configured.
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0005, T1562
	References
	N/A
	Severity
	50
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	Additional Information
	Maturity: production
	Creation Date: 2020/06/09
	Risk Level: medium
	False Positives
	• WAF rules or rule groups may be deleted by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Rule deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS ElastiCache Security Group Modified or Deleted	Identifies when an ElastiCache security group has been modified or deleted.
	More details
	Rule ID
	`aws_47`
	Query
	`{'selection1': {'eventSource': 'elasticache.amazonaws.com'}, 'selection2': {'eventName': ['Delete Cache Security Group', 'Authorize Cache Security Group Ingress', 'Revoke Cache Security Group Ingress', 'AuthorizeCacheSecurityGroupEgress', 'RevokeCacheSecurityGroupEgress']}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber AWS configured.
	Rule Source

Title	Description
	eloped internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0005, T1562 **References** N/A **Severity** 25 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2021/07/19 **Risk Level**: low **False Positives**: • A ElastiCache security group deletion may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Security Group deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS WAF Access Control List Deletion	Identifies the deletion of a specified AWS Web Application Firewall (WAF) access control list.
	
	More details
	
	Rule ID
	
	`aws_49`
	
	Query
	
	`{'selection1': {'eventSource': 'waf.amazonaws.com'}, 'selection2': {'eventName': 'DeleteWebACL'}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	
	Stellar Cyber AWS configured.
	
	Rule Source
	
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	
	TA0005, T1562
	
	References
	N/A
	
	Severity
	
	50
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id

Title	Description
	itional Information **Maturity**: production **Creation Date**: 2020/05/21 **Risk Level**: medium **False Positives** • Firewall ACL's may be deleted by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Web ACL deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS CloudWatch Log Stream Deletion	Identifies the deletion of an AWS CloudWatch log stream, which permanently deletes all associated archived log events with the stream.
	
	More details
	
	Rule ID
	`aws_52`
	
	Query
	`{'selection1': {'eventSource': 'logs.amazonaws.com'}, 'selection2': {'eventName': 'DeleteLogStream'}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber AWS configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0005, T1562, TA0040, T1485
	
	References
	N/A
	
	Severity
	50
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information
	Maturity: production
	Creation Date: 2020/05/20
	Risk Level: medium
	False Positives
	• A log stream may be deleted by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Log stream deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS SAML Activity	Identifies when SAML activity has occurred in AWS. An adversary could manipulate SAML to maintain access to the target. More details **Rule ID**

Title	Description
	_53 **Query** `{'selection1': {'eventSource': 'iam.amazonaws.com', 'eventName': 'AssumeRoleWithSAML'}, 'selection2': {'eventSource': 'sts.amazonaws.com', 'eventName': 'UpdateSAMLProvider'}, 'condition': 'selection1 or selection2'}` **Log Source** Stellar Cyber AWS configured. **Rule Source** Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0001, T1078, TA0005, T1550 **References** N/A **Severity** 25 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2021/09/22 **Risk Level**: low **False Positives** • SAML Provider could be updated by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. SAML Provider updates by unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS CloudWatch Log Group Deletion	Identifies the deletion of a specified AWS CloudWatch log group. When a log group is deleted, all the archived log events associated with the log group are also permanently deleted.
	More details
	Rule ID
	`aws_55`
	Query
	`{'selection1': {'eventSource': 'logs.amazonaws.com'}, 'selection2': {'eventName': 'DeleteLogGroup'}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber AWS configured.
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures

Title	Description
	 005, T1562, TA0040, T1485 **References** N/A **Severity** 50 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2020/05/18 **Risk Level**: medium **False Positives**: • Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Log group deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS KMS Customer Managed Key Disabled or Scheduled for Deletion	Identifies attempts to disable or schedule the deletion of an AWS KMS Customer Managed Key (CMK). Deleting an AWS KMS key is destructive and potentially dangerous. It deletes the key material and all metadata associated with the KMS key and is irreversible. After a KMS key is deleted, the data that was encrypted under that KMS key can no longer be decrypted, which means that data becomes unrecoverable.
	
	More details
	
	Rule ID
	`aws_56`
	
	Query
	`{'selection1': {'eventSource': 'kms.amazonaws.com'}, 'selection2': {'eventName': ['DisableKey', 'ScheduleKeyDeletion']}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber AWS configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0040, T1485
	
	References
	N/A
	
	Severity
	50
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information

Title	Description
	Maturity / **Creation Date** / **Risk Level** / **False Positives** production / 2022/09/21 / medium • A KMS customer managed key may be disabled or scheduled for deletion by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Key deletions by unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS Redshift Cluster Creation	Identifies the creation of an Amazon Redshift cluster. Unexpected creation of this cluster by a non-administrative user may indicate a permission or role issue with current users. If unexpected, the resource may not properly be configured and could introduce security vulnerabilities.
	
	More details
	
	Rule ID
	`aws_61`
	
	Query
	`{'selection1': {'eventSource': 'redshift.amazonaws.com'}, 'selection2': {'eventName': 'CreateCluster'}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber AWS configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0003, T1078
	
	References
	N/A
	
	Severity
	25
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information
	Maturity / **Creation Date** / **Risk Level** / **False Positives**
	production / 2022/04/12 / low
	• Valid clusters may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Cluster creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS EFS File System or Mount Deleted	Detects when an EFS File System or Mount is deleted. An adversary could break any file system using the mount target that is being deleted, which might disrupt instances or applications using those mounts. The mount must be deleted prior to deleting the File System, or the adversary will be unable to delete the File System.

Title	Description

	More details
	
	Rule ID
	`aws_67`
	
	Query
	`{'selection1': {'eventSource': 'elasticfilesystem.amazonaws.com'}, 'selection2': {'eventName': ['DeleteMountTarget', 'DeleteFileSystem']}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber AWS configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0040, T1485
	
	References
	N/A
	
	Severity
	50
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information
	Maturity: production
	Creation Date: 2021/08/27
	Risk Level: medium
	False Positives:
	• File System or Mount being deleted may be performed by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. File System Mount deletion by unfamiliar users should be investigated. If known behavior is causing false positives, it can be exempted from the rule.

AWS Security Token Service (STS) AssumeRole Usage	Identifies the use of AssumeRole. AssumeRole returns a set of temporary security credentials that can be used to access AWS resources. An adversary could use those credentials to move laterally and escalate privileges.
	
	More details
	
	Rule ID
	`aws_70`
	
	Query
	`{'selection1': {'eventSource': 'sts.amazonaws.com'}, 'selection2': {'eventName': 'AssumedRole'}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber AWS configured.

Title	Description
	Source Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0004, T1548, TA0008, T1550 **References** N/A **Severity** 25 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2021/05/17 **Risk Level**: low **False Positives** • Automated processes that use Terraform may lead to false positives.

AWS Lambda UpdateFunctionCode	This analytic is designed to detect IAM users attempting to update/modify AWS lambda code via the AWS CLI to gain persistence, further access into AWS environment and to facilitate planting backdoors. In this instance, an attacker may upload malicious code/binary to a lambda function which will be executed automatically when the function is triggered.
	More details
	Rule ID
	`aws_89`
	Query
	`{'selection2': {'eventSource': 'lambda.amazonaws.com'}, 'selection3': {'eventName': 'UpdateFunctionCode*'}, 'selection4': {'errorCode': 'success'}, 'selection5': {'userIdentity_type': 'IAMUser'}, 'condition': 'selection2 and selection3 and selection4 and selection5'}`
	Log Source
	Stellar Cyber AWS configured.
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1204
	References
	• https://sysdig.com/blog/exploit-mitigate-aws-lambdas-mitre/
	Severity
	70
	Suppression Logic Based On
	• service_id
	• aws.eventSource

Title	Description
	• aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2022-02-24 **Risk Level**: medium **False Positives**: • While this search has no known false positives, it is possible that an AWS admin or an authorized IAM user has updated the lambda function code legitimately.

AWS ECR Container Scanning Findings	This search looks for AWS CloudTrail events from AWS Elastic Container Registry (ECR) Service.
	
	More details
	
	Rule ID
	`aws_90`
	
	Query
	`{'selection2': {'eventSource': 'ecr.amazonaws.com'}, 'selection3': {'eventName': 'DescribeImageScanFindings'}, 'condition': 'selection2 and selection3'}`
	
	Log Source
	Stellar Cyber AWS configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0002, T1204
	
	References
	• https://docs.aws.amazon.com/AmazonECR/latest/userguide/image-scanning.html
	
	Severity
	10
	
	Suppression Logic Based On
	• service_id
	• aws.eventSource
	• aws.eventName
	• stellar.rule_id
	
	Additional Information
	
	Maturity: production
	Creation Date: 2022-08-25
	Risk Level: medium
	False Positives:
	• unknown

AWS SAML Access by Provider User and Principal	This search provides specific SAML access from specific Service Provider, user and targeted principal at AWS. It also provides specific information to detect abnormal access or potential credential hijack or forgery, specially in federated environments using SAML protocol inside the perimeter or cloud provider. More details **Rule ID** `aws_111` **Query**

Title	Description
	 `election1': {'eventSource': 'sts.amazonaws.com'}, 'sel ection2': {'eventName': 'AssumeRoleWithSAML'}, 'condition ': 'selection1 and selection2'}` **Log Source** Stellar Cyber AWS configured. **Rule Source** Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0005, T1078 **References** • https://www.cisa.gov/uscert/ncas/alerts/aa21-008a • https://www.splunk.com/en_us/blog/security/a-golden-saml-journey-solarwinds-continued.html • https://www.fireeye.com/content/dam/fireeye-www/blog/pdfs/wp-m-unc2452-2021-000343-01.pdf • https://www.cyberark.com/resources/threat-research-blog/golden-saml-newly-discovered-attack-technique-forges-authentication-to-cloud-apps **Severity** 80 **Suppression Logic Based On** • service_id • aws.eventSource • aws.eventName • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2021-01-26 **Risk Level**: medium **False Positives**: • Attacks using a Golden SAML or SAML assertion hijacks or forgeries are very difficult to detect as accessing cloud providers with these assertions looks exactly like normal access, however things such as source IP sourceIPAddress user, and principal targeted at receiving cloud provider along with endpoint credential access and abuse detection searches can provide the necessary context to detect these attacks.

KMS Keys Creation	This search provides detection of KMS Keys Creation
	
	More details
	
	Rule ID
	
	`aws_118`
	
	Query
	
	`{'selection1': {'eventSource': 'kms.amazonaws.com'}, 'sel ection2': {'eventName': 'CreateKey'}, 'selection3': {'eve ntName': 'PutKeyPolicy'}, 'condition': 'selection1 and (s election2 or selection3)'}`
	
	Log Source
	
	Stellar Cyber AWS configured.
	
	Rule Source

Title	Description
	eloped internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0040, T1486

References

- https://rhinosecuritylabs.com/aws/s3-ransomware-part-1-attack-vector/
- https://github.com/d1vious/git-wild-hunt
- https://www.youtube.com/watch?v=PgzNib37g0M

Severity

50

Suppression Logic Based On

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2021-01-11	medium	• unknown

© 2026 Stellar Cyber . All rights reserved.