Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Rules Contributing to Sensitive Windows Active Directory Attribute Modification Alerts 6.3.0

The following rules are used to identify suspicious activity with sensitive Windows Active Directory attribute modification. Any one or more of these will trigger Sensitive Windows Active Directory Attribute Modification Alert. Details for each rule can be viewed by clicking the **More Details** link in the description.

Windows Events Required: 4742, 5136

The Windows Detect Profile (Low Volume) covers these required Windows events.

Title	Description
Suspicious LDAP-Attributes Used	Detects the usage of particular AttributeLDAPDisplayNames, which are known for data exchange via LDAP by the tool LDAPFragger and are additionally not commonly used in companies. More details
User account exposed to Kerberoasting	Detects when a user account has the servicePrincipalName attribute modified. Attackers can abuse write privileges over a user to configure Service Principle Names (SPNs) so that they can perform Kerberoasting. Administrators can also configure this for legitimate purposes, exposing the account to Kerberoasting. More details
Powerview Add-DomainObjectAcl DCSync AD Extend Right	Backdooring domain object to grant the rights associated with DCSync to a regular user or machine account using Powerview\Add-DomainObjectAcl DCSync Extended Right cmdlet, will allow to re-obtain the pwd hashes of any user/computer More details
Possible Shadow Credentials Added	Detects possible addition of shadow credentials to an active directory object. More details
Potential Shadow Credentials added to AD Object	Identify the modification of the msDS-KeyCredentialLink attribute in an Active Directory Computer or User Object. Attackers can abuse control over the object and create a key pair, append to raw public key in the attribute, and obtain persistent and stealthy access to the target user or computer object.

Title	Description
	More details
AdminSDHolder Backdoor	Detects modifications in the AdminSDHolder object. Attackers can abuse the SDProp process to implement a persistent backdoor in Active Directory. SDProp compares the permissions on protected objects with those defined on the AdminSDHolder object. If the permissions on any of the protected accounts and groups do not match, the permissions on the protected accounts and groups are reset to match those of the domain's AdminSDHolder object, regaining their Administrative Privileges. More details
Possible DC Shadow Attack	Detects DCShadow via create new SPN More details
Modification of the msPKIAccountCredentials	Identify the modification of the msPKIAccountCredentials attribute in an Active Directory User Object. Attackers can abuse the credentials roaming feature to overwrite an arbitrary file for privilege escalation. ms-PKI-AccountCredentials contains binary large objects (BLOBs) of encrypted credential objects from the credential manager store, private keys, certificates, and certificate requests. More details
Windows AD SID History Attribute Modified	Detects modifications to the SID History attribute in Active Directory. This detection identifies changes to the sIDHistory attribute which can be exploited by adversaries to inherit permissions from other accounts, potentially granting unauthorized access. If confirmed malicious, this activity could allow attackers to maintain persistent access and escalate privileges within the domain, posing a significant security risk. More details

© 2026 Stellar Cyber . All rights reserved.