Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

# Rules Contributing to Suspicious AWS RDS Event

The following rules are used to identify suspicious activity related to AWS RDS events. Any one or more of these will trigger Suspicious AWS RDS Event Alert. Details for each rule can be viewed by clicking the **More Details** link in the description.

| Title | Description |
| --- | --- |
| Restore Public AWS RDS Instance | Detects the recovery of a new public database instance from a snapshot. It may be a part of data exfiltration.<br><br>More details<br><br>**Rule ID**<br><br>`aws_1`<br><br>**Query**<br><br>`{'selection_source': {'eventSource': 'rds.amazonaws.com', 'responseElements_publiclyAccessible': True, 'eventName': 'RestoreDBInstanceFromDBSnapshot'}, 'condition': 'selection_source'}`<br><br>**Log Source**<br><br>Stellar Cyber AWS configured for:<br><br>• AWS Cloudtrail<br><br>**Rule Source**<br><br>SigmaHQ,c3f265c7-ff03-4056-8ab2-d486227b4599<br><br>Author: faloker<br><br>**Tactics, Techniques, and Procedures**<br><br>TA0010, T1020<br><br>**References**<br><br>• https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/rds__explore_snapshots/main.py,<br><br>**Severity**<br><br>75 |

| Title | Description |
| --- | --- |
| | **Suppression Logic Based On**<br>• service_id<br>• aws.eventSource<br>• aws.eventName<br>• stellar.rule_id<br><br>**Additional Information**<br>**Maturity**: test<br>**Creation Date**: 2020/02/12<br>**Risk Level**: high<br>**False Positives**:<br>• Unknown |
| AWS RDS Master Password Change | Detects the change of database master password. It may be a part of data exfiltration.<br><br>More details<br><br>**Rule ID**<br>`aws_14`<br><br>**Query**<br>`{'selection_source': {'eventSource': 'rds.amazonaws.com', 'responseElements_pendingModifiedValues_masterUserPassword\|contains': '*', 'eventName': 'ModifyDBInstance'}, 'condition': 'selection_source'}`<br><br>**Log Source**<br>Stellar Cyber AWS configured for:<br>• AWS Cloudtrail<br><br>**Rule Source**<br>SigmaHQ,8a63cdd4-6207-414a-85bc-7e032bd3c1a2<br><br>Author: faloker<br><br>**Tactics, Techniques, and Procedures**<br>TA0010, T1020<br><br>**References**<br>• https://github.com/RhinoSecurityLabs/pacu/blob/866376cd711666c775bbfcde0524c817f2c5b181/pacu/modules/rds__explore_snapshots/main.py<br><br>**Severity**<br>50<br><br>**Suppression Logic Based On**<br>• service_id<br>• aws.eventSource<br>• aws.eventName<br>• stellar.rule_id<br><br>**Additional Information**<br>**Maturity**: experimental<br>**Creation Date**: 2020/02/12<br>**Risk Level**: medium<br>**False Positives**:<br>• Benign changes to a db instance |
| AWS RDS Snapshot Export | Identifies the export of an Amazon Relational Database Service (RDS) Aurora database snapshot.<br><br>More details<br><br>**Rule ID**<br>`aws_21`<br><br>**Query** |

| Title | Description |
| --- | --- |
| | `{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'StartExportTask'}, 'condition': 'selection1 and selection2'}`<br><br>**Log Source**<br><br>Stellar Cyber AWS configured.<br><br>**Rule Source**<br><br>Developed internally by Stellar Cyber<br><br>**Tactics, Techniques, and Procedures**<br><br>TA0010, T1567<br><br>**References**<br>N/A<br><br>**Severity**<br><br>25<br><br>**Suppression Logic Based On**<br>• service_id<br>• aws.eventSource<br>• aws.eventName<br>• stellar.rule_id<br><br>**Additional Information**<br><br>**Maturity**: production<br>**Creation Date**: 2021/06/06<br>**Risk Level**: low<br>**False Positives**:<br>• Exporting snapshots may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Snapshot exports from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. |
| AWS RDS Cluster Creation | Identifies the creation of a new Amazon Relational Database Service (RDS) Aurora DB cluster or global database spread across multiple regions.<br><br>More details<br><br>**Rule ID**<br><br>`aws_36`<br><br>**Query**<br><br>`{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': ['CreateDBCluster', 'CreateGlobalCluster']}, 'condition': 'selection1 and selection2'}`<br><br>**Log Source**<br><br>Stellar Cyber AWS configured.<br><br>**Rule Source**<br><br>Developed internally by Stellar Cyber<br><br>**Tactics, Techniques, and Procedures**<br><br>TA0003, T1133<br><br>**References**<br>N/A |

| Title | Description |
| --- | --- |

**Severity**

25

**Suppression Logic Based On**

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

**Additional Information**

| Maturity | Creation Date | Risk Level | False Positives |
| --- | --- | --- | --- |
| production | 2020/05/20 | low | • Valid clusters may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Cluster creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. |

---

AWS RDS Snapshot Restored

Identifies when an attempt was made to restore an RDS Snapshot. Snapshots are sometimes shared by threat actors in order to exfiltrate bulk data or evade detection after performing malicious activities. If the permissions were modified, verify if the snapshot was shared with an unauthorized or unexpected AWS account.

More details

**Rule ID**

`aws_59`

**Query**

```
{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'RestoreDBInstanceFromDBSnapshot', 'responseElements_publiclyAccessible': False}, 'condition': 'selection1 and selection2'}
```

**Log Source**

Stellar Cyber AWS configured.

**Rule Source**

Developed internally by Stellar Cyber

**Tactics, Techniques, and Procedures**

TA0005, T1578

**References**

N/A

**Severity**

50

**Suppression Logic Based On**

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

**Additional Information**

| Maturity | Creation Date | Risk Level | False Positives |
| --- | --- | --- | --- |
| production | 2021/06/29 | medium | • Restoring snapshots may be done by a system or network administrator. Verify whether the user identity, user agent, and/or |

| Title | Description |
|---|---|
| | **Maturity** / **Creation Date** / **Risk Level** / **False Positives**<br>n<br>hostname should be making changes in your environment. Snapshot restoration by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. |
| AWS RDS Instance/Cluster Stoppage | Identifies that an Amazon Relational Database Service (RDS) cluster or instance has been stopped.<br><br>More details<br><br>**Rule ID**<br>`aws_60`<br><br>**Query**<br>`{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': ['StopDBCluster', 'StopDBInstance']}, 'condition': 'selection1 and selection2'}`<br><br>**Log Source**<br>Stellar Cyber AWS configured.<br><br>**Rule Source**<br>Developed internally by Stellar Cyber<br><br>**Tactics, Techniques, and Procedures**<br>TA0040, T1489<br><br>**References**<br>N/A<br><br>**Severity**<br>50<br><br>**Suppression Logic Based On**<br>• service_id<br>• aws.eventSource<br>• aws.eventName<br>• stellar.rule_id<br><br>**Additional Information**<br>**Maturity** / **Creation Date** / **Risk Level** / **False Positives**<br>production / 2020/05/20 / medium<br>• Valid clusters or instances may be stopped by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Cluster or instance stoppages from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. |
| AWS Deletion of RDS Instance or Cluster | Identifies the deletion of an Amazon Relational Database Service (RDS) Aurora database cluster, global database cluster, or database instance.<br><br>More details<br><br>**Rule ID**<br>`aws_64`<br><br>**Query** |

| Title | Description |
| --- | --- |
| |  <br>`{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': ['DeleteDBCluster', 'DeleteGlobalCluster', 'DeleteDBInstance']}, 'condition': 'selection1 and selection2'}`<br>**Log Source**<br>Stellar Cyber AWS configured.<br>**Rule Source**<br>Developed internally by Stellar Cyber<br>**Tactics, Techniques, and Procedures**<br>TA0040, T1485<br>**References**<br>N/A<br>**Severity**<br>50<br>**Suppression Logic Based On**<br>• service_id<br>• aws.eventSource<br>• aws.eventName<br>• stellar.rule_id<br>**Additional Information**<br>**Maturity**: production<br>**Creation Date**: 2020/05/21<br>**Risk Level**: medium<br>**False Positives**<br>• Clusters or instances may be deleted by a system administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Cluster or instance deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. |
| AWS RDS Security Group Deletion | Identifies the deletion of an Amazon Relational Database Service (RDS) Security group.<br>More details<br>**Rule ID**<br>`aws_65`<br>**Query**<br>`{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'DeleteDBSecurityGroup'}, 'condition': 'selection1 and selection2'}`<br>**Log Source**<br>Stellar Cyber AWS configured.<br>**Rule Source**<br>Developed internally by Stellar Cyber<br>**Tactics, Techniques, and Procedures**<br>TA0040, T1531<br>**References**<br>N/A<br>**Severity** |

| Title | Description |
| --- | --- |
| | 25  <br>**Suppression Logic Based On**<br>• service_id<br>• aws.eventSource<br>• aws.eventName<br>• stellar.rule_id<br>**Additional Information**<br>**Maturity**: production<br>**Creation Date**: 2021/06/05<br>**Risk Level**: low<br>**False Positives**<br>• An RDS security group deletion may be done by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Security group deletions by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. |
| AWS RDS Instance Creation | Identifies the creation of an Amazon Relational Database Service (RDS) Aurora database instance.<br>More details<br>**Rule ID**<br>`aws_68`<br>**Query**<br>`{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'CreateDBInstance'}, 'condition': 'selection1 and selection2'}`<br>**Log Source**<br>Stellar Cyber AWS configured.<br>**Rule Source**<br>Developed internally by Stellar Cyber<br>**Tactics, Techniques, and Procedures**<br>TA0003, T1078<br>**References**<br>N/A<br>**Severity**<br>25<br>**Suppression Logic Based On**<br>• service_id<br>• aws.eventSource<br>• aws.eventName<br>• stellar.rule_id<br>**Additional Information**<br>**Maturity**: production<br>**Creation Date**: 2021/06/06<br>**Risk Level**: low<br>**False Positives**<br>• A database instance may be created by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. Instances creations by unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. |

| Title | Description |
| --- | --- |
| AWS RDS Snapshot Created | A copy of an AWS RDS database has been created.<br><br>More details<br><br>**Rule ID**<br>`aws_97`<br><br>**Query**<br>`{'selection1': {'eventSource': 'rds.amazonaws.com'}, 'selection2': {'eventName': 'CreateDBSnapshot'}, 'condition': 'selection1 and selection2'}`<br><br>**Log Source**<br>Stellar Cyber AWS configured.<br><br>**Rule Source**<br>Developed internally by Stellar Cyber<br><br>**Tactics, Techniques, and Procedures**<br>TA0009, T1074<br><br>**References**<br>N/A<br><br>**Severity**<br>50<br><br>**Suppression Logic Based On**<br>• service_id<br>• aws.eventSource<br>• aws.eventName<br>• stellar.rule_id<br><br>**Additional Information**<br>**Maturity**: test<br>**Creation Date**: 2022/01/05<br>**Risk Level**: medium<br>**False Positives**: N/A |
| AWS RDS Security Group Modified | A RDS security group has been modified.<br><br>More details<br><br>**Rule ID**<br>`aws_103`<br><br>**Query**<br>`{'selection1': {'eventSource': 'ec2.amazonaws.com'}, 'selection2': {'eventName': 'AuthorizeDBSecurityGroupIngress'}, 'selection3': {'eventName': 'RevokeDBSecurityGroupIngress'}, 'selection4': {'eventName': 'AuthorizeDBSecurityGroupEgress'}, 'selection5': {'eventName': 'RevokeDBSecurityGroupEgress'}, 'selection6': {'userAgent': 'cloudformation.amazonaws.com'}, 'condition': 'selection1 and (selection2 or selection3 or selection4 or selection5) and not selection6'}`<br><br>**Log Source**<br>Stellar Cyber AWS configured.<br><br>**Rule Source**<br>Developed internally by Stellar Cyber |

| Title | Description |
| --- | --- |

**Tactics, T[illegible]ques, and Procedures**

TA0003, T1098

**References**

N/A

**Severity**

50

**Suppression Logic Based On**

- service_id
- aws.eventSource
- aws.eventName
- stellar.rule_id

**Additional Information**

| Maturity | Creation Date | Risk Level | False Positives |
| --- | --- | --- | --- |
| test | 2022/01/05 | medium | N/A |



© 2026 Stellar Cyber . All rights reserved.