Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Rules Contributing to Suspicious OCI IAM Activity: Impact Alert 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The following rules are used to identify suspicious OCI IAM activity usually in the impact stage. Any one or more of these will trigger the Suspicious OCI IAM Activity: Impact Alert. Details for each rule can be viewed by clicking the **More Details** link in the description.

Title	Description

OCI IAM Successful Group Deletion	Identifies the deletion of a specified Oracle Cloud Infrastructure (OCI) Identity and Access Management (IAM) group, which is a collection of users who share a similar set of access privileges. The group must be empty.
	
	More details
	
	Rule ID
	`oci_audit_1`
	
	Query
	`{'selection1': {'eventName': 'deletegroup'}, 'selection2': {'status': ['200', '204']}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber OCI configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0040, T1531
	
	References
	N/A
	
	Severity
	25

Title	Description
	Suppression Logic Based On • oracle.data.resourceId • oracle.data.eventName • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2025/02/21 **Risk Level**: low **False Positives** • Routine administrative tasks may trigger alerts when IAM groups are deleted as part of regular maintenance or restructuring. To manage this, create exceptions for known maintenance periods or specific administrative accounts. • Automated scripts or tools that manage IAM resources might delete groups as part of their normal operation. Identify these scripts and exclude their actions from triggering alerts by using specific user or role identifiers. • Temporary groups created for short-term projects or testing purposes might be deleted frequently. Document these groups and exclude their deletion from monitoring by using naming conventions or tags. • Changes in organizational structure or policy might necessitate the deletion of certain groups. Coordinate with relevant teams to anticipate these changes and adjust monitoring rules accordingly.

OCI IAM Deactivation of MFA Device	Identifies the deactivation of a specified multi-factor authentication (MFA) time-based one-time password (TOTP) device and removes it from association with the user for which it was originally enabled.
	
	More details
	
	Rule ID
	`oci_audit_15`
	
	Query
	`{'selection': {'eventName': 'deletemfatotpdevice'}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber OCI configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0040, T1531, TA0003, T1556.006
	
	References
	N/A
	
	Severity
	50
	
	Suppression Logic Based On
	• oracle.data.resourceId
	• oracle.data.eventName
	• stellar.rule_id
	
	Additional Information

Title	Description

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/26	medium	• A MFA device may be deactivated by a system or network administrator. Verify whether the user identity, user agent, and/or hostname should be making changes in your environment. MFA device deactivations from unfamiliar users or hosts should be investigated. If known behavior is causing false positives, it can be exempted from the rule. • While this activity can be done by administrators, all users must use MFA. The security team should address any potential benign true positive (B-TP), as this configuration can risk the user and domain.

© 2026 Stellar Cyber . All rights reserved.