Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Rules Contributing to Suspicious OCI IAM Activity: Persistence Alert 6.0.0

This topic covers a feature that is not available for all customers yet. See Early Access Program Features and Topics Under Development.

The following rules are used to identify suspicious OCI IAM activity usually in the persistence stage. Any one or more of these will trigger the Suspicious OCI IAM Activity: Persistence Alert. Details for each rule can be viewed by clicking the **More Details** link in the description.

Title	Description

OCI IAM Failure Group Deletion	Identifies failed attempts to delete OCI IAM groups, detecting events where the DeleteGroup action fails due to errors like Forbidden, Not Found, or Conflict. This activity is significant as it may indicate unauthorized attempts to modify IAM group configurations, which could be a precursor to privilege escalation or other malicious actions. If confirmed malicious, this could allow an attacker to disrupt IAM policies, potentially leading to unauthorized access or denial of service within the OCI environment.
	
	More details
	
	Rule ID
	`oci_audit_2`
	
	Query
	`{'selection1': {'eventName': 'deletegroup'}, 'selection2': {'status': ['400', '401', '403', '404', '409', '412', '429']}, 'condition': 'selection1 and selection2'}`
	
	Log Source
	Stellar Cyber OCI configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0003, T1098
	
	References
	N/A

Title	Description
	Severity  10 **Suppression Logic Based On** • oracle.data.resourceId • oracle.data.eventName • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2025/02/21 **Risk Level**: medium **False Positives** • This detection will require tuning to provide high fidelity detection capabilities. Tune based on src addresses (corporate offices, VPN terminations) or by groups of users. Not every user with OCI access should have permission to delete groups (least privilege).

OCI IAM Delete Policy	The following detection identifies when a policy is deleted on OCI. This does not identify whether successful or failed, but the error messages tell a story of suspicious attempts.
	More details
	Rule ID
	`oci_audit_3`
	Query
	`{'selection': {'eventName': 'deletepolicy'}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber OCI configured.
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0003, T1098
	References
	N/A
	Severity
	20
	Suppression Logic Based On
	• oracle.data.resourceId
	• oracle.data.eventName
	• stellar.rule_id
	Additional Information
	Maturity: experimental
	Creation Date: 2025/02/21
	Risk Level: medium
	False Positives
	• This detection will require tuning to provide high fidelity detection capabilities. Tune based on src addresses (corporate offices, VPN terminations) or by groups of users. Not every user with OCI access should have permission to delete policies (least privilege). In addition, this may be saved separately and tuned for failed or success attempts only.

Title	Description

OCI IAM Group Creation	Identifies the creation of a group in Oracle Cloud Infrastructure (OCI) Identity and Access Management (IAM). Groups specify permissions for multiple users. Any user in a group automatically has the permissions that are assigned to the group.
	
	More details
	
	Rule ID
	`oci_audit_4`
	
	Query
	`{'selection': {'eventName': 'creategroup'}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber OCI configured.
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0003, T1136
	
	References
	N/A
	
	Severity
	25
	
	Suppression Logic Based On
	• oracle.data.resourceId
	• oracle.data.eventName
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2025/02/24
	Risk Level: low
	False Positives:
	• Routine administrative actions by authorized personnel can trigger alerts. Regularly review and document legitimate group creation activities to differentiate them from unauthorized actions.
	• Automated scripts or tools used for infrastructure management may create groups as part of their normal operation. Identify and whitelist these scripts to prevent unnecessary alerts.
	• Temporary groups created for short-term projects or testing purposes might be flagged. Implement a naming convention for such groups and exclude them from alerts based on this pattern.
	• Scheduled tasks or maintenance activities that involve group creation should be logged and approved in advance. Use these logs to create exceptions in the detection rule.
	• Third-party integrations or services that require group creation for functionality can cause false positives. Verify these integrations and adjust the rule to exclude their known actions.

OCI IAM Policy Modification	OCI IAM policies associated with a user have been modified. More details **Rule ID** `oci_audit_8` **Query**

Title	Description
	{'selectio {'eventName': ['addusertogroup', 'removeuserfromgroup']}, 'condition': 'selection'}

Log Source

Stellar Cyber OCI configured.

Rule Source

Developed internally by Stellar Cyber

Tactics, Techniques, and Procedures

TA0003, T1098

References

N/A

Severity

50

Suppression Logic Based On

- oracle.data.resourceId
- oracle.data.eventName
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2025/02/24	medium	N/A

© 2026 Stellar Cyber . All rights reserved.