Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Rules Contributing to Suspicious PowerShell Script Alert Type 6.1.0 6.3.0

The following rules are used to identify suspicious activity relating to PowerShell scripts. Any one or more of these will trigger the PowerShell Script Alert. Details for each rule can be viewed by clicking the **More Details** link in the description.

Windows Events Required: 4104

The Windows Detect Profile (Low Volume) covers these required Windows events.

Title	Description

PowerShell Mailbox Collection Script	Detects PowerShell scripts that can be used to collect data from mailboxes. Adversaries may target user email to collect sensitive information.
	
	More details
	
	Rule ID
	`powershell_scriptblock_1`
	
	Query
	`{'selection1': {'ScriptBlockText|contains': ['Microsoft.Office.Interop.Outlook', 'Interop.Outlook.olDefaultFolders', '::olFolderInBox', 'Microsoft.Exchange.WebServices.Data.Folder', 'Microsoft.Exchange.WebServices.Data.FileAttachment']}, 'condition': 'selection1'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0009, T1114
	
	References
	N/A

Title	Description
	everity 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2023/01/11 **Risk Level**: medium **False Positives**: N/A

Live Memory Dump Using Powershell	Detects usage of a PowerShell command to dump the live memory of a Windows machine
	More details
	Rule ID
	`powershell_scriptblock_3`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Get-StorageDiagnosticInfo', '-IncludeLiveDump']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,cd185561-4760-45d6-a63e-a51325112cae
	Author: Max Altgelt (Nextron Systems)
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0006, T1003
	References
	• https://docs.microsoft.com/en-us/powershell/module/storage/get-storagediagnosticinfo
	Severity
	74
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: test
	Creation Date: 2021/09/21
	Risk Level: high
	False Positives
	• Diagnostics

Invoke-Obfuscation CLIP+ Launcher - PowerShell	Detects Obfuscated use of Clip.exe to execute PowerShell More details **Rule ID** `powershell_scriptblock_4` **Query**

Title	Description
	 `'selection_4104': {'ScriptBlockText|re': '.*cmd.{0,5}(?:/c|/r).+clip(?:\\.exe)?.{0,4}&&.+clipboard]::\\(\\s\\\\\"\\{\\d\\}.+-f.+"'}, 'condition': 'selection_4104'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,73e67340-0d25-11eb-adc1-0242ac120002 Author: Jonathan Cheong, oscd.community **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1027 **References** • https://github.com/SigmaHQ/sigma/issues/1009 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2020/10/13 **Risk Level**: high **False Positives**: • Unknown

Suspicious Service DACL Modification Via Set-Service Cmdlet - PS	Detects usage of the "Set-Service" powershell cmdlet to configure a new SecurityDescriptor that allows a service to be hidden from other utilities such as "sc.exe", "Get-Service"...etc. (Works only in powershell 7)
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_5`
	
	Query
	
	`{'selection_sddl_flag': {'ScriptBlockText|contains': ['-SecurityDescriptorSddl ', '-sd ']}, 'selection_set_service': {'ScriptBlockText|contains|all': ['Set-Service ', 'D;;'], 'ScriptBlockText|contains': [';;;IU', ';;;SU', ';;;BA', ';;;SY', ';;;WD']}, 'condition': 'all of selection_*'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,22d80745-6f2c-46da-826b-77adaededd74
	
	Author: Nasreddine Bencherchali (Nextron Systems)

Title	Description
	Tactics, Techniques, and Procedures TA0002, T1059.001, TA0003, T1574.011 **References** • https://twitter.com/Alh4zr3d/status/1580925761996828672 • https://learn.microsoft.com/en-us/powershell/module/microsoft.powershell.management/set-service?view=powershell-7.2 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2022/10/24 Risk Level: high False Positives: • Rare intended use of hidden services • Rare FP could occure due to the non linearity of the ScriptBlockText log

Potential Invoke-Mimikatz PowerShell Script	Detects Invoke-Mimikatz PowerShell script and alike. Mimikatz is a credential dumper capable of obtaining plaintext Windows account logins and passwords.
	More details
	Rule ID
	`powershell_scriptblock_6`
	Query
	`{'selection_1': {'ScriptBlockText|contains|all': ['DumpCreds', 'DumpCerts']}, 'selection_2': {'ScriptBlockText|contains': 'sekurlsa::logonpasswords'}, 'selection_3': {'ScriptBlockText|contains|all': ['crypto::certificates', 'CERT_SYSTEM_STORE_LOCAL_MACHINE']}, 'condition': '1 of selection*'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	SigmaHQ,189e3b02-82b2-4b90-9662-411eb64486d4
	Author: Tim Rauch, Elastic (idea)
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0006, T1003
	References
	• https://www.elastic.co/guide/en/security/current/potential-invoke-mimikatz-powershell-script.html#potential-invoke-mimikatz-powershell-script
	Severity
	74
	Suppression Logic Based On
	• computer_name

Title	Description
	 • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/09/28 **Risk Level**: high **False Positives**: • Mimikatz can be useful for testing the security of networks

Disable-WindowsOptionalFeature Command PowerShell	Detect built in PowerShell cmdlet Disable-WindowsOptionalFeature, Deployment Image Servicing and Management tool. Similar to DISM.exe, this cmdlet is used to enumerate, install, uninstall, configure, and update features and packages in Windows images
	
	More details
	
	Rule ID
	`powershell_scriptblock_7`
	
	Query
	`{'selection_cmd': {'ScriptBlockText|contains|all': ['Disable-WindowsOptionalFeature', '-Online', '-FeatureName']}, 'selection_feature': {'ScriptBlockText|contains': ['Windows-Defender-Gui', 'Windows-Defender-Features', 'Windows-Defender', 'Windows-Defender-ApplicationGuard']}, 'condition': 'all of selection*'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,99c4658d-2c5e-4d87-828d-7c066ca537c3
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1562.001
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/5b67c9b141fa3918017f8fa44f2f88f0b1ecb9e1/atomics/T1562.001/T1562.001.md
	• https://docs.microsoft.com/en-us/powershell/module/dism/disable-windowsoptionalfeature?view=windowsserver2022-ps
	
	Severity
	74
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/09/10
	Risk Level: high
	False Positives:
	• Unknown

Powershell DNSExfiltration	DNSExfiltrator allows for transferring (exfiltrate) a file over a DNS request covert channel

Title	Description

	 e details
	
	Rule ID
	
	`powershell_scriptblock_8`
	
	Query
	
	`{'selection_cmdlet': [{'ScriptBlockText|contains': 'Invoke-DNSExfiltrator'}, {'ScriptBlockText|contains|all': [' -i ', ' -d ', ' -p ', ' -doh ', ' -t ']}], 'condition': 'selection_cmdlet'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,d59d7842-9a21-4bc6-ba98-64bfe0091355
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001, TA0010, T1048
	
	References
	
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1048/T1048.md#atomic-test-3---dnsexfiltration-doh
	• https://github.com/Arno0x/DNSExfiltrator
	
	Severity
	
	74
	
	Suppression Logic Based On
	
	• computer_name
	• stellar.rule_id
	
	Additional Information
	
	Maturity: test
	Creation Date: 2022/01/07
	Risk Level: high
	False Positives:
	• Legitimate script

Powershell Empire agent CnC activity	A Powershell Empire framework agent is running on the machine, and it's trying to access the CnC server.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_9`
	
	Query
	
	`{'selection1': {'ScriptBlockText|contains': 'IF($PSVERSIonTAblE.PSVERsIOn.MajOr -ge 3){'}, 'selection2': {'ScriptBlockText|contains': '[Ref].ASsEmbLY.GeTTYpe('}, 'selection3': {'ScriptBlockText|contains': 'System.Management.Automation.AmsiUtils'}, 'condition': 'selection1 and selection2 and selection3'}`
	
	Log Source

Title	Description
	tellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts **Rule Source** Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0002, T1059.001 **References** N/A **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2022/05/01 **Risk Level**: medium **False Positives**: N/A

Powershell Directory Enumeration	Detects technique used by MAZE ransomware to enumerate directories using Powershell
	More details
	Rule ID
	`powershell_scriptblock_10`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['foreach', 'Get-ChildItem', '-Path ', '-ErrorAction ', 'SilentlyContinue', 'Out-File ', '-append']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,162e69a7-7981-4344-84a9-0f1c9a217a52
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0007, T1083
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1083/T1083.md
	• https://www.mandiant.com/resources/tactics-techniques-procedures-associated-with-maze-ransomware-incidents
	Severity
	49

Title	Description
	uppression Logic Based On • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2022/03/17 **Risk Level**: medium **False Positives**: • Legitimate PowerShell scripts

Invoke-Obfuscation Via Use MSHTA - PowerShell	Detects Obfuscated Powershell via use MSHTA in Scripts
	
	More details
	
	Rule ID
	`powershell_scriptblock_11`
	
	Query
	`{'selection_4104': {'ScriptBlockText|contains|all': ['set', '&&', 'mshta', 'vbscript:createobject', '.run', '(window.close)']}, 'condition': 'selection_4104'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,e55a5195-4724-480e-a77e-3ebe64bd3759
	
	Author: Nikita Nazarov, oscd.community
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1027
	
	References
	• https://github.com/SigmaHQ/sigma/issues/1009
	
	Severity
	74
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2020/10/08
	Risk Level: high
	False Positives:
	• Unknown

Root Certificate Installed - PowerShell	Adversaries may install a root certificate on a compromised system to avoid warnings when connecting to adversary controlled web servers.
	
	More details
	
	Rule ID
	`powershell_scriptblock_12`
	
	Query
	`{'selection1': {'ScriptBlockText|contains|all': ['Move-Item', 'Cert:\\LocalMachine\\Root']}, 'selection2': {'ScriptBlockText|contains|all': ['Import-`

Title	Description
	 ertificate', 'Cert:\\LocalMachine\\Root']}, 'condition': '1 of selection*'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,42821614-9264-4761-acfc-5772c3286f76 Author: oscd.community, @redcanary, Zach Stanford @svch0st **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1553.004 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1553.004/T1553.004.md **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2020/10/10 **Risk Level**: medium **False Positives**: • Help Desk or IT may need to manually add a corporate Root CA on occasion. Need to test if GPO push doesn't trigger FP
Clearing Windows Console History	Identifies when a user attempts to clear console history. An adversary may clear the command history of a compromised account to conceal the actions undertaken during an intrusion. More details **Rule ID** powershell_scriptblock_15 **Query** {'selection1': {'ScriptBlockText|contains': 'Clear-History'}, 'selection2a': {'ScriptBlockText|contains': ['Remove-Item', 'rm']}, 'selection2b': {'ScriptBlockText|contains': ['ConsoleHost_history.txt', '(Get-PSReadlineOption).HistorySavePath']}, 'condition': 'selection1 or selection2a and selection2b'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source**

Title	Description
	 igmaHQ,bde47d4b-9987-405c-94c7-b080410e8ea7 Author: Austin Songer @austinsonger **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1070.003 **References** • https://stefanos.cloud/blog/kb/how-to-clear-the-powershell-command-history/ • https://www.shellhacks.com/clear-history-powershell/ • https://community.sophos.com/sophos-labs/b/blog/posts/powershell-command-history-forensics **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2021/11/25 **Risk Level**: high **False Positives**: • Unknown

Windows Firewall Profile Disabled	Detects when a user disables the Windows Firewall via a Profile to help evade defense.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_16`
	
	Query
	
	`{'selection_args': {'ScriptBlockText|contains|all': ['Set-NetFirewallProfile ', ' -Enabled ', ' False']}, 'selection_opt': {'ScriptBlockText|contains': [' -All ', 'Public', 'Domain', 'Private']}, 'condition': 'all of selection*'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,488b44e7-3781-4a71-888d-c95abfacf44d
	
	Author: Austin Songer @austinsonger
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001, TA0005, T1562.004
	
	References
	
	• https://docs.microsoft.com/en-us/powershell/module/netsecurity/set-netfirewallprofile?view=windowsserver2019-ps
	• https://www.tutorialspoint.com/how-to-get-windows-firewall-profile-settings-using-powershell
	• http://powershellhelp.space/commands/set-netfirewallrule-psv5.php

Title	Description
	 • http://woshub.com/manage-windows-firewall-powershell/ • https://www.elastic.co/guide/en/security/current/windows-firewall-disabled-via-powershell.html **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2021/10/12 **Risk Level**: medium **False Positives**: • Unknown

Suspicious Portable Executable Encoded in Powershell Script	Detects the presence of a portable executable (PE) in a PowerShell script by looking for its encoded header. Attackers embed PEs into PowerShell scripts to inject them into memory, avoiding defences by not writing to disk.
	More details
	Rule ID
	`powershell_scriptblock_17`
	Query
	`{'selection1': {'ScriptBlockText|contains': 'TVqQAAMAAAAEAAAA'}, 'selection2': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	N/A
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: production
	Creation Date: 2021/10/15
	Risk Level: medium
	False Positives: N/A

PowerShell Suspicious Script with Screenshot Capabilities	Detects PowerShell scripts that can take screenshots, which is a common feature in post-exploitation kits and remote access tools (RATs). More details **Rule ID** `powershell_scriptblock_19`

Title	Description
	Query `{'selection1': {'ScriptBlockText|contains': 'CopyFromScreen'}, 'selection2': {'ScriptBlockText|contains': 'System.Drawing.Bitmap'}, 'selection3': {'ScriptBlockText|contains': 'Drawing.Bitmap'}, 'selection4': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (selection2 or selection3) and (not selection4)'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts **Rule Source** Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0009, T1113 **References** N/A **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: production; Creation Date: 2021/10/19; Risk Level: medium; False Positives: N/A

Registry-Free Process Scope COR_PROFILER	Adversaries may leverage the COR_PROFILER environment variable to hijack the execution flow of programs that load the .NET CLR. The COR_PROFILER is a .NET Framework feature which allows developers to specify an unmanaged (or external of .NET) profiling DLL to be loaded into each .NET process that loads the Common Language Runtime (CLR). These profiliers are designed to monitor, troubleshoot, and debug managed code executed by the .NET CLR. (Citation: Microsoft Profiling Mar 2017) (Citation: Microsoft COR_PROFILER Feb 2013)
	More details
	Rule ID
	`powershell_scriptblock_20`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['$env:COR_ENABLE_PROFILING', '$env:COR_PROFILER', '$env:COR_PROFILER_PATH']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,23590215-4702-4a70-8805-8dc9e58314a2

Title	Description
	Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0003, T1574.012 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1574.012/T1574.012.md#atomic-test-3---registry-free-process-scope-cor_profiler **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity** test **Creation Date** 2021/12/30 **Risk Level** medium **False Positives** • Legitimate administrative script

Title	Description

Invoke-Obfuscation RUNDLL LAUNCHER - PowerShell	Detects Obfuscated Powershell via RUNDLL LAUNCHER
	
	More details
	
	Rule ID
	`powershell_scriptblock_21`
	
	Query
	`{'selection_4104': {'ScriptBlockText|contains|all': ['rundll32.exe', 'shell32.dll', 'shellexec_rundll', 'powershell']}, 'condition': 'selection_4104'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,e6cb92b4-b470-4eb8-8a9d-d63e8583aae0
	
	Author: Timur Zinniatullin, oscd.community
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1027
	
	References
	• https://github.com/SigmaHQ/sigma/issues/1009
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2020/10/18
	Risk Level: medium
	False Positives:
	• Unknown

Execution via CL_Invocation.ps1 - Powershell	Detects Execution via SyncInvoke in CL_Invocation.ps1 module
	
	More details
	
	Rule ID
	`powershell_scriptblock_23`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['CL_Invocation.ps1', 'SyncInvoke']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,4cd29327-685a-460e-9dac-c3ab96e549dc

Title	Description
	Author: oscd.community, Natalia Shornikova **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1216 **References** • https://lolbas-project.github.io/lolbas/Scripts/CI_invocation/ • https://twitter.com/bohops/status/948061991012327424 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2020/10/14 **Risk Level**: high **False Positives**: • Unknown

Suspicious TCP Tunnel Via PowerShell Script	Detects powershell scripts that creates sockets/listeners which could be indicative of tunneling activity
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_24`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains|all': ['[System.Net.HttpWebRequest]', 'System.Net.Sockets.TcpListener', 'AcceptTcpClient']}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,bd33d2aa-497e-4651-9893-5c5364646595
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001, TA0011, T1090
	
	References
	
	• https://github.com/Arno0x/PowerShellScripts/blob/a6b7d5490fbf0b20f91195838f3a11156724b4f7/proxyTunnel.ps1
	
	Severity
	
	49
	
	Suppression Logic Based On
	
	• computer_name
	• stellar.rule_id
	
	Additional Information

Title	Description			
	Maturity	**Creation Date**	**Risk Level**	**False Positives**
	experimental	2022/07/08	medium	• Unknown

Powershell Store File In Alternate Data Stream	Storing files in Alternate Data Stream (ADS) similar to Astaroth malware.
	
	More details
	
	Rule ID
	`powershell_scriptblock_25`
	
	Query
	`{'selection_compspec': {'ScriptBlockText|contains|all': ['Start-Process', '-FilePath "$env:comspec" ', '-ArgumentList ', '>']}, 'condition': 'selection_compspec'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,a699b30e-d010-46c8-bbd1-ee2e26765fe9
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1564.004
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1564.004/T1564.004.md
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2021/09/02
	Risk Level: medium
	False Positives: • Unknown

Potential PowerShell Obfuscation Using Character Join	Detects specific techniques often seen used inside of PowerShell scripts to obfscuate Alias creation
	
	More details
	
	Rule ID
	`powershell_scriptblock_26`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['-Alias', ' -Value (-join(']}, 'condition': 'selection'}`
	
	Log Source

Title	Description
	tellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,e8314f79-564d-4f79-bc13-fbc0bf2660d8 Author: Nasreddine Bencherchali (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1027 **References** N/A **Severity** 24 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2023/01/09 **Risk Level**: low **False Positives**: • Unknown

Windows UAC Bypass	A User Account Control Bypass activity was detected. This can be due to either regular operation or because an attacker is trying to escalate privileges.
	More details
	Rule ID
	`powershell_scriptblock_27`
	Query
	`{'selection1': {'ScriptBlockText|contains': 'Invoke-UACBypass'}, 'selection2': {'ScriptBlockText|contains': 'Invoke-EventVwrBypass'}, 'selection3': {'ScriptBlockText|contains': 'Invoke-SDCLTBypass'}, 'condition': 'selection1 or selection2 or selection3'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	N/A
	Severity
	49

Title	Description
	Suppression Logic Based On • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2022/05/01 **Risk Level**: medium **False Positives**: N/A

Suspicious IO.FileStream	Open a handle on the drive volume via the \\.\ DOS device path specifier and perform direct access read of the first few bytes of the volume.
	
	More details
	
	Rule ID
	`powershell_scriptblock_28`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['New-Object', 'IO.FileStream', '\\\\.\\']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,70ad982f-67c8-40e0-a955-b920c2fa05cb
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1070.003
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1006/T1006.md
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2022/01/09
	Risk Level: medium
	False Positives:
	• Legitimate PowerShell scripts

Invoke-Obfuscation VAR+ Launcher - PowerShell	Detects Obfuscated use of Environment Variables to execute PowerShell
	
	More details
	
	Rule ID
	`powershell_scriptblock_29`
	
	Query
	`{'selection_4104': {'ScriptBlockText|re': '.*cmd.{0,5}(?:/c|/r)(?:\\s|)"set\\s[a-zA-Z]{3,6}.*(?:\\{\\d\\})`

Title	Description
	 1,}\\\\"\\s+?-f(?:.*\\)) {1,}.*"'}, 'condition': 'selection_4104'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,0adfbc14-0ed1-11eb-adc1-0242ac120002 Author: Jonathan Cheong, oscd.community **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1027 **References** • https://github.com/SigmaHQ/sigma/issues/1009 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2020/10/15 **Risk Level**: high **False Positives**: • Unknown
Powershell XML Execute Command	Adversaries may abuse PowerShell commands and scripts for execution. PowerShell is a powerful interactive command-line interface and scripting environment included in the Windows operating system. (Citation: TechNet PowerShell) Adversaries can use PowerShell to perform a number of actions, including discovery of information and execution of code More details **Rule ID** powershell_scriptblock_30 **Query** {'selection_xml': {'ScriptBlockText|contains|all': ['New- Object', 'System.Xml.XmlDocument', '.Load']}, 'selection_exec': {'ScriptBlockText|contains': ['IEX ', 'Invoke-Expression ', 'Invoke-Command ', 'ICM - ']}, 'condition': 'all of selection_*'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,6c6c6282-7671-4fe9-a0ce-a2dcebdc342b Author: frack113

Title	Description
	actics, Techniques, and Procedures TA0002, T1059.001 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1059.001/T1059.001.md#atomic-test-8---powershell-xml-requests **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental; Creation Date: 2022/01/19; Risk Level: medium; False Positives: • Legitimate administrative script

Dump Credentials from Windows Credential Manager With PowerShell	Adversaries may search for common password storage locations to obtain user credentials. Passwords are stored in several places on a system, depending on the operating system or application holding the credentials.
	More details
	Rule ID
	`powershell_scriptblock_33`
	Query
	`{'selection_kiddie': {'ScriptBlockText|contains': ['Get-PasswordVaultCredentials', 'Get-CredManCreds']}, 'selection_rename_Password': {'ScriptBlockText|contains|all': ['New-Object', 'Windows.Security.Credentials.PasswordVault']}, 'selection_rename_credman': {'ScriptBlockText|contains|all': ['New-Object', 'Microsoft.CSharp.CSharpCodeProvider', '[System.Runtime.InteropServices.RuntimeEnvironment]::GetRuntimeDirectory())', 'Collections.ArrayList', 'System.CodeDom.Compiler.CompilerParameters']}, 'condition': '1 of selection_*'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,99c49d9c-34ea-45f7-84a7-4751ae6b2cbc
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0006, T1555
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1555/T1555.md

Title	Description
	everity 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2021/12/20 **Risk Level**: medium **False Positives** • Unknown

Potential Suspicious Windows Feature Enabled	Detects usage of the built-in PowerShell cmdlet "Enable-WindowsOptionalFeature" used as a Deployment Image Servicing and Management tool. Similar to DISM.exe, this cmdlet is used to enumerate, install, uninstall, configure, and update features and packages in Windows images
	
	More details
	
	Rule ID
	`powershell_scriptblock_35`
	
	Query
	`{'selection_cmd': {'ScriptBlockText|contains|all': ['Enable-WindowsOptionalFeature', '-Online', '-FeatureName']}, 'selection_feature': {'ScriptBlockText|contains': ['TelnetServer', 'Internet-Explorer-Optional-amd64', 'TFTP', 'SMB1Protocol', 'Client-ProjFS', 'Microsoft-Windows-Subsystem-Linux']}, 'condition': 'all of selection*'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,55c925c1-7195-426b-a136-a9396800e29b
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	
	References
	• https://docs.microsoft.com/en-us/powershell/module/dism/enable-windowsoptionalfeature?view=windowsserver2022-ps
	• https://learn.microsoft.com/en-us/windows/win32/projfs/enabling-windows-projected-file-system
	• https://learn.microsoft.com/en-us/windows/wsl/install-on-server
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information

Title	Description			
	Maturity	**Creation Date**	**Risk Level**	**False Positives**
	experimental	2022/09/10	medium	• Unknown

Suspicious PowerShell Mailbox SMTP Forward Rule	Detects usage of the powerShell Set-Mailbox Cmdlet to set-up an SMTP forwarding rule.
	
	More details
	
	Rule ID
	`powershell_scriptblock_36`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Set-Mailbox ', ' -DeliverToMailboxAndForward ', ' -ForwardingSmtpAddress ']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,15b7abbb-8b40-4d01-9ee2-b51994b1d474
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	
	References
	• https://m365internals.com/2022/10/07/hunting-in-on-premises-exchange-server-logs/
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/10/26
	Risk Level: medium
	False Positives: • Legitimate usage of the cmdlet to forward emails

Powershell Add Name Resolution Policy Table Rule	Detects powershell scripts that adds a Name Resolution Policy Table (NRPT) rule for the specified namespace. This will bypass the default DNS server and uses a specified server for answering the query.
	
	More details
	
	Rule ID
	`powershell_scriptblock_37`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Add-DnsClientNrptRule', '-Namesp', '-NameSe']}, 'condition': 'selection'}`

Title	Description
	Log Source Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,4368354e-1797-463c-bc39-a309effbe8d7 Author: Borna Talebi **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0040, T1565 **References** • https://twitter.com/NathanMcNulty/status/1569497348841287681 • https://docs.microsoft.com/en-us/powershell/module/dnsclient/add-dnsclientnrptrule?view=windowsserver2022-ps **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2021/09/14 Risk Level: high False Positives: • Unknown

Security Software Discovery by Powershell	Adversaries may attempt to get a listing of security software, configurations, defensive tools, and sensors that are installed on a system or in a cloud environment. This may include things such as firewall rules and anti-viru
	More details
	Rule ID
	`powershell_scriptblock_38`
	Query
	`{'selection_1': {'ScriptBlockText|contains|all': ['get-process', '.Description', '-like']}, 'selection_2': {'ScriptBlockText|contains': ['"*virus*"', '"*carbonblack*"', '"*defender*"', '"*cylance*"']}, 'condition': 'all of selection_*'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,904e8e61-8edf-4350-b59c-b905fc8e810c
	Author: frack113, Anish Bogati, Nasreddine Bencherchali (Nextron Systems)
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0007, T1518.001

Title	Description
	References • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1518.001/T1518.001.md **Severity** 24 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2021/12/16 Risk Level: low False Positives: • Unknown

Suspicious New-PSDrive to Admin Share	Adversaries may use to interact with a remote network share using Server Message Block (SMB). The adversary may then perform actions as the logged-on user.
	More details
	Rule ID
	`powershell_scriptblock_39`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['New-PSDrive', '-psprovider ', 'filesystem', '-root ', '\\\\', '$']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,1c563233-030e-4a07-af8c-ee0490a66d3a
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0008, T1021.002
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1021.002/T1021.002.md#atomic-test-2---map-admin-share-powershell
	• https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.management/new-psdrive?view=powershell-7.2
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: experimental
	Creation Date: 2022/08/13
	Risk Level: medium
	False Positives: • Unknown

Title	Description

PowerShell Script with Token Impersonation Capabilities	Detects scripts that contain PowerShell functions, structures, or Windows API functions related to token impersonation/theft. Attackers may duplicate then impersonate another user's token to escalate privileges and bypass access controls.
	
	More details
	
	Rule ID
	`powershell_scriptblock_40`
	
	Query
	`{'selection1': {'ScriptBlockText|contains': ['Invoke-TokenManipulation', 'ImpersonateNamedPipeClient', 'NtImpersonateThread']}, 'selection2': {'ScriptBlockText|contains': 'STARTUPINFOEX'}, 'selection3': {'ScriptBlockText|contains': 'UpdateProcThreadAttribute'}, 'selection4': {'ScriptBlockText|contains': 'AdjustTokenPrivileges'}, 'selection5': {'ScriptBlockText|contains': 'SeDebugPrivilege'}, 'selection6': {'UserId': 'S-1-5-18'}, 'condition': '(selection1 or (selection2 and selection3) or (selection4 and selection5)) and (not selection6)'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, T1106, TA0005, T1134
	
	References
	N/A
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: production
	Creation Date: 2022/08/17
	Risk Level: medium
	False Positives: N/A

Disable of ETW Trace - Powershell	Detects usage of powershell cmdlets to disable or remove ETW trace sessions
	
	More details
	
	Rule ID
	`powershell_scriptblock_41`
	
	Query
	`{'selection_pwsh_remove': {'ScriptBlockText|contains': 'Remove-EtwTraceProvider '}, 'selection_pwsh_set': {'ScriptBlockText|contains|all': ['Set-`

Title	Description
	 twTraceProvider ', '0x11']}, 'condition': '1 of selection*'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,115fdba9-f017-42e6-84cf-d5573bf2ddf8 Author: Nasreddine Bencherchali (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1070, T1562.006 **References** • https://medium.com/palantir/tampering-with-windows-event-tracing-background-offense-and-defense-4be7ac62ac63 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/06/28 **Risk Level**: high **False Positives**: • Unknown
Service Registry Permissions Weakness Check	Adversaries may execute their own malicious payloads by hijacking the Registry entries used by services. Adversaries may use flaws in the permissions for registry to redirect from the originally specified executable to one that they control, in order to launch their own code at Service start. Windows stores local service configuration information in the Registry under HKLM\SYSTEM\CurrentControlSet\Services More details **Rule ID** powershell_scriptblock_42 **Query** {'selection': {'ScriptBlockText|contains|all': ['get-acl', 'REGISTRY::HKLM\\SYSTEM\\CurrentControlSet\\Services\\']}, 'condition': 'selection'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,95afc12e-3cbb-40c3-9340-84a032e596a3 Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0003, T1574.011

Title	Description
	References • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1574.011/T1574.011.md#atomic-test-1---service-registry-permissions-weakness • https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.security/get-acl?view=powershell-7.2 **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2021/12/30 **Risk Level**: medium **False Positives** • Legitimate administrative script

Potential COM Objects Download Cradles Usage - PS Script	Detects usage of COM objects that can be abused to download files in PowerShell by CLSID
	More details
	Rule ID
	`powershell_scriptblock_43`
	Query
	`{'selection_1': {'ScriptBlockText|contains': '[Type]::GetTypeFromCLSID('}, 'selection_2': {'ScriptBlockText|contains': ['0002DF01-0000-0000-C000-000000000046', 'F6D90F16-9C73-11D3-B32E-00C04F990BB4', 'F5078F35-C551-11D3-89B9-0000F81FE221', '88d96a0a-f192-11d4-a65f-0040963251e5', 'AFBA6B42-5692-48EA-8141-DC517DCF0EF1', 'AFB40FFD-B609-40A3-9828-F88BBE11E4E3', '88d96a0b-f192-11d4-a65f-0040963251e5', '2087c2f4-2cef-4953-a8ab-66779b670495', '000209FF-0000-0000-C000-000000000046', '00024500-0000-0000-C000-000000000046']}, 'condition': 'all of selection_*'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Script Block Logging must be enable
	Rule Source
	SigmaHQ,3c7d1587-3b13-439f-9941-7d14313dbdfe
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	• https://learn.microsoft.com/en-us/dotnet/api/system.type.gettypefromclsid?view=net-7.0
	• https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=57

Title	Description
	everity 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/12/25 **Risk Level**: medium **False Positives**: • Legitimate use of the library

Dnscat Execution	Dnscat exfiltration tool execution
	More details
	Rule ID
	`powershell_scriptblock_44`
	Query
	`{'selection': {'ScriptBlockText|contains': 'Start-Dnscat2'}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,a6d67db4-6220-436d-8afc-f3842fe05d43
	Author: Daniil Yugoslavskiy, oscd.community
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0010, T1048
	References
	N/A
	Severity
	95
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: test
	Creation Date: 2019/10/24
	Risk Level: critical
	False Positives:
	• Legitimate usage of PowerShell Dnscat2 — DNS Exfiltration tool (unlikely)

Suspicious Unblock-File	Remove the Zone.Identifier alternate data stream which identifies the file as downloaded from the internet. More details **Rule ID** `powershell_scriptblock_45`

Title	Description
	Query `{'selection': {'ScriptBlockText|contains|all': ['Unblock-File ', '-Path ']}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,5947497f-1aa4-41dd-9693-c9848d58727d Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1553 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1553.005/T1553.005.md#atomic-test-3---remove-the-zoneidentifier-alternate-data-stream • https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.utility/unblock-file?view=powershell-7.2 **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity** test **Creation Date** 2022/02/01 **Risk Level** medium **False Positives** • Legitimate PowerShell scripts

AMSI Bypass Pattern Assembly GetType	Detects code fragments found in small and obfuscated AMSI bypass PowerShell scripts
	More details
	Rule ID
	`powershell_scriptblock_47`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['[Ref].Assembly.GetType', 'SetValue($null,$true)', 'NonPublic,Static']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,e0d6c087-2d1c-47fd-8799-3904103c5a98
	Author: Florian Roth (Nextron Systems)

Title	Description
	actics, Techniques, and Procedures TA0002, T1059.001, TA0005, T1562.001 **References** • https://www.mdsec.co.uk/2018/06/exploring-powershell-amsi-and-logging-evasion/ **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/11/09 **Risk Level**: high **False Positives**: • Unknown

Remove Account From Domain Admin Group	Adversaries may interrupt availability of system and network resources by inhibiting access to accounts utilized by legitimate users. Accounts may be deleted, locked, or manipulated (ex: changed credentials) to remove access to accounts.
	More details
	Rule ID
	`powershell_scriptblock_48`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Remove-ADGroupMember', '-Identity ', '-Members ']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,48a45d45-8112-416b-8a67-46e03a4b2107
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0040, T1531
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1531/T1531.md#atomic-test-3---remove-account-from-domain-admin-group
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information

Title	Description			
	Maturity	Creation Date	Risk Level	False Positives
	test	2021/12/26	medium	• Unknown

Suspicious Hyper-V Cmdlets	Adversaries may carry out malicious operations using a virtual instance to avoid detection
	
	More details
	
	Rule ID
	`powershell_scriptblock_49`
	
	Query
	`{'selection': {'ScriptBlockText|contains': ['New-VM', 'Set-VMFirmware', 'Start-VM']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,42d36aa1-3240-4db0-8257-e0118dcdd9cd
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1564.006
	
	References
	• https://docs.microsoft.com/en-us/virtualization/hyper-v-on-windows/quick-start/enable-hyper-v
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1564.006/T1564.006.md#atomic-test-3---create-and-start-hyper-v-virtual-machine
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/04/09
	Risk Level: medium
	False Positives: • Legitimate PowerShell scripts			

Zip A Folder With PowerShell For Staging In Temp - PowerShell Script	Use living off the land tools to zip a file and stage it in the Windows temporary folder for later exfiltration
	
	More details
	
	Rule ID
	`powershell_scriptblock_50`
	
	Query
	`{'selection_4104': {'ScriptBlockText|contains|all': ['Compress-Archive ', ' -Path ', ' -`			

Title	Description
	estinationPath ', '$env:TEMP\\']}, 'condition': 'selection_4104'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,b7a3c9a3-09ea-4934-8864-6a32cacd98d9 Author: Nasreddine Bencherchali (Nextron Systems), frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0009, T1074.001 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1074.001/T1074.001.md **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2021/07/20 **Risk Level**: medium **False Positives**: • Unknown
PowerShell ShellCode	Detects Base64 encoded Shellcode More details **Rule ID** powershell_scriptblock_52 **Query** {'selection': {'ScriptBlockText|contains': 'AAAAYInlM'}, 'selection2': {'ScriptBlockText|contains': ['OiCAAAAYInlM', 'OiJAAAAYInlM']}, 'condition': 'selection and selection2'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,16b37b70-6fcf-4814-a092-c36bd3aafcbd Author: David Ledbetter (shellcode), Florian Roth (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1055 **References**

Title	Description
	 • https://twitter.com/cyb3rops/status/1063072865992523776 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2018/11/17 **Risk Level**: high **False Positives** • Unknown

Suspicious Eventlog Clear	Detects usage of known powershell cmdlets such as "Clear-EventLog" to clear the windows event logs
	
	More details
	
	Rule ID
	`powershell_scriptblock_53`
	
	Query
	`{'selection': {'ScriptBlockText|contains': ['Clear-EventLog ', 'Remove-EventLog ', 'Limit-EventLog ', 'Clear-WinEvent ']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,0f017df3-8f5a-414f-ad6b-24aff1128278
	
	Author: Nasreddine Bencherchali (Nextron Systems), Swachchhanda Shrawan Poudel (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1070.001
	
	References
	• https://twitter.com/oroneequalsone/status/1568432028361830402
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1070.001/T1070.001.md
	• https://eqllib.readthedocs.io/en/latest/analytics/5b223758-07d6-4100-9e11-238cfdd0fe97.html
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information

Title	Description
	Maturity / **Creation Date** / **Risk Level** / **False Positives** experiment al / 2022/09/12 / medium / • Rare need to clear logs before doing something. Sometimes used by installers or cleaner scripts. The script should be investigated to determine if it's legitimate

Powershell Local Email Collection	Adversaries may target user email on local systems to collect sensitive information. Files containing email data can be acquired from a users local system, such as Outlook storage or cache files.
	
	More details
	
	Rule ID
	`powershell_scriptblock_54`
	
	Query
	`{'selection': {'ScriptBlockText|contains': ['Get-Inbox.ps1', 'Microsoft.Office.Interop.Outlook', 'Microsoft.Office.Interop.Outlook.olDefaultFolders', '-comobject outlook.application']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,2837e152-93c8-43d2-85ba-c3cd3c2ae614
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0009, T1114.001
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1114.001/T1114.001.md
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2021/07/21
	Risk Level: medium
	False Positives: • Unknown

Suspicious FromBase64String Usage On Gzip Archive - Ps Script	Detects attempts of decoding a base64 Gzip archive in a PowerShell script. This technique is often used as a method to load malicious content into memory afterward. More details **Rule ID** `powershell_scriptblock_55`

Title	Description
	Query `{'selection': {'ScriptBlockText|contains|all': ['FromBase64String', 'MemoryStream', 'H4sI']}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,df69cb1d-b891-4cd9-90c7-d617d90100ce Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001 **References** • https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=43 **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/12/23 **Risk Level**: medium **False Positives** • Legitimate administrative script

PowerShell ADRecon Execution	Detects execution of ADRecon.ps1 for AD reconnaissance which has been reported to be actively used by FIN7
	More details
	Rule ID
	`powershell_scriptblock_56`
	Query
	`{'selection': {'ScriptBlockText|contains': ['Function Get-ADRExcelComOb', 'Get-ADRGPO', 'Get-ADRDomainController', 'ADRecon-Report.xlsx']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,bf72941a-cba0-41ea-b18c-9aca3925690d
	Author: Bhabesh Raj
	Tactics, Techniques, and Procedures

Title	Description

A0002, T1059.001

References

- https://github.com/sense-of-security/ADRecon/blob/11881a24e9c8b207f31b56846809ce1fb189bcc9/ADRecon.ps1
- https://bi-zone.medium.com/from-pentest-to-apt-attack-cybercriminal-group-fin7-disguises-its-malware-as-an-ethical-hackers-c23c9a75e319

Severity

74

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2021/07/16	high	• Unknown

Access to Browser Login Data

Adversaries may acquire credentials from web browsers by reading files specific to the target browser. Web browsers commonly save credentials such as website usernames and passwords so that they do not need to be entered manually in the future. Web browsers typically store the credentials in an encrypted format within a credential store.

More details

Rule ID

`powershell_scriptblock_57`

Query

```
{'selection_cmd': {'ScriptBlockText|contains|all': ['Copy-Item', '-Destination']}, 'selection_path': {'ScriptBlockText|contains': ['\\Opera Software\\Opera Stable\\Login Data', '\\Mozilla\\Firefox\\Profiles', '\\Microsoft\\Edge\\User Data\\Default', '\\Google\\Chrome\\User Data\\Default\\Login Data', '\\Google\\Chrome\\User Data\\Default\\Login Data For Account']}, 'condition': 'all of selection_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,fc028194-969d-4122-8abe-0470d5b8f12f

Author: frack113

Tactics, Techniques, and Procedures

TA0002, T1059.001, TA0006, T1555.003

References

- https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1555.003/T1555.003.md

Severity

Title	Description
9 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2022/01/30 **Risk Level**: medium **False Positives** • Unknown	

Abuse of Service Permissions to Hide Services Via Set-Service - PS	Detects usage of the "Set-Service" powershell cmdlet to configure a new SecurityDescriptor that allows a service to be hidden from other utilities such as "sc.exe", "Get-Service"...etc. (Works only in powershell 7)
	
	More details
	
	Rule ID
	`powershell_scriptblock_58`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Set-Service ', 'DCLCWPDTSD'], 'ScriptBlockText|contains': ['-SecurityDescriptorSddl ', '-sd ']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,953945c5-22fe-4a92-9f8a-a9edc1e522da
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0003, T1574.011
	
	References
	• https://twitter.com/Alh4zr3d/status/1580925761996828672
	• https://learn.microsoft.com/en-us/powershell/module/microsoft.powershell.management/set-service?view=powershell-7.2
	
	Severity
	74
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/10/17
	Risk Level: high
	False Positives
	• Rare intended use of hidden services
	• Rare FP could occure due to the non linearity of the ScriptBlockText log

Computer Discovery And Export Via Get-ADComputer Cmdlet -	Detects usage of the Get-ADComputer cmdlet to collect computer information and output it to a file

Title	Description

PowerShell	 e details
	
	Rule ID
	`powershell_scriptblock_59`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Get-ADComputer ', ' -Filter *'], 'ScriptBlockText|contains': [' | Select ', 'Out-File', 'Set-Content', 'Add-Content']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,db885529-903f-4c5d-9864-28fe199e6370
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0007, T1033
	
	References
	• http://blog.talosintelligence.com/2022/09/lazarus-three-rats.html
	• https://www.microsoft.com/en-us/security/blog/2022/10/18/defenders-beware-a-case-for-post-ransomware-investigations/
	• https://www.cisa.gov/uscert/sites/default/files/publications/aa22-320a_joint_csa_iranian_government-sponsored_apt_actors_compromise_federal%20network_deploy_crypto%20miner_credential_harvester.pdf
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/11/17
	Risk Level: medium
	False Positives:
	• Legitimate admin scripts may use the same technique, it's better to exclude specific computers or users who execute these commands or scripts often

PowerShell PSAttack	Detects the use of PSAttack PowerShell hack tool
	
	More details
	
	Rule ID
	`powershell_scriptblock_60`
	
	Query
	`{'selection': {'ScriptBlockText|contains': 'PS ATTACK!!!'}, 'condition': 'selection'}`

Title	Description
	Log Source Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,b7ec41a4-042c-4f31-a5db-d0fcde9fa5c5 Author: Sean Metcalf (source), Florian Roth (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001 **References** • https://adsecurity.org/?p=2921 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2017/03/05 Risk Level: high False Positives: • Unknown

PowerShell Invoke-NinjaCopy script	Detects PowerShell scripts that contain the default exported functions used on Invoke-NinjaCopy. Attackers can use Invoke-NinjaCopy to read SYSTEM files that are normally locked, such as the NTDS.dit file or registry hives.
	More details
	Rule ID
	`powershell_scriptblock_61`
	Query
	`{'selection1': {'ScriptBlockText|contains': ['StealthReadFile', 'StealthReadFileAddr', 'StealthCloseFileDelegate', 'StealthOpenFile', 'StealthCloseFile', 'Invoke-NinjaCopy']}, 'selection2': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0006, T1003
	References
	N/A
	Severity
	49

Title	Description
	Suppression Logic Based On • computer_name • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2023/01/23 **Risk Level**: medium **False Positives**: N/A

Delete Volume Shadow Copies via WMI with PowerShell - PS Script	Deletes Windows Volume Shadow Copies with PowerShell code and Get-WMIObject. This technique is used by numerous ransomware families such as Sodinokibi/REvil
	
	More details
	
	Rule ID
	`powershell_scriptblock_62`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Get-WmiObject', 'Win32_Shadowcopy', '.Delete()']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,e17121b4-ef2a-4418-8a59-12fb1631fa9e
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0040, T1490
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1490/T1490.md#atomic-test-5---windows---delete-volume-shadow-copies-via-wmi-with-powershell
	
	Severity
	80
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2021/12/26
	Risk Level: high
	False Positives:
	• Unknown

PowerShell ICMP Exfiltration	Detects Exfiltration Over Alternative Protocol - ICMP. Adversaries may steal data by exfiltrating it over an un-encrypted network protocol other than that of the existing command and control channel. More details **Rule ID** `powershell_scriptblock_63` **Query**

Title	Description
	 `'selection': {'ScriptBlockText|contains|all': ['New-Object', 'System.Net.NetworkInformation.Ping', '.Send(' ]}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,4c4af3cd-2115-479c-8193-6b8bfce9001c Author: Bartlomiej Czyz @bczyz1, oscd.community **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0010, T1048.003 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1048.003/T1048.003.md#atomic-test-2---exfiltration-over-alternative-protocol---icmp **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2020/10/10 **Risk Level**: medium **False Positives**: • Legitimate usage of System.Net.NetworkInformation.Ping class

AD Groups Or Users Enumeration Using PowerShell - ScriptBlock	Adversaries may attempt to find domain-level groups and permission settings. The knowledge of domain-level permission groups can help adversaries determine which groups exist and which users belong to a particular group. Adversaries may use this information to determine which users have elevated permissions, such as domain administrators.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_64`
	
	Query
	
	`{'test_2': {'ScriptBlockText|contains': 'get-ADPrincipalGroupMembership'}, 'test_7': {'ScriptBlockText|contains|all': ['get-aduser', '-f ', '-pr ', 'DoesNotRequirePreAuth']}, 'condition': '1 of test_*'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source

Title	Description
	 igmaHQ,88f0884b-331d-403d-a3a1-b668cf035603 Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0007, T1069.001 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1069.002/T1069.002.md **Severity** 24 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2021/12/15 **Risk Level**: low **False Positives**: • Unknown

Tamper Windows Defender Remove-MpPreference - ScriptBlockLogging	Detects attempts to remove windows defender configuration using the 'MpPreference' cmdlet
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_65`
	
	Query
	
	`{'selection_remove': {'ScriptBlockText|contains': 'Remove-MpPreference'}, 'selection_tamper': {'ScriptBlockText|contains': ['-ControlledFolderAccessProtectedFolders ', '-AttackSurfaceReductionRules_Ids ', '-AttackSurfaceReductionRules_Actions ', '-CheckForSignaturesBeforeRunningScan ']}, 'condition': 'all of selection_*'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,ae2bdd58-0681-48ac-be7f-58ab4e593458
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001, TA0005, T1562.001
	
	References
	
	• https://techcommunity.microsoft.com/t5/core-infrastructure-and-security/windows-10-controlled-folder-access-event-search/ba-p/2326088
	
	Severity

Title	Description
	4 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/08/05 **Risk Level**: high **False Positives** • Legitimate PowerShell scripts

Invoke-Obfuscation COMPRESS OBFUSCATION - PowerShell	Detects Obfuscated Powershell via COMPRESS OBFUSCATION
	More details
	Rule ID
	`powershell_scriptblock_66`
	Query
	`{'selection_4104': {'ScriptBlockText|contains|all': ['new-object', 'text.encoding]::ascii'], 'ScriptBlockText|contains': ['system.io.compression.deflatestream', 'system.io.streamreader'], 'ScriptBlockText|endswith': 'readtoend'}, 'condition': 'selection_4104'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,20e5497e-331c-4cd5-8d36-935f6e2a9a07
	Author: Timur Zinniatullin, oscd.community
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1027
	References
	• https://github.com/SigmaHQ/sigma/issues/1009
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: experimental
	Creation Date: 2020/10/18
	Risk Level: medium
	False Positives
	• Unknown

Potential Data Exfiltration Via Audio File	Detects potential exfiltration attempt via audio file using PowerShell More details **Rule ID** `powershell_scriptblock_67` **Query**

Title	Description
	 `'selection_main': {'ScriptBlockText|contains|all': ['[System.Math]::', '[IO.FileMode]::', 'BinaryWriter']}, 'selection_header_wav': {'ScriptBlockText|contains|all': ['0x52', '0x49', '0x46', '0x57', '0x41', '0x56', '0x45', '0xAC']}, 'condition': 'selection_main and 1 of selection_header_*'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,e4f93c99-396f-47c8-bb0f-201b1fa69034 Author: Nasreddine Bencherchali (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001 **References** • https://github.com/gtworek/PSBits/blob/e97cbbb173b31cbc4d37244d3412de0a114dacfb/NoDLP/bin2wav.ps1 **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2023/01/16 **Risk Level**: medium **False Positives**: • Unknown

Create Volume Shadow Copy with Powershell	Adversaries may attempt to access or create a copy of the Active Directory domain database in order to steal credential information
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_68`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains|all': ['win32_shadowcopy', ').Create(', 'ClientAccessible']}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,afd12fed-b0ec-45c9-a13d-aa86625dac81
	
	Author: frack113
	
	Tactics, Techniques, and Procedures

Title	Description
	A0002, T1059.001, TA0006, T1003.003 **References** • https://attack.mitre.org/datasources/DS0005/ **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2022/01/12 Risk Level: high False Positives: • Legitimate PowerShell scripts

Invoke-Obfuscation Obfuscated IEX Invocation - PowerShell	Detects all variations of obfuscated powershell IEX invocation code generated by Invoke-Obfuscation framework from the following code block \u2014
	
	More details
	
	Rule ID
	`powershell_scriptblock_69`
	
	Query
	`{'selection_iex': [{'ScriptBlockText|re': '\\$PSHome\\[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$PSHome\\['}, {'ScriptBlockText|re': '\\$ShellId\\[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$ShellId\\['}, {'ScriptBlockText|re': '\\$env:Public\\[\\s*\\d{1,3}\\s*\\]\\s*\\+\\s*\\$env:Public\\['}, {'ScriptBlockText|re': '\\$env:ComSpec\\[(\\s*\\d{1,3}\\s*,){2}'}, {'ScriptBlockText|re': '*mdr*\\W\\s*\\)\\.Name'}, {'ScriptBlockText|re': '\\$VerbosePreference\\.ToString\\('}], 'condition': 'selection_iex'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,1b9dc62e-6e9e-42a3-8990-94d7a10007f7
	
	Author: Daniel Bohannon (@Mandiant/@FireEye), oscd.community
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1027
	
	References
	• https://github.com/danielbohannon/Invoke-Obfuscation/blob/f20e7f843edd0a3a7716736e9eddfa423395dd26/Out-ObfuscatedStringCommand.ps1#L873-L888
	
	Severity
	74
	
	Suppression Logic Based On
	• computer_name

Title	Description
	 • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2019/11/08 **Risk Level**: high **False Positives**: • Unknown

Malicious ShellIntel PowerShell Commandlets	Detects Commandlet names from ShellIntel exploitation scripts.
	More details
	Rule ID
	`powershell_scriptblock_70`
	Query
	`{'selection': {'ScriptBlockText|contains': ['Invoke-SMBAutoBrute', 'Invoke-GPOLinks', 'Invoke-Potato']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,402e1e1d-ad59-47b6-bf80-1ee44985b3a7
	Author: Max Altgelt (Nextron Systems), Tobias Michalski (Nextron Systems)
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	• https://github.com/ShellIntel/scripts/
	Severity
	74
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: test
	Creation Date: 2021/08/09
	Risk Level: high
	False Positives:
	• Unknown

Change User Agents with WebRequest	Adversaries may communicate using application layer protocols associated with web traffic to avoid detection/network filtering by blending in with existing traffic. Commands to the remote system, and often the results of those commands, will be embedded within the protocol traffic between the client and server.
	More details
	Rule ID
	`powershell_scriptblock_71`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Invoke-WebRequest', '-UserAgent ']}, 'condition': 'selection'}`

Title	Description
	Log Source Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,d4488827-73af-4f8d-9244-7b7662ef046e Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0011, T1071.001 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1071.001/T1071.001.md#t1071001---web-protocols **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2022/01/23 Risk Level: medium False Positives: • Unknown

Powershell Timestomp	Adversaries may modify file time attributes to hide new or changes to existing files. Timestomping is a technique that modifies the timestamps of a file (the modify, access, create, and change times), often to mimic files that are in the same folder.
	More details
	Rule ID
	`powershell_scriptblock_72`
	Query
	`{'selection_ioc': {'ScriptBlockText|contains': ['.CreationTime =', '.LastWriteTime =', '.LastAccessTime =', '[IO.File]::SetCreationTime', '[IO.File]::SetLastAccessTime', '[IO.File]::SetLastWriteTime']}, 'condition': 'selection_ioc'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,c6438007-e081-42ce-9483-b067fbef33c3
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1070.006
	References

Title	Description
	 • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1070.006/T1070.006.md • https://www.offensive-security.com/metasploit-unleashed/timestomp/ **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2021/08/03 **Risk Level**: medium **False Positives** • Legitimate admin script

Powershell MsXml COM Object	Adversaries may abuse PowerShell commands and scripts for execution. PowerShell is a powerful interactive command-line interface and scripting environment included in the Windows operating system. (Citation: TechNet PowerShell) Adversaries can use PowerShell to perform a number of actions, including discovery of information and execution of code
	More details
	Rule ID
	`powershell_scriptblock_73`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['New-Object', '-ComObject', 'MsXml2.', 'XmlHttp']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,78aa1347-1517-4454-9982-b338d6df8343
	Author: frack113, MatilJ
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1059.001/T1059.001.md#atomic-test-7---powershell-msxml-com-object---with-prompt
	• https://docs.microsoft.com/en-us/previous-versions/windows/desktop/ms766431(v=vs.85)
	• https://www.trendmicro.com/en_id/research/22/e/uncovering-a-kingminer-botnet-attack-using-trend-micro-managed-x.html
	Severity
	49
	Suppression Logic Based On
	• computer_name

Title	Description
	 • stellar.rule_id **Additional Information** **Maturity** / **Creation Date** / **Risk Level**: experimental / 2022/01/19 / medium **False Positives** • Legitimate administrative script

User Discovery And Export Via Get-ADUser Cmdlet - PowerShell	Detects usage of the Get-ADUser cmdlet to collect user information and output it to a file
	
	More details
	
	Rule ID
	`powershell_scriptblock_74`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Get-ADUser ', ' -Filter *'], 'ScriptBlockText|contains': [' > ', ' | Select ', 'Out-File', 'Set-Content', 'Add-Content']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,c2993223-6da8-4b1a-88ee-668b8bf315e9
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0007, T1033
	
	References
	• http://blog.talosintelligence.com/2022/09/lazarus-three-rats.html
	• https://www.microsoft.com/en-us/security/blog/2022/10/18/defenders-beware-a-case-for-post-ransomware-investigations/
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity / **Creation Date** / **Risk Level**: experimental / 2022/11/17 / medium
	False Positives
	• Legitimate admin scripts may use the same technique, it's better to exclude specific computers or users who execute these commands or scripts often

Active Directory Group Enumeration With Get-AdGroup	Detects usage of the "Get-AdGroup" cmdlet to enumerate Groups within Active Directory More details **Rule ID**

Title	Description
	owershell_scriptblock_75 **Query** `{'selection': {'ScriptBlockText|contains|all': ['Get-AdGroup ', '-Filter']}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,8c3a6607-b7dc-4f0d-a646-ef38c00b76ee Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0007, T1069.002 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1018/T1018.md **Severity** 24 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/03/17 **Risk Level**: low **False Positives**: • Unknown

WMIC Unquoted Services Path Lookup - PowerShell	Detects known WMI recon method to look for unquoted service paths, often used by pentest inside of powershell scripts attackers enum scripts
	
	More details
	
	Rule ID
	`powershell_scriptblock_76`
	
	Query
	`{'selection': {'ScriptBlockText|contains': ['Get-WmiObject ', 'gwmi '], 'ScriptBlockText|contains|all': [' Win32_Service ', 'Name', 'DisplayName', 'PathName', 'StartMode']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,09658312-bc27-4a3b-91c5-e49ab9046d1b
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures

Title	Description
	TA0002, T1047, T1059.001 **References** • https://github.com/nccgroup/redsnarf/blob/35949b30106ae543dc6f2bc3f1be10c6d9a8d40e/redsnarf.py • https://github.com/S3cur3Th1sSh1t/Creds/blob/eac23d67f7f90c7fc8e3130587d86158c22aa398/PowershellScripts/jaws-enum.ps1 • https://www.absolomb.com/2018-01-26-Windows-Privilege-Escalation-Guide/ **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2022/06/20 Risk Level: medium False Positives: • Unknown

Get-ADUser Enumeration Using UserAccountControl Flags	Detects AS-REP roasting is an attack that is often-overlooked. It is not very common as you have to explicitly set accounts that do not require pre-authentication.
	More details
	Rule ID
	`powershell_scriptblock_77`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Get-ADUser', '-Filter', 'useraccountcontrol', '-band', '4194304']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,96c982fe-3d08-4df4-bed2-eb14e02f21c8
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0007, T1033
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1069.002/T1069.002.md#atomic-test-11---get-aduser-enumeration-using-useraccountcontrol-flags-as-rep-roasting
	• https://shellgeek.com/useraccountcontrol-flags-to-manipulate-properties/
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id

Title	Description
	Additional Information **Maturity**: test **Creation Date**: 2022/03/17 **Risk Level**: medium **False Positives**: • Legitimate PowerShell scripts

Windows Defender Exclusions Added - PowerShell	Detects modifications to the Windows Defender configuration settings using PowerShell to add exclusions
	
	More details
	
	Rule ID
	`powershell_scriptblock_79`
	
	Query
	`{'selection_args_exc': {'ScriptBlockText|contains': [' -ExclusionPath ', ' -ExclusionExtension ', ' -ExclusionProcess ', ' -ExclusionIpAddress ']}, 'selection_args_pref': {'ScriptBlockText|contains': ['Add-MpPreference ', 'Set-MpPreference ']}, 'condition': 'all of selection*'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,c1344fa2-323b-4d2e-9176-84b4d4821c88
	
	Author: Tim Rauch, Elastic (idea)
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1562
	
	References
	• https://www.elastic.co/guide/en/security/current/windows-defender-exclusions-added-via-powershell.html
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/09/16
	Risk Level: medium
	False Positives:
	• Unknown

Suspicious Get-ADReplAccount	The DSInternals PowerShell Module exposes several internal features of Active Directory and Microsoft Entra ID. These include FIDO2 and NGC key auditing, offline ntds.dit file manipulation, password auditing, DC recovery from IFM backups and password hash calculation. More details **Rule ID** `powershell_scriptblock_80` **Query**

Title	Description
	 `'selection': {'ScriptBlockText|contains|all': ['Get-ADReplAccount', '-All ', '-Server ']}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,060c3ef1-fd0a-4091-bf46-e7d625f60b73 Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0006, T1003.006 **References** • https://www.powershellgallery.com/packages/DSInternals • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1003.006/T1003.006.md#atomic-test-2---run-dsinternals-get-adreplaccount **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2022/02/06 **Risk Level**: medium **False Positives**: • Legitimate PowerShell scripts

PowerShell Suspicious Script with Audio Capture Capabilities	Detects PowerShell scripts that can record audio, a common feature in popular post-exploitation tooling.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_81`
	
	Query
	
	`{'selection1': {'ScriptBlockText|contains': 'Get-MicrophoneAudio'}, 'selection2': {'ScriptBlockText|contains': 'waveInGetNumDevs'}, 'selection3': {'ScriptBlockText|contains': 'mciSendStringA'}, 'selection4': {'UserId': 'S-1-5-18'}, 'condition': '(selection1 or (selection2 and selection3)) and (not selection4)'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	
	Rule Source
	
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures

Title	Description
	A0002, T1059.001, TA0009, T1123 **References** N/A **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2021/10/19 **Risk Level**: medium **False Positives**: N/A

PowerShell Suspicious Script with Clipboard Retrieval Capabilities	Detects PowerShell scripts that can get the contents of the clipboard, which attackers can abuse to retrieve sensitive information like credentials, messages, etc.
	
	More details
	
	Rule ID
	`powershell_scriptblock_82`
	
	Query
	`{'selection1': {'ScriptBlockText|contains': 'Get-Clipboard'}, 'selection2': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0009, T1115
	
	References
	N/A
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: production
	Creation Date: 2023/01/12
	Risk Level: medium
	False Positives: N/A

PowerShell Get-Process LSASS in ScriptBlock	Detects a Get-Process command on lsass process, which is in almost all cases a sign of malicious activity More details **Rule ID** `powershell_scriptblock_83`

Title	Description
	Query `{'selection': {'ScriptBlockText|contains': 'Get-Process lsass'}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,84c174ab-d3ef-481f-9c86-a50d0b8e3edb Author: Florian Roth (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0006, T1003.001 **References** • https://twitter.com/PythonResponder/status/1385064506049630211 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2021/04/23 **Risk Level**: high **False Positives** • Legitimate certificate exports invoked by administrators or users (depends on processes in the environment - filter if unusable)

Password Policy Discovery With Get-AdDefaultDomainPasswordPolicy	Detetcts PowerShell activity in which Get-Addefaultdomainpasswordpolicy is used to get the default password policy for an Active Directory domain.
	More details
	Rule ID
	`powershell_scriptblock_84`
	Query
	`{'selection': {'ScriptBlockText|contains': 'Get-AdDefaultDomainPasswordPolicy'}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,bbb9495b-58fc-4016-b9df-9a3a1b67ca82
	Author: frack113
	Tactics, Techniques, and Procedures

Title	Description
	A0002, T1059.001, TA0007, T1201 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1201/T1201.md#atomic-test-9---enumerate-active-directory-password-policy-with-get-addefaultdomainpasswordpolicy • https://docs.microsoft.com/en-us/powershell/module/activedirectory/get-addefaultdomainpasswordpolicy **Severity** 24 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test; Creation Date: 2022/03/17; Risk Level: low False Positives: • Legitimate PowerShell scripts

Suspicious PowerShell Invocations - Generic	Detects suspicious PowerShell invocation command parameters
	More details
	Rule ID
	`powershell_scriptblock_85`
	Query
	`{'selection_encoded': {'ScriptBlockText|contains': [' -enc ', ' -EncodedCommand ', ' -ec ']}, 'selection_hidden': {'ScriptBlockText|contains': [' -w hidden ', ' -window hidden ', ' -windowstyle hidden ', ' -w 1 ']}, 'selection_noninteractive': {'ScriptBlockText|contains': [' -noni ', ' -noninteractive ']}, 'condition': 'all of selection*'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,ed965133-513f-41d9-a441-e38076a0798f
	Author: Florian Roth (Nextron Systems)
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	N/A
	Severity
	74
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id

Title	Description
	Additional Information Maturity: test Creation Date: 2017/03/12 Risk Level: high False Positives: • Very special / sneaky PowerShell scripts

NTFS Alternate Data Stream	Detects writing data into NTFS alternate data streams from powershell. Needs Script Block Logging.
	
	More details
	
	Rule ID
	`powershell_scriptblock_88`
	
	Query
	`{'selection_content': {'ScriptBlockText|contains': ['set-content', 'add-content']}, 'selection_stream': {'ScriptBlockText|contains': '-stream'}, 'condition': 'all of selection*'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,8c521530-5169-495d-a199-0a3a881ad24e
	
	Author: Sami Ruohonen
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1564.004
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1564.004/T1564.004.md
	
	Severity
	74
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2018/07/24
	Risk Level: high
	False Positives:
	• Unknown

Suspicious Invoke-Item From Mount-DiskImage	Adversaries may abuse container files such as disk image (.iso, .vhd) file formats to deliver malicious payloads that may not be tagged with MOTW. More details **Rule ID** `powershell_scriptblock_89` **Query**

Title	Description
	 `'selection': {'ScriptBlockText|contains|all': ['Mount-DiskImage ', '-ImagePath ', 'Get-Volume', '.DriveLetter', 'invoke-item ', '):\\']}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,902cedee-0398-4e3a-8183-6f3a89773a96 Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1553 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1553.005/T1553.005.md#atomic-test-2---mount-an-iso-image-and-run-executable-from-the-iso • https://docs.microsoft.com/en-us/powershell/module/storage/mount-diskimage?view=windowsserver2022-ps **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity** test **Creation Date** 2022/02/01 **Risk Level** medium **False Positives** • Legitimate PowerShell scripts

PowerShell WMI Win32_Product Install MSI	Detects the execution of an MSI file using PowerShell and the WMI Win32_Product class
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_90`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains|all': ['Invoke-CimMethod ', '-ClassName ', 'Win32_Product ', '-MethodName ', '.msi']}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,91109523-17f0-4248-a800-f81d9e7c081d
	
	Author: frack113

Title	Description
	actics, Techniques, and Procedures TA0002, T1059.001, TA0005, T1218.007 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1218.007/T1218.007.md **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2022/04/24 Risk Level: medium False Positives: • Unknown

Suspicious GetTypeFromCLSID ShellExecute	Detects suspicious Powershell code that execute COM Objects
	More details
	Rule ID
	`powershell_scriptblock_92`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['::GetTypeFromCLSID(', '.ShellExecute(']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,8bc063d5-3a3a-4f01-a140-bc15e55e8437
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0003, T1546.015
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1546.015/T1546.015.md#atomic-test-2---powershell-execute-com-object
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: experimental
	Creation Date: 2022/04/02
	Risk Level: medium
	False Positives:
	• Legitimate PowerShell scripts

Title	Description

Silence.EDA Detection	Detects Silence EmpireDNSAgent as described in the Group-IP report
	
	More details
	
	Rule ID
	`powershell_scriptblock_93`
	
	Query
	`{'empire': {'ScriptBlockText|contains|all': ['System.Diagnostics.Process', 'Stop-Computer', 'Restart-Computer', 'Exception in execution', '$cmdargs', 'Close-Dnscat2Tunnel']}, 'dnscat': {'ScriptBlockText\|contains\|all': ['set type=$LookupType`nserver', '$Command \| nslookup 2>&1 \| Out-String', 'New-RandomDNSField', '[Convert]::ToString($SYNOptions, 16)', '$Session.Dead = $True', '$Session["Driver"] -eq']}, 'condition': 'empire and dnscat'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,3ceb2083-a27f-449a-be33-14ec1b7cc973
	
	Author: Alina Stepchenkova, Group-IB, oscd.community
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0011, T1071.004, T1572, TA0040, T1529
	
	References
	• https://www.group-ib.com/resources/threat-research/silence_2.0.going_global.pdf
	
	Severity
	95
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2019/11/01
	Risk Level: critical
	False Positives:
	• Unknown

Potential Active Directory Enumeration Using AD Module - PsScript	Detects usage of the "Import-Module" cmdlet to load the "Microsoft.ActiveDirectory.Management.dl" DLL. Which is often used by attackers to perform AD enumeration. More details **Rule ID** `powershell_scriptblock_94` **Query**

Title	Description
	 `'selection_generic': {'ScriptBlockText|contains|all': ['Import-Module ', 'Microsoft.ActiveDirectory.Management.dll']}, 'selection_specific': {'ScriptBlockText|contains': 'ipmo Microsoft.ActiveDirectory.Management.dll'}, 'condition': '1 of selection_*'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enable **Rule Source** SigmaHQ,9e620995-f2d8-4630-8430-4afd89f77604 Author: frack113, Nasreddine Bencherchali **Tactics, Techniques, and Procedures** TA0002, T1059.001 **References** • https://github.com/samratashok/ADModule • https://twitter.com/cyb3rops/status/1617108657166061568?s=20 • https://www.ired.team/offensive-security-experiments/active-directory-kerberos-abuse/active-directory-enumeration-with-ad-module-without-rsat-or-admin-privileges **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2023/01/22 **Risk Level**: medium **False Positives**: • Legitimate use of the library for administrative activity

Automated Collection Bookmarks Using Get-ChildItem PowerShell	Adversaries may enumerate browser bookmarks to learn more about compromised hosts. Browser bookmarks may reveal personal information about users (ex: banking sites, interests, social media, etc.) as well as details about internal network resources such as servers, tools/dashboards, or other related infrastructure.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_95`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains|all': ['Get-ChildItem', ' -Recurse ', ' -Path ', ' -Filter Bookmarks', ' -ErrorAction SilentlyContinue', ' -Force']}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:

Title	Description
	• Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,e0565f5d-d420-4e02-8a68-ac00d864f9cf Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0007, T1217 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1217/T1217.md **Severity** 24 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2021/12/13 **Risk Level**: low **False Positives**: • Unknown

SyncAppvPublishingServer Execution to Bypass Powershell Restriction	Detects SyncAppvPublishingServer process execution which usually utilized by adversaries to bypass PowerShell execution restrictions.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_96`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains': 'SyncAppvPublishingServer.exe'}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,dddfebae-c46f-439c-af7a-fdb6bde90218
	
	Author: Ensar Şamil, @sblmsrsn, OSCD Community
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001, TA0005, T1218
	
	References
	
	• https://lolbas-project.github.io/lolbas/Binaries/Syncappvpublishingserver/
	
	Severity
	
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id

Title	Description
	Additional Information **Maturity**: test **Creation Date**: 2020/10/05 **Risk Level**: medium **False Positives**: • App-V clients

Disable Powershell Command History	Detects scripts or commands that disabled the Powershell command history by removing psreadline module
	
	More details
	
	Rule ID
	`powershell_scriptblock_97`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Remove-Module', 'psreadline']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,602f5669-6927-4688-84db-0d4b7afb2150
	
	Author: Ali Alwashali
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1070.003
	
	References
	• https://twitter.com/DissectMalware/status/1062879286749773824
	
	Severity
	74
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/08/21
	Risk Level: high
	False Positives:
	• Legitimate script that disables the command history

Manipulation of User Computer or Group Security Principals Across AD	Adversaries may create a domain account to maintain access to victim systems. Domain accounts are those managed by Active Directory Domain Services where access and permissions are configured across systems and services that are part of that domain..
	
	More details
	
	Rule ID
	`powershell_scriptblock_98`
	
	Query
	`{'selection': {'ScriptBlockText|contains': 'System.DirectoryServices.AccountManagement'}, 'condition': 'select`

Title	Description
	on'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,b29a93fb-087c-4b5b-a84d-ee3309e69d08 Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0003, T1136.002 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1136.002/T1136.002.md#atomic-test-3---create-a-new-domain-account-using-powershell • https://docs.microsoft.com/en-us/dotnet/api/system.directoryservices.accountmanagement?view=dotnet-plat-ext-6.0 **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2021/12/28 Risk Level: medium False Positives: • Legitimate administrative script
PowerShell Suspicious Payload Encoded and Compressed	Identifies the use of .NET functionality for decompression and base64 decoding combined in PowerShell scripts, which malware and security tools heavily use to deobfuscate payloads and load them directly in memory to bypass defenses. More details **Rule ID** powershell_scriptblock_99 **Query** {'selection1': {'ScriptBlockText|contains': 'System.IO.Compression.DeflateStream'}, 'selection2': {'ScriptBlockText|contains': 'System.IO.Compression.GzipStream'}, 'selection3': {'ScriptBlockText|contains': 'IO.Compression.DeflateStream'}, 'selection4': {'ScriptBlockText|contains': 'IO.Compression.GzipStream'}, 'selection5': {'ScriptBlockText|contains': 'FromBase64String'}, 'selection6': {'UserId': 'S-1-5-18'}, 'condition': '(selection1 or selection2 or selection3 or selection4) and selection5 and (not selection6)'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts

Title	Description
	ule Source Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1027, T1140 **References** N/A **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2021/10/19 **Risk Level**: medium **False Positives** • Legitimate PowerShell Scripts which makes use of compression and encoding.

Powershell Trigger Profiles by Add_Content	Adversaries may gain persistence and elevate privileges by executing malicious content triggered by PowerShell profiles.
	More details
	Rule ID
	`powershell_scriptblock_100`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Add-Content', '$profile', '-Value'], 'ScriptBlockText|contains': ['Start-Process', '"']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,05b3e303-faf0-4f4a-9b30-46cc13e69152
	Author: frack113, Nasreddine Bencherchali (Nextron Systems)
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0003, T1546.013
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1546.013/T1546.013.md
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id

Title	Description
	Additional Information **Maturity**: test **Creation Date**: 2021/08/18 **Risk Level**: medium **False Positives**: Unknown

Windows Screen Capture with CopyFromScreen	Adversaries may attempt to take screen captures of the desktop to gather information over the course of an operation. Screen capturing functionality may be included as a feature of a remote access tool used in post-compromise operations
	
	More details
	
	Rule ID
	`powershell_scriptblock_101`
	
	Query
	`{'selection': {'ScriptBlockText|contains': '.CopyFromScreen'}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,d4a11f63-2390-411c-9adf-d791fd152830
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0009, T1113
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1113/T1113.md#atomic-test-6---windows-screen-capture-copyfromscreen
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2021/12/28
	Risk Level: medium
	False Positives: Unknown

Clear PowerShell History - PowerShell	Detects keywords that could indicate clearing PowerShell history
	
	More details
	
	Rule ID
	`powershell_scriptblock_102`
	
	Query
	`{'selection1a': {'ScriptBlockText|contains': ['del', 'Remove-Item', 'rm']}, 'selection1b': {'ScriptBlockText|contains': '(Get-`

Title	Description
	 SReadlineOption).HistorySavePath'}, 'selection_2': {'ScriptBlockText|contains|all': ['Set-PSReadlineOption', '-HistorySaveStyle', 'SaveNothing']}, 'selection_3': {'ScriptBlockText|contains|all': ['Set-PSReadlineOption', '-HistorySaveStyle', 'SaveNothing']}, 'condition': '1 of selection_* or all of selection1*'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,26b692dc-1722-49b2-b496-a8258aa6371d Author: Ilyas Ochkov, Jonhnathan Ribeiro, Daniil Yugoslavskiy, oscd.community **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1070.003 **References** • https://gist.github.com/hook-s3c/7363a856c3cdbadeb71085147f042c1a **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2022/01/25 Risk Level: medium False Positives: • Legitimate PowerShell scripts
PowerShell Share Enumeration Script	Detects scripts that contain PowerShell functions, structures, or Windows API functions related to windows share enumeration activities. Attackers, mainly ransomware groups, commonly identify and inspect network shares, looking for critical information for encryption and/or exfiltration. More details **Rule ID** powershell_scriptblock_103 **Query** {'selection1': {'ScriptBlockText|contains': ['Invoke-ShareFinder', 'Invoke-ShareFinderThreaded']}, 'selection2': {'ScriptBlockText|contains': 'shi1_netname'}, 'selection3': {'ScriptBlockText|contains': 'shi1_remark'}, 'selection4': {'ScriptBlockText|contains': 'NetShareEnum'}, 'selection5': {'ScriptBlockText|contains': 'NetApiBufferFree'}, 'selection6': {'UserId': 'S-1-5-18'}, 'condition': '(selection1 or (selection2 and selection3) or (selection4 and selection5)) and (not selection6)'}

Title	Description
	Log Source Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts **Rule Source** Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0002, T1059.001, T1106, TA0007, T1135 **References** N/A **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: production; Creation Date: 2022/08/17; Risk Level: medium; False Positives: N/A

DirectorySearcher Powershell Exploitation	Enumerates Active Directory to determine computers that are joined to the domain
	More details
	Rule ID
	`powershell_scriptblock_104`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['New-Object ', 'System.DirectoryServices.DirectorySearcher', '.PropertiesToLoad.Add', '.findall()', 'Properties.name']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,1f6399cf-2c80-4924-ace1-6fcff3393480
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0007, T1018
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1018/T1018.md#atomic-test-15---enumerate-domain-computers-within-active-directory-using-directorysearcher
	Severity
	49
	Suppression Logic Based On

Title	Description
	 • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2022/02/12 **Risk Level**: medium **False Positives**: • Unknown

Invoke-Obfuscation STDIN+ Launcher - Powershell	Detects Obfuscated use of stdin to execute PowerShell
	More details
	Rule ID
	`powershell_scriptblock_105`
	Query
	`{'selection_4104': {'ScriptBlockText|re': '.*cmd.{0,5}(?:/c|/r).+powershell.+(?:\\$?\\{?input\\}?|noexit).+"'}, 'condition': 'selection_4104'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,779c8c12-0eb1-11eb-adc1-0242ac120002
	Author: Jonathan Cheong, oscd.community
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1027
	References
	• https://github.com/SigmaHQ/sigma/issues/1009
	Severity
	74
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: experimental
	Creation Date: 2020/10/15
	Risk Level: high
	False Positives: • Unknown

Powershell Install a DLL in System Directory	Uses PowerShell to install/copy a a file into a system directory such as "System32" or "SysWOW64"
	More details
	Rule ID
	`powershell_scriptblock_106`
	Query
	`{'selection_copy': {'ScriptBlockText|contains|all': ['Copy-Item ', '-Destination ']}, 'selection_paths': {'ScriptBlockText|c`

Title	Description
	ntains': ['\\Windows\\System32', '\\Windows\\SysWOW64']}, 'condition': 'all of selection*'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,63bf8794-9917-45bc-88dd-e1b5abc0ecfd Author: frack113, Nasreddine Bencherchali (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1556.002 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1556.002/T1556.002.md#atomic-test-1---install-and-register-password-filter-dll **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2021/12/27 **Risk Level**: high **False Positives**: • Unknown
Deletion of Volume Shadow Copies via WMI with PowerShell - PS Script	Detects deletion of Windows Volume Shadow Copies with PowerShell code and Get-WMIObject. This technique is used by numerous ransomware families such as Sodinokibi/REvil More details **Rule ID** powershell_scriptblock_107 **Query** {'selection_get': {'ScriptBlockText|contains': ['Get-WmiObject', 'gwmi', 'Get-CimInstance', 'gcim']}, 'selection_shadowcopy': {'ScriptBlockText|contains': 'Win32_Shadowcopy'}, 'selection_delete': {'ScriptBlockText|contains': ['.Delete()', 'Remove-WmiObject', 'rwmi', 'Remove-CimInstance', 'rcim']}, 'condition': 'all of selection*'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts **Rule Source** SigmaHQ,c1337eb8-921a-4b59-855b-4ba188ddcc42 Author: Tim Rauch, frack113

Title	Description
	actics, Techniques, and Procedures TA0002, T1059.001, TA0040, T1490 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1490/T1490.md#atomic-test-5---windows---delete-volume-shadow-copies-via-wmi-with-powershell • https://www.elastic.co/guide/en/security/current/volume-shadow-copy-deletion-via-powershell.html **Severity** 80 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental; Creation Date: 2022/09/20; Risk Level: high; False Positives: • Unknown

Code Executed Via Office Add-in XLL File	Adversaries may abuse Microsoft Office add-ins to obtain persistence on a compromised system. Office add-ins can be used to add functionality to Office programs
	More details
	Rule ID
	`powershell_scriptblock_108`
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['new-object ', '-ComObject ', '.application', '.RegisterXLL']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,36fbec91-fa1b-4d5d-8df1-8d8edcb632ad
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0003, T1137.006
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1137.006/T1137.006.md
	Severity
	74
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id

Title	Description
	Additional Information **Maturity**: test **Creation Date**: 2021/12/28 **Risk Level**: high **False Positives**: • Unknown

PSAsyncShell - Asynchronous TCP Reverse Shell	Detects the use of PSAsyncShell an Asynchronous TCP Reverse Shell written in powershell
	
	More details
	
	Rule ID
	`powershell_scriptblock_109`
	
	Query
	`{'selection': {'ScriptBlockText|contains': 'PSAsyncShell'}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,afd3df04-948d-46f6-ae44-25966c44b97f
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	
	References
	• https://github.com/JoelGMSec/PSAsyncShell
	
	Severity
	74
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/10/04
	Risk Level: high
	False Positives:
	• Unlikely

Recon Information for Export with PowerShell	Once established within a system or network, an adversary may use automated techniques for collecting internal data
	
	More details
	
	Rule ID
	`powershell_scriptblock_110`
	
	Query
	`{'selection_action': {'ScriptBlockText|contains': ['Get-Service ', 'Get-ChildItem ', 'Get-Process ']}, 'selection_redirect': {'ScriptBlockText|contains': '> $env:TEMP\\'}, 'condition': 'all of selection*'}`

Title	Description
	Log Source Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,a9723fcc-881c-424c-8709-fd61442ab3c3 Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0009, T1119 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1119/T1119.md **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2021/07/30 Risk Level: medium False Positives: • Unknown

Enable Windows Remote Management	Adversaries may use Valid Accounts to interact with remote systems using Windows Remote Management (WinRM). The adversary may then perform actions as the logged-on user.
	More details
	Rule ID
	`powershell_scriptblock_111`
	Query
	`{'selection_cmdlet': {'ScriptBlockText|contains': 'Enable-PSRemoting '}, 'condition': 'selection_cmdlet'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,991a9744-f2f0-44f2-bd33-9092eba17dc3
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0008, T1021.006
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1021.006/T1021.006.md#atomic-test-1---enable-windows-remote-management

Title	Description
	 • https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.core/enable-psremoting?view=powershell-7.2 **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2022/01/07 **Risk Level**: medium **False Positives** • Legitimate script

Enumerate Credentials from Windows Credential Manager With PowerShell	Adversaries may search for common password storage locations to obtain user credentials. Passwords are stored in several places on a system, depending on the operating system or application holding the credentials.
	
	More details
	
	Rule ID
	`powershell_scriptblock_112`
	
	Query
	`{'selection_cmd': {'ScriptBlockText|contains|all': ['vaultcmd', '/listcreds:']}, 'selection_option': {'ScriptBlockText|contains': ['Windows Credentials', 'Web Credentials']}, 'condition': 'all of selection_*'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,603c6630-5225-49c1-8047-26c964553e0e
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0006, T1555
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1555/T1555.md
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2021/12/20
	Risk Level: medium
	False Positives
	• Unknown

Title	Description

Potential Persistence Via Security Descriptors - ScriptBlock	Detects usage of certain functions and keywords that are used to manipulate security descriptors in order to potentially set a backdoor. As seen used in the DAMP project.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_114`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains|all': ['win32_Trustee', 'win32_Ace', '.AccessMask', '.AceType', '.SetSecurityDescriptor'], 'ScriptBlockText|contains': ['\\Lsa\\JD', '\\Lsa\\Skew1', '\\Lsa\\Data', '\\Lsa\\GBG']}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,2f77047c-e6e9-4c11-b088-a3de399524cd
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001
	
	References
	
	• https://github.com/HarmJ0y/DAMP
	
	Severity
	
	74
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	
	Maturity: experimental
	Creation Date: 2023/01/05
	Risk Level: high
	False Positives:
	• Unknown

PowerShell Script with Encryption/Decryption Capabilities	Identifies the use of Cmdlets and methods related to encryption/decryption of files in PowerShell scripts, which malware and offensive security tools can abuse to encrypt data or decrypt payloads to bypass security solutions.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_115`
	
	Query
	
	`{'selection1': {'ScriptBlockText|contains': 'Cryptography.AESManaged'}, 'selection2': {'ScriptBlockText|contains': 'Cryptography.RijndaelManaged'}, 'selection3': {'ScriptBlockText|contains': 'Cryptography.SHA1Managed'}, 'selection4': {'ScriptBlockText|contains': 'Cryptography.SHA256Managed'}, 'selection5': {'ScriptBlockText|cont`

Title	Description
	 ins': 'Cryptography.SHA384Managed'}, 'selection6': {'ScriptBlockText|contains': 'Cryptography.SHA512Managed'}, 'selection7': {'ScriptBlockText|contains': 'Cryptography.SymmetricAlgorithm'}, 'selection8': {'ScriptBlockText|contains': 'PasswordDeriveBytes'}, 'selection9': {'ScriptBlockText|contains': 'Rfc2898DeriveBytes'}, 'selection10': {'ScriptBlockText|contains': 'CipherMode'}, 'selection11': {'ScriptBlockText|contains': 'PaddingMode'}, 'selection12': {'ScriptBlockText|contains': '.CreateEncryptor'}, 'selection13': {'ScriptBlockText|contains': '.CreateDecryptor'}, 'selection14': {'UserId': 'S-1-5- 18'}, 'condition': '(selection1 or selection2 or selection3 or selection4 or selection5 or selection6 or selection7 or selection8 or selection9) and selection10 and selection11 and (selection12 or selection13) and (not selection14)'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts **Rule Source** Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1140, T1027 **References** N/A **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2023/01/23 **Risk Level**: medium **False Positives**: • Legitimate PowerShell Scripts which makes use of encryption.
Suspicious SSL Connection	Adversaries may employ a known encryption algorithm to conceal command and control traffic rather than relying on any inherent protections provided by a communication protocol. More details **Rule ID** powershell_scriptblock_116 **Query** {'selection': {'ScriptBlockText|contains|all': ['System.Net.Security.SslStream', 'Net.Security.RemoteCertificateValidationCallback', '.AuthenticateAsClient']}, 'condition': 'selection'} **Log Source**

Title	Description
	tellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,195626f3-5f1b-4403-93b7-e6cfd4d6a078 Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0011, T1573 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1573/T1573.md#atomic-test-1---openssl-c2 • https://medium.com/walmartglobaltech/openssl-server-reverse-shell-from-windows-client-aee2dbfa0926 **Severity** 24 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2022/01/23 Risk Level: low False Positives: • Legitimate administrative script

Potential Keylogger Activity	Detects PowerShell scripts that contains reference to keystroke capturing functions
	More details
	Rule ID
	`powershell_scriptblock_117`
	Query
	`{'selection': {'ScriptBlockText|contains': '[Windows.Input.Keyboard]::IsKeyDown([System.Windows.Input.Key]::'}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,965e2db9-eddb-4cf6-a986-7a967df651e4
	Author: Nasreddine Bencherchali (Nextron Systems)
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0006, T1056.001
	References
	• https://twitter.com/ScumBots/status/1610626724257046529
	• https://www.virustotal.com/gui/file/d4486b63512755316625230e0c9c81655093be93876e0d80732e7eeaf7d83476/content

Title	Description
	 • https://www.virustotal.com/gui/file/720a7ee9f2178c70501d7e3f4bcc28a4f456e200486dbd401b25af6da3b4da62/content • https://learn.microsoft.com/en-us/dotnet/api/system.windows.input.keyboard.iskeydown?view=windowsdesktop-7.0 **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2023/01/04 **Risk Level**: medium **False Positives** • Unknown

Invoke-Obfuscation Via Use Clip - Powershell	Detects Obfuscated Powershell via use Clip.exe in Scripts
	More details
	Rule ID
	`powershell_scriptblock_118`
	Query
	`{'selection_4104': {'ScriptBlockText|re': '(?i).*?echo.*clip.*&&.*(Clipboard|i`?n`?v`?o`?k`?e`?).*'}, 'condition': 'selection_4104'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,db92dd33-a3ad-49cf-8c2c-608c3e30ace0
	Author: Nikita Nazarov, oscd.community
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1027
	References
	• https://github.com/SigmaHQ/sigma/issues/1009
	Severity
	74
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: experimental
	Creation Date: 2020/10/09
	Risk Level: high
	False Positives
	• Unknown

Execution via CL_Mutexverifiers.ps1	Detects Execution via runAfterCancelProcess in CL_Mutexverifiers.ps1 module More details **Rule ID**

Title	Description
	owershell_scriptblock_119 **Query** `{'selection': {'ScriptBlockText|contains|all': ['CL_Mutexverifiers.ps1', 'runAfterCancelProcess']}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,39776c99-1c7b-4ba0-b5aa-641525eee1a4 Author: oscd.community, Natalia Shornikova **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1216 **References** • https://lolbas-project.github.io/lolbas/Scripts/CL_mutexverifiers/ • https://twitter.com/pabraeken/status/995111125447577600 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2020/10/14 Risk Level: high False Positives: • Unknown

Bloodhound Hack Tool Usage via PowerShell	Detects the usage of PowerShell to execute Bloodhound hacktool on endpoint
	More details
	Rule ID
	`powershell_scriptblock_120`
	Query
	`{'selection': {'ScriptBlockText|contains': ['Invoke-BloodHound', 'Invoke-AzureHound', 'Get-BloodHoundData']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0007, T1482
	References

Title	Description
	• https://github.com/BloodHoundAD/BloodHound **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2023/03/30 **Risk Level**: high **False Positives**: • Unknown

Suspicious X509Enrollment - Ps Script	Detect use of X509Enrollment
	More details
	Rule ID
	`powershell_scriptblock_121`
	Query
	`{'selection': {'ScriptBlockText|contains': ['X509Enrollment.CBinaryConverter', '884e2002-217d-11da-b2a4-000e7bbb2b09']}, 'condition': 'selection'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,504d63cb-0dba-4d02-8531-e72981aace2c
	Author: frack113
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	• https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=42
	• https://speakerdeck.com/heirhabarov/hunting-for-powershell-abuse?slide=41
	• https://learn.microsoft.com/en-us/dotnet/api/microsoft.hpc.scheduler.store.cx509enrollmentwebclassfactoryclass?view=hpc-sdk-5.1.6115
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: experimental
	Creation Date: 2022/12/23
	Risk Level: medium
	False Positives: • Legitimate administrative script

Add New Windows Capability - ScriptBlock	Detects usage of the "Add-WindowsCapability" cmdlet to add new windows capabilities. Notable capabilities could be "OpenSSH" and others.

Title	Description

e details

Rule ID

```
powershell_scriptblock_122
```

Query

```
{'selection_cmdlet': {'ScriptBlockText|contains': 'Add-
WindowsCapability '}, 'selection_capa': {'ScriptBlockTe
xt|contains': 'OpenSSH.'}, 'condition': 'all of selecti
on_*'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts
- Requirements: Script Block Logging must be enabled

Rule Source

SigmaHQ,155c7fd5-47b4-49b2-bbeb-eb4fab335429

Author: Nasreddine Bencherchali (Nextron Systems)

Tactics, Techniques, and Procedures

TA0002, T1059.001

References

- https://learn.microsoft.com/en-us/windows-server/administration/openssh/openssh_install_firstuse?tabs=powershell
- https://www.virustotal.com/gui/file/af1c82237b6e5a3a7cdbad82cc498d298c67845d92971bada450023d1335e267/content

Severity

49

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
experimental	2023/01/22	medium	• Legitimate usage of the capabilities by administartors or users. Filter accordingly

Invoke-Obfuscation Via Use Rundll32 - PowerShell	Detects Obfuscated Powershell via use Rundll32 in Scripts

More details

Rule ID

```
powershell_scriptblock_123
```

Query

```
{'selection_4104': {'ScriptBlockText|contains|all': ['&
&', 'rundll32', 'shell32.dll', 'shellexec_rundll'], 'Sc
riptBlockText|contains': ['value', 'invoke', 'comspec',
 'iex']}, 'condition': 'selection_4104'}
```

Log Source

Stellar Cyber Windows Server Sensor configured for:

- Monitoring PowerShell scripts

Title	Description
	• Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,a5a30a6e-75ca-4233-8b8c-42e0f2037d3b Author: Nikita Nazarov, oscd.community **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1027 **References** • https://github.com/SigmaHQ/sigma/issues/1009 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2019/10/08 Risk Level: high False Positives: • Unknown

Anti-VM check with WMI Query	WMI Queries allow to inspect Windows properties like the BIOS features. This technique is used by malware to identify virtual and sandboxed host machines, in order to evade security analysis.
	More details
	Rule ID
	`powershell_scriptblock_124`
	Query
	`{'selection1': {'ScriptBlockText|contains': '-query'}, 'selection2': {'ScriptBlockText|re': '.*(Get-WMIObject|gwmi) .*?-query .*? win32_(BIOS|SystemBIOS).*? (bochs|qemu|VBOX|VirtualBox|VM).*'}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	N/A
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id

Title	Description
	Additional Information **Maturity**: test **Creation Date**: 2022/05/01 **Risk Level**: medium **False Positives**: N/A

Suspicious Connection to Remote Account	Adversaries with no prior knowledge of legitimate credentials within the system or environment may guess passwords to attempt access to accounts. Without knowledge of the password for an account, an adversary may opt to systematically guess the password using a repetitive or iterative mechanism
	
	More details
	
	Rule ID
	`powershell_scriptblock_125`
	
	Query
	`{'selection': {'ScriptBlockText|contains': ['System.DirectoryServices.Protocols.LdapDirectoryIdentifier', 'System.Net.NetworkCredential', 'System.DirectoryServices.Protocols.LdapConnection']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,1883444f-084b-419b-ac62-e0d0c5b3693f
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0006, T1110.001
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1110.001/T1110.001.md#atomic-test-2---brute-force-credentials-of-single-active-directory-domain-user-via-ldap-against-domain-controller-ntlm-or-kerberos
	
	Severity
	24
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2021/12/27
	Risk Level: low
	False Positives:
	• Unknown

Suspicious Export-PfxCertificate	Detects Commandlet that is used to export certificates from the local certificate store and sometimes used by threat actors to steal private keys from compromised machines More details **Rule ID** `powershell_scriptblock_126`

Title	Description
	Query `{'selection': {'ScriptBlockText|contains': ['Export-PfxCertificate', 'export-certificate']}, 'filter_moduleexport': {'ScriptBlockText|contains': 'CmdletsToExport = @('}, 'condition': 'selection and not 1 of filter*'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,aa7a3fce-bef5-4311-9cc1-5f04bb8c308c Author: Florian Roth (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0006, T1552.004 **References** • https://us-cert.cisa.gov/ncas/analysis-reports/ar21-112a • https://docs.microsoft.com/en-us/powershell/module/pki/export-pfxcertificate • https://dev.to/iamthecarisma/managing-windows-pfx-certificates-through-powershell-3pj • https://learn.microsoft.com/en-us/powershell/module/pki/export-certificate?view=windowsserver2022-ps **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2021/04/23 Risk Level: high False Positives: • Legitimate certificate exports invoked by administrators or users (depends on processes in the environment - filter if unusable)

Powershell Sensitive File Discovery	Detect adversaries enumerate sensitive files
	More details
	Rule ID
	`powershell_scriptblock_127`
	Query
	`{'selection_action': {'ScriptBlockText|contains': ['ls', 'get-childitem', 'gci']}, 'selection_recurse': {'ScriptBlockText|contains': '-recurse'}, 'selection_file': {'ScriptBlockText|contains': ['.pass', '.kdbx', '.kdb']}, 'condition': 'all of selection_*'}`

Title	Description
	Log Source Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,7d416556-6502-45b2-9bad-9d2f05f38997 Author: frack113 **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0007, T1083 **References** • https://twitter.com/malmoeb/status/1570814999370801158 **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/09/16 **Risk Level**: medium **False Positives**: • Unknown

Invoke-Obfuscation VAR++ LAUNCHER OBFUSCATION - PowerShell	Detects Obfuscated Powershell via VAR++ LAUNCHER
	More details
	Rule ID
	`powershell_scriptblock_128`
	Query
	`{'selection_4104': {'ScriptBlockText|re': '(?i).*&&set.*(\\{\\d\\}){2,}\\\\"\\s+?-f.*&&.*cmd.*/c'}, 'condition': 'selection_4104'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	SigmaHQ,e54f5149-6ba3-49cf-b153-070d24679126
	Author: Timur Zinniatullin, oscd.community
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0005, T1027
	References
	• https://github.com/SigmaHQ/sigma/issues/1009
	Severity
	74
	Suppression Logic Based On

Title	Description
	 • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2020/10/13 **Risk Level**: high **False Positives**: • Unknown

Testing Usage of Uncommonly Used Port	Adversaries may communicate using a protocol and port paring that are typically not associated. For example, HTTPS over port 8088(Citation: Symantec Elfin Mar 2019) or port 587(Citation: Fortinet Agent Tesla April 2018) as opposed to the traditional port 443.
	
	More details
	
	Rule ID
	`powershell_scriptblock_129`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['Test-NetConnection', '-ComputerName ', '-port ']}, 'filter': {'ScriptBlockText|contains': [' 443 ', ' 80 ']}, 'condition': 'selection and not filter'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,adf876b3-f1f8-4aa9-a4e4-a64106feec06
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0011, T1571
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1571/T1571.md#atomic-test-1---testing-usage-of-uncommonly-used-port-with-powershell
	• https://docs.microsoft.com/en-us/powershell/module/nettcpip/test-netconnection?view=windowsserver2022-ps
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: test
	Creation Date: 2022/01/23
	Risk Level: medium
	False Positives:
	• Legitimate administrative script

Troubleshooting Pack Cmdlet Execution	Detects execution of "TroubleshootingPack" cmdlets to leverage CVE-2022-30190 or action similar to "msdt" lolbin (as described in LOLBAS) More details **Rule ID**

Title	Description
	owershell_scriptblock_130 **Query** `{'selection': {'ScriptBlockText|contains|all': ['Invoke-TroubleshootingPack', 'C:\\Windows\\Diagnostics\\System\\PCW', '-AnswerFile', '-Unattended']}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,03409c93-a7c7-49ba-9a4c-a00badf2a153 Author: Nasreddine Bencherchali (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1202 **References** • https://twitter.com/nas_bench/status/1537919885031772161 • https://lolbas-project.github.io/lolbas/Binaries/Msdt/ **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: experimental **Creation Date**: 2022/06/21 **Risk Level**: medium **False Positives**: • Legitimate usage of "TroubleshootingPack" cmdlet for troubleshooting purposes

Invoke-Obfuscation Via Stdin - Powershell	Detects Obfuscated Powershell via Stdin in Scripts
	
	More details
	
	Rule ID
	`powershell_scriptblock_131`
	
	Query
	`{'selection_4104': {'ScriptBlockText|re': '(?i).*(set).*&&\\s?set.*(environment|invoke|\\$\\{?input).*&&.*"'}, 'condition': 'selection_4104'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,86b896ba-ffa1-4fea-83e3-ee28a4c915c7

Title	Description
	Author: Nikita Nazarov, oscd.community **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0005, T1027 **References** • https://github.com/SigmaHQ/sigma/issues/1009 **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2020/10/12 Risk Level: high False Positives: • Unknown

Suspicious Mount-DiskImage	Adversaries may abuse container files such as disk image (.iso, .vhd) file formats to deliver malicious payloads that may not be tagged with MOTW.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_132`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains|all': ['Mount-DiskImage ', '-ImagePath ']}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,29e1c216-6408-489d-8a06-ee9d151ef819
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001, TA0005, T1553
	
	References
	
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1553.005/T1553.005.md#atomic-test-1---mount-iso-image
	• https://docs.microsoft.com/en-us/powershell/module/storage/mount-diskimage?view=windowsserver2022-ps
	
	Severity
	
	24
	
	Suppression Logic Based On
	
	• computer_name
	• stellar.rule_id
	
	Additional Information

Title	Description
	Maturity: test Creation Date: 2022/02/01 Risk Level: low False Positives: Legitimate PowerShell scripts

Suspicious PowerShell Mailbox Export to Share - PS	Detects usage of the powerShell New-MailboxExportRequest Cmdlet to exports a mailbox to a remote or local share, as used in ProxyShell exploitations
	
	More details
	
	Rule ID
	`powershell_scriptblock_133`
	
	Query
	`{'selection': {'ScriptBlockText|contains|all': ['New-MailboxExportRequest', ' -Mailbox ', ' -FilePath \\\\']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,4a241dea-235b-4a7e-8d76-50d817b146c4
	
	Author: Nasreddine Bencherchali (Nextron Systems)
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	
	References
	• https://youtu.be/5mqid-7zp8k?t=2481
	• https://blog.orange.tw/2021/08/proxylogon-a-new-attack-surface-on-ms-exchange-part-1.html
	• https://peterjson.medium.com/reproducing-the-proxyshell-pwn2own-exploit-49743a4ea9a1
	• https://m365internals.com/2022/10/07/hunting-in-on-premises-exchange-server-logs/
	
	Severity
	95
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2022/10/26
	Risk Level: critical
	False Positives: Unknown

Data Compressed - PowerShell	An adversary may compress data (e.g., sensitive documents) that is collected prior to exfiltration in order to make it portable and minimize the amount of data sent over the network. More details **Rule ID** `powershell_scriptblock_134` **Query**

Title	Description
	 `'selection': {'ScriptBlockText|contains|all': ['-Recurse', '|', 'Compress-Archive']}, 'condition': 'selection'}` **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,6dc5d284-69ea-42cf-9311-fb1c3932a69a Author: Timur Zinniatullin, oscd.community **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0009, T1560 **References** • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1560/T1560.md **Severity** 24 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: test **Creation Date**: 2019/10/21 **Risk Level**: low **False Positives**: • Highly likely if archive operations are done via PowerShell.

PowerShell Create Local User	Detects creation of a local user via PowerShell
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_135`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains': 'New-LocalUser'}, 'condition': 'selection'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,243de76f-4725-4f2e-8225-a8a69b15ad61
	
	Author: @ROxPinTeddy
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001, TA0003, T1136.001
	
	References

Title	Description
	 • https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1136.001/T1136.001.md **Severity** 49 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: test Creation Date: 2020/04/11 Risk Level: medium False Positives: • Legitimate user creation

WMI lateral movement using MSI package	Windows Management Instrumentation (WMI) is able to install MSI packages in remote computers. An attacker can use it to performa lateral movement and execute malicious code.
	More details
	Rule ID
	`powershell_scriptblock_136`
	Query
	`{'selection1': {'ScriptBlockText|contains': 'win32_product'}, 'selection2': {'ScriptBlockText|contains': 'install'}, 'selection3': {'ScriptBlockText|contains': '-ComputerName'}, 'selection4': {'ScriptBlockText|contains': '-Credential'}, 'condition': 'selection1 and selection2 and selection3 and selection4'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001
	References
	N/A
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: test
	Creation Date: 2022/05/01
	Risk Level: medium
	False Positives: N/A

Replace Desktop Wallpaper by Powershell	An adversary may deface systems internal to an organization in an attempt to intimidate or mislead users. This may take the form of modifications to internal websites, or directly to user systems with the replacement of the desktop wallpaper

Title	Description

	 e details
	
	Rule ID
	
	`powershell_scriptblock_137`
	
	Query
	
	`{'selection_1': {'ScriptBlockText|contains|all': ['Get-ItemProperty', 'Registry::', 'HKEY_CURRENT_USER\\Control Panel\\Desktop\\', 'WallPaper']}, 'selection_2': {'ScriptBlockText|contains': 'SystemParametersInfo(20,0,*,3)'}, 'condition': '1 of selection_*'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	
	SigmaHQ,c5ac6a1e-9407-45f5-a0ce-ca9a0806a287
	
	Author: frack113
	
	Tactics, Techniques, and Procedures
	
	TA0002, T1059.001, TA0040, T1491.001
	
	References
	
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1491.001/T1491.001.md
	
	Severity
	
	24
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	
	Maturity: test
	Creation Date: 2021/12/26
	Risk Level: low
	False Positives:
	• Unknown

PowerShell MiniDump Script	This rule detects PowerShell scripts capable of dumping process memory using WindowsErrorReporting or Dbghelp.dll MiniDumpWriteDump. Attackers can use this tooling to dump LSASS and get access to credentials.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_138`
	
	Query
	
	`{'selection1': {'ScriptBlockText|contains': ['MiniDumpWriteDump', 'MiniDumpWithFullMemory', 'pmuDetirWpmuDiniM']}, 'selection2': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}`
	
	Log Source
	
	Stellar Cyber Windows Server Sensor configured for:
	
	• Monitoring PowerShell scripts

Title	Description
	ule Source Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0002, T1059.001, TA0006, T1003 **References** N/A **Severity** 74 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2021/10/05 **Risk Level**: high **False Positives** • PowerShell scripts that use this capability for troubleshooting.

PowerShell PSReflect Script	Detects the use of PSReflect in PowerShell scripts. Attackers leverage PSReflect as a library that enables PowerShell to access win32 API functions.
	More details
	Rule ID
	`powershell_scriptblock_139`
	Query
	`{'selection1': {'ScriptBlockText|contains': ['New-InMemoryModule', 'Add-Win32Type', 'psenum', 'DefineDynamicAssembly', 'DefinedynamicModule', 'Reflection.TypeAttributes', 'Reflection.Emit.OpCodes', 'Reflection.Emit.CustomAttributeBuilder', 'Runtime.InteropServices.DllImportAttribute']}, 'selection2': {'UserId': 'S-1-5-18'}, 'condition': 'selection1 and (not selection2)'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, T1106
	References
	N/A
	Severity
	49
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id

Title	Description
	Additional Information **Maturity**: production **Creation Date**: 2021/10/15 **Risk Level**: medium **False Positives**: • Legitimate PowerShell scripts that make use of PSReflect to access the win32 API

Winlogon Helper DLL	Winlogon.exe is a Windows component responsible for actions at logon/logoff as well as the secure attention sequence (SAS) triggered by Ctrl-Alt-Delete. Registry entries in HKLM\Software[Wow6432Node]Microsoft\Windows NT\CurrentVersion\Winlogon\ and HKCU\Software\Microsoft\Windows NT\CurrentVersion\Winlogon\ are used to manage additional helper programs and functionalities that support Winlogon. Malicious modifications to these Registry keys may cause Winlogon to load and execute malicious DLLs and/or executables.
	
	More details
	
	Rule ID
	`powershell_scriptblock_140`
	
	Query
	`{'selection': {'ScriptBlockText|contains': 'CurrentVersion\\Winlogon'}, 'selection2': {'ScriptBlockText|contains': ['Set-ItemProperty', 'New-Item']}, 'condition': 'all of selection*'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	
	Rule Source
	SigmaHQ,851c506b-6b7c-4ce2-8802-c703009d03c0
	
	Author: Timur Zinniatullin, oscd.community
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0003, T1547.004
	
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1547.004/T1547.004.md
	
	Severity
	49
	
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	
	Additional Information
	Maturity: experimental
	Creation Date: 2019/10/21
	Risk Level: medium
	False Positives:
	• Unknown

Code Executed Via Office Add-in	Adversaries may abuse Microsoft Office add-ins to obtain persistence on a compromised system. Office add-ins can be used to add functionality to Office programs. More details

Title	Description

	Rule ID
	`powershell_scriptblock_147`
	Query
	`{'selection_xll': {'ScriptBlockText|contains|all': ['Copy', '\\Microsoft\\AddIns\\', '.xll']}, 'selection_wll': {'ScriptBlockText|contains|all': ['Copy', '\\Microsoft\\Word\\Startup\\', '.wll']}, 'selection_xlam': {'ScriptBlockText|contains|all': ['Copy', '\\Microsoft\\Excel\\XLSTART\\', '.xlam']}, 'selection_ppam': {'ScriptBlockText|contains|all': ['Copy', '\\Microsoft\\Addins\\', '.ppam']}, 'condition': '1 of selection_*'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	• Requirements: Script Block Logging must be enabled
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0003, T1137.006
	References
	• https://github.com/redcanaryco/atomic-red-team/blob/f339e7da7d05f6057fdfcdd3742bfcf365fee2a9/atomics/T1137.006/T1137.006.md
	Severity
	74
	Suppression Logic Based On
	• computer_name
	• stellar.rule_id
	Additional Information
	Maturity: test
	Creation Date: 2024/01/26
	Risk Level: high
	False Positives
	• Unknown

Potential Unconstrained Delegation Discovery Via Get-ADComputer - ScriptBlock	Detects the use of the "Get-ADComputer" cmdlet in order to identify systems which are configured for unconstrained delegation.
	More details
	Rule ID
	`powershell_scriptblock_148`
	Query
	`{'selection1': {'ScriptBlockText|contains': 'Get-ADComputer'}, 'selection2': {'ScriptBlockText|contains': ['-Properties*TrustedForDelegation', '-Properties*TrustedToAuthForDelegation', '-Properties*msDS-AllowedToDelegateTo', '-Properties*PrincipalsAllowedToDelegateToAccount', '-LDAPFilter*(userAccountControl:1.2.840.113556.1.4.803:=524288)']}, 'condition': 'selection1 and selection2'}`

Title	Description
	Log Source Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enable **Rule Source** Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0043, T1589.002, TA0007, T1018, TA0006, T1558 **References** • https://pentestlab.blog/2022/03/21/unconstrained-delegation/ • https://learn.microsoft.com/en-us/powershell/module/activedirectory/get-adcomputer?view=windowsserver2022-ps **Severity** 50 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2025-03-05 Risk Level: medium False Positives: • Legitimate use of the library for administrative activity

PowerShell Kerberos Ticket Dump	Detects PowerShell scripts that have the capability of dumping Kerberos tickets from LSA, which potentially indicates an attacker's attempt to acquire credentials for lateral movement.
	More details
	Rule ID
	`powershell_scriptblock_149`
	Query
	`{'selection1': {'ScriptBlockText|contains': 'LsaCallAuthenticationPackage'}, 'selection2': {'ScriptBlockText|contains': ['KerbRetrieveEncodedTicketMessage', 'KerbQueryTicketCacheMessage', 'KerbQueryTicketCacheExMessage', 'KerbQueryTicketCacheEx2Message', 'KerbRetrieveTicketMessage', 'KerbDecryptDataMessage']}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0006, T1003, T1558
	References

Title	Description
	N/A **Severity** 75 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** **Maturity**: production **Creation Date**: 2023/07/26 **Risk Level**: high **False Positives**: N/A

DSInternals Suspicious PowerShell Cmdlets - ScriptBlock	Detects execution and usage of the DSInternals PowerShell module. Which can be used to perform what might be considered as suspicious activity such as dumping DPAPI backup keys or manipulating NTDS.DIT files. The DSInternals PowerShell Module exposes several internal features of Active Directory and Azure Active Directory. These include FIDO2 and NGC key auditing, offline ntds.dit file manipulation, password auditing, DC recovery from IFM backups and password hash calculation.
	
	More details
	
	Rule ID
	
	`powershell_scriptblock_150`
	
	Query
	
	`{'selection': {'ScriptBlockText|contains': ['Add-ADDBSidHistory', 'Add-ADNgcKey', 'Add-ADReplNgcKey', 'ConvertFrom-ADManagedPasswordBlob', 'ConvertFrom-GPPrefPassword', 'ConvertFrom-ManagedPasswordBlob', 'ConvertFrom-UnattendXmlPassword', 'ConvertFrom-UnicodePassword', 'ConvertTo-AADHash', 'ConvertTo-GPPrefPassword', 'ConvertTo-KerberosKey', 'ConvertTo-LMHash', 'ConvertTo-MsoPasswordHash', 'ConvertTo-NTHash', 'ConvertTo-OrgIdHash', 'ConvertTo-UnicodePassword', 'Disable-ADDBAccount', 'Enable-ADDBAccount', 'Get-ADDBAccount', 'Get-ADDBBackupKey', 'Get-ADDBDomainController', 'Get-ADDBGroupManagedServiceAccount', 'Get-ADDBKdsRootKey', 'Get-ADDBSchemaAttribute', 'Get-ADDBServiceAccount', 'Get-ADDefaultPasswordPolicy', 'Get-ADKeyCredential', 'Get-ADPasswordPolicy', 'Get-ADReplAccount', 'Get-ADReplBackupKey', 'Get-ADReplicationAccount', 'Get-ADSIAccount', 'Get-AzureADUserEx', 'Get-BootKey', 'Get-KeyCredential', 'Get-LsaBackupKey', 'Get-LsaPolicy', 'Get-SamPasswordPolicy', 'Get-SysKey', 'Get-SystemKey', 'New-ADDBRestoreFromMediaScript', 'New-ADKeyCredential', 'New-ADNgcKey', 'New-NTHashSet', 'Remove-ADDBObject', 'Save-DPAPIBlob', 'Set-ADAccountPasswordHash', 'Set-ADDBAccountPassword', 'Set-ADDBBootKey', 'Set-ADDBDomainController', 'Set-ADDBPrimaryGroup', 'Set-ADDBSysKey', 'Set-AzureADUserEx', 'Set-LsaPolicy', 'Set-SamAccountPasswordHash', 'Set-WinUserPasswordHash', 'Test-``

Title	Description
	 DDBPasswordQuality', 'Test-ADPasswordQuality', 'Test-ADReplPasswordQuality', 'Test-PasswordQuality', 'Unlock-ADDBAccount', 'Write-ADNgcKey', 'Write-ADReplNgcKey']}, 'condition': 'selection'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts • Requirements: Script Block Logging must be enabled **Rule Source** SigmaHQ,846c7a87-8e14-4569-9d49-ecfd4276a01c Author: Nasreddine Bencherchali (Nextron Systems) **Tactics, Techniques, and Procedures** TA0002, T1059.001 **References** • https://github.com/MichaelGrafnetter/DSInternals/blob/39ee8a69bbdc1cfd12c9afdd7513b4788c4895d4/Src/DSInternals.PowerShell/DSInternals.psd1 **Severity** 75 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: experimental Creation Date: 2024-06-26 Risk Level: high False Positives: • Legitimate usage of DSInternals for administration or audit purpose.
Windows PowerSploit GPP Discovery	The following analytic detects the execution of the Get-GPPPassword PowerShell cmdlet, which is used to search for unsecured credentials in Group Policy Preferences (GPP). This detection leverages PowerShell Script Block Logging to identify specific script block text associated with this cmdlet. Monitoring this activity is crucial as it can indicate an attempt to retrieve and decrypt stored credentials from SYSVOL, potentially leading to unauthorized access. If confirmed malicious, this activity could allow an attacker to escalate privileges or move laterally within the network by exploiting exposed credentials. More details **Rule ID** powershell_scriptblock_151 **Query** {'selection': {'ScriptBlockText|contains': ['Get-GPPPassword', 'Get-CachedGPPPassword']}, 'condition': 'selection'} **Log Source** Stellar Cyber Windows Server Sensor configured for: • Monitoring PowerShell scripts

Title	Description
	Rule Source Developed internally by Stellar Cyber **Tactics, Techniques, and Procedures** TA0006, T1552.006 **References** • https://pentestlab.blog/2017/03/20/group-policy-preferences/ • https://adsecurity.org/?p=2288 • https://www.hackingarticles.in/credential-dumping-group-policy-preferences-gpp/ • https://adsecurity.org/?p=2288 • https://support.microsoft.com/en-us/topic/ms14-025-vulnerability-in-group-policy-preferences-could-allow-elevation-of-privilege-may-13-2014-60734e15-af79-26ca-ea53-8cd617073c30 **Severity** 50 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: production Creation Date: 2025-02-10 Risk Level: medium False Positives: • Unknown

Windows PowerView Unconstrained Delegation Discovery	The following analytic detects the use of PowerView commandlets to discover Windows endpoints with Kerberos Unconstrained Delegation. It leverages PowerShell Script Block Logging (EventCode=4104) to identify specific commands like `Get-DomainComputer` or `Get-NetComputer` with the `-Unconstrained` parameter. This activity is significant as it indicates potential reconnaissance efforts by adversaries or Red Teams to map out privileged delegation settings in Active Directory. If confirmed malicious, this could allow attackers to identify high-value targets for further exploitation, potentially leading to privilege escalation or lateral movement within the network.
	More details
	Rule ID
	`powershell_scriptblock_152`
	Query
	`{'selection1': {'ScriptBlockText|contains': ['Get-DomainComputer', 'Get-NetComputer']}, 'selection2': {'ScriptBlockText|contains': '-Unconstrained'}, 'condition': 'selection1 and selection2'}`
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	Rule Source
	Developed internally by Stellar Cyber
	Tactics, Techniques, and Procedures

Title	Description
	A0007, T1018 **References** • https://adsecurity.org/?p=1667 • https://docs.microsoft.com/en-us/defender-for-identity/cas-isp-unconstrained-kerberos • https://www.ired.team/offensive-security-experiments/active-directory-kerberos-abuse/domain-compromise-via-unrestricted-kerberos-delegation • https://www.cyberark.com/resources/threat-research-blog/weakness-within-kerberos-delegation **Severity** 50 **Suppression Logic Based On** • computer_name • stellar.rule_id **Additional Information** Maturity: production Creation Date: 2024-11-13 Risk Level: medium False Positives: • Administrators or power users may leverage PowerView for system management or troubleshooting.

Get-ForestTrust with PowerShell Script Block	The following analytic detects the execution of the Get-ForestTrust command from PowerSploit using PowerShell Script Block Logging (EventCode=4104). This method captures the full command sent to PowerShell, providing detailed visibility into potentially suspicious activities. Monitoring this behavior is crucial as it can indicate an attempt to gather domain trust information, which is often a precursor to lateral movement or privilege escalation. If confirmed malicious, this activity could allow an attacker to map trust relationships within the domain, facilitating further exploitation and access to sensitive resources.
	
	More details
	
	Rule ID
	`powershell_scriptblock_153`
	
	Query
	`{'selection': {'ScriptBlockText|contains': ['get-foresttrust']}, 'condition': 'selection'}`
	
	Log Source
	Stellar Cyber Windows Server Sensor configured for:
	• Monitoring PowerShell scripts
	
	Rule Source
	Developed internally by Stellar Cyber
	
	Tactics, Techniques, and Procedures
	TA0002, T1059.001, TA0007, T1482
	
	References
	• https://powersploit.readthedocs.io/en/latest/Recon/Get-ForestTrust/
	• https://www.splunk.com/en_us/blog/security/hunting-for-malicious-powershell-using-script-block-logging.html
	
	Severity

Title	Description
	

Suppression Logic Based On

- computer_name
- stellar.rule_id

Additional Information

Maturity	Creation Date	Risk Level	False Positives
production	2024-11-13	medium	• False positives may be present. Tune as needed.

© 2026 Stellar Cyber . All rights reserved.