Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Configuring SentinelOne Connectors 6.4.0

This connector allows Stellar Cyber to collect data from external sources and add the records to the data lake.

SentinelOne integration with Stellar Cyber provides advanced threat detection and response capabilities, combining AI-powered endpoint protection with real-time threat intelligence and automated response workflows to improve incident response and threat mitigation.

A SentinelOne connector allows you to collect logs, discover assets, and see vulnerabilities. If you enable **Respond** options on this connector, with the correct type of user account, you can perform the following endpoint response actions:

- Contain (Isolate) Host
- Initiate Scan
- Kill Threat
- Quarantine Threat
- Remediate Threat

Rate limits for the SentinelOne connector are detailed in Guidance on SentinelOne Connector Rate Limits.

The following error from SentinelOne, 503 Service Temporarily Unavailable, is treated by Stellar Cyber as the following error, 429 Too Many Requests, and is not shown on the DP connector list. This will be addressed in a later release.

This connector is improved to use less memory. Under certain scenarios if there is an error reaching the third-party API, some duplicate messages may be sent.

Stellar Cyber connectors with the Collect function (collectors) may skip collecting some data when the ingestion volume is large, which potentially can lead to data loss. This can happen when the processing capacity of the collector is exceeded.

Connector Overview: SentinelOne

Capabilities

- Collect: **Yes**
- Respond: **Yes**
- Native Alerts Mapped: **Yes**
- Runs on: **DP**
- Interval: **Configurable**

Collected Data

Content Type	Index	API	Mapped to AlertIndex
Host (Agents)	Assets	https://<sentinelone region url>/web/api/v2.1/agents	
Threats	Syslog, Alerts	https://<sentinelone region url>/web/api/v2.1/threats	Yes
Vulnerabilities This content type needs the Applications View Risks permission. See Obtaining SentinelOne Credentials for details.	Scan	Three related API calls are used for this data: https://<sentinelone region url>/web/api/v2.1/agents https://<sentinelone region url>/web/api/v2.1/installed-applications https://<sentinelone region url>/web/api/v2.1/private/installed-applicatio	

Content Type	Index	API	Mapped to Alert Index
		ns/<app id>/cves	
Support added for the following in v4.3.5:			
 The following content types require an upgraded subscription (STAR), as well as permissions. See Obtaining SentinelOne Credentials for details.			
Alerts	Syslog	https://<sentinelone region url>/web/api/v2.1/cloud-detection/alerts	
Deep Visibility(Events)	Syslog	https://<sentinelone region url>/web/api/v2.1/dv/events?queryId={query_id}	
Events (Threat Events)	Syslog	https://<sentinelone region url>/web/api/v2.1/threats/{threat id}/explore/events?limit=1000	
Rogues	Syslog	https://<sentinelone region url>/web/api/v2.1/rogues/table-view	
Threat Notes	Syslog	https://<sentinelone region url>/web/api/v2.1/threats/{threat id}/notes?limit=1000	
Support added for the following in v5.3.0:			

Content Type	Index	API	Mapped to Alert Index
Activities	Syslog	https://<sentinelone region url>/web/api/v2.1/activities	
Support added for the following in v6.0.0: 6.0.0			
Misconfigurations	Syslog	/web/api/v2.1/xspm/findings/misconfigurations/graphql	
Unified Alerts	Syslog	/web/api/v2.1/unifiedalerts/graphql	

Domain

<Host URL>

where <Host URL> is a variable from the configuration of this connector

Response Actions

Action	Required Fields	API

Contain (Isolate) Host	`agentRealtimeInfo and agentRealtimeInfo.agentId`	`https://<sentinelone region url>/web/api/v2.1/agents/actions/disconnect`
		revert:
		`https://<sentinelone region url>/web/api/v2.1/agents/actions/connect`

Initiate Scan	`agentRealtimeInfo and agentRealtimeInfo.agentId`	`https://<sentinelone region url>/web/api/v2.1/agents/actions/initiate-scan`

Action	Required Fields	API
Kill Threat	`msg_origin.source is 'Sentinel_endpoint' or` `msg_origin.source is 'Sentinel' and threatInfo and threatInfo.threatId are valid`	`https://<sentinelone region url>/web/api/v2.1/threats/mitigate/kill`

Quarantine Threat	`msg_origin.source is 'Sentinel_endpoint' or`
	`msg_origin.source is 'Sentinel' and threatInfo and threatInfo.threatId are valid`
		`https://<sentinelone region url>/web/api/v2.1/threats/mitigate/quarantine`
		revert:
		`https://<sentinelone region url>/web/api/v2.1/threats/mitigate/un-quarantine`

Remediate Threat	`msg_origin.source is 'Sentinel_endpoint' or`
	`msg_origin.source is 'Sentinel' and threatInfo.detectionType is 'dynamic' and the following fields are present and valid: threatInfo, threatInfo.threatId`
	The endpoint must also be either a Mac OS or Windows host. if it is not, then a Quarantine is performed instead.
		`https://<sentinelone region url>/web/api/v2.1/threats/mitigate/remediate`
		revert:
		`https://<sentinelone region url>/web/api/v2.1/threats/mitigate/rollback-remediation`

Third Party Native Alert Integration Details

SentinelOne Cloud

SentinelOne's threat dataset includes a variety of fields that enable Stellar Cyber to map the native SentinelOne alerts to the Stellar Cyber Alert index. For example, `threatInfo.classification` describes the event (such as Trojan). That and other fields in the `threatInfo` record support direct mapping of SentinelOne's MITRE | ATT&CK Tactic and Technique fields to Stellar Cyber's XDR Kill Chain. Of the assorted collected data types noted above, only the Threat (msg_class: `sentinelone_threat_detection`) are directly mapped to the Alert index. Select the Threat content type.

For details, see Integration of Third Party Native Alerts.

SentinelOne Singularity Identity 6.3.0

This connector ingests logs from SentinelOne to get the raw alerts that are stored in the Syslog index. Select the Unified Alerts content type.

Stellar Cyber maps SentinelOne alerts. The alerts are read from the Syslog index, enriched with Stellar Cyber fields, and mapped (with deduplication) to the Alerts index.

Deduplication is by `tenantid` and `sentinelone.external_id`.

For details, see Integration of Third Party Native Alerts.

Required Credentials and Configurations

- Host URL and API Key (Admin).
- To **Collect**, the SentinelOne User Account can have either the Viewer or Admin role. To **Respond**, the user Role must be Admin.

Locating Records

Use the following fields as a guide to query for records:

- **msg_origin.source**: `sentinelone_endpoint`
- **msg_origin.vendor**: `sentinelone`
- **msg_origin.category**: `endpoint`
- **msg_class**:

Events (Threat Events)	Hosts (Agents)	Deep Visibility
`sentinelone_threat_events`	`sentinelone_host`	`sentinelone_deep_visibility`
Alerts	**Rogues**	**Threat**
`sentinelone_cloud_detection_alerts`	`sentinelone_rogues_table`	`sentinelone_threat_detection`
Threat Notes	**Vulnerabilities**	**Activities**
`sentinelone_threat_notes`	`sentinelone_vulnerabilities`	`sentinelone_activities`
Misconfigurations	**Unified Alerts**	
`sentinelone_misconfigurations` 6.0.0	`sentinelone_unified_alerts` 6.0.0	

For SentinelOne Cloud, to search the Original Records in the Syslog index, use the query: `msg_class:sentinelone_threat_detection`

For SentinelOne Singularity Identity, to search the alerts in the Alerts index or the Original Records in the Syslog index, use the query: `msg_class:sentinelone_unified_alerts AND sentinelone.detectionSource.product: Identity AND (NOT event.severity_str: INFO)`
6.3.0

Adding a SentinelOne Connector

To add a SentinelOne connector:

1. Obtain SentinelOne credentials
2. Add the connector in Stellar Cyber
3. Test the connector
4. Verify ingestion


You can also configure SentinelOne to send logs to the Stellar Cyber parser. However, the connector allows you to assign a tenant, while the parser does not.

Obtaining SentinelOne Credentials


As part of this procedure, you specify the credentials of an account on the SentinelOne server that will be used to retrieve data. This account **must have read/view permissions or better on**

the SentinelOne server. To perform response actions, the account must have an **administrative** role.

1. Log into your **SentinelOne Management Console** as an administrative user (for example: https://usea1-partners.sentinelone.net/login).
2. From the Management Console navigation pane, select **Settings**.




3. Navigate to **Site Info**.




4. Make sure that Licenses is **Complete** for the site.

> Some content types require an upgraded subscription (STAR), as well as permissions, otherwise the connector will not produce expected results. If that is the case, select Add-ons **STAR**.


5. In the tab for **Users**, choose **Roles**.
    - To support the collect only function in Stellar Cyber, choose either **Viewer** or **Admin**.




    - To support the respond function in Stellar Cyber, choose **Admin**.




6. To support the Vulnerabilities content type, with the **Admin** role, choose Applications, and select Permissions including View Risks.




7. For the role, set the following permissions for certain content types:
    - To support the Deep Visibility content type, choose **Deep Visibility View**.



    - To support the Threats content type, choose **Threats View**.




    - To support the Rogues content type, choose **Rogues View**.





If these features are Not allowed (greyed out), contact SentinelOne.


8. Click **Save**.
9. Choose the **Users** tab and select the option to add a **New User** for the account you will use with the Stellar Cyber connector.



10. In the **User Details**, enter the information for the new user.




11. Make sure to assign a role to the account, either **Viewer** or **Admin**.



12. Log out of the **SentinelOne Management Console** and then log back in with the username you created. You are prompted to create a **password** for that user. Create the password and complete the login.
13. When logged into the SentinelOne online console as an administrative user, you need to generate an API token for the connector configuration. The token can be generated from a console user or from a service user.


    The following steps are to generate the API token from a console user:

    a. Click the username from the top right of the console and select **My User.**



    b. In the dialog that displays, click the link to **Generate** an **API Token**.


    c. This displays the token with a warning to copy it. If you forget the token, you will need to regenerate it. **Download** it now or **Copy** it and save it to a file for later use in the connector you configure in Stellar Cyber.




    d. Exit the console and proceed to the next section.

    The following steps are to generate the API token from a service user:


    a. Click the **USERS** tab and choose **Service Users**. Then select **Create New Service User** from the **Actions** menu.




b. Enter the **Name** of the **New Service User** and choose an **Expiration Date**.Then click **Next**.




c. You can set the **Scope of Access** for the **Account** or the **Site**.



d. To set the **Scope of Access** for the **Account**, select **Account**. Choose **Admin** or **Viewer** from the dropdown menu for the role. Choose **Admin** for respond actions.




e. To set the **Scope of Access** for the **Site**, select **Site**. Choose **Admin** or **Viewer** from the dropdown menu for the role. Choose **Admin** for respond actions.



f. Click **Create User**.

g. Copy the **API Token**.




Store the API key in a safe location. It cannot be retrieved later although it can be regenerated.

h. Click **Close**.


Adding the Connector in Stellar Cyber

To add a SentinelOne connector in Stellar Cyber:

1. Log in to Stellar Cyber.
2. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.




3. Click **Create** and select **Connector**.



The **General** tab of the **Add Connector** screen appears. The information on this tab cannot be changed after you add the connector.

4. Choose **Endpoint Security** from the **Category** dropdown.
5. Choose **SentinelOne** from the **Type** dropdown.




The asterisk (*) indicates a required field.

6. Enable the **Function** for **Collect** and/or **Respond**.
7. Enter a **Name**.

Notes:

- This field does not accept multibyte characters.
- It is recommended that you follow a naming convention such as tenantname-connectortype.

8. Choose a **Tenant Name**. The Interflow records created by this connector include this tenant name.
9. Choose the device on which to run the connector.
10. (Optional) When the **Function** is **Collect**, you can apply **Log Filters**. For information, see Managing Log Filters.
11. Click **Next**. The **Configuration** tab appears.



The asterisk (*) indicates a required field.

12. Enter the **Host URL**. This is the address of your SentinelOne server.

For release versions prior to v4.3.4, ensure the URL does not include a trailing "/" symbol.

13. Enter the **API Key** (token) you created above.

In earlier releases, Stellar Cyber supported use of a Username / Password combination. However, SentinelOne now enforces use of 2FA, which necessitates use of a token with API communications.

14. (Optional) Enter **Site**. This is a string and can be either a site ID or a site name. In the SentinelOne management console, navigate to **Settings > Sites**, click the site, and click **Site Info** for the value. A site ID is a long numeric string, for example: 775505036300366067.
15. Choose the **Content Type**. The following logs are supported:

- **Vulnerabilities**

This content type requires a permission. See Obtaining SentinelOne Credentials for details.

The SentinelOne connector only supports single scope for the Vulnerabilities API. If multiple scopes are needed:

- create multiple users: one scope per user
- create multiple connectors: one connector per user


- **Hosts** (Agents)
- **Threats**
- The following logs are supported for v4.3.5, and later.

  These content types require an upgraded subscription, as well as permissions. See Obtaining SentinelOne Credentials for details.


  - **Alerts**
  - **Events** (Threat Events)
  - **Threat Notes**
  - **Rogues**
  - **Deep Visibility**
- The following logs are supported for v5.3.0, and later.
  - **Activities**
  - **Misconfigurations** 6.0.0
  - **Unified Alerts** 6.0.0

16. Click the **Advanced Settings** checkbox to enter the interval, in minutes, for each content type selected. The interval is how often the logs are collected. There are default values for the interval, based on the content type. Most content types have a 5 minute default interval, but **Deep Visibility** has a 30 minute default interval.

    Also for **Deep Visibility**, you can specify the number of items retrieved in the interval. The default is 20000. Use caution when adjusting the limit. If it is too high, there are risks, for example, the SentinelOne API might not support the high number. 6.4.0

17. Click **Next**. The final confirmation tab appears.

18. Click **Submit**.

The new connector is immediately active.

Guidance on SentinelOne Connector Rate Limits

Some customers using the SentinelOne connector in Stellar Cyber may occasionally experience API rate limit issues when retrieving data from SentinelOne endpoints. Limits are enforced by SentinelOne to ensure fair use and platform stability across tenants.

Why This Happens

SentinelOne applies API rate limits at the tenant or console level. For larger MSSP environments or those running multiple integrations, these limits can sometimes be reached during periods of high activity or large data pulls.

Recommended Customer Actions

The following are recommended actions you can take:

1. **Contact SentinelOne Support or Your TAM**

   If you encounter rate limit issues, please reach out to your **SentinelOne Technical Account Manager (TAM)** or **SentinelOne Support** to request a rate limit increase.

   - SentinelOne's official guidance on rate limiting can be found here: API rate limits
   - Rate limit increases are reviewed and approved by SentinelOne

2. **Review Your API Usage**

   Review how frequently your SentinelOne data is being queried. In some cases, reducing the query frequency or adjusting collection intervals can help avoid rate limit thresholds.

3. **Dedicated Consoles (for MSSPs)**

   MSSPs operating on shared SentinelOne consoles may not be able to request IP whitelisting or dedicated rate limit adjustments.

   However, if your organization operates a **dedicated SentinelOne console**, you can contact SentinelOne Support to ask about potential configuration options specific to your tenant.

Summary

While rate limits are controlled by SentinelOne, our integration is designed to ensure reliable data collection even under constrained conditions.

If you continue to experience interruptions, please contact Stellar Cyber Support for assistance. Providing your SentinelOne case number (if you have opened one) will help us coordinate more effectively with the SentinelOne team.


Testing the Connector

When you add (or edit) a connector, we recommend that you run a test to validate the connectivity parameters you entered. The test validates authentication and connectivity.



For connectors running on a sensor, Stellar Cyber recommends that you allow 30-60 seconds for new or modified configuration details to be propagated to the sensor before performing a test.

1. Click **System | INTEGRATIONS | Connectors**. The **Connector Overview** appears.



2. Locate the connector by name that you added, or modified, or that you want to test.
3. Click **Test** at the right side of that row. The test runs immediately.

Note that you may run only one test at a time.

Stellar Cyber conducts a basic connectivity test for the connector and reports a success or failure result. A successful test indicates that you entered all of the connector information correctly.

To aid troubleshooting your connector, the dialog remains open until you explicitly close it by using the **X** button. If the test fails, you can select the button from the same row to review and correct issues.

The connector status is updated every five (5) minutes. A successful test clears the connector status, but if issues persist, the status reverts to failed after a minute.


Repeat the test as needed.

Display sample messages...


Success !



Failure with summary of issue:



Show More example detail:



If the test fails, the common HTTP status error codes are as follows:

HTTP Error Code	HTTP Standard Error Name	Explanation	Recommendation
400	Bad Request	This error occurs when there is an error in the connector configuration.	Did you configure the connector correctly?
401	Unauthorized	This error occurs when an authentication credential is invalid or when a user does not have sufficient privileges to access a specific API.	Did you enter your credentials correctly? Are your credentials expired? Are your credentials entitled or licensed for that specific resource?

HTTP Error Code	HTTP Standard Error Name	Explanation	Recommendation
403	Forbidden	This error occurs when the permission or scope is not correct in a valid credential.	Did you enter your credentials correctly? Do you have the required role or permissions for that credential?
404	Not Found	This error occurs when a URL path does not resolve to an entity.	Did you enter your API URL correctly?
429	Too Many Requests	This error occurs when the API server receives too much traffic or if a user's license or entitlement quota is exceeded.	The server or user license/quota will eventually recover. The connector will periodically retry the query. If this occurs unexpectedly or too often, work with your API provider to investigate the server limits, user licensing, or quotas.

For a full list of codes, refer to HTTP response status codes.

Verifying Ingestion

To verify ingestion:

1. Select **Threat Hunting**. The **Interflow Search** tab appears.
2. Set the **Indices** for the type of content you collected:
    - For **Threats**, change the **Indices** to **Syslog** or **Alerts**.
    - For **Hosts**, change the **Indices** to **Assets**. Note that hosts discovered through this connector show SentinelOne as a data source.
    - For **Vulnerabilities**, change the **Indices** to **Scans**.
    - For all other data types, change the **Indices** to **Syslog**.
3. Search for the msg_class corresponding to the data type you want to view:
    - Vulnerabilities: `sentinelone_vulnerabilities`
    - Hosts (Agents): `sentinelone_host`
    - Threats: `sentinelone_threat_detection`
    - Alerts: `sentinelone_cloud_detection_alerts`
    - Events (Threat Events): `sentinelone_threat_events`
    - Threat Notes: `sentinelone_threat_notes`
    - Rogues: `sentinelone_rogues_table`
    - Deep Visibility: `sentinelone_deep_visibility`
    - Activities: `sentinelone_activities`
    - Misconfigurations: `sentinelone_misconfigurations` 6.0.0

- Unified Alerts: `sentinelone_unified_alerts` 6.0.0



© 2026 Stellar Cyber . All rights reserved.