Stellar Cyber 6.6.0s is now live! Discover all the updates in the release notes!

Standard Metadata Dictionary

Stellar Cyber monitors your network to collect and respond to data reported from multiple sources such as network packets, endpoint telemetry, cloud logs, and threat intelligence feeds. Each type of data is handled differently before being populated into a standardized set of fields referred to as metadata. Where applicable, and based on your configuration and the type of content, the data may be de-duplicated, normalized, and enriched as it passes through sensors and the data processor, on its way to becoming part of an Interflow record.

Standard Metadata Fields in Interflow Records

The table below lists the standard metadata fields in the Stellar Cyber Interflow record, the type of data recorded, and a description. You can use these fields as part of your searches or queries that you build, along with vendor specific fields and values.

About GDPR Compliance

The table below is also a summary of the data collected by the Stellar Cyber platform and can be used as part of your GDPR compliance strategy.

Metadata Field	Type	Description
_id2	string	Elasticsearch ID of the earlier of two login records.
_index2	string	Elasticsearch index of the earlier of two login records.
access_mask	string	Object access mask.
access_subject	string	The subject entity that performed the object access.
accumulated_anomalous_failures	integer	Score in the TRW model, indicating degree of abnormal activities. Used for Machine Learning.
action	string	The action to be taken. Examples are **allow** or **block**.
actual	integer	Real value input for Machine Learning to process.
actual_range	string	Actual login time range.
ade	object	Namespace for all ADE-related fields.
aella_tuples	string	The concatenated fields of srcip, dstip, dstport, and appid.
alert_time	date	Time of anomaly being detected.

Metadata Field	Type	Description
appid	long	The ID of an application identified by the DPI engine.
appid_family	string	The name of the application family to which the application belongs, such as network service, database, web, etc.
appid_name	string	The name of an application identified by the DPI engine, such as HTTP, DHCP, Google, etc.
appid_stdport	string	Whether the application is using the standard port.
appid_tags	list	The application's tags.
asset_view	integer	Whether the record contains a summary of scan results for one asset.
assignee	string	The user assigned to this event record.
attack_start_date	string	The time an attack began, reported by the sensor.
case_id	string	For Case Management, the ID of the case to which the record belongs, if any.
case_name	string	For Case Management, the name of the case to which the record belongs, if any.
cloud	object	From ECS. The fields are related to the cloud or infrastructure from which the events are coming. The namespace fields are cloud.resource.type, cloud.resource.id, and cloud.resource.name.
command	string	The command that was run in a system.
comments	list	A list of all comments made on the record.
computer_name	string	The host name of the endpoint.
correlation_info	object	Information about individual records involved in a correlation event.
custom_ser_field	object	reserved field (Used by ActZero only for now)
days_silent	integer	Time interval (days) between latest two appearances.
detect_date	date	The time when an attack was detected by the sensor.
detect_origin	string	The direction of the attack based on Stellar Cyber analysis of metadata..
detected_field	string	Identification field of the alert type.
detected_value	ip	Identification field's value of the alert type.
detection_flag	integer	A special flag to encode what alert type(s) to which this record might be applicable.
detector_index	integer	Index of alert types for ML jobs. A Machine Learning job can have multiple alert types, each one with a detected_field value.
device	object	From OCSF, the device object represents an addressable computer system or host. The namespace field is device.name.

Metadata Field	Type	Description
dhcp	object	From ECS. Information about DHCP. The namespace fields are dhcp.assigned_ip and dhcp.server_ip.
direction	string	The direction of the maltrace event.
distance_deviation	float	The distance deviation between two login geolocations.
diversity	integer	Typical variety of elements for an entity (1–100). The higher value, the more variety it has.
dns	object	From ECS. Information about DNS. The namespace fields are dns.resolved_ip, dns.answers, dns.answers.name, dns.answers.type, dns.answers.data, dns.question.name, dns.question.registered_domain, and dns.question.top_level_domain.
domain_creation	date	Creation time of the domains associated with those in the domain_list, such as a UNIX timestamp.
domain_list	list_of_string	List of domains.
domain_reputation	string	Formatted list of (one or more) domain reputations, separated by a comma.
dscp_name	string	Name as described in the commonly used DSCP values in RFC 2475 Best Effort, Expedited Forwarding, AF11, AF12, AF13, AF21, AF22, AF23, AF31, AF32, AF33, AF41, AF42, AF43.
dstip	ip	Destination IP address of the session.
dstip_aella_flag	integer	The flag indicating how the destination IP address will be processed.
dstip_asn	integer	Autonomous System Number (ASN) responsible for the destination IP address.
dstip_asn_org	string	Organization name associated with the ASN for the destination iP address
dstip_assetid	string	The asset ID associated with the destination IP address.
dstip_domain_creation	date	The creation date of the domain associated with the destination IP address.
dstip_geo	object	Geo location information for the destination IP address.
dstip_geo_point	string	Geo point of the destination IP address.
dstip_host	string	Host name or DNS name for the destination IP address.
dstip_reputation	string	Reputation of the destination IP address from Threat Intelligence, such as Good, Bad, Scanner, Spyware, etc.
dstip_reputation_source	string	The source of the reputation data.
dstip_sig_id	string	The signature ID concatenated with the dstip.
dstip_source	string	Destination IP source.
dstip_tag	string	The asset tag associated with the destination IP address.

Metadata Field	Type	Description
dstip_type	string	The IP address type for the destination IP address, such as private, multicast, or public.
dstip_username	string	The username associated with the destination IP address.
dstip_usersid	string	The user ID associated with the destination IP address. For Windows, security identifier (SID) is used.
dstip_version	string	Indicates if the destination IP address is IPv4 or IPv6.
dstmac	string	Destination MAC address.
dstport	integer	Layer 4 destination port.
duration	integer	Session duration in milliseconds.
email	object	From ECS. The event fields are used for context information about the log or metric email itself. The namespace fields are email.subject, email.sender.address, email.recipient.addresses, email.to.addresses, email.from.address, and email.x_mailer.
end_bucket_time	integer	End time of the data that caused the anomaly, in milliseconds (combines with the start_bucket_time to form a time range).
end_reason	integer	Reason the session ended 1–4: normal 5: TCP reset 10–25: ICMP-related.
engid	string	ID of the sensor.
engid_device_class	string	The high level operating system of the sensor.
engid_device_desc	string	OS version of the sensor. For agent sensors, this is the host OS version.
engid_gateway	string	The gateway of the sensor.
engid_name	string	The hostname of the sensor.
event	object	From ECS. The event fields are used for context information about the log or metric event itself. Examples of namespace fields are event.id, event.type, and event.category. Full list of namespace fields event.action, event.created, event.description, event.description_id, event.end, event.id, event.name, event.old, event.old.driver_letter, event.old.extension, event.old.subjectUserName, event.old.subjectUserSid, event.old.type, event.provider, event.reason, event.severity, event.severity_str, event.start, event.tactic.name, event.technique.name, event.type, event.url, event.ms_incident_id, event.category,

Metadata Field	Type	Description
		event.threat.name, event.vpn.phase, event.vpn.type, event.outcome, and event.sig_id
event_category	string	The kill chain event category for the Machine Learning job.
event_data	object	This field's sub fields are the metadata associated with this Windows event.
event_description	string	The general description of the event.
event_detail	object	Used in gsuite-related alert types.
event_id	integer	The ID of the event.
event_name	string	The event name for the job.
event_score	float	Combination of severity, fidelity, and threat_score.
event_source	string	The data source for the Machine Learning job results.
event_status	string	The current status of a given event record. Can be new, in_progress, closed, or ignored.
event_summary	object	Summarized data points from records contributing to an alert.
event_tags	list	The upper-level namespace for tags.
event_tags.tag	string	A given tag's name.
event_type	string	The event type for the Machine Learning job.
exec_user	string	The user that executed a command, from auth_log.
fidelity	integer	Machine Learning confidence that an attack is happening. From 0–100, with a higher value indicating higher confidence.
file	object	From ECS. A file is a set of information that has been created on or has existed on a filesystem. The namespace fields are file.name, file.path, file.file_hash, file.hash.md5, file.hash.sha1, file.hash.sha256, and file_threat_indicator. See threat_indicator object.
file_list	list_of_object	A list of file objects.
file_name	string	File name extracted from traffic.
file_path	string	Directory holding the fileName on the endpoint.
file_size	integer	File size in bytes.
fileid	string	Unique identifier for the file. It is a hash based on MD5 and SHA-256.
fileName	string	File name of the threat on the endpoint.
fw_policy_id	string	The rule or policy that the firewall checks against.
group	string	The detected threat group to which the threat belongs.
handler	string	Handler identifier.
host	object	From ECS. A host is a general computing instance. The namespace fields are host.ip, host.id, host.mac,

Metadata Field	Type	Description
		host.name, and host.external_ip.
host	string	Host name of the host IP address.
host_list	list_of_object	A list of host objects.
hostip	ip	The host IP address of the endpoint.
hostip_asn	integer	Autonomous System Number (ASN) responsible for the host IP address.
hostip_asn_org	string	Organization name associated with the ASN for the host iP address
hostip_assetid	string	The asset ID associated with the host IP address.
hostip_domain_creation	date	The creation time of the domains associated with the host IP address.
hostip_geo	object	Geo location information for the host IP address.
hostip_geo_point	string	Geo point of the host IP address.
hostip_hoat	string	Host name of the host IP address.
hostip_reputation	string	Reputation of the host IP address.
hostip_reputation_source	string	The source of the reputation data.
hostip_sig_id	string	The signature ID concatenated with hostip.
hostip_source	string	Host IP source.
hostip_tag	string	The asset tag associated with the host IP address.
hostip_type	string	The type of the host IP address.
hostip_username	string	The username associated with the host IP address.
hostip_usersid	string	The user ID associated with the host IP address. For Windows, security identifier (SID) is used.
hostip_version	string	Indicates if the host IP address is IPv4 or IPv6.
hostname	string	The host name (Linux Audit).
icmp_type	string	The ICMP message type.
ids	object	Namespace for all IDS related fields.
in_bytes_delta	integer	The number of bytes the client received from the server since the last update.
in_bytes_total	integer	Total number of bytes the client received from the server during the session.
in_rate	float	The incoming traffic rate, from the client to the server (in_bytes_delta / delta).
inbytes_delta	integer	The number of bytes the client received from the server since the last update.
inbytes_total	integer	Total number of bytes the client received from the server during the session.

Metadata Field	Type	Description
inpkts_delta	integer	The number of packets the client received from the server since the last update.
inpkts_total	integer	Total number of packets the client received from the server during the session.
ips	object	Namespace for all IPS related fields. The namespace fields are ips.severity, ips.signature_id, ips.signature, and ips.action.
is_dga	string	Whether a DNS request is DGA.
keywords	string	Top-level field from Windows agent, parsed from Windows events
last_login_time	date	Time of the earlier of two login records.
lateral	boolean	Whether the connection is from private to private.
locid	string	Location of the sensor if the location is assigned by the user from the user interface.
log_name	string	Top-level field from Windows agent, parsed from Windows events
login_failure_rate	float	Rate of login failures per minute in the period.
login_result	string	The login result of any user login events.
login_type	string	The login type of the login events.
login_user	string	The username associated with the login event.
lstm_prob	integer	DGA probability based on the long short-term memory model.
mac	list	A list of MAC addresses associated with the host.
maltrace-cloud	object	The malicious activity for this file, from cloud analysis.
md5	string	The MD5 hash value of this file.
metadata	object	Whether any field (such as domain, url, ip) in the metadata is in the whitelist.
msg_class	string	Whether this record belongs to an endpoint class.
msg_data	list_of_object	Used for extra, ingested data that is not mapped to specific fields and is not required for analytics or search.
msg_origin	object	The device category, such as IdP, endpoint, or firewall. Note that records ingested from Stellar Cyber sensors will have **msg_origin.source** set to **linux_agent**, **windows_agent**, **network_sensor**, **security_sensor**, or **modular_sensor** and will also include the **msg_origin.category** field set to **traffic**.
msgtype	integer	Integer value of the Stellar Cyber internal message type **1**—metadata for a session that started but has not yet

Metadata Field	Type	Description
		finished **2**—metadata for a just finished session **3**—meta data update for an on-going session **4**—metadata for a short session that has finished.
msgtype_name	string	String value of the Stellar Cyber internal message type **start**—a new session started **end**—an existing session ended **update**—stats and metadata update for an ongoing session **startend**—a short session started and ended.
netid_name	string	The name of a network ID.
new_dns_record	string	Whether the DNS A record has never been seen before.
num_failed	integer	Number of failures in the time period.
num_successful	integer	Number of successes in the time period.
opcode	string	Top-level field from Windows agent, parsed from Windows events
org_id	string	Organization ID.
org_name	string	Organization name.
orig_id	string	Elasticsearch ID of the data causing the anomaly.
orig_index	string	Elasticsearch index of the data causing the anomaly.
out_bytes_delta	integer	The number of bytes sent to the server by the client since the last update.
out_bytes_total	integer	The number of bytes sent by the client to the server during the session.
out_rate	float	The outgoing traffic rate, from the server to the client (out_bytes_delta / delta).
out_record_delta	integer	The number of records (logs) from the log forwarder to the DP since the last update.
out_record_total	integer	The total number of records (logs) from the log forwarder to the DP.
outbytes_delta	integer	The number of bytes sent to the server by the client since the last update.
outbytes_total	integer	The number of bytes sent by the client to the server during the session.
outpkts_delta	integer	The number of packets sent to the server by the client since the last update.
outpkts_total	integer	The number of packets sent to the server by the client during the session.

Metadata Field	Type	Description
parent_child	string	The concatenation of parent process name and child process name.
parent_proc_name	string	The parent process of the running process.
parser_err_msg	string	Parsing error message. In the case of a parsing error, the complete log is put into this field. If the **keep raw message** option is enabled in the UI, the original log will be put into this field, regardless of parsing error.
parser_raw_msg	string	If the **Raw Log Capture** feature is enabled in the sensor profile, this field indicates the raw, unparsed message. In the case of a parsing error, the entire error log.
percent_failed	float	num_fail/(num_fail+num_success)
process	object	From ECS. Information about a process. Examples of namespace fields are process.name, process.command_line, and process.parent.hash.md5. Full list of namespace fields process.command_id, process.command_line, process.executable, process.name, process.hash.md5, process.hash.sha1, process.hash.sha256, process.file_hash, process.owner, process.parent.command_line, process.parent.executable, process.parent.name, process.parent.owner, process.parent.pid, process.pid, process.parent.hash.md5, process.parent.hash.sha1, process.parent.hash.sha256, process.parent.file_hash, process.threat_indicator, and process.parent.threat_indicator
process_id	integer	The process ID that generated the log.
process_list	list_of_object	A list of process objects.
process_name	string	On an agent sensor, the name of the process that opened the connection. The process is correlated with the network connection.
process_user	string	On an agent sensor, the user who started the process that opened the connection. The user information is correlated with the network connection.
processing_time	integer	Processing time from the sensor.
proto	integer	IP header protocol type **1**—ICMP **2**—IGMP

Metadata Field	Type	Description
		6—TCP **17**—UDP
proto_name	string	Layer 4 protocol name. Can be TCP, UDP, ICMP, or IGMP.
provider_guid	string	Top-level field from Windows agent, parsed from Windows events
query_count	integer	Number of DNS queries in a tunnel.
receive_time	date	Time the event was received by the DP.
record_number	string	Top-level field from Windows agent, parsed from Windows events
registry	object	From ECS. These fields contain information about a registry. The namespace field is registry.key.
remote_ip	ip	The IP address of the remote entity involved in the event.
remote_ip_asn	integer	Autonomous System Number (ASN) responsible for the remote IP address.
remote_ip_asn_org	string	Organization name associated with the ASN for the remote iP address
remote_ip_domain_creation	date	The creation time of the domains associated with the remote IP address.
remote_ip_geo	object	Geo location information for the remote IP address.
remote_ip_geo_point	string	Geo point of the remote IP address.
remote_ip_reputation	string	Remote IP address reputation.
remote_ip_reputation_source	string	Source of the reputation data.
remote_ip_source	string	Remote IP source.
remote_ip_type	string	The type of the remote IP address.
remote_ip_username	string	The username associated with the remote IP address.
remote_ip_usersid	string	The user ID associated with the remote IP address. For Windows, security identifier (SID) is used.
remote_ip_version	string	Indicates if the remote IP address is IPv4 or IPv6.
remote_port	integer	The port of the remote entity involved in the event.
response_time	integer	Server processing time calculated by the sensor.
rule	object	The rule name. The namespace field is rule.name.
saved_query	string	For storing queries used for Threat Hunting.
scan_end	date	The security scan end time.
scan_start	date	The security scan start time.
sds_engid	string	The ID of the security sensor that generated the event.
sds_engid_name	string	The name of the security sensor that generated the event.

Metadata Field	Type	Description
severity	integer	Severity of the event. From 0–100, with a higher value indicating higher severity.
sha256	string	The SHA-256 hash value of this file.
smb_denied_count	integer	Number of times access was denied in a single SMB session.
smb_username_count	integer	Number of unique usernames used in a single SMB session.
smb_username_set	list	The set of unique usernames observed in the SMB session.
source_name	string	Top-level field from Windows agent, parsed from Windows events
srcip	ip	Source IP address of the session.
srcip_asn	integer	Autonomous System Number (ASN) responsible for the source IP address.
srcip_asn_org	string	Organization name associated with the ASN for the source iP address
srcip_assetid	string	The asset ID associated with the source IP address.
srcip_domain_creation	date	The creation time of the domains associated with the source IP address.
srcip_geo	object	Geo location information for the source IP address.
srcip_geo_point	string	Geo point of the source IP address.
srcip_geo2	string	Geo location of the earlier of two login records.
srcip_host	string	Host name or DNS name for the source IP address.
srcip_reputation	string	Reputation of the source IP address from Threat Intelligence, such as Good, Bad, Scanner, Spyware, etc.
srcip_reputation_source	string	The source of the reputation data.
srcip_sig_id	string	The signature ID concatenated with srcip.
srcip_source	string	Source IP source.
srcip_tag	string	The asset tag associated with the source IP address.
srcip_type	string	IP address type for the source IP address, such as private, multicast, or public.
srcip_username	string	The username associated with the source IP address.
srcip_usersid	string	The user ID associated with the source IP address. For Windows, security identifier (SID) is used.
srcip_version	string	Indicates if the source IP address is IPv4 or IPv6.
srcmac	string	Source MAC address.
srcport	integer	Layer 4 source port.

Metadata Field	Type	Description
stability	integer	Amount of time without change for an entity (1–100). The higher value, the more stability it has.
start_bucket_time	date	Start time of the data that caused the anomaly.
state	string	The current state of the session Established Closed HalfOpened Aborted Created Closing Expired.
suspicious_ips	list	A list of suspicious IP addresses that could do credential stuffing in a cloud service.
task	string	Top-level field from Windows agent, parsed from Windows events
tcp_rtt	integer	Round trip time for a TCP connection, which represents the network delay.
tenant_name	string	The name of the tenant.
tenantid	string	The ID of the tenant.
threat	string	The detected threat category to which the threat belongs.
threat_indicator	object	From ECS. Information about a threat indicator. The namespace fields are threat_indicator.labels, threat_indicator.sources, threat_indicator.score, and threat_indicator.file.hash.
threat_list	list_of_object	A list of threat objects.
threat_score	integer	Threat score (0–100).
time_deviation	float	Difference between two login times, in seconds.
timestamp	date	Time of an action, such as start of session, time of update, etc.
tls	object	TLS-related metadata, such as fingerprint, issuerdn, ja3, etc.
tos	integer	Type of Service value in the IP header.
total_entropy	float	Total entropy of DNS queries in a tunnel.
totalbytes	integer	Total number of bytes received and sent by client for a session.
totalpackets	integer	Total number of packets received and sent by client for a session.
travel_speed	float	Travel speed (in mph) between two login locations.

Metadata Field	Type	Description
type	string	Top-level field from Windows agent, parsed from Windows events
typical	integer	The typical value that Machine Learning calculated.
typical_range	string	Typical login time range such as 10:00am-11:00am.
unknown_users_to_login_failure	float	Ratio of unknown usernames (unknown_users_rate) to login failures (login_failure_rate) in the period.
unknown_users_rate	float	Rate of unknown login usernames per minute in the period.
url	string	The URL that is a reference to a web resource.
url_list	list	List of URLs.
url_reputation	string	Reputation of the URL.
user	object	Information about a Windows user. The namespace fields are user.domain, user.id, user.name, and user.full_name.
user_action	object	The upper-level namespace for all user action fields.
user_agemt	string	Original user agent. The namespace field is user_agent_original.
user_list	list_of_object	A list of user objects.
username	string	The user name.
user_profile	object	Used to store information for Active Directory connector.
verdict_share	boolean	Whether or not to share the record in Threat Intelligence.
vlan	integer	VLAN ID.
vuln_count	float	The number of vulnerabilities.
vuln_score	float	The overall vulnerability score.
vulnerabilities	list_of_object	List of vulnerabilities.
vulnerability	object	Vulnerability information as reported by original source.
write_by	string	Service that writes the document (mostly alerts) to Elasticsearch.
write_time	date	Time the event was written to Elasticsearch.
xdr_event	object	The XDR kill chain info of each alert, such as stage, tactic, technique.
xgb_prob	integer	DGA probability based on the XGBoost model.

© 2026 Stellar Cyber . All rights reserved.