Contributing to rme

Contents

1 Contributing to `rme` **1**

2 Style guide **1**

3 Fixing typos **1**

4 Bigger changes **2**
4.1 Pull request[1] process 2
4.2 Code style 2

5 Code of Conduct **2**

6 Additional references **2**

1 Contributing to `rme`

Contributions to these notes are very much appreciated; anything from one-character typo corrections to new chapters or rewrites. The GitHub repository for this project[2] provides a Pull Request system for submitting contributions. See https://happygitwithr.com/pr-extend for an explanation of the pull request system and the available R utility functions for working with pull requests.

2 Style guide

- Every abstract concept (definition or theorem) should have at least one concrete example immediately following it.
- More structure (headers, labels) is better.
- Make each conceptual chunk as compact as possible:
  - Decompose large, complicated, difficult concepts into smaller, simpler, and easier pieces.
  - Decompose long derivations into smaller lemmas.
  - When manipulating part of a larger expression, isolate that part in a lemma.
- Add slide breaks[3] between exercises/theorems and solutions/proofs

3 Fixing typos

This book is written using Quarto[4]. You can fix typos, spelling mistakes, or grammatical errors directly using the GitHub web interface by making changes in the corresponding *source* file. This generally means you'll need to edit a `.qmd` file.

[1] https://usethis.r-lib.org/articles/pr-functions.html#whats-a-pull-request
[2] https://github.com/Morrison-Lab/rme
[3] https://quarto.org/docs/presentations/revealjs/#creating-slides
[4] https://quarto.org/docs/books/

4 Bigger changes

If you want to make a bigger change, it's a good idea to first file an issue and make sure someone from the development team agrees that it's needed.

4.1 Pull request[5] process

- Fork the package and clone onto your computer. If you haven't done this before, we recommend using `usethis::create_from_github("Morrison-Lab/rme", fork = TRUE)`.
- Install all development dependencies with `devtools::install_dev_deps()`. Make sure you can build the book by running `quarto render` in a Terminal.
- Create a Git branch for your pull request (PR). We recommend using `usethis::pr_init("brief-description-of-change")`. Details at https://usethis.r-lib.org/articles/pr-functions.html
- Make your changes, commit to git, and then create a PR by running `usethis::pr_push()`, and following the prompts in your browser. The title of your PR should briefly describe the change. The body of your PR should contain `Fixes #issue-number`.
- Add a bullet to the top of `NEWS.md` (i.e. just below the first header). Follow the style described in https://style.tidyverse.org/news.html.

4.2 Code style

- New code should follow the tidyverse style guide[6]. You can use the styler[7] package to apply these styles, but please don't restyle code that has nothing to do with your PR.

5 Code of Conduct

Please note that the `rme` project is released with a Contributor Code of Conduct[8]. By contributing to this project you agree to abide by its terms.

6 Additional references

For a detailed discussion on contributing to this and other projects, please see the Tidyverse development contributing guide[9] and the Tidyverse code review principles[10]. This project is not part of the tidyverse, but we have borrowed their development processes.

[5] https://usethis.r-lib.org/articles/pr-functions.html#whats-a-pull-request
[6] https://style.tidyverse.org
[7] https://CRAN.R-project.org/package=styler
[8] https://contributor-covenant.org/version/2/1/CODE_OF_CONDUCT.html
[9] https://rstd.io/tidy-contrib
[10] https://code-review.tidyverse.org/