

# Decipherment as Regression

Solving Historical Substitution Ciphers by Learning Symbol Recurrence Relations

---

Nishant Kambhatla, Logan Born, Anoop Sarkar

May 2023

Findings of the Association for Computational Linguistics: EACL 2023

*Presented by Morten Munk Andersen*

## Contents

1. Why this paper? .....	3
2. Methodology .....	5
2.1 Recurrent Integer Sequences .....	6
2.2 Generative Decipherment Model .....	8
3. Results .....	13
3.1 Synthetic Ciphers .....	14
3.2 Z408 Cipher .....	15
3.3 Historical Ciphers .....	17
3.4 Monoalphabetic Ciphers .....	19
3.5 Unseen Language Ciphers .....	20
4. Contributions .....	22
5. Limitations .....	24
6. Relevance .....	26

7. Questions? .....	28
---------------------	----

# 1. Why this paper?

---

# 1. Why this paper?

## Relevancy

- Homophonic substitution ciphers

## Ranking

- Core2023 Ranking: A

## Recency

- May 2023

### Decipherment as Regression: Solving Historical Substitution Ciphers by Learning Symbol Recurrence Relations

Nishant Kambhatla Logan Born Anoop Sarkar  
School of Computing Science, Simon Fraser University  
8888 University Drive, Burnaby BC, Canada  
{nkambhat, loborn, anoop}@sfu.ca

#### Abstract

Solving substitution ciphers involves mapping sequences of cipher symbols to fluent text in a target language. This has conventionally been formulated as a search problem, to find the decipherment key using a character-level language model to constrain the search space. This work instead frames decipherment as a sequence prediction task, using a Transformer-based causal language model to learn recurrences between characters in a ciphertext. We introduce a novel technique for transcribing arbitrary substitution ciphers into a common *recurrence encoding*. By leveraging this technique, we (i) create a large synthetic dataset of homophonic ciphers using random keys, and (ii) train a decipherment model that predicts the plaintext sequence given a recurrence-encoded ciphertext. Our method achieves strong results on synthetic 1:1 and homophonic ciphers, and cracks several real historic homophonic ciphers. Our analysis shows that the model learns recurrence relations between cipher symbols and recovers decipherment keys in its self-attention.<sup>1</sup>




Figure 1: The homophonic substitution key for the *Simeone de Crema* written in Mantua in 1401 AD. The top line maps each character in the alphabet to its reversed-alphabet equivalent; each vowel is substituted by three additional symbols.

sequences (D’Ascoli et al., 2022). We rethink decipherment as a regression task that predicts a natural language plaintext by learning a recurrence relation between integer-coded ciphertext symbols.

There exist large collections of historical ciphers (see [de-crypt.org](https://de-crypt.org))<sup>2</sup>, in the form of encrypted letters and more informal communications, of which many remain undeciphered. Many of these texts employ complex *homophonic substitution ciphers*, which mask the frequencies of letters by using a larger alphabet than the underlying language. Figure 1 shows the first known homophonic cipher from 1401 AD<sup>3</sup>. Automated computational deci-

## 2. Methodology


---



## 2.1 Recurrent Integer Sequences

## Capturing first/repeated symbol occurrences

- Spaces denoted as **underscore**
- Unseen symbols denoted as **incremental integer**
- Recurring symbols denoted as represented **previous integer**
- Works for ciphers with different symbol sets






## 2.1 Recurrent Integer Sequences

## Capturing first/repeated symbol occurrences

- Spaces denoted as **underscore**
- Unseen symbols denoted as **incremental integer**
- Recurring symbols denoted as represented **previous integer**
- Works for ciphers with different symbol sets



## The authors consider this a novel approach

## 2.2 Generative Decipherment Model

**Remember:** Ciphertext is now a Recurrent Integer Sequence

**This makes every cipher comparable**

**Dataset made by authors**

- 2 million unique homophonic substitution ciphers
- Including their corresponding plaintexts
- Uses Modern English

## 2.2 Generative Decipherment Model

### CausalLM

- Reads from left to right - can only look back
- Past words affect predicted words - (sort of like autocorrect)

## 2.2 Generative Decipherment Model

### CausalLM

- Reads from left to right - can only look back
- Past words affect predicted words - (sort of like autocorrect)

$$[X^l, Y^l] = \text{FFN} \circ \text{SelfAttn}([X^{l-1}, Y^{l-1}], \text{Mask})$$

- $X^{l-1} \rightarrow$  Cipher at layer previous to  $l$
- $Y^{l-1} \rightarrow$  Text at layer previous to  $l$
- SelfAttn  $\rightarrow$  Captures positions related to previous symbols/letters
- Mask  $\rightarrow$  The attention mask used by SelfAttn
- FFN  $\rightarrow$  Result is fed to Feed-Forward Neural Network  $X$

## 2.2 Generative Decipherment Model

### CausalLM

- Reads from left to right - can only look back
- Past words affect predicted words - (sort of like autocorrect)

$$[X^l, Y^l] = \text{FFN} \circ \text{SelfAttn}([X^{l-1}, Y^{l-1}], \text{Mask})$$

- $X^{l-1} \rightarrow$  Cipher at layer previous to  $l$
- $Y^{l-1} \rightarrow$  Text at layer previous to  $l$
- SelfAttn  $\rightarrow$  Captures positions related to previous symbols/letters
- Mask  $\rightarrow$  The attention mask used by SelfAttn
- FFN  $\rightarrow$  Result is fed to Feed-Forward Neural Network  $X$

**Above produces the representation at  $[X^l, Y^l]$**

**Remember:** CausalLM only looks back!

## 2.2 Generative Decipherment Model

### Loss function

$$L^{\text{CLM}}(X, Y) = L^{\text{SRC}} + L^{\text{TGT}} = -\log P(X) - \log P(Y|X)$$

- $L^{\text{SRC}} \rightarrow$  Source loss - error predicting cipher seq
- $L^{\text{TGT}} \rightarrow$  Target loss - error predicting plaintext seq
- $-\log P(X) \rightarrow$  Probability of reproducing correct cipher symbols
- $-\log P(X|Y) \rightarrow$  Probability of predicting plaintext given cipher

## 2.2 Generative Decipherment Model

### Loss function

$$L^{\text{CLM}}(X, Y) = L^{\text{SRC}} + L^{\text{TGT}} = -\log P(X) - \log P(Y|X)$$

- $L^{\text{SRC}} \rightarrow$  Source loss - error predicting cipher seq
- $L^{\text{TGT}} \rightarrow$  Target loss - error predicting plaintext seq
- $-\log P(X) \rightarrow$  Probability of reproducing correct cipher symbols
- $-\log P(X|Y) \rightarrow$  Probability of predicting plaintext given cipher


**Low probability = high loss, and vice versa**

Probability can be seen as confidence

## 2.2 Generative Decipherment Model

### Why CausalLM?

- Predict the cipher symbols in a sequence
- Predict plaintext in the sequence
- Model learns the mappings





## 2.2 Generative Decipherment Model

### Considered models

- Seq2seq
- Target-Only CausalLM
- PrefixLM

### Why are they weaker?

- Only predicts plaintext
- Does not learn cipher symbol recurrence patterns

## 3. Results

---

## 3.1 Synthetic Ciphers

### How can we measure?

- Symbol Error Rate (SER)
- 0% = Perfect decipherment
- 100% Total gibberish

### What can we observe?

- Between 400 - 700 chars
- Three key ranges
- CausalLM outperforms the others 🎉

#keys	Model	Max Len.	
		400	700
30-45	Seq-to-Seq	72.30	fail
	PrefixLM	54.73	69.50
	CausalLM (tgt)	29.99	37.20
	CausalLM	<b>0.40</b>	<b>0.21</b>
40-65	PrefixLM	69.50	54.73
	CausalLM (tgt)	29.99	37.20
	CausalLM	<b>0.83</b>	<b>0.80</b>
30-85	PrefixLM	70.52	71.82
	CausalLM (tgt)	42.05	42.69
	CausalLM	<b>2.25</b>	<b>2.19</b>

## 3.1 Synthetic Ciphers

### How can we measure?

- Symbol Error Rate (SER)
- 0% = Perfect decipherment
- 100% Total gibberish

### What can we observe?

- Between 400 - 700 chars
- Three key ranges
- CausalLM outperforms the others 🎉

#keys	Model	Max Len.	
		400	700
30-45	Seq-to-Seq	72.30	fail
	PrefixLM	54.73	69.50
	CausalLM (tgt)	29.99	37.20
	CausalLM	<b>0.40</b>	<b>0.21</b>
40-65	PrefixLM	69.50	54.73
	CausalLM (tgt)	29.99	37.20
	CausalLM	<b>0.83</b>	<b>0.80</b>
30-85	PrefixLM	70.52	71.82
	CausalLM (tgt)	42.05	42.69
	CausalLM	<b>2.25</b>	<b>2.19</b>

**Fun observation:** seq2seq does not even converge at longer ciphers 🤖

## 3.2 Z408 Cipher

### But what about real ciphers?

- Z408 = 408 characters
- 54 symbols
- From the 1960's
- No spaces !



<https://zodiackiller.fandom.com/wiki/408-cipher>

## 3.2 Z408 Cipher

### Hill-climbing

- Keep the best candidates

### Beam search

- Keep N best candidates

Method	Search	SER (%)	Speed
LM+EM (2013)	1M restarts	11.0	–
<i>n</i> –gram LM (2013)	beam 100K	94.6	4000
	beam 1M	2.7	35000
LSTM LM (2018)	beam 100K	2.4	5600
	beam 1M	1.9	50000
Ours (greedy)	beam 1	<b>1.9</b>	1 sec
Ours (best)	beam 200	<b>1.9</b>	2 sec

## 3.2 Z408 Cipher

### Hill-climbing

- Keep the best candidates

### Beam search

- Keep N best candidates

Method	Search	SER (%)	Speed
LM+EM (2013)	1M restarts	11.0	–
<i>n</i> –gram LM (2013)	beam 100K	94.6	4000
	beam 1M	2.7	35000
LSTM LM (2018)	beam 100K	2.4	5600
	beam 1M	1.9	50000
Ours (greedy)	beam 1	<b>1.9</b>	1 sec
Ours (best)	beam 200	<b>1.9</b>	2 sec

### CausalLM 🎮

- Faster (it does not search)
- Better (even with smaller beam)

## 3.3 Historical Ciphers

### What about historical ciphers?

#### TNA\_SP106/5

- 1624, UK
- Homophonic substitution
- 171 characters
- 47 symbols to 27 letters
- Not many recurrences (3.6 avg)

#### The homophonic 40-65 key model

- They used beam size 1000
- Achieved 18% SER



## 3.3 Historical Ciphers

### What about historical ciphers?

#### TNA\_SP106/5

- 1624, UK
- Homophonic substitution
- 171 characters
- 47 symbols to 27 letters
- Not many recurrences (3.6 avg)

#### The homophonic 40-65 key model

- They used beam size 1000
- Achieved 18% SER

**Remember:** This is a hard cipher in an out-of-domain language


## 3.3 Historical Ciphers

### BnF\_fr2988\_f01

- 1524-1549, Italy
- Homophonic substitution
- 2 pages long
- 35 symbols
- More recurrences but older language

### The homophonic 30-45 key model

- Achieved 1.13% SER





## 3.4 Monoalphabetic Ciphers

### CausalLM + Rec

- Recurrence Integer Sequence

### CausalLM + Freq

- Described in another paper
- Summary:
  - encoded with frequency rank
  - unlike REC which is left to right order

### CausalLM Observations

- CausalLM
  - Weaker on short ciphers
  - Still comparable to other models!

(Near) perfect SER on >128 ciphers!

cipher length →	<128	>128
Beam + 6-gram (Nuhn et al., 2013)	22.00	0.00
Beam + LM ((Kambhatla et al., 2018))	10.89	0.00
Beam + LM + Freq. Match (ibid.)	11.32	0.00
Seq2Seq + Freq. (Aldarrab and May)	7.68	0.00
Causal LM + Freq.	10.56	0.00
Causal LM + Rec.	11.30	0.02

## 3.5 Unseen Language Ciphers

### What if we don't know the language of the cipher?

- Multilingual model
- Trained on 13 languages (Latin included)
- No language ID's during training!
- Frequency based encoding
  - Likely due to Zipfian consistency

	SER (%)
Multilingual Seq2Seq (2021)	5.47
Multilingual Causal LM (ours)	<b>4.10</b>

Results on the monoalphabetic Borg cipher in 17th century Latin

## 3.5 Unseen Language Ciphers

### What about the main model?

Zero-shot on 400 chars of Borg

- SER 45.14%
- Not too good

But in real life...

- Domain expert evaluates output
- If they correct 3 words manually:
  - SER 3.89%
  - Pretty good!

## 3.5 Unseen Language Ciphers

### What about the main model?

Zero-shot on 400 chars of Borg

- SER 45.14%
- Not too good

But in real life...

- Domain expert evaluates output
- If they correct 3 words manually:
  - SER 3.89%
  - Pretty good!

### Remember:

The main model has never seen Latin before!

## 4. Contributions

---



## 4. Contributions

### 1. The Seq2seq dataset

### 2. Novel Recurrence Integer Sequence

- Captures repetition and position
- Works for both mono- and homophonic

### 3. Analysis of REC in Transformer LM

- Faster and more accurate

### 4. Practical application of solver

- Fully automated
- Solved real historical ciphers

## 5. Limitations

---

## 5. Limitations

### Cipher Sizes

- Not superior for shorter ciphers  $< 128$  with less frequencies
- Inefficient for longer ciphers  $> 1500$

### The paper tries a lot!

- The model tries to do it all
- ... But it does it well!

### Where is the data from?

- Authors use 3 different datasets + ciphers
- Hard to keep track of which and when?

They did not compare with AZDecrypt

## 5. Limitations

### Cipher Sizes

- Not superior for shorter ciphers  $<128$  with less frequencies
- Inefficient for longer ciphers  $>1500$

### The paper tries a lot!

- The model tries to do it all
- ... But it does it well!

### Where is the data from?

- Authors use 3 different datasets + ciphers
- Hard to keep track of which and when?

They did not compare with AZDecrypt

### What happens with transpositioned ciphers like Z340? 🐱

## 6. Relevance

---

## 6. Relevance

### Does not solve modern encryption ⚠️

- They are too advanced

### Historical Value 📖

- Solve other ciphers

### Cryptanalysis advancement 🧐

- Deeper knowledge of classic ciphers

### More LM use cases 🤖

- What else can we use LMs for?

## 7. Questions?

---