

# Generierung des Eingangssingals für Barrier Bucket RF Systeme and der GSI



TECHNISCHE  
UNIVERSITÄT  
DARMSTADT

**Jonas Christ, Artem Moskalew, Maximilian Nolte  
Jens Harzheim, M.Sc.**

Projektseminar Beschleunigertechnik



Institut für Theorie  
Elektromagnetischer Felder  
Computational Electromagnetics  
Research Group at GSCE

# Outline

---

- 1** Einführung
  - Problemstellung
  - Zielsetzung
  - Gegeben
- 2** Erreichtes
  - Gerätekommunikation
  - Code
- 3** Evaluierung
  - Gerätekommunikation
  - Code
- 4** Ausblick



---

# Problemstellung

---

---

# Zielsetzung

---

---

# Gegeben

---

MLBS.py

---

# Gegeben

---

FFT.py

MLBS.py

# Gegeben

---

FFT.py

MLBS.py

getH.py

# Gegeben

---

FFT.py

MLBS.py

getH.py

computeUin.py



# Gegeben

---

FFT.py

MLBS.py

getH.py

computeUin.py


runme\_compute.py

---


## Erreichtes: das VISA-Handbuch

---


# Erreichtes: Code




## Erreichtes: Code



## Erreichtes: Code




## Erreichtes: Code




```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )
```

## Erreichtes: Code



```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )  
2 H = measure_H ( )
```


## Erreichtes: Code



```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )  
2 H = measure_H ( )  
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
```



## Erreichtes: Code



```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )  
2 H = measure_H ( )  
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
```

## Erreichtes: Code




```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )  
2 H = measure_H ( )  
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
```

## Erreichtes: Code




```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )  
2 H = measure_H ( )  
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )  
4 Uin = Uquest_ideal
```

## Erreichtes: Code




```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )  
2 H = measure_H ( )  
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )  
4 Uin = Uquest_ideal  
5 Uout_measured = measure_Uout ( Uin )
```

## Erreichtes: Code




```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )  
2 H = measure_H ( )  
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )  
4 Uin = Uquest_ideal  
5 Uout_measured = measure_Uout ( Uin )  
6 Uquest_measured = compute_Uquest ( Uout_measured , H )
```

## Erreichtes: Code




```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )
2 H = measure_H ( )
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
4 Uin = Uquest_ideal
5 Uout_measured = measure_Uout ( Uin )
6 Uquest_measured = compute_Uquest ( Uout_measured , H )
7 a = compute_a ( Uin , Uquest_measured , N )
```

## Erreichtes: Code



```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )
2 H = measure_H ( )
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
4 Uin = Uquest_ideal
5 Uout_measured = measure_Uout ( Uin )
6 Uquest_measured = compute_Uquest ( Uout_measured , H )
7 a = compute_a ( Uin , Uquest_measured , N )
8 K = compute_K ( a )
```


## Erreichtes: Code



```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )
2 H = measure_H ( )
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
4 Uin = Uquest_ideal
5 Uout_measured = measure_Uout ( Uin )
6 Uquest_measured = compute_Uquest ( Uout_measured , H )
7 a = compute_a ( Uin , Uquest_measured , N )
8 K = compute_K ( a )
```




## Erreichtes: Code




```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )
2 H = measure_H ( )
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
4 Uin = Uquest_ideal
5 Uout_measured = measure_Uout ( Uin )
6 Uquest_measured = compute_Uquest ( Uout_measured , H )
7 a = compute_a ( Uin , Uquest_measured , N )
8 K = compute_K ( a )
```

## Erreichtes: Code




```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )
2 H = measure_H ( )
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
4 Uin = Uquest_ideal
5 Uout_measured = measure_Uout ( Uin )
6 Uquest_measured = compute_Uquest ( Uout_measured , H )
7 a = compute_a ( Uin , Uquest_measured , N )
8 K = compute_K ( a )
9 Uin = compute_Uin ( Uquest_ideal , K )
```

## Erreichtes: Code



```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )
2 H = measure_H ( )
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
4 Uin = Uquest_ideal
5 Uout_measured = measure_Uout ( Uin )
6 Uquest_measured = compute_Uquest ( Uout_measured , H )
7 a = compute_a ( Uin , Uquest_measured , N )
8 K = compute_K ( a )
9 Uin = compute_Uin ( Uquest_ideal , K )
```

## Erreichtes: Code



```
1 Uout_ideal = generate_BBsignal ( fq_rep , fq_bb , vpp )
2 H = measure_H ( )
3 Uquest_ideal = compute_Uquest ( Uout_ideal , H )
4 Uin = Uquest_ideal
5 Uout_measured = measure_Uout ( Uin )
6 Uquest_measured = compute_Uquest ( Uout_measured , H )
7 a = compute_a ( Uin , Uquest_measured , N )
8 K = compute_K ( a )
9 Uin = compute_Uin ( Uquest_ideal , K )
10 Uout = measure_Uout ( Uin )
```



---

# Evaluierung: Gerätekommunikation

---



---

# Evaluierung: Python-Code für die nichtlinere Verzerrung

---

---

# Ausblick

---