

**B**

bge-reranker-base

Text Classification • baai

@cf/baai/bge-reranker-base

Different from embedding model, reranker uses question and document as input and directly output similarity instead of embedding. You can get a relevance score by inputting query and passage to the reranker. And the score can be mapped to a float value in $[0,1]$ by sigmoid function.

Model Info

Unit Pricing	\$0.0031 per M input tokens
--------------	-----------------------------

Usage

▼ Worker

TypeScript

```
export interface Env {  
  AI: Ai;  
}  
  
export default {  
  async fetch(request, env):  
    Promise<Response> {  
    const query = 'Which one is cooler?'  
    const contexts = [  
      {  
        text: 'a cyberpunk lizzard'  
      },  
      {  
        text: 'a cyberpunk cat'  
      }  
    ];  
  
    const response = await  
env.AI.run('@cf/baai/bge-reranker-base', {  
  query, contexts });  
  
    return Response.json(response);  
  },  
} satisfies ExportedHandler<Env>;
```

▼ Python

Python

```
import os
import requests

ACCOUNT_ID = "your-account-id"
AUTH_TOKEN = os.environ.get("CLOUDFLARE_AUTH_TOKEN")

response = requests.post(
    f"https://api.cloudflare.com/client/v4/accounts/{ACCOUNT_ID}/workers-ai/reranker-base",
    headers={"Authorization": f"Bearer {AUTH_TOKEN}"},
    json={
        "query": "Which one is better?",
        "contexts": [
            {"text": "a cyberpunk lizzard"},
            {"text": "a cyberpunk car"}
        ]
    }
)
result = response.json()
print(result)
```

▼ curl

```
curl
```

```
https://api.cloudflare.com/client/v4/accounts/  
reranker-base \  
-X POST \  
-H "Authorization: Bearer $CLOUDFLARE_AUTH_TOKEN" \  
-d '{ "query": "Which one is better?", "contexts": [  
{"text": "a cyberpunk cat"}] }'
```

Parameters

* indicates a required field

Input

- **query** **string** required min 1

A query you wish to perform against the provided contexts.

- **top_k** **integer** min 1

Number of returned results starting with the best score.

- **contexts** **array** required

List of provided contexts. Note that the index in this array is important, as the response will refer to it.

- **items** **object**

- **text** **string** min 1

One of the provided context content

Output

- **response** **array**

- **items** **object**

- **id** **integer**

Index of the context in the request

- **score** **number**

Score of the context under the index.

API Schemas

The following schemas are based on JSON Schema

Input

Output

```
{  
  "type": "object",  
  "properties": {  
    "query": {  
      "type": "string",  
      "minLength": 1,  
      "description": "A query you wish  
to perform against the provided contexts."  
    },  
    "top_k": {  
      "type": "integer",  
      "minimum": 1,  
      "description": "Number of returned  
results starting with the best score."  
    },  
    "contexts": {  
      "type": "array",  
      "items": {  
        "type": "object",  
        "properties": {  
          "text": {  
            "type": "string",  
            "minLength": 1,  

```

```
      "description": "One of
the provided context content"
    }
  },
  "description": "List of provided
contexts. Note that the index in this array is
important, as the response will refer to it."
}
},
"required": [
  "query",
  "contexts"
]
}
```

Was this helpful?



[Previous](#)

[← Dashboard](#)

[Next](#)

[Workers Bindings →](#)

Resources

[API](#)

[New to Cloudflare?](#)

[Directory](#)

[Sponsorships](#)

[Open Source](#)

Company

[cloudflare.com](#)

[Our team](#)

[Careers](#)

Support

[Help Center](#)

[System Status](#)

[Compliance](#)

[GDPR](#)

Tools

[Cloudflare Radar](#)

[Speed Test](#)

[Is BGP Safe Yet?](#)

[RPKI Toolkit](#)

[Certificate Transparency](#)

Community

 [X](#)

 [Discord](#)

 [YouTube](#)

 [GitHub](#)

© 2025 Cloudflare, Inc. • [Privacy Policy](#) • [Terms of Use](#)

• [Report Security Issues](#) • [Trademark](#) •  [Cookie Preferences](#)