



Directory > R2 >

R2 Data Catalog >

Connect to Iceberg engines >

Pylceberg

 Copy page



Pylceberg

Below is an example of using [Pylceberg ↗](#) to connect to R2 Data Catalog.

Prerequisites

- Sign up for a [Cloudflare account ↗](#).
- [Create an R2 bucket](#) and [enable the data catalog](#).
- [Create an R2 API token](#) with both [R2 and data catalog permissions](#).
- Install the [Pylceberg ↗](#) and [PyArrow ↗](#) libraries.

Example usage

Python

```
import pyarrow as pa

from pyiceberg.catalog.rest import RestCatalog
from pyiceberg.exceptions import
NamespaceAlreadyExistsError

# Define catalog connection details (replace
variables)
WAREHOUSE = "<WAREHOUSE>"
TOKEN = "<TOKEN>"
CATALOG_URI = "<CATALOG_URI>"

# Connect to R2 Data Catalog
catalog = RestCatalog(
    name="my_catalog",
    warehouse=WAREHOUSE,
    uri=CATALOG_URI,
    token=TOKEN,
)

# Create default namespace
catalog.create_namespace("default")

# Create simple PyArrow table
df = pa.table({
```

```
"id": [1, 2, 3],  
"name": ["Alice", "Bob", "Charlie"],  
})
```

Create an Iceberg table

```
test_table = ("default", "my_table")  
table = catalog.create_table(  
    test_table,  
    schema=df.schema,  
)
```

Was this helpful?



Previous

← DuckDB

Next

Snowflake →

Last updated: Apr 9, 2025

Resources

[API](#)

Support

[Help Center](#)

[New to Cloudflare?](#)[Directory](#)[Sponsorships](#)[Open Source](#)

Company

[cloudflare.com](#)[Our team](#)[Careers](#)[System Status](#)[Compliance](#)[GDPR](#)

Tools

[Cloudflare Radar](#)[Speed Test](#)[Is BGP Safe Yet?](#)[RPKI Toolkit](#)[Certificate Transparency](#)

Community

[!\[\]\(111c5272ee3f91361f0d2e3665dd6ad0_img.jpg\) X](#)[!\[\]\(6befd466863f06afb75445d91429f055_img.jpg\) Discord](#)[!\[\]\(13163d77073735089069a7603de98433_img.jpg\) YouTube](#)[!\[\]\(2cf6801d0ea3db56ed897b0c35d9ff86_img.jpg\) GitHub](#)

© 2025 Cloudflare, Inc. • [Privacy Policy](#) • [Terms of Use](#)

• [Report Security Issues](#) • [Trademark](#) •  [Cookie Preferences](#)

