

# AMRAS Build Manual




Figure 1 Screenshot from Autodesk Fusion 360

## Table of Contents

Table of Contents .....	1
Introduction.....	3
Parts List .....	4
Assembly .....	5
Software 1 .....	5
Installing Raspberry Pi OS.....	5
Installing the necessary python packages .....	5
Configuring the Raspberry Pi.....	5
Hardware .....	6
Dry Running .....	6

Crafting the Projectiles .....	7
Glueing Magnets .....	7
Installing the Camera.....	8
Preparing and installing the trafos .....	8
Mounting the Raspberry Pi.....	10
Adding the arms .....	10
Wiring the Base Mount .....	11
Software 2 .....	14
Running AMRAS.....	14
Command Line Arguments.....	14

## Introduction

AMRAS is the abbreviation for the German long form “Anti-Mitbewohner-Raketen-Abwehr-System” which translates to Anti-Roommate-Rocket-Defence-System.

It uses a combination of a Raspberry Pi, a camera, some servos, trafos and rubbing alcohol to propel rockets into anyone’s face who dares to enter its vicinity

This guide will show you how to build and start it, have fun!

I got inspired when reddit flushed [this video](#) onto my frontpage and I thought “that’s kinda cool, but I have a 3D printer and a Raspberry Pi, I could do that better”.

My code is based on Adrian Rosebrock’s [tutorial](#) who used a similar setup to track faces. While he used a PID controller for moving the servos, I had to fall back to a simpler movement, but this will hopefully soon be fixed.

Also thank you to Florian Geißegger BSc, my roommate who ironically helped me with the soldering and had some general input.

## Parts List

These are not affiliate links, just the parts I used. It should also work with slightly different hardware, but then you would need to adapt the 3D models for custom mounting holes.

- A Raspberry Pi 3B (a newer version should also work, but this is what I have tested with)
- [Power Supply](#)
- [Camera](#)
- [Servo Controller](#)
- 4x [Transformer/Spark generator](#)
- 2x [Servo](#)
- [4-Band Relais](#)
- Some [Cables](#)
- 3x [Ball Bearing](#)
- 4x [Mini Magnets](#) for keeping the lid shut
- [Syringes](#) to craft rockets out of
- 3x [Switches](#)
- Micro USB Cable to provide power for the Raspberry Pi (or USB-C if using a newer model)
- SD Card with minimum 8GB for the operating system
- Bunch of Screws (I used Wood Screws)
  - Raspi: 4x 2,0x10mm
  - Kamera: 4x 2,0x10mm
  - Main Body Fillings: 24x 2,9x13mm
  - Arms: 4x 2,9x13mm
  - Servo Shield: 4x 2,0x10mm
  - Relais: 1x 2,0x10mm
- All printed 3D parts

## Assembly

### Software 1

#### Installing Raspberry Pi OS

Install Raspberry Pi OS on the SD card and boot your Raspberry Pi.

#### Installing the necessary python packages

Open the terminal on your raspberry pi and enter following commands:

```
sudo pip3 install opencv-python
```

```
sudo pip3 install smbus
```

```
sudo pip3 install imutils
```

```
sudo pip3 install "camera[array]"
```

```
sudo pip3 install adafruit_servokit
```

```
sudo pip3 install adafruit_motor
```

#### Configuring the Raspberry Pi

Enter '`sudo raspi-config`' to open the Raspberry Pi Software Configuration Tool, go to 'Advanced' and enable Camera and I2C (and SSH, if you want to control AMRAS remotely)




Figure 2 Raspberry Pi Software Configuration Tool

## Hardware

### Dry Running

I recommend connecting all parts according to the circuit diagram first, just so you don't end up having any missing/broken parts which will need to be swapped. (This can be quite tedious, trust me)




Figure 3 Circuit Diagram




Figure 4 This is just ~90% correct, I forgot to take a new picture after making some adjustments

After making sure everything is connected properly, run `test_servos.py` to check functionality.

Try not to move the servos afterwards, as this would move the home/default position of AMRAS.



### Crafting the Projectiles

Use the rocket fin template provided with the other files to cut fins and the tip out of rubber or similar. Cut off the tip of the syringes and glue the hole shut. Glue on the parts to create the projectiles.



*Figure 5 The finished projectiles*

To shoot them, you will need to put in a drop of rubbing alcohol and put them into their “missile bays”. The evaporated alcohol will propel them.

### Glueing Magnets


Start by glueing the magnets for the lid in place, making sure to have the proper polarity.



*Figure 6 Lid and Main Body with the Magnets*

### Installing the Camera


Screw in the Camera, the ribbon cable should fit into the recess below it.



*Figure 7 The Camera screwed in place*

### Preparing and installing the trafos

Poke two holes through the end pieces of the syringes and passthrough the output cables of the trafos through both the mount and the syringe end piece. The endpiece needs to be cut off to be slotted into the cross-holes.



*Figure 8 Installation of trafo, syringe endpiece and mount*


After making sure you have enough cable length to mount the trafos in the main body, glue the cables in place. Also the two output cables should almost touch, to generate an arc for igniting the evaporated alcohol.






*Figure 9 Checking the cable length*

The input cables of the trafos will need to be extended for about 30cm, to be able to reach through the arms, I also recommend marking them by colour, to be able to differentiate them later.



*Figure 10 Cable extensions*



*Figure 11 Colour-coding*

Now it is time to mount all the trafos and servo Y, while also putting the cables in the right places.

The slot for the connectors between servo and arm you probably need to slightly trim the plastic, I didn't get the perfect form.




Figure 12 Main Body all parts installed

### Mounting the Raspberry Pi

Screw the Raspberry Pi into the provided space on the lid, making sure to pay attention to the orientation.




Figure 13 The mounted Raspberry Pi

Plug in the cables and close the lid for now.

### Adding the arms

Put the ball bearings into place and add the arms, while passing the cables through.






*Figure 14 Arms and ball bearings added*

### Wiring the Base Mount

This is by far the most tedious task, fyi.


Start by feeding all the cables into the base mount and screwing base mount and the arms together.

Then tuck away all the cables, which will go to the relays, and install the servo controller and the adapter for the power supply.




*Figure 15 Servo Controller installed*

Next install the relais and make sure to connect all the wires which will need to be connected. It is a very tight fit, you will need to bend the pins down slightly, to be able to shove the relais into its place.



*Figure 16 Relais installed*

Solder the switches, to allow the three different stages (Raspberry Pi, Relais and Servos, Trafos) to be turned on separately.



*Figure 17 The switches wired and soldered*


Put in the power panel, glueing is optional, but it should also hold up without.



*Figure 18 Power Panel in place*



Lastly put in Servo X and connect all the remaining cables. Tuck everything away so it will not interfere with the ball bearing in the base. Again the connector between servo and base will need to be trimmed slightly.



*Figure 19 Servo X installed*

After putting the remaining ball bearing onto the base you can slot in the finished construction and plug the cable in, you are finished building AMRAS.



*Figure 20 Finished AMRAS*



## Software 2

### Running AMRAS

If everything is connected properly, it should now be as easy as running `init_amras.py`.

For calibrating I recommend plugging in the Raspberry Pi into a monitor with mouse and keyboard, afterwards it is easily possible to just run it using SSH.

You can alter the `mid_offset` (line 24 in `init_amras.py`) variable for calibration in case the camera is not mounted perfectly flush/centered.

Also, you might want to play around bit with the translation multiplier (line 22), but I decided it is good enough for me, also getting the PID controller to work is the goal anyways.

### Command Line Arguments

It is possible to provide some arguments when running the program, to change the console output, the movement implementation...

Arg	Type	Required	Default	Description
-c, --cascade	String	True	-	Path to the haar cascade
-a, --armed	Bool	False	False	Option to arm the turret
-p, --pid	Bool	False	False	Option to use PID over more basic movement (currently not working)
-v, --verbose	Bool	False	False	Option to show console output
-i, --image	Bool	False	False	Option to draw image

### Examples:

```
python3 init_amras.py -c frontalface.xml -a True
```

Starts AMRAS without showing any output, tracking faces, and shooting when on target.

```
python3 init_amras.py -c ball.xml -i True -v True
```

Starts AMRAS while showing various values in the console, also enables camera feed and will track balls, recommended for calibrating the offset.