



By: Mahmoud Abdelaziz

REACT JS



CONTENT

- JSX
- jsx syntax limitations
- Class vs Fn. Component
- State & Props & Children Props
- Life Cycle Methods
- Events
- Form
- Routing
- Styling
- Pure Components
- React hooks
- Context API
- React.Lazy
- Lifting State up
- uuid , conditional
Render
- Call Api





DAY 1


- Introduction
 - Framework Vs Library
 - Tools Behind
 - Why React
 - MPA Vs SPA
- How React Engine Works
- Create React Project
- Components
 - Class Comp
 - Function Comp
 - State And Props




Agenda




Framework vs Library




Framework vs Library



Framework







React.js was created by [Jordan Walke](#), a software engineer at Facebook.

He developed React in [2011](#).



React was first used in Facebook's news feed and [2012](#) on Instagram before being open-sourced in [2013](#). Since then, it has grown to become one of the most popular libraries for building web applications.





SP





MP





How React Works



How React Works



How React Works



- Reconciliation Process
- Diffing Algorithm
- Fiber Engine

First Rule 🖐️ "Don't Mutate"


Shallow comparison $O(n)$ ✓

Deep comparison $O(n)^3$



Diffing rules

1. Different Elements Same Position




Diffing rules

2. Same Elements Same Position


```
<button className="blue" />
```



```
<button className="red" />
```



Stay same
State Preserved



Component - Component instance - React Element

Component 🤔

A Component is a reusable function or class that defines how a part of the UI should look and behave.

Component Instance

A Component Instance is a specific execution of a component with its own state, props, and lifecycle.

```
<User></User>
```

React Element (VD)

A React Element is a plain JavaScript object that describes what should appear on the U

```
function User(){
  return(
    <>
      <div className="content">
        <h1>this is a user component</h1>
        <span>hello</span>
      </div>
    </>
  )
}
export default User;
```



```
React.createElement(
  React.Fragment,
  null,
  React.createElement(
    "div",
    { className: "content" },
    React.createElement(
      "h1",
      null,
      "this is a user component"
    ),
    React.createElement(
      "span",
      null,
      "hello"
    )
  )
);
```




```
{
  $$typeof: Symbol(react.transitional.element),
  key: null,
  props: {},
  type: function User() {},
  _owner: {tag: 0, key: null, stateNode: null, elementType: function User() {}},
  _store: {validated: 0},
  ref: null,
  _debugInfo: null,
  _debugStack: "Error: react-stack-top-frame",
  _debugTask: {
    run: function () {}
  }
}
```




Component - Component instance - React Element




From Component To DOM



Re-Render With Reconciliation Process




Re-Render With Reconciliation Process




Task: React js

Show



Tools Behind


With Create-React-App Library



With Vite 




With Create-React-App Library




With Vite 



With Create-React-App Library



With Vite 



Create React App

Step 1: Add a DOM Container to the HTML

First, open the HTML page you want to edit. Add an empty `<div>` tag to mark the spot where you want to display something with React. For example:

```
<!-- ... existing HTML ... -->

<div id="like_button_container"></div>

<!-- ... existing HTML ... -->
```

Step 2: Add the Script Tags

Next, add three `<script>` tags to the HTML page right before the closing `</body>` tag:

```
<!-- ... other HTML ... -->

<!-- Load React. -->
<!-- Note: when deploying, replace "development.js" with "production.min.js". -->
<script src="https://unpkg.com/react@17/umd/react.development.js" crossorigin></script>
<script src="https://unpkg.com/react-dom@17/umd/react-dom.development.js" crossorigin></script>

<!-- Load our React component. -->
<script src="like_button.js"></script>

</body>
```

```
// ... the starter code you pasted ...

const domContainer = document.querySelector('#like_button_container');
ReactDOM.render(e(LikeButton), domContainer);
```

React From Scratch

Create-React-App Library





```
npx create-react-app my-app
cd my-app
npm start
```



```
npm create vite@latest my-app
cd my-app
npm run dev
```



State and Props




DAY 2


- Children Props
- Component Life Cycle Methods
- Events
- Call API
 - Fetch & Axios
- Dealing With Images
 - Public Folder
 - ✗ Images are not included in the build process (no optimizations)
 - ✗ You must manually ensure files exist—no Webpack/Vite validation.
 - src Folder
 - ✔ Webpack/Vite optimizes and hashes images (better Compression + Caching)
 - ✔ Ensures images exist at compile time Webpack/Vite validation



Component Life Cycle



Component Life Cycle




Trigger Update and Useless Rerender

Trigger Update

- state
- props
- ForceUpdate
- parent and child relationship


cause useless rerender



cause useless rerender

Avoid Useless Rerender

- `shouldComponentUpdate(nextProps, nextState)`
- `PureComponent`





DAY 3

- Props Changes & Send data from child to parent
- Form
- Components Interaction
- Styling
 - Bootstrap
 - css modules



Components Interaction





THANK YOU