

Nafath Application Service

Product Integration Guide

Main Product Page — Integration Reference · Elm · Rabet Platform

1. Abbreviations

Abbreviation	Meaning
Nafath	Digital identity verification and authentication application by Elm.
MFA	Multi-Factor Authentication
JWT	JSON Web Token
JWK	JSON Web Key
RSA-SHA256	Cryptographic algorithm used to sign Nafath JWT tokens.
UUID	Universally Unique Identifier (used for requestId).
OTP	One-Time Password
NIN	National Identification Number
SP	Service Provider (Client consuming Nafath APIs).
IdP	Identity Provider
MOI	Ministry of Interior
SPL	Saudi Post (now SPL) — National Address authority.
HOH	Head of Household
THKI	User device verification attributes.
IP	Internet Protocol address
API	Application Programming Interface
HTTP	Hypertext Transfer Protocol
JSON	JavaScript Object Notation
NSI	Nafath System Interface (API identifiers in this document)

2. Introduction

Nafath Application enables users to verify and authenticate their digital identities safely and reliably. It provides access to public and private entities' applications and platforms through three main services:

- Requests acceptance
- Activation via Biometrics
- Verification via Biometrics

This Integration Guide is intended for technical teams and organizations engaging with the Nafath service through Elm's Rabet platform. The document consolidates all technical prerequisites, authentication setup, API specifications, callback handling, error codes and reference data required to successfully integrate with Nafath.

Target Users

- Service Providers (Clients) — any public or private entity that requires verifying or authenticating an end-user identity (e.g., banks, telecom, government portals, fintech).
- Nafath Integration Providers — integrators developing on behalf of Service Providers.
- Technical roles: developers, system integrators, security architects, QA engineers, technical project managers.

Prerequisites

- Service Provider must be registered with the Nafath service through the Rabet platform.
- Valid APP-ID and APP-KEY values issued after registration on Rabet.
- A client-hosted Callback API endpoint to receive request status and user information. The callback must be hosted inside Saudi Arabia.
- Ability to consume REST/JSON over secure HTTPS.
- Ability to validate JWT signed with RSA-SHA256 using Elm's JWK or public certificate.
- Outbound and inbound connectivity allowed to the Nafath IPs: 195.170.180.7 and 195.170.180.6.
- End-user must hold a valid National ID, Iqama, Visa or Border number registered in the Nafath ecosystem.
- End-user must have the Nafath mobile application installed and activated on their device.

3. Common Scenario

Authentication Setup, Request Headers, JWT & JWK Verification

Definition

Nafath uses an asynchronous, app-push authentication model. Service Providers (SPs) call Nafath REST APIs over HTTPS and authenticate every request with two static credentials (APP-ID and APP-KEY) plus the end-user / client IP in the X-Forwarded-For header. The request/response payloads are JSON; the asynchronous callback that delivers the user identity is carried in a JSON Web Token (JWT) signed by Elm using RSA-SHA256. Service Providers must verify the JWT signature with Elm's JSON Web Key (JWK) or public certificate before trusting the user attributes.

This Common Scenario page consolidates the cross-cutting integration requirements — headers, environments, JWT, JWK retrieval, the deep link to open the Nafath app, error codes and the transaction-lifetime rules — that apply to every business scenario built on top of Nafath.

Related Business Rules

ID	Description
1	The Service Provider must be registered on the Rabet platform before consuming any Nafath API. APP-ID and APP-KEY are obtained after registration.
2	APP-ID and APP-KEY must be sent on every request. APP-KEY must never be exposed on a client device or in browser JavaScript — Nafath APIs are server-to-server only.
3	The X-Forwarded-For header is mandatory and must carry both the end-user IP and the client/server IP, separated by a comma (e.g., 10.1.8.13,9.8.7.6) without brackets.
4	The callback URL hosted by the Service Provider must reside inside the Kingdom of Saudi Arabia.
5	All callback traffic from Nafath originates from IPs 195.170.180.7 and 195.170.180.6. These must be allow-listed on the SP firewall.
6	All callbacks deliver a JWT signed with RSA-SHA256. The SP must validate the JWT signature using Elm's JWK (kid match) or Elm's public certificate before processing user data.
7	The requestId supplied on Send Request must be a UUID and must be unique per transaction. It is echoed back on the callback so the SP can correlate.
8	The transId returned by Send Request is the Nafath-side transaction identifier and must be used when polling Retrieve Request Status.
9	The random number returned by Send Request must be displayed to the end-user so they can match the same number on the Nafath app screen.
10	The user can only act inside the Decision Interval (first 180 s of a 200 s transaction lifetime). After 180 s an inactive transaction transitions to EXPIRED; after 200 s any status call returns error 400-034-051.
11	Only one active transaction is permitted per National ID at a time. Creating a second request while another is active returns error 400-034-050.
12	The 'local' query parameter ('ar' or 'en') controls the language of strings returned inside the JWT. Default is 'ar' when omitted.
13	The SP must implement an idempotent and authenticated callback endpoint, and must respond quickly (HTTP 2xx) before performing heavy downstream work.

Sequence / Activity Diagram

Figure 1: Retrieving the JWK. · Figure 2: Nafath authentication process. [Diagrams to be inserted.]

The Service Provider obtains APP-ID/APP-KEY from Rabet, downloads Elm's JWK once (or on rotation), then on every business flow it: (1) sends an authentication request to Nafath, (2) shows the returned random number to the end-user, (3) optionally polls Retrieve Request Status, and (4) receives the final signed JWT on its callback endpoint. The SP verifies the JWT signature against the JWK before consuming the user attributes.

Related System Interfaces

NSI001 : Retrieve JWK

Returns Elm's JSON Web Key set used to verify the signature of every JWT delivered to the callback endpoint. The 'kid' value inside the JWT header must match the 'kid' of one of the keys returned by this API.

ID Number	NSI001
Name	Retrieve JWK
Description	Returns Elm's JSON Web Key set used to verify Nafath JWT signatures.
URL	{{nafathBaseUrl}}/api/v1/mfa/jwk nafathBaseUrl -> from Environments section
Method	GET
Pre-requisites	Valid APP-ID and APP-KEY registered on Rabet.

Inputs — Headers

Name	Type	Required	Description	Example
APP-ID	String	Yes	Consumer API access app id (issued via Rabet).	your-app-id
APP-KEY	String	Yes	Consumer API access app key (issued via Rabet).	your-app-key
X-Forwarded-For	String	Yes	End-user IP, client IP separated by comma.	10.1.8.13,9.8.7.6
Content-Type	String	Yes	Response media type.	application/json

Inputs — Body

No request body.

Output (HTTP 200)

Name	Type	Description
keys	Array	Array of JWK objects.
keys[].kty	String	Key type (e.g., RSA).
keys[].e	String	RSA exponent (e.g., AQAB).
keys[].use	String	Intended use (e.g., 'sig' for signature).
keys[].kid	String	Key ID — must match 'kid' in the JWT header.
keys[].alg	String	Algorithm (e.g., RS256).
keys[].n	String	RSA public-key modulus (Base64URL).

Sample Response

```
{
  "keys": [
    {
      "kty": "RSA",
      "e": "AQAB",
      "use": "sig",
      "kid": "jwk-1234",
      "alg": "RS256",
      "n": "4eOdMN7k2CkCOIwpo9_BZF9-fbLnflLRfRtMzzxUf9R..."
    }
  ]
}
```

Reference Data

Error Handling & Validation

HTTP Code Error code	Response Description	Reason
403	Authentication failed	Invalid APP-KEY or APP-ID.
404	No Mapping Rule matched	Invalid URL.
500	Internal server error	The service is not running properly.
503	Service unavailable	System down.
422-031-046	Invalid Request	Invalid Data has been sent.
400-034-050	Invalid Request, There Is Active Trx	A new request was created while an active request still exists for the same Id.
400-034-053	Invalid Request, Trx Not Exist	Status was requested with a wrong transId.
400-034-051	Invalid Request, Trx Expired	Status was requested with an expired transId (past 200 s).

Error Body Example

```
{
  "status": "422",
  "timestamp": null,
  "message": "Invalid Request",
  "code": "422-031-046",
  "reference": 1613
}
```

Environments

Name	Testing	Pre-Production	Production
Nafath Base URL	https://rabet-nafath.api.elm.sa/nafath-sandbox	https://rabet-nafath.api.elm.sa/stg/	https://rabet-nafath.api.elm.sa/
Source IPs (callback)	195.170.180.7, 195.170.180.6	195.170.180.7, 195.170.180.6	195.170.180.7, 195.170.180.6
APP-ID	From Rabet sandbox registration	From Rabet staging registration	From Rabet production registration
APP-KEY	From Rabet sandbox registration	From Rabet staging registration	From Rabet production registration

FAQs

Question	Answer
Q1: What is Nafath?	Nafath is Elm's national digital identity verification and authentication application. It lets Service Providers verify and authenticate end-users via the Nafath mobile app using three services: requests acceptance, activation via biometrics, and verification via biometrics.
Q2: How does the SP authenticate to the Nafath APIs?	Every request must carry APP-ID and APP-KEY headers (issued via Rabet) plus an X-Forwarded-For header with the end-user IP and the client IP separated by a comma.
Q3: Why do I need to retrieve the JWK?	The callback delivers a JWT signed by Elm with RSA-SHA256. The SP must verify the signature using the JWK whose 'kid' matches the JWT header 'kid'. Without verification the JWT contents must not be trusted.
Q4: How often should I refresh the JWK?	Cache the JWK locally and refresh on a schedule (e.g., daily) or whenever JWT signature verification fails with an unknown 'kid'. Elm may rotate keys; using JWK 'kid' lookup makes rotation transparent.

Question	Answer
Q5: Can the JWT be verified without calling the JWK API?	Yes — Elm also provides a public certificate that can be used to verify the JWT signature. The JWK approach is the recommended pattern because it supports automatic key rotation.
Q6: How long is a Nafath transaction alive?	The total transaction lifetime is 200 seconds. The user can act only inside the Decision Interval (first 180 s). Between 180 s and 200 s an unanswered transaction reports EXPIRED; after 200 s any status call returns error 400-034-051.
Q7: What happens if I create two requests for the same user?	The second request fails with error 400-034-050 (Invalid Request, There Is Active Trx) until the first one is COMPLETED, REJECTED or EXPIRED.
Q8: What does the 'random' value returned by Send Request mean?	It is a short number that must be displayed to the end-user on the SP's screen. The same number is shown in the Nafath app so the user can confirm they are accepting the correct request.
Q9: Does Nafath support Arabic and English?	Yes. Pass local=ar or local=en on the Send Request query string. The JWT user attributes returned on the callback are localized accordingly. Default is 'ar' if not specified.
Q10: Where should the callback be hosted?	Inside Saudi Arabia. Inbound traffic comes from 195.170.180.7 and 195.170.180.6 — allow-list both IPs on your firewall.
Q11: Which HTTP codes signal an authentication problem?	HTTP 403 (Authentication failed) means an invalid APP-ID or APP-KEY. HTTP 404 means an invalid URL. 500/503 signal a Nafath-side outage.
Q12: Can I open the Nafath app from my service-provider mobile app?	Yes. Use the deep link nafath://home on iOS and nic://nafath on Android to redirect the end-user from the SP app to the Nafath app.
Q13: How do I match the JWT to my original request?	Compare the requestId echoed on the callback with the UUID you generated on Send Request. The transId returned by Send Request is also embedded in the JWT body.
Q14: Are there rate limits?	Nafath enforces standard Elm-platform rate limits; sustained load above the agreed throughput should be coordinated with the Nafath PM.
Q15: What is the difference between '...WithBio' and '...WithoutBio' service keys?	The non-WithoutBio service keys (e.g., 'OpenBankAccount') require Verification via Biometrics and have a 180 s lifetime; the 'WithoutBio' variants (e.g., 'OpenAccountWithoutBio') accept simple in-app acceptance and have a 60 s lifetime.

Others — Deep Links

Platform	Deep Link URL
iOS	nafath://home
Android	nic://nafath

Others — Transaction Lifetime

Successful action: if the end-user accepts or rejects inside the first 180 s, the status returns 'COMPLETED' or 'REJECTED' until the 200 s window ends.

Unsuccessful / no action: status returns 'WAITING' until 180 s, then 'EXPIRED' until 200 s. After 200 s any retrieval returns error 400-034-051.

4. Business Scenarios

Scenario 1 — Nafath User Authentication Flow (Send Request → Status → Callback)

Definition

The main function of this business scenario is to authenticate a Nafath end-user inside a Service-Provider (SP) journey. The flow consists of three mandatory APIs plus one asynchronous client-hosted callback:

- Send Request (NSI002) — the SP creates a new Nafath authentication transaction for a given National ID / Iqama / Visa / Border number.
- Retrieve Request Status (NSI003) — optional polling to know whether the user has accepted, rejected, or let the transaction expire.
- Receive Callback (NSI004) — the SP-hosted endpoint that receives the final signed JWT containing the verified user attributes once the user acts in the Nafath app.

The end-user is identified by their National ID and must take action through the Nafath mobile application within the transaction lifetime (200 s total, with a 180 s Decision Interval). The 'service' field passed on Send Request determines whether biometric verification is required (e.g., 'OpenBankAccount' = with biometrics, 'OpenAccountWithoutBio' = without biometrics).

Related Business Rules

ID	Description
1	The SP must already hold a valid APP-ID and APP-KEY issued through the Rabet platform. APP-KEY must never be exposed in client-side code.
2	Every API call must carry APP-ID, APP-KEY and X-Forwarded-For (end-user IP, client IP). Content-Type is application/json.
3	requestId on Send Request must be a UUID generated by the SP and unique per transaction; it is echoed back on the callback for correlation.
4	Only one active transaction is allowed per National ID. Creating a second one while another is active returns error 400-034-050.
5	The 'random' number returned by Send Request must be displayed to the end-user on the SP screen so they can match it with the number shown in the Nafath app.
6	Service keys ending with 'WithoutBio' have a 60 s transaction lifetime and do not require biometric verification. All other service keys have a 180 s lifetime and require biometrics.
7	Total transaction lifetime is 200 s. The user can only act inside the first 180 s (Decision Interval). After 180 s an inactive transaction reports EXPIRED. After 200 s any status call returns error 400-034-051.
8	Retrieve Request Status returns one of: WAITING, COMPLETED, REJECTED, EXPIRED. The SP should poll judiciously (e.g., every 3-5 s) and also rely on the callback as the source of truth.
9	The callback URL must be hosted inside the Kingdom of Saudi Arabia and reachable from Nafath source IPs 195.170.180.7 and 195.170.180.6.
10	On callback, the SP must verify the JWT signature using Elm's JWK (see Common Scenario, NSI001) or Elm's public certificate before consuming any user attribute.
11	The JWT 'aud' must equal the SP name registered on Rabet, and the JWT 'transId' must match the transId originally returned by Send Request.
12	When the JWT 'status' is COMPLETED, the SP must use the user attributes from the JWT (refer to Appendix tables for the structure based on identity type).
13	When the JWT 'status' is REJECTED, the SP must terminate the flow and inform the user that the request was rejected from the Nafath app.
14	If the end-user is a minor and the service is account opening, the Minor Workflow applies: the request must originate from the minor's Nafath, then from the guardian (Head of Household) — see 'Others — Minor Workflow'.

ID	Description
15	The callback handler should respond with HTTP 2xx as quickly as possible and process the payload asynchronously to avoid timeouts on the Nafath side.

Sequence / Activity Diagram

Figure 1: Nafath authentication process. [Diagram to be inserted.]

(1) SP calls Send Request with the user's National ID and the chosen service key; Nafath returns transId + random. (2) SP shows the random number to the user and the user opens the Nafath app via deep link. (3) The Nafath app presents the request; the user accepts (with or without biometrics) or rejects. (4) Optionally the SP polls Retrieve Request Status. (5) Nafath posts the signed JWT to the SP callback. (6) SP verifies the JWT signature using the JWK from NSI001, then consumes the user attributes.

Related System Interfaces

NSI002 : Send Request

Creates a new Nafath authentication request for the targeted user.

ID Number	NSI002
Name	Send Request
Description	Creates a new request within the Nafath app for the targeted user. Returns the transaction ID and a random number to be shown to the user.
URL	{{nafathBaseUrl}}/api/v1/mfa/request?local={ar en}&requestId={UUID} nafathBaseUrl -> from Environments section (Common Scenario)
Method	POST
Pre-requisites	Valid APP-ID and APP-KEY. End-user has Nafath app installed and registered.

Inputs — Headers

Name	Type	Required	Description
APP-ID	String	Yes	Consumer API access app id.
APP-KEY	String	Yes	Consumer API access app key.
X-Forwarded-For	String	Yes	End-user IP, client IP separated by comma.
Content-Type	String	Yes	Request media type (application/json).

Inputs — Query Parameters

Name	Type	Required	Description
local	String	Yes	'ar' or 'en'. Default 'ar' if omitted. Controls the language of the JWT user attributes.
requestId	String (UUID)	Yes	Unique identifier generated by the client used to correlate the callback to the original request.

Inputs — Body

Name	Type	Required	Description
nationalId	String	Yes	Targeted user's National ID, Iqama, Visa or Border number.
service	String	Yes	Service Type key (see Service Types table in 'Others').

Sample Request Body

```
{
  "nationalId": "10xxxxxxxx",
  "service": "Login"
}
```

Output (HTTP 200)

Name	Type	Description
transId	String	Transaction Identifier returned by Nafath.
random	String	Random number that the SP must display to the end-user.

Sample Response

```
{
  "transId": "3a4a3b26-3b8f-4d4f-90fe-d1a4ef834e8d",
  "random": "80"
}
```

NSI003 : Retrieve Request Status

Polls the status of an existing Nafath transaction.

ID Number	NSI003
Name	Retrieve Request Status
Description	Returns the current status of a Nafath transaction: WAITING, COMPLETED, REJECTED or EXPIRED.
URL	{{nafathBaseUrl}}/api/v1/mfa/request/status
Method	POST
Pre-requisites	Valid transId and random returned by Send Request (NSI002).

Inputs — Headers

Name	Type	Required	Description
APP-ID	String	Yes	Consumer API access app id.
APP-KEY	String	Yes	Consumer API access app key.
X-Forwarded-For	String	Yes	End-user IP, client IP.
Content-Type	String	Yes	application/json

Inputs — Body

Name	Type	Required	Description
nationalId	String	Yes	Targeted user identifier supplied originally on Send Request.
transId	String	Yes	Transaction ID returned by Send Request.
random	String	Yes	Random number returned by Send Request.

Sample Request Body

```
{
  "nationalId": "10xxxxxxxx",
  "transId": "33833c25-8b98-4afe-b766-29041e2037af",
  "random": "80"
}
```

Output (HTTP 200)

Name	Description
status	WAITING COMPLETED REJECTED EXPIRED.

Status Values

Status	Description
WAITING	Request still in progress; the user has not yet taken action.
EXPIRED	Request timed out (no action within the 180 s Decision Interval).
REJECTED	Request has been rejected by the user inside the Nafath app.
COMPLETED	Request was accepted by an authenticated end-user.

NSI004 : Receive Callback (SP-hosted)

Callback endpoint implemented and hosted by the Service Provider. Nafath calls it once the end-user accepts or rejects the request, delivering a signed JWT with the user attributes (on COMPLETED) and the final status.

ID Number	NSI004
Name	Receive Callback
Description	Client-side endpoint that receives the signed JWT containing the request status and the verified user information. Must be hosted inside Saudi Arabia.
URL	POST https://{CLIENT_CALLBACK_URI}
Method	POST
Pre-requisites	Endpoint registered with Elm; allow-list Nafath source IPs 195.170.180.7 and 195.170.180.6; JWK retrieved via NSI001 for signature verification.

Inputs — Headers

Name	Type	Required	Description
Authorization	String	No	Optional bearer token based on the SP's own security requirements.
Content-Type	String	Yes	application/json

Inputs — Body

Name	Type	Required	Description
token	String (JWT)	Yes	JWT signed by Elm containing request status and user information. Must be verified using the JWK (NSI001) or Elm's public certificate before processing.
transId	String	Yes	Transaction ID created on Send Request.
requestId	String	Yes	Request UUID originally generated by the SP on Send Request.

Sample Callback Body

```
{
  "token": "eyJraWQiOiJqd2stMTIzNCIsImFsZyI6IlJTMjU2In0...",
  "transId": "3a4a3b26-3b8f-4d4f-90fe-d1a4ef834e8d",
  "requestId": "3765587f-9c7c-46b8-9332-35fab7a53f"
}
```

Decoded JWT (example)

```
{
  "aud": "SP_NAME",
  "nbf": 1661155914,
  "transId": "3a4a3b26-3b8f-4d4f-90fe-d1a4ef834e8d",
  "iss": "Nafath App",
  "exp": 1661155914,
  "iat": 1661155614,
  "status": "COMPLETED"
}
```

Expected SP Response

HTTP 200 OK with empty (or SP-defined) body, returned as quickly as possible. Heavy downstream processing should be moved off the critical callback path.

Reference Data

Error Handling & Validation

HTTP Code Error code	Response Description	Reason
403	Authentication failed	Invalid APP-KEY or APP-ID.

HTTP Code Error code	Response Description	Reason
404	No Mapping Rule matched	Invalid URL.
500	Internal server error	The service is not running properly.
503	Service unavailable	System down.
422-031-046	Invalid Request	Invalid data has been sent (e.g., malformed body, unknown service key).
400-034-050	Invalid Request, There Is Active Trx	A new request was created while another is still active for the same National ID.
400-034-053	Invalid Request, Trx Not Exist	Status was requested with a wrong unknown transId.
400-034-051	Invalid Request, Trx Expired	Status was requested for an expired transId (past the 200 s lifetime).

Environments

Name	Testing	Pre-Production	Production
Nafath Base URL	https://rabet-nafath.api.elm.sa/nafath-sandbox	https://rabet-nafath.api.elm.sa/stg/	https://rabet-nafath.api.elm.sa/
Source IPs (callback)	195.170.180.7, 195.170.180.6	195.170.180.7, 195.170.180.6	195.170.180.7, 195.170.180.6
APP-ID	From Rabet sandbox registration	From Rabet staging registration	From Rabet production registration
APP-KEY	From Rabet sandbox registration	From Rabet staging registration	From Rabet production registration

FAQs

Question	Answer
Q1: What is the purpose of the Send Request API?	It creates a new Nafath transaction for a specific National ID and service. It returns a transId (used by status callback) and a random number that must be shown to the end-user.
Q2: What value should I pass in 'service'?	One of the supported Service Types (see Service Types table in 'Others'). The choice controls whether biometric verification is required and what the transaction lifetime is.
Q3: What is the difference between Login and OpenBankAccount?	'Login' is a simple acceptance flow with a 60 s lifetime and no biometrics. 'OpenBankAccount' requires biometric verification and has a 180 s lifetime, reflecting the higher assurance level for KYC-sensitive operations.
Q4: Why do I receive 400-034-050?	There is already an active transaction for the same National ID. Wait for the existing transaction to terminate (COMPLETED, REJECTED or EXPIRED) before creating a new one.
Q5: Why do I receive 400-034-053?	The transId supplied to Retrieve Request Status does not exist — it was never created or it was created against a different environment.
Q6: Why do I receive 400-034-051?	The transaction is older than 200 s. The user can no longer act on it and its status cannot be retrieved. Create a new transaction.
Q7: How long does the user have to take action?	180 seconds (the Decision Interval). After that the transaction is considered EXPIRED for 20 more seconds, then becomes unretrievable.
Q8: How do I correlate a callback with my original request?	Match the requestId returned in the callback body with the UUID you generated on Send Request. The transId is also embedded in the signed JWT for verification.

Question	Answer
Q9: How do I validate the JWT delivered on the callback?	Retrieve the JWK via NSI001, locate the key whose 'kid' matches the JWT header 'kid', then verify the RS256 signature. Reject the callback if signature, 'aud' or 'transId' do not match.
Q10: What does the 'aud' claim represent in the JWT?	The audience — it is the SP name registered on Rabet. SPs must validate that 'aud' matches their own registered name to prevent replay attacks across tenants.
Q11: What user attributes do I receive on COMPLETED?	It depends on the user identity type: National ID, Iqama, Visa, or Border number. See the Appendix tables in 'Others' for the full attribute lists.
Q12: Is OTP involved in this flow?	No — Nafath uses in-app acceptance (with optional biometrics) rather than SMS OTP.
Q13: Can I rely only on the callback and skip status polling?	Yes. The callback is authoritative. Polling is useful only when the SP needs to update its UI in near real time while the user is still on the page.
Q14: How do I deep-link to the Nafath app from my own mobile app?	Use nafath://home on iOS and nic://nafath on Android. The user can then approve/reject the request that was created by NSI002.
Q15: What is the Minor Account-Opening workflow?	When the end-user is a minor (isMinor=true), opening a bank account requires two Nafath requests: first by the minor and then by their guardian (Head of Household). See the Minor Workflow diagram in 'Others'.

Others

Service Types (Service Key, Timeout, Biometric Verification)

Service Type	Service Key	Timeout	Bio
Login	Login	60 sec	No
Open Bank Account	OpenBankAccount	180 sec	Yes
Open Account	OpenAccount	180 sec	Yes
Device verification	VerifyUsedDevice	180 sec	Yes
Money transfer	MoneyTransfer	180 sec	Yes
Add Recipient	AddRecipient	180 sec	Yes
Digital service enrollment	RequestDigitalServicesEnrollment	180 sec	Yes
Create credit card	CreateCreditCard	180 sec	Yes
Personal loan	PersonalLoan	180 sec	Yes
Real estate loan	RealEstateLoan	180 sec	Yes
Rental loan	RentalLoan	180 sec	Yes
Vehicle loan	VehicleLoan	180 sec	Yes
Consumerism loan	ConsumerismLoan	180 sec	Yes
House devices loan	HouseDevicesLoan	180 sec	Yes
Guardian Consent for Opening Bank Account	GuardianConsentforOpeningBankAccount	180 sec	Yes
Recipient approval	RecipientApproval	180 sec	Yes
Update Recipient Information	UpdateRecipientInformation	180 sec	Yes
Open Account For Company	OpenAccountForCompany	180 sec	Yes
Increase Bank Account Limit	IncreaseBankAccountLimit	180 sec	Yes
Reset Password	ResetPassword	180 sec	Yes
Device verification (without bio)	DeviceVerificationWithoutBio	60 sec	No

Service Type	Service Key	Timeout	Bio
Money transfer (without bio)	MoneyTransferWithoutBio	60 sec	No
Add recipient (without bio)	AddRecipientWithoutBio	60 sec	No
Digital service enrollment (without bio)	DigitalServiceEnrollmentWithoutBio	60 sec	No
Create credit card (without bio)	CreateCreditCardWithoutBio	60 sec	No
Personal loan (without bio)	PersonalLoanWithoutBio	60 sec	No
Real Estate loan (without bio)	RealEstateLoanWithoutBio	60 sec	No
Rental loan (without bio)	RentalLoanWithoutBio	60 sec	No
Vehicle loan (without bio)	VehicleLoanWithoutBio	60 sec	No
Consumerism loan (without bio)	ConsumerismLoanWithoutBio	60 sec	No
House devices loan (without bio)	HouseDevicesLoanWithoutBio	60 sec	No
Recipient approval (without bio)	RecipientApprovalWithoutBio	60 sec	No
Open Account (without bio)	OpenAccountWithoutBio	60 sec	No
Reset Password (without bio)	ResetPasswordWithoutBio	60 sec	No
Add Authorized To Account (without bio)	AddAuthorizedToAccountWithoutBio	60 sec	No

User Types (ID starts with)

#	Type	ID Starts With
1	National ID (هوية مواطن)	1
2	Resident ID Iqama (هوية مقيم)	2
3	Visitor ID (هوية زائر)	3 - 6

User Attributes — Logged in by National ID

#	Attribute	Type	Description
1	nin	String	User identifier (National ID).
2	nationality	String	Nationality code (e.g., SAU).
3	idVersionNumber	String	Version of the identity (e.g., 4).
4	idIssuePlace	String	Card issue location (e.g., الرياض).
5	idIssueDateG	Date	Saudi Identity Card issue date — Gregorian.
6	idIssueDate	Date	Saudi Identity Card issue date — Hijri.
7	idExpiryDateG	Date	Gregorian ID expiration date.
8	idExpiryDate	Date	Hijri ID expiration date.
9	gender	String	M F.
10	firstName	String	Arabic first name.
11	fatherName	String	Arabic father name.
12	grandFatherName	String	Arabic grand-father name.
13	familyName	String	Arabic family name.
14	englishFirstName	String	English first name.
15	englishSecondName	String	English second name.
16	englishThirdName	String	English third name.
17	englishLastName	String	English last name.

#	Attribute	Type	Description
18	dateOfBirthG	Date	Date of birth — Gregorian.
19	dateOfBirthH	Date	Date of birth — Hijri.
20	socialStatusCode	String	Social status code (see Social Status table).
21	lastTravelExitDate	Date	Last travel exit date — Hijri.
22	passportNumber	String	Passport number.
23	placeOfBirth	String	Place of birth.
24	lastTravelEntryDateG	Date	Last travel entry date — Gregorian.
25	lastTravelExitDateG	Date	Last travel exit date — Gregorian.
26	occupationCode	String	Occupation code (O = Other, G = Government).
27	nationalityCode	String	Nationality code (see Nationality Lookups).
28	totalNumberOfCurrentDependents	String	Number of current dependents.
29	lastTravelEntryDate	Date	Last travel entry date — Hijri.
30	socialStatusDesc	String	Social status description.
31	nationalAddress	List	List of registered addresses (see National Address Attributes).
32	isMinor	Boolean	True if user is a minor.
33	hohInfo	Object	Head-of-Household information (see HOH Attributes).

User Attributes — Logged in by Iqama Number

#	Attribute	Type	Description
1	iqamaNumber	String	User identifier (Iqama).
2	nationalityCode	String	Nationality code.
3	nationalityDesc	String	Nationality description.
4	dateOfBirthG	Date	Date of birth — Gregorian.
5	dateOfBirthH	Date	Date of birth — Hijri.
6	englishFirstName	String	English first name.
7	englishSecondName	String	English second name.
8	englishThirdName	String	English third name.
9	englishLastName	String	English last name.
10	firstName	String	Arabic first name.
11	secondName	String	Arabic second name.
12	thirdName	String	Arabic third name.
13	lastName	String	Arabic last name.
14	gender	String	M F.
15	iqamaVersionNumber	String	Identity version number.
16	iqamaExpiryDateG	Date	Iqama expiry date — Gregorian.
17	iqamaExpiryDateH	Date	Iqama expiry date — Hijri.
18	iqamaIssueDateG	Date	Iqama issue date — Gregorian.
19	iqamaIssueDateH	Date	Iqama issue date — Hijri.

#	Attribute	Type	Description
20	iqamaIssuePlaceCode	String	Iqama issue place code.
21	iqamaIssuePlaceDesc	String	Iqama issue place description.
22	socialStatusCode	String	Social status code.
23	placeOfBirthDesc	String	Place of birth description.
24	sponsorName	String	Sponsor name.
25	occupationDesc	String	Occupation description.
26	passportNumber	String	Passport number.
27	legalStatus	String	Legal status.
28	socialStatus	String	Social status.
29	occupationCode	String	Occupation code (O = Other, G = Government).
30	placeOfBirthCode	String	Place of birth code.
31	inOutIndecator	String	In/Out indicator.
32	nationalAddress	List	List of registered addresses.

User Attributes — Logged in by Visa Number

#	Attribute	Type	Description
1	firstName	String	First name.
2	secondName	String	Second name.
3	thirdName	String	Third name.
4	lastName	String	Last name.
5	translatedFirstName	String	Translated first name.
6	translatedSecondName	String	Translated second name.
7	translatedThirdName	String	Translated third name.
8	translatedLastName	String	Translated last name.
9	birthhDate	Date	Date of birth — Hijri.
10	birthgDate	Date	Date of birth — Gregorian.
11	gender	String	M F.
12	nationalityCode	String	Nationality code.
13	nationalityDesc	String	Nationality description.
14	occupationCode	String	Occupation code.
15	occupationDescAr	String	Arabic occupation description.
16	occupationDescEn	String	English occupation description.
17	birthCountryDescAr	String	Birth country (Arabic).
18	birthCountryDescEn	String	Birth country (English).
19	visaNumber	String	Visa number.
20	duration	String	Days from visa issue to visa expiry.
21	visaIssueDate	Date	Visa issue date.
22	visaExpiryDate	Date	Final date the visitor may enter Saudi Arabia.
23	finalDepartureDate	Date	Last day the visitor may remain in Saudi Arabia.
24	numberOfEntriesCode	String	1 = Single Entry, 9 = Multiple Entry.

#	Attribute	Type	Description
25	numberOfEntriesDescAr	String	Number of entries description.
26	visaTypeCode	String	Visa type code.
27	visaTypeDescAr	String	Visa type description (Arabic).
28	visaTypeDescEn	String	Visa type description (English).
29	passportNumber	String	Passport number.
30	passportIssueDate	String	Passport issue date.
31	passportExpiryDate	String	Passport expiry date.

User Attributes — Logged in by Border Number

#	Attribute	Type	Description
1	firstName	String	English first name.
2	secondName	String	English second name.
3	thirdName	String	English third name.
4	lastName	String	English last name.
5	translatedFirstName	String	Translated first name.
6	translatedSecondName	String	Translated second name.
7	translatedThirdName	String	Translated third name.
8	translatedLastName	String	Translated last name.
9	entryDate	Date	Date of entry.
10	birthDateG	Date	Date of birth — Gregorian.
11	gender	String	M F.
12	nationalityCode	String	Nationality code.
13	nationalityDesc	String	Nationality description.
14	duration	String	Days from visa issue to visa expiry.
15	visaIssueDate	Date	Visa issue date.
16	visaExpiryDate	Date	Visa expiry date.
17	finalDepartureDate	Date	Last legal day in Saudi Arabia.
18	numberOfEntriesCode	String	1 = Single, 9 = Multiple.
19	numberOfEntriesDescAr	String	Number of entries description.
20	occupationCode	String	Occupation code.
21	occupationDescAr	String	Arabic occupation description.
22	occupationDescEn	String	English occupation description.
23	birthCountryDescAr	String	Birth country (Arabic).
24	birthCountryDescEn	String	Birth country (English).
25	visaNumber	String	Visa number.
26	visaTypeCode	String	Visa type code.
27	visaTypeDescAr	String	Visa type description (Arabic).
28	visaTypeDescEn	String	Visa type description (English).
29	passportNumber	String	Passport number.
30	passportIssueDate	String	Passport issue date.
31	passportExpiryDate	String	Passport expiry date.

National Address Attributes (New SPL)

Attribute	Type	Description
streetName	String	Street name (e.g., At Tawbah).
city	String	City (e.g., JEDDAH).
additionalNumber	String	Additional number (e.g., 3030).
district	String	District (e.g., Ash Sharafiyah Dist.).
unitNumber	String	Unit number.
buildingNumber	String	Building number.
postCode	String	Post code (e.g., 12345).
locationCoordinates	String	Latitude longitude string.
isPrimaryAddress	String	Whether this is the primary address.
cityId	String	City ID.
regionId	String	Region ID.
districtId	String	District ID.
regionNameL2	String	Region name in English.
cityL2	String	City in English.
streetL2	String	Street in English.
districtL2	String	District in English.
regionName	String	Region name (Arabic).

Driving License Attributes

Attribute	Type	Description
issueDateG	String	Driving issue date (Gregorian).
typeDescEn	String	License type in English.
licenseIssueLocationDescEn	String	License issue location in English.
typeDescAr	String	License type in Arabic.
statusDescAr	String	License status in Arabic.
expiryDateG	String	Driving expiry date (Gregorian).
licenseIssueLocationCode	String	License issue location code.
statusDescEn	String	License status in English.
licenseIssueLocationDescAr	String	License issue location in Arabic.
issueDate	String	License issue date.
expiryDate	String	License expiry date.
typeCode	String	License type code.
statusCode	String	License status code.

User Device Verification (THKI) Attributes

Attribute	Type	Description
deviceName	Boolean	True if device name matches.
ip	Boolean	True if IP address matches.
model	Boolean	True if device model matches.

Attribute	Type	Description
os	Boolean	True if device operating system matches.

Head of Household (HOH) Attributes

Attribute	Type	Description
id	String	HOH National ID.
firstName	String	HOH first name.
fatherName	String	HOH father name.
grandFatherName	String	HOH grand-father name.
familyName	String	HOH family name.

Social Status Lookup

Code	Sex	English	Arabic
0	M	SINGLE	أعزب
1	F	SINGLE	غير متزوجة
1	M	ONE WIFE	زوجة واحدة
2	F	MARRIED	متزوجه
2	M	TWO WIVES	زوجتين
3	F	DIVORCED	مطلقة
3	M	THREE WIVES	ثلاث زوجات
4	F	WIDOW	أرملة
4	M	FOUR WIVES	أربع زوجات
5	F	PENDING DIVORCED	مطلقة معلقة

Nationality Lookups (excerpt)

The full Nationality lookup list is published in the Nafath Integration Guide (Appendix). The most commonly used codes are listed below; refer to the official guide for the complete table.

Code	English Name	Arabic Name
101	Arab Emirates	الإمارات العربية
102	Jordan	الأردن
103	Bahrain	البحرين
106	Oman	عمان
108	Qatar	قطر
109	Kuwait	الكويت
113	Saudi Arabia	العربية السعودية
207	Egypt	مصر
304	Pakistan	باكستان
305	Bangladesh	بنجلاديش
308	Thailand	تايلند
309	Turkey	تركيا
321	India	الهند
323	Japan	اليابان
325	China	الصين الشعبية
503	Germany	ألمانيا

Code	English Name	Arabic Name
506	United Kingdom	المملكة المتحدة
516	France	فرنسا
601	United States	الولايات المتحدة
610	Canada	كندا
701	Australia	استراليا

Minor Account-Opening Workflow

When the end-user's profile has isMinor = true, opening a bank account uses a two-step workflow:

- Step 1 — Request sent by the minor: the SP calls Send Request (NSI002) for the minor with service 'OpenBankAccount'. The minor approves it in the Nafath app. The SP receives a COMPLETED callback containing the minor's identity attributes and hohInfo (Head of Household).
- Step 2 — Request sent by the client (service provider) to the guardian: the SP creates a second Send Request for the guardian (hohInfo.id) with service 'GuardianConsentforOpeningBankAccount'. The guardian approves it in their Nafath app; the SP receives a second COMPLETED callback confirming the guardian's consent.

Both callbacks must be verified with the JWK (NSI001) and correlated through their respective requestIds. Account opening proceeds only after the guardian's callback is COMPLETED.