















































VERBAL Price List				
S/N	Model	Features	Image	DP Price
Basic HD IP Phone				
1	GRP2601 (Equivalent GXP1610)	2 SIP Accounts, 2 Lines, 132 x 48 (2.21") LCD display , Non PoE , Color, 5-Way Audio Conferencing, HD audio supporting all major codecs, Dual 10/100/1000mbps Network port with Power Adapter .		3800
2	GRP2601P (Equivalent GXP1615)	2 SIP Accounts, 2 Lines, 132 x 48 (2.21") LCD display , PoE , Color, 5-Way Audio Conferencing, HD audio supporting all major codecs, Dual 10/100/1000mbps Network port.		4000
3	GXP1615 POE	2 SIP Accounts, 2 Lines, 132 x 48 (2.21") LCD display , PoE , Color, 5-Way Audio Conferencing, HD audio supporting all major codecs, Dual 10/100/1000mbps Network port.		4000
4	GRP2602P (Equivalent Higher GXP1625)	4 SIP Accounts, 2 Lines, 132 x 48 (2.21") backlit graphical LCD display , PoE, Color, 5-Way Audio Conferencing. Swappable faceplate to allow for easy logo customization, HD audio supporting all major codecs, Dual 10/100/1000mbps Network port. Without Adapter		5520
5	GRP2602P (Equivalent Higher GXP1625)	4 SIP Accounts, 2 Lines, 132 x 48 (2.21") backlit graphical LCD display , PoE, Color, 5-Way Audio Conferencing. Swappable faceplate to allow for easy logo customization, HD audio supporting all major codecs, Dual 10/100/1000mbps Network port. With Adapter		5750
6	GXP1630	3 SIP accounts, 3 line keys, 4-way conferencing, 3 XML programmable context-sensitive soft keys, nHD audio on speakerphone and handset, Dual-switched Gigabit ports, integrated PoE, 8 dual-colored BLF/speed dial keys, EHS support for Plantronics, headsets, Up to 1000 contacts, call history up to 100 calls.		7475
7	GXP1760W	6 lines, 6 dual-color line keys (with 3 SIP accounts), 4 XML programmable context-sensitive soft keys, 5-way audio conferencing for easy conference calls, 24 digitally programmable & customizable BLF/fast-dial keys, Built-in USB port for importing and exporting data only, uilt-in PoE to power the devices and give it a network connection, Supports EHS compatible Plantronics's headsets, Auto speed-dialing function, TR-989, AES encryption technology.		13225
8	SERVER UCM6300			
9	UCM6301	Model : UCM6301 Analog Telephone FXS Ports : 1 RJ11 Port PSTN Line FXO Ports : 1 RJ11 Port Users: 500 Concurrent calls (G.711): 75 Max concurrent SRTP calls (G.711): 50		42,000.00
10	UCM6302	Model : UCM6302 Analog Telephone FXS Ports : 2 RJ11 Port PSTN Line FXO Ports : 2 RJ11 Port Users: 100 Concurrent calls (G.711): 150 Max concurrent SRTP calls (G.711): 100		68,000.00
11	UCM6304	Model : UCM6304 Analog Telephone FXS Ports : 4 RJ11 Port PSTN Line FXO Ports : 4 RJ11 Port Users: 2000 Concurrent calls (G.711): 300 Max concurrent SRTP calls (G.711): 200		132,000.00
12	Mid Range Non Cloud HD IP Phone			
13	GXP1782	4 SIP accounts, 8 lines, 8 dual-color line keys, 4 XML programmable context sensitive soft keys; 5-way audio conferencing for easy conference calls; Dual- switched 10/100Mbps ports; Built-in USB; Supports headset, EHS-capable Plantronics headsets, TLS and SRTP security encryption technology; Up to 2,000 contacts, call history Up to 100 calls.		8625

14	GXP2130	3 Lines, 3 SIP Accounts, 4-way voice conferencing, PoE + GigE, Color, 2.8 inch color-screen LCD, 8 dual-colored BLF/speed-dial keys, Integrated Bluetooth, 4 programmable context-sensitive soft keys		9775
15	GXP2135	4 SIP accounts, 8 lines, 4 XML programmable context-sensitive soft keys, Dual switched, auto-sensing Gigabit ports, HD audio on the handset and speakerphone; full duplex speakerphone, Supports EHS compatible Plantronics headsets, 4-way audio conferencing, Built-in Bluetooth, Built		10350
16	Cloud Managed High End HD IP Phone			
17	GRP2612P	2 SIP Accounts, 4 Lines, 2.4 in scrn, PoE, Color, Swappable faceplate to allow for easy logo customization, HD audio supporting all major codecs, including wideband codecs G.722 and Opus, Up to 16 digital BLF Keys, Without Power Adapter		7475
18	GRP2612W	2 SIP Accounts, 4 Lines, built-in dual-band WiFi, Color, Swappable faceplate to allow for easy logo customization, HD audio supporting all major codecs, including wideband codecs G.722 and Opus, Up to 16 digital BLF Keys Without Power Adapter		10350
19	GRP2613	6 Lines, 3 SIP Accounts, 2.8 in scrn, PoE + GigE, Color, Swappable face plates to allow for easy logo customization, Dual switched autosensing 10/100/1000 Mbps Gigabit ethernet ports with integrated PoE, Up to 24 digital BLF keys		8625
20	GRP2614	4 Lines, 4 SIP Accounts, 2.8 in + 2.4 in scrn, PoE + GigE, Color, HD audio, handset and speakerphone with support for wide-band audio, Dual LCD screens with digital BLF keys, Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE, Integrated Bluetooth,		16675
21	GRP2615	10 line keys with up to 5 SIP accounts Integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz) 40 built-in digital BLF keys; available extension module offers 40 BLF/speed dial keys per module		19550
22	GRP2616	HD audio, handset and speakerphone with support for wide-band audio 6 line keys with up to 6 SIP accounts Dual LCD screens with digital BLF Keys Enterprise-level protection including secure boot, dual firmware images, and encrypted data storage Integrated dual-band 802.11 a/b/g/n/ac Wi-Fi		18400
23	High End Non Cloud HD IP Master/Operator Phone			
24	Master IP Phone GXP2140	4 SIP accounts, supports 4 lines, 5-way voice conferencing, HD audio on speakerphone and handset, 5 programmable context-sensitive soft keys, 4.3-inch (480x272) color-screen LCD, Dual Gigabit ports, Integrated USB, EHS for Plantronics headsets, Integrated Bluetooth, Integrated PoE,		12650
25	Operator Phone GXP2160	Supports 6 lines, 6 SIP accounts and 5-way voice conferencing, 4.3 inch (480x272) color-screen LCD, Dual Gigabit ports, integrated PoE, HD audio on speakerphone and handset, 5 programmable context-sensitive soft keys, 24 dual-colored BLF/speed dial keys, Integrated Bluetooth		15870
26	Master IP Phone GXP2170	6 SIP accounts, 12 lines, 5 soft keys and 5-way voice conferencing, 4.3-inch (480x272) color-screen LCD, Dual Gigabit ports, Supports up to four GXP2200EXT Modules for BLF/speed-dial access to up to 160 contacts, integrated Bluetooth, Integrated PoE.		16100
27	ANDROIDE Video IP Phone			
28	GXV3370	16 SIP accounts and 16 lines, Built-in camera for video calling with privacy shutter, Runs on Android 7.0 operating system, Dual-switched auto-sensing 10/100/1000Mbps network ports, Integrated dual-band Wi-Fi (2.4GHz & 5GHz), Built-in Bluetooth, Built-in PoE/PoE+, Speakerphone with HD acoustic chamber, advanced echo cancellation & excellent double-talk performance, 4-core 1.3GHz ARM Cortex A53		29325

29	GXV3380	16 lines with up to 16 SIP accounts, 8" (1280x800) capacitive 10-point touch screen IPS LCD, Built-in 2 megapixel camera for video calling with privacy shutter, Runs on the Android 7.x operating system, Built-in Bluetooth for syncing with mobile devices and connecting Bluetooth headsets, Dual-switched auto-sensing 10/100/1000Mbps network ports, Integrated dualband Wi-Fi (2.4GHz & 5GHz), Built-in PoE/PoE+ for power and network connections. Dual-		43700
30	GXV3350	16 lines with up to 16 SIP accounts Built-in 1 mega-pixel CMOS tiltable camera for video calling with privacy wheel Runs on the Android 7.0 operating system Built-in Bluetooth for syncing with mobile devices and connecting Bluetooth headsets Dual-switched auto-sensing 10/100/1000Mbps network ports Integrated dualband Wi-Fi (2.4GHz & 5GHz) Built-in PoE/PoE+ for power and network connections		27600
31				
32	WP820	2 SIP accounts, 2 lines, HD voice & dual MIC design with AEC and Noise Shield Technology, Accelerometer and configurable button for push-to-talk, panic and other related functions, Bluetooth for syncing headsets and mobile devices, Dual-band WiFi with efficient antenna design and advanced roaming support, Micro USB port and 3.5mm headset jack, Dual-band WiFi with efficient antenna design		23000
33	WP810	Dual-band Wi-Fi with efficient antenna design and advanced roaming support 2 SIP accounts, 2 lines HD voice & dual MIC design with AEC and Noise Shield Technology Rechargeable 1500mAh battery, 6 hour talk time, 120-hour standby		12650
34				
35	HT801	Supports 1 SIP profile through a single FXS port and a single 10/100Mbps port Supports 3-way voice conferencing Failover SIP server automatically switches to secondary server if main server loses connection Supports T.38 Fax for creating Fax-over-IP		4600
36	HT802	Supports 2 SIP profiles through 2 FXS ports and a single 10/100Mbps port, TLS and SRTP security encryption technology to protect calls and accounts, Automated provisioning options include TR-069 and XML config files, Supports 3-way voice conferencing, Failover SIP server		5060
37	HT812	Supports 2 SIP profiles through 2 FXS ports and dual Gigabit ports, Supports 2 SIP profiles through 2 FXS ports and dual Gigabit ports, TLS and SRTP security encryption technology to protect calls and accounts, Automated provisioning options include TR-069 and XML config files, Supports 3-way voice conferencing, Failover SIP server automatically switches to secondary server if main server loses connection, Supports T.38 Fax for creating Fax-over-IP		5520
38	HT813	Supports 2 SIP profiles through 1 FXS port and 1 FXO port, Dual 100Mbps LAN and WAN ports, Lifeline support (FXS port will be hard-relayed to FXO port) in case of power outage, 3-way voice conferencing per port, Automated & secure provisioning options using TR069, Supports T.38 Fax for reliable Fax-over-IP, Failover SIP server automatically switches to secondary server if main server loses connection		8050
39	HT814	Supports 2 SIP profiles through 4 FXS ports and dual Gigabit ports, Includes a built-in NAT router which can handle routing speeds up to 100MBps, TLS and SRTP security encryption technology to protect calls and accounts, Automated provisioning options include TR-069 and XML config files Supports 3-way voice conferencing, Failover SIP server automatically switches to secondary server if main server loses connection, Supports T.38 Fax for creating Fax-over-IP		10925
40	HT818	Supports 2 SIP profiles and 8 FXS ports, Strong AES encryption with security certificate per unit, Automated & secure provisioning options using TR069, 3-way voice conferencing per port, Exceptional voice quality with wide-band HD codec, Supports T.38 Fax for reliable Fax-over-IP, Supports dual Gigabit network ports, High performance NAT		19550
41	FXS gateway FXS Analog VoIP Gateway			

42	GXW4216	16 FXS ports, GXW4248 includes 2 50-pin Telco connectors, 1 Gigabit network port, 132x48 backlit graphic display with support for multiples languages, 4 SIP server profiles per system, independent SIP account per port, Designed and tested for full interoperability with leading IP-PBXs, soft-switches and SIP-based environments,		46000
43	GXW4224	24 FXS ports, GXW4248 includes 2 50-pin Telco connectors, 1 Gigabit network port, 132x48 backlit graphic display with support for multiples languages, 4 SIP server profiles per system, independent SIP account per port, Designed and tested for full interoperability with leading IP-PBXs, soft-switches and SIP-based environments,		64400
44	GXW4232	32 telephone FXS ports with both RJ11 and 50-pin Telco connectors, as well as per port LED, Gigabit Ethernet and a backlit 128x32 graphic LCD display with support for multiple languages, 2 SIP server profiles per system and independent SIP account per port, Supported voice/fax codecs include G.711, G.723.1, G.726, G.729A/B, iLBC,		77050
45	GXW4248	48 telephone FXS ports with both RJ11 and 50-pin Telco connectors, as well as per port LED, Gigabit Ethernet and a backlit 128x32 graphic LCD display with support for multiple languages, 2 SIP server profiles per system and independent SIP account per port, Supported voice/fax codecs include G.711, G.723.1, G.726, G.729A/B, iLBC,		97750
46	FXO Gateways TNT Line			
47	GXW4104	4 ports, 2 10/100 Mbps network ports, Comprehensive codec support, caller ID, flexible dial plans and security protection, Advanced security protection with SRTP, Designed and tested for full interoperability with leading IP-PBXs, soft-switches and SIP-based environments, PSTN		27600
48	GXW4108	8 ports, 2 10/100 Mbps network ports, Comprehensive codec support, caller ID, flexible dial plans and security protection, Advanced security protection with SRTP, Designed and tested for full interoperability with leading IP-PBXs, soft-switches and SIP-based environments, PSTN		32200
49				
50	GAC2500	6 SIP accounts and 6 lines, 7-way voice conferencing, Runs Android 4.4 and offers full access to the Google Play Store and all Android apps, such as Skype, Google Hangouts and more, Bluetooth to support syncing of headsets and mobile devices, Built-in 7- way conference bridge, 4.3" (800x480) capacitive touch screen for easy use, Autosensing Gigabit port, built-in PoE support, Built-in WiFi support offers mobility and network flexibility, Full HD audio support to maximize		46000
51	GVC3210	Sharp HD video resolutions up to 4k Ultra HD, Runs on Android 6.x operating system with full access to applications in the Google Play store, Built-in Bluetooth for use with Bluetooth speakers/ microphones, keyboards, data exchange, etc., Integrated dual band WiFi to pair with video and web conferencing service, Built- in 4-MIC array with beam-forming, support for external audio equipment and innovative Noise Shield technology, Advanced camera with 16M pixel CMOS sensor, 90 FOV wide angle lens and ePTZ		103500
52	GVC3202	1080p Full-HD video, up to 3-way video conferences, support for 2 monitor outputs through 2 HDMI outputs, 3-way hybrid-protocol conferencing with no external MCUs/servers or extra software licenses, PTZ Camera with 9x optical zoom, Based on Android and offers full access to the Google Play Store to conference with Android apps such as Skype,		184000
53	GVC3200	1080p Full-HD video, up to 9-way video conferences, support for 3 monitor outputs through 3 HDMI outputs, 9-way hybrid-protocol conferencing with no external MCUs/servers or extra software licenses, PTZ camera with 12x zoom, Can be installed in three simple steps, Plug and Play connection to Grandstream's IPVideoTalk video conferencing service, Supports most SIP and H.323 video conferencing platforms		287500
54	GVC3220 [Support All Cloud VC Platform]	1080p Full-HD video, 12x Optical Zoom, up to 5-way video conferences at 1080P Resolution and 9-way with 720p @30fps conference, 5-way hybrid-protocol conferencing with no external MCUs/servers or extra software licenses, PTZ camera with 12x zoom, Can be installed in three simple steps, Plug and Play connection to Grandstream's IPVideoTalk video conferencing service, Supports most SIP and H.323 video conferencing platforms. GVC3220 is based on Android 9.0 and offer s powerful features including 4K Ultra HD video, the ability to locally host up to 5 way		#VALUE!
55	Enterprise Room Access Point			

56	GWN7602	1.17Gbps aggregate wireless throughput, 1x Gigabit and 3x 100Mbit wireline speed Up to 100 meters coverage range Self power adaptation upon auto detection of PoE/PoE+ and PSE Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device <u>Support up to 80 Wi-Fi client devices</u>		8050
57	GWN7605	1.27Gbps aggregate wireless throughput and 2xGigabit wireline ports Dual-band 2x2:2 MU-MIMO with beamforming technology Self power adaptation upon auto detection of PoE/PoE+ Supports 100+ concurrent Wi-Fi client devices Up to 165-meter coverage range Advanced QoS to ensure real-time performance of low-latency applications Embedded controller can manage up to 50 local GWN series APs; GWN.Cloud offers unlimited AP management; GWN Manager offers premise-based software		9200
58	GWN7600	1.27Gbps wireless throughput and 2x Gigabit wireline ports, Dual-band 2x2:2 MU- MIMO with beam-forming technology, Support 802.3af Power-over-Ethernet (PoE), Support 450+ concurrent WiFi client devices, Advanced QoS to ensure real-time performance of low-latency applications, Up to 165-meter coverage range, Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device, Embedded controller allows GWN7600 to auto-discover, auto-provision and manage up to 30 GWN7600s in a network		12650
59	GWN7615	Support for up to 16 SSIDs per radio and up to 200+ concurrent WiFi clients, Dual-band 3x3:3 MU-MIMO technology and a sophisticated antenna design for maximum network throughput of up to 1.75Gbps and expanded coverage range of up to 175 meters, Dual Gigabit ports with support for PoE/PoE+, USB port for future applications such as location based service and other IoT (Internet of Things) applications, User friendly built-in provisioning controller (via Web interface) allows any GWN7610 to auto discover, auto-provision and manage networks of up to 50 GWN7610s without requiring separate controller hardware/software and without a single point of		14950
60	GWN7630	2.33 Gbps wireless throughput and 2 Gigabit wireline ports, Dual-band 4x4:4 MU- MIMO technology, Self power adaptation upon auto detection of PoE or PoE+, Supports 200+ concurrent Wi-Fi client devices, Up to 175-meter coverage range, Advanced QoS to ensure real-time performance of low-latency applications, Anti- hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/ random default password per device, Embedded controller can manage up to 50 local GWN series APs; GWN.Cloud offers unlimited AP		19550