

Analysis of Laminar Flow Dynamics

Computational Modeling and PDF Rendering Standards

Gemini Research Group

Department of Applied Physics, Simulation Lab

May 30, 2026

ABSTRACT

This report outlines the structural requirements for converting complex scientific data into the Portable Document Format (PDF). It demonstrates the integration of mathematical notation, tabular experimental results, and high-fidelity typography. Focus is placed on the Hagen-Poiseuille relationship as a primary case study for fluid dynamics simulation.

1. Theoretical Framework

To accurately model the pressure drop in a cylindrical pipe for laminar flow, we employ the **Hagen-Poiseuille Equation**. This physical law describes the relationship between the volumetric flow rate and the physical properties of the fluid and the conduit.

$$Q = \pi r^4 \Delta P / 8 \eta L$$

Where the variables are defined as follows:

- ΔP : The pressure difference between the two ends of the pipe.
- r : The internal radius of the pipe (meters).
- η : The dynamic viscosity of the fluid (Pascal-seconds).
- L : The total length of the pipe segment (meters).

2. Experimental Data Results

The following trials were conducted using a digital pressure transducer. The data highlights the sensitivity of flow rate (Q) to the radius (r).

Trial ID	Pressure (ΔP)	Radius (r)	Viscosity (η)	Calculated Q (m ³ /s)
RF-001	120 Pa	0.05 m	0.001	0.042
RF-002	150 Pa	0.05 m	0.001	0.053
RF-003	200 Pa	0.06 m	0.001	0.088
RF-004	250 Pa	0.07 m	0.001	0.141

3. PDF Conversion Standards

Scientific publishing requires specific metadata and rendering protocols to ensure reproducibility:

- Font Embedding:** All Unicode mathematical symbols (Δ , π , Σ) must be embedded in the PDF/A-1a format.
- Vectorization:** Graphs must use vector primitives rather than rasterized pixels to maintain clarity at high zoom levels.
- Hyperlinking:** Cross-references to tables and equations should remain interactive within the electronic document.