## **Definition: (Minimal) Average Length**

For efficiency reasons, we are often interested in the average (expected) length of a code  ${\cal C}$ :

## **Definition: Average length**

Let  $\ell(s)$  denote the length of a string  $s \in \{0,1\}^*$  . The (average) length of a code C for a source  $P_X$  is defined as

$$\ell_C(P_X) := \mathbb{E}[\ell(C(X))] = \sum_{x \in \mathcal{X}} P_X(x) \ell(C(x)) \,.$$

## **Example**

The following are all codes for the source  $P_X$ , with  $\mathcal{X} = \{\mathtt{a},\mathtt{b},\mathtt{c},\mathtt{d}\}$ :

x	$P_X(x)$	$C_1(x)$	$C_2(x)$	$C_3(x)$	$C_4(x)$
a	0.5	00	0	0	0
b	0.25	01	10	010	01
С	0.125	10	110	01	011
d	0.125	11	111	10	111

For the codes above, we obtain the following average codeword lengths:  $\ell_{C_1}(P_X) = 2, \ell_{C_2}(P_X) = \ell_{C_4}(P_X) = \frac{1}{2} \cdot 1 + \frac{1}{4} \cdot 2 + \frac{1}{8} \cdot 3 + \frac{1}{8} \cdot 3 = \frac{7}{4} = 1.75$  and  $\ell_{C_3}(P_X) = \frac{1}{2} \cdot 1 + \frac{1}{4} \cdot 3 + \frac{1}{8} \cdot 2 + \frac{1}{8} \cdot 2 = \frac{7}{4} = 1.75.$  We see that the codes  $C_2$ ,  $C_3$ ,  $C_4$  have a smaller average codeword length, but  $C_2$  and  $C_4$  are preferred over  $C_3$  because their unique decodability. Notice that the individual codeword lengths of codes  $C_2$  and  $C_4$  correspond exactly to the surprisal values of  $P_X$  in bits, e.g.  $\ell(C_2(b)) = \ell(C_4(b)) = 2 = -\log P_X(b).$  Therefore, the computations of the entropy H(X) and of the average code length  $\ell_{C_2}(P_X)$  are exactly the same, and we have that  $H(X) = \ell_{C_2}(P_X) = \ell_{C_4}(P_X)$ . We will see later that this property characterizes optimal codes.

decide whether this button is necessary, and whether the title of this block should be question instead of example

**Definition: Minimal code length** 

created: 2018-12-12

## Information Theory | Definition: (Minimal) Average Length The minimal code length of a source ${\cal P}_X$ is defined as

$$\ell_{\min}(P_X) := \min_{C \in \mathfrak{C}} \ell_C(P_X)$$

where  ${\mathfrak C}$  is some class of codes, for example the set of all prefix-free codes (resulting in  $\ell_{\min}^{\mathrm{p.f.}}$ ), or the set of all uniquely decodable codes (resulting in  $\ell_{\min}^{\mathrm{u.d.}}$ ).

created: 2018-12-12