

Features

- 6 mm Round / Single-Turn / Cermet Industrial / Open Frame
- Cross slot adjustment options
- Horizontal and vertical mounting styles
- Dust resistant/splash resistant covers
- PC board stand-offs and retention feature
- Front and top adjust styles
- RoHS compliant*
- For trimmer applications/processing quidelines, click here

3306 - 6 mm Round Trimpot® Trimming Potentiometer

Electrical Characteristics

Standard Resistance Range

Absolute Minimum Resistance

Environmental Characteristics

Power Rating (100 volts max.)

Physical Characteristics

260 ° ±20 °
4.5 oz-in. max.
6.5 oz -in. min.
Solderable pins
Manufacturer's
ark, resistance code
200 pcs. per bag
H-90

Aqueous cleaning not recommended.

How To Order 3306 W - 1 - 103 Model Style Standard Product Resistance Code


Standard Resistance Table


Resistance	Resistance
(Ohms)	Code
100	101
200	201
500	501
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
25,000	253
50,000	503
100,000	104
200,000	204
250,000	254
500,000	504
1,000,000	105


Popular distribution resistance values listed in boldface.

Product Dimensions


Top Adjust Common Dimensions










SUGGESTED PWB LAYOUT - STYLE F











SUGGESTED PWB LAYOUT - STYLES K, P, W





DIMENSIONS:	MM (INCHES)
TOLERANCES: $\pm \frac{0.3}{(.012)}$	EXCEPT WHERE NOTED

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011. "Trimpot" is a registered trademark of Bourns, Inc. Specifications are subject to change without notice.