Lotek Tag Lifespan Model

John Brzustowski

4 April, 2016

We need some reasonable upper bound for the lifetimes of tags, by battery and BI.

Lotek provides a short table here:

http://www.lotek.com/bird+bat-nano.pdf (As of 1 April, 2016)

and there are additional models listed in "ANTC Spec Sheet.pdf" (no source), including the only numbers for battery type "3-1". Since lifetime is listed as depending only on the battery (numeric portion of model string), we model on that.

```
lt = as.tbl(read.csv("./lotekTagLifespanByBatteryAndBI.csv"))
```

Add inverses of columns bi and dutyCycle, for modelling

```
ls = lt %>% mutate(biInv = 1.0 / bi, dcInv = 1.0 / dutyCycle)
```

```
print(ls)
```

```
# A tibble: 40 x 6
   battery    bi dutyCycle lifespan biInv dcInv
    <fctr> <dbl>     <dbl>    <int> <dbl> <dbl>
1        1    10       0.5       45   0.1     2
2        1    10       1.0       33   0.1     1
3        1     2       1.0       10   0.5     1
4        1     5       1.0       21   0.2     1
5        2    10       0.5       71   0.1     2
6        2    10       1.0       52   0.1     1
7        2     2       1.0       16   0.5     1
8        2     5       1.0       33   0.2     1
9      3-1    10       0.5       87   0.1     2
10     3-1    10       1.0       64   0.1     1
# ... with 30 more rows
```

A simple model assumes that the battery capacity, K, depends on the battery model, and that tag power consumption r is a sum of a baseline rate r_0 plus a pulse-dependent rate r_1. All tags transmit 4 pulses per burst, so the pulse-dependent rate r_1 depends only on duty cycle and burst interval like so: $r_1 = r_p * \frac{dutyCyle}{BI}$

The full non-linear model is :

$$lifespan = \frac{K}{r_0 + \frac{r_p * dutyCycle}{BI}}$$

This is over-parameterized (we can divide top and bottom by r_0 to get a model with two parameters), so we simplify by rewriting K/r_0 as D, the number of days of battery life at the baseline rate, and r_p/r_0 be r_t, the relative rate of power consumption during transmission, versus baseline. The new model is:

$$lifespan = \frac{D}{1 + \frac{r_t * dutyCycle}{BI}}$$

We fit the model to each type of battery:

```r
par = res = pred = NULL
bnames = unique(ls$battery)
for (m in bnames) {
    res[[m]] = nls(lifespan~D / (1 + rt * dutyCycle / bi),
                   subset(ls, battery==m), list(D = 500, rt = 5))
    par = rbind(par, c(coefficients(res[[m]]), max(residuals(res[[m]])))))
    pred = rbind(pred,
                 data.frame(
                     battery=m,
                     bi=1:40,
                     lifespan=predict(res[[m]], list(bi=1:40, dutyCycle=1))
                 ))
}
rownames(par) = bnames
colnames(par) = c("D", "rt", "Max Residual (days)")
```

Stu Mackenzie pointed out there is a light-weight version of the *NTQB-1* which he's dubbed *NTQB-1-LW*, with "~2/3 the lifetime of the NTQB-1". For now we'll assume that means the D parameter for that model is 2/3 that for the NTQB-1

```r
par = rbind(c(par[["1","D"]] * 2 / 3, par[["1", "rt"]], NA), par)
rownames(par)[1] = "1-LW"
pred = rbind(data.frame(
    battery="1-LW",
    bi=1:40,
    lifespan=par[["1-LW", "D"]] / (1 + par[["1-LW", "rt"]] / (1:40)))
  , pred)
```

Now map model names to batteries. We do this as a simple table because the naming scheme isn't consistent enough to bother doing it programmatically.

```r
## Models and the batteries they correspond to

modelBattery = list(
"NTQB-1-LW"  = "1-LW",
"NTQB-1"     = "1",
"NTQB-2"     = "2",
"NTQB-3-2"   = "3-2",
"NTQB-4-2"   = "4-2",
"NTQB-6-1"   = "6-1",
"NTQB-6-2"   = "6-2",
"NTQBW-3-2"  = "3-2",
"NTQBW-2"    = "2",
"NTQBW-4-2"  = "4-2",
"NTQBW-6-2"  = "6-2",
"ANTC-M1-1"  = "1",
"ANTC-M2-1"  = "2",
"ANTC-M3-1"  = "3-1",
"ANTC-M3-2"  = "3-2",
"ANTC-M4-2"  = "4-2",
"ANTC-M4-2S" = "4-2",
```

```r
"ANTC-M4-2L" = "4-2",
"ANTC-M6-1"  = "6-1",
"ANTC-M6-2"  = "6-2",
"ANTCW-M1-1"  = "1",
"ANTCW-M2-1"  = "2",
"ANTCW-M3-1"  = "3-1",
"ANTCW-M3-2"  = "3-2",
"ANTCW-M4-2"  = "4-2",
"ANTCW-M4-2S" = "4-2",
"ANTCW-M4-2L" = "4-2",
"ANTCW-M6-1"  = "6-1",
"ANTCW-M6-2"  = "6-2",
"ACT-521" = "521",
"ACT-626" = "626",
"ACT-393" = "393"
)

modPar = NULL
for (b in names(modelBattery))
    modPar = rbind(modPar, par[modelBattery[[b]],])
rownames(modPar) = names(modelBattery)
```

The results show good agreement with the data table from Lotek:

```r
print(round(par, 1))
```

	D	rt	Max Residual (days)
1-LW	48.5	12.3	NA
1	72.8	12.3	0.3
2	114.7	12.2	0.4
3-1	138.5	11.8	0.4
3-2	271.6	11.9	0.2
4-2	547.0	11.8	0.2
6-1	775.5	11.7	0.1
6-2	1469.0	11.7	0.2
521	304.1	20.1	1.3
626	608.3	20.1	2.6
393	1839.8	24.3	3.3

The parameter r_t can be interpreted as the ratio of energy consumed during 1 second with a burst to that consumed during 1 second without a burst. Estimates of this parameter vary only by 5% across tag types, and in monotonic fashion, perhaps due to variation in battery internal resistance. The table provided by Lotek only covers $2 <= BI <= 20$ (the larger value from BI=10s @ 50% duty cycle); curves are extrapolated down to 1s and from 20 to 40s using the fitted model.

```r
xyplot(log10(lifespan)~bi, groups=battery, pred,
       auto.key=list(corner=c(.6,.1), columns=3),
       main="Reported (X) and Predicted (o) Tag Lifespan by Battery Type",
       xlab="Burst Interval (seconds)",
       ylab="Lifespan (log10(days); 1->10, 2->100, 3->1000)",
       type="b",
       panel = function(x, y, type, groups, ...) {
```

```
    panel.xyplot(x, y, type, groups, ...)
    meas = which(x %in% c(2, 5, 10, 20) & groups != "1-LW")
    panel.points(x[meas], y[meas], pch="X", cex=1.5)
    panel.abline(h=0, lty=2, col="gray")
    }
)
```

Reported (X) and Predicted (o) Tag Lifespan by Battery Type