







TP 7

Transfer Learning


Convolutional Layer




Different operations

Operation	Kernel ω	Image result $g(x,y)$
Identity	$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$	
Edge detection	$\begin{bmatrix} 1 & 0 & -1 \\ 0 & 0 & 0 \\ 1 & 0 & 1 \end{bmatrix}$	
	$\begin{bmatrix} 0 & -1 & 0 \\ 1 & 4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$	
	$\begin{bmatrix} -1 & -1 & -1 \\ 1 & 8 & 1 \\ 1 & 1 & 1 \end{bmatrix}$	
Sharpen	$\begin{bmatrix} 0 & -1 & 0 \\ 1 & 5 & 1 \\ 0 & 1 & 0 \end{bmatrix}$	


Convolutional Networks





Example of Train and Validation Learning Curves Showing an Overfit Model

ConvNets for NLP





Tips & Tricks

Why normalize inputs?

$$J(w, b) = \frac{1}{m} \sum_{i=1}^m \mathcal{L}(\hat{y}^{(i)}, y^{(i)})$$



Unnormalized:

$w_1: x_1: 1 \dots 1000 \leftarrow$
 $w_2: x_2: 0 \dots 1 \leftarrow$
 $-1 \dots 1$




$x_1: 0 \dots 1$
 $x_2: -1 \dots 1$
 $x_3: 1 \dots 2$

Normalized:



Data Augmentation



Different augmentations

Tranable Data Augmentation




Figure 1. Overview of our proposed model. We propose to use a **differentiable data augmentation pipeline** to achieve faster policy search by using adversarial learning.

Strong Data Augmentation





Figure 4: A realization of AUGMIX. Augmentation operations such as translate_x and weights such as m are randomly sampled. Randomly sampled operations and their compositions allow us to explore the semantically equivalent input space around an image. Mixing these images together produces a new image without veering too far from the original.


Mixed Data Augmentation

Mixup in Action




Mix-up works by blending 2 images with alpha % from image_1 and (1-alpha) % from image_2


Optimizer




Dropout




Batch normalization



internal covariate shift ?



Training loss smoother



VGG and Imagenet

VGG16




FIGURE 1 – Réseau VGG16

Summary of VGG16 Architecture


Layer		Feature Map	Size	Kernel Size	Stride	Activation
Input	Image	1	224 x 224 x 3	-	-	-
1	2 X Convolution	64	224 x 224 x 64	3x3	1	relu
	Max Pooling	64	112 x 112 x 64	3x3	2	relu
3	2 X Convolution	128	112 x 112 x 128	3x3	1	relu
	Max Pooling	128	56 x 56 x 128	3x3	2	relu
5	2 X Convolution	256	56 x 56 x 256	3x3	1	relu
	Max Pooling	256	28 x 28 x 256	3x3	2	relu
7	3 X Convolution	512	28 x 28 x 512	3x3	1	relu
	Max Pooling	512	14 x 14 x 512	3x3	2	relu
10	3 X Convolution	512	14 x 14 x 512	3x3	1	relu
	Max Pooling	512	7 x 7 x 512	3x3	2	relu
13	FC	-	25088	-	-	relu
14	FC	-	4096	-	-	relu
15	FC	-	4096	-	-	relu
Output	FC	-	1000	-	-	Softmax

Imagenet

ImageNet Challenge

IMAGENET

- 1,000 object classes (categories).
- Images:
 - 1.2 M train
 - 100k test.




The popular ImageNet Challenge based on the ImageNet Database

Accuracy of object detection software against the human eye

ImageNet (2010-2018)

IMAGENET

Percentage Error Rate %



2010

2011

2012

2013

2014


2015


2016

2017

Large Scale Visual Recognition Challenge Year

Network Complexity by Operations and Weights Sizes






```
vgg16 = torchvision.models.vgg16(pretrained=True)  
vgg16.eval()
```

```
pred(["cat.jpg"])
```

'Egyptian cat'




Imagenet

ImageNet Challenge


IMAGENET

- 1,000 object classes (categories).
- Images:
 - 1.2 M train
 - 100k test.



The popular ImageNet Challenge based on the ImageNet Database

15 scene dataset




Transfer Learning



Transfer learning and domain adaptation refer to the situation where what has been learned in one setting ... is exploited to improve generalization in another setting


— Page 526, [Deep Learning](#), 2016.



MODEL

KNOWLEDGE

Target task




MODEL

Traditional ML


vs

Transfer Learning


- Isolated, single task learning:
 - Knowledge is not retained or accumulated. Learning is performed w.o. considering past learned knowledge in other tasks




- Learning of a new tasks relies on the previous learned tasks:
 - Learning process can be faster, more accurate and/or need less training data



Traditional Learning vs Transfer Learning








Figure 7. Comparative description of SIFT encoding and CNN transfer learning for the construction of informative features.

CNN Features off-the-shelf: an Astounding Baseline for Recognition


Ali Sharif Razavian Hossein Azizpour Josephine Sullivan Stefan Carlsson

CVAP, KTH (Royal Institute of Technology)

Stockholm, Sweden

{razavian, azizpour, sullivan, stefanc}@csc.kth.se

sculptures dataset. The results are achieved using a linear SVM classifier (or L2 distance in case of retrieval) applied to a feature representation of size 4096 extracted from a layer in the net. The representations are further modified using simple augmentation techniques e.g. jittering. The



Faster training process: As discussed in the previous point, the training time for transfer learning is less, compared to training from scratch: transfer learning reduces the number of trainable parameters.

Model generalizes better: Transfer learning allows the model to perform better on new, unseen data, because state-of-the-art pretrained models are trained to learn generic features, thus allowing them to avoid overfitting.

Which layers ?




[Convolutional Neural Networks] features are more generic in early layers and more original-dataset-specific in later layers

— Transfer Learning, [CS231n Convolutional Neural Networks for Visual Recognition](#)



reproduced with permission from the original authors. All rights reserved. © 2016 Stanford University




- co-adaptation: Gradient descent was able to find a good solution the first time, but this was only possible because the layers were jointly trained.
- specificity: the specialization of higher layer neurons to their original task at the expense of performance on the target task, which was expected

Transfer Learning


ImageNet





randomly initialized
weights



Network trained to
classify 1000 classes





Fine-tune model
(update weights)



New data
New classes

Performances





Tips

- extraies features différentes résolutions
- petit learning rate quand fine tune
- attention à la batch normalization ! quelles statistiques utilisées ?