

Package ‘moultdbtools’

January 3, 2022

Title Combined analysis of NCBI taxonomy and GBIF taxonomy

Version 0.0.0.9000

Description The NCBI is the go to resource for taxonomic studies but it only contains data on extant species whereas the GBIF also includes extinct species. ‘moultdbtools’ is useful for the combined analysis of the NCBI taxonomy and GBIF taxonomy.

License CC0

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.2

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Imports purrr,
dplyr,
vroom,
ggplot2,
rje

Depends R (>= 2.10)

LazyData true

R topics documented:

get_lineages	2
get_status	2
get_validity	3
load_population	3
load_sample	4
load_taxonomies	4
plot_mdb	5
prepare_comparable_rank_dist	5
prepare_rank_dist	6
term_conversion	6
Index	8

get_lineages	<i>Get entries that have lineage information for both the GBIF and NCBI data</i>
--------------	--

Description

Get entries that have lineage information for both the GBIF and NCBI data

Usage

```
get_lineages(x)
```

Arguments

x A tibble created with `load_taxonomies()` or `load_population()` or `load_sample()`.

Value

A tibble with complete lineage data

Examples

```
get_lineages(load_sample())
```

get_status	<i>Filter a combined taxonomy by GBIF taxonomic status/synonym</i>
------------	--

Description

Filter a combined taxonomy by GBIF taxonomic status/synonym

Usage

```
get_status(x, status = "all")
```

Arguments

x A tibble created with `load_taxonomies()` or `load_population()` or `load_sample()`.

status Filter on GBIF assigned status (i.e. "doubtful", "accepted", "proparte synonym", "synonym", "homotypic synonym", "heterotypic synonym"). Can be a string or a vector of strings. Defaults to no filtering.

Value

A filtered tibble

Examples

```
get_status(load_sample(), "synonym")
get_status(load_sample(), c("accepted", "doubtful"))
```

get_validity	<i>Validate entries of a merged taxonomy</i>
--------------	--

Description

Validate entries of a merged taxonomy

Usage

```
get_validity(x, valid = TRUE, rank = "family")
```

Arguments

x	A tibble created with <code>load_taxonomies()</code> or <code>load_population()</code> or <code>load_sample()</code> .
valid	A logical indicating whether the returned data should include valid or invalid entries (defaults to <code>valid</code>).
rank	A string with GBIF rank that will be used to examine an NCBI lineage for validation purposes. Must be "phylum", "class", "order" or "family". Defaults to family.

Value

A validated tibble

Examples

```
get_validity(load_sample(), valid = TRUE)
```

load_population	<i>Load previously merged GBIF and NCBI taxonomies</i>
-----------------	--

Description

`load_population()` imports a previously merged taxonomy from your file system. An example of an previously merged taxonomy can be downloaded from https://drive.google.com/file/d/1gpvm9QKd0cuGo_cIXPkAgG1B-qfKZZU6/view?usp=sharing.

Usage

```
load_population(x)
```

Arguments

x	Path to a text file containing previously merged NCBI and GBIF taxonomies (compressed or uncompressed).
---	---

Value

A tibble

Examples

```
## Not run: load_population("path/to/merged_taxonomies")
```

load_sample	<i>Load a sample of previously merged GBIF and NCBI taxonomies</i>
-------------	--

Description

load_sample() returns a small subset of previously merged GBIF and NCBI taxonomies.

Usage

```
load_sample()
```

Value

A tibble containing a sample of merged GBIF and NCBI taxonomic data.

Examples

```
load_sample()
```

load_taxonomies	<i>Load and merge GBIF and NCBI taxonomic data</i>
-----------------	--

Description

load_taxonomies() parses and merges a GBIF Taxon.tsv() file (available within the <https://hosted-datasets.gbif.org/datasets/backbone/current/backbone.zip> archive) and a Taxonkit (<https://bioinf.shenwei.me/taxonkit/download/>) output file obtained by running: taxonkit list --ids 1 | taxonkit lineage --show-lineage-taxids --show-lineage-ranks --show-rank --show-name > All.lineages.tsv.

Usage

```
load_taxonomies(GBIF_path, NCBI_path)
```

Arguments

GBIF_path	Path to the GBIF backbone taxonomy (compressed or uncompressed).
NCBI_path	Path to the NCBI taxonomy (compressed or uncompressed).

Value

A tibble containing merged GBIF and NCBI taxonomic data.

Examples

```
## Not run: load_taxonomies("path/to/GBIF/Taxon.tsv", "path/to/NCBI-Taxonkit/All.lineages.tsv")
```

plot_mdb

*Generic for plot_mdb methods***Description**

A custom generic for methods that plot package:moultdbtools data types

Usage

```
plot_mdb(x)
```

Arguments

x An object of the class one_rank or the class all_ranks.

Value

A ggplot2 derived plot

Examples

```
plot_mdb(prepare_rank_dist(load_sample()))
plot_mdb(prepare_comparable_rank_dist(load_sample()))
plot_mdb(prepare_rank_dist(get_status(load_sample()), status = "synonym", NCBI = FALSE))
plot_mdb(prepare_comparable_rank_dist(get_validity(get_status(load_sample()), valid = TRUE)))
```

prepare_comparable_rank_dist

*Get comparable NCBI and GBIF taxonomic ranks***Description**

prepare_comparable_rank_dist(), like prepare_rank_dist(), returns taxonomic ranks aggregated by frequency for data derived from the NCBI, the GBIF, or both. However, prepare_comparable_rank_dist() only includes taxonomic ranks that have at least one NCBI and one GBIF representative.

Usage

```
prepare_comparable_rank_dist(x, GBIF = TRUE, NCBI = TRUE)
```

Arguments

x A tibble created with load_taxonomies() or load_population() or load_sample().

GBIF A boolean indicating whether GBIF taxonomic ranks are to be retrieved.

NCBI A boolean indicating whether NCBI taxonomic ranks are to be retrieved.

Value

A list of tibble(s) assigned to the S3 class one_rank or to the S3 class all_ranks.

Examples

```
prepare_comparable_rank_dist(load_sample())
prepare_comparable_rank_dist(get_status(load_sample(), "accepted"), NCBI = FALSE)
```

prepare_rank_dist	<i>Get all NCBI and GBIF taxonomic ranks</i>
-------------------	--

Description

prepare_rank_dist() returns taxonomic ranks aggregated by frequency for data derived from the NCBI, the GBIF, or both.

Usage

```
prepare_rank_dist(x, GBIF = TRUE, NCBI = TRUE)
```

Arguments

x	A tibble created with load_taxonomies() or load_population() or load_sample().
GBIF	A boolean indicating whether GBIF taxonomic ranks are to be retrieved.
NCBI	A boolean indicating whether NCBI taxonomic ranks are to be retrieved.

Value

A list of tibble(s) assigned to the S3 class one_rank or to the S3 class all_ranks.

Examples

```
prepare_rank_dist(load_sample())
prepare_rank_dist(load_sample(), NCBI=FALSE)
```

term_conversion	<i>Convert GBIF terms to NCBI terms</i>
-----------------	---

Description

term_conversion converts GBIF terminology to NCBI terminology where there is no biological provenance for the difference.

Usage

```
term_conversion(x)
```

Arguments

x	A tibble created with load_taxonomies() or load_population() or load_sample().
---	--

Value

A tibble with converted terms.

Examples

```
term_conversion(load_sample())
```

Index

get_lineages, [2](#)
get_status, [2](#)
get_validity, [3](#)

load_population, [3](#)
load_sample, [4](#)
load_taxonomies, [4](#)

plot_mdb, [5](#)
prepare_comparable_rank_dist, [5](#)
prepare_rank_dist, [6](#)

term_conversion, [6](#)