

# **From ImageNet to Image Classification:**

## **Contextualizing Progress on Benchmarks**

Dimitris Tsipras | Shibani Santurkar | Logan Engstrom | Andrew Ilyas |  
Aleksander Małdry

Review presented by Mounica Subramani

# Overview

Problem Statement

Original Work

ImageNet Dataset

- ImageNet creation pipeline
- Revisiting ImageNet Labels

Proposed Work

Framework – From Label Validation to Image Classification

- Obtaining Candidate Labels
- Image Classification via CLASSIFY task

Quantifying benchmark-task alignment of ImageNet

- Multi-object images
- Bias in label validation

Model Evaluation

# Problem Statement



This paper takes a step towards understanding how closely the widely-used vision benchmarks align with real-world tasks, that they are meant to approximate.



Building rich Machine Learning datasets in a scalable manner often necessitates a crowd-sourced data collection pipeline.



This paper analysis pinpoints, how a noisy data collection pipeline can lead to a systematic misalignment between the resulting benchmark and the real-world task it serves as a proxy for.

# Original Work



Data created through scalable methods, like building a dataset with the help of large group of people (Annotators)



Annotators were not asked to classify images, but rather to validate a specific automatically-obtained candidate label without knowledge of other classes in the dataset.



Leads to systemic annotation issues in the dataset, multi-object image problem and bias in the label validation



These issues results in tension between building realistic large-scale benchmarks and the scalable data collection pipeline

# Correct Labels?



(a) missile



(b) stage



(c) monastery



(d) Staffordshire bull terrier

ImageNet  
Labels

projectile

acoustic guitar

church

American  
Staffordshire terrier

# ImageNet Dataset



ImageNet is a prototypical example of large-scale dataset



It has 1000 classes and more than million images



Created through automated data collection and crowd-sourced filtering



Creation Pipeline has two stages

Image and Label collection

Image validation via *CONTAINS* task






# Image and label collection

Selected a set of classes using WordNet hierarchy

For each class, sourced images by querying several search engines

To expand image pool, performed queries in several languages

Label for image is given by the WordNet node that was used for query search



: Single-tag retrieval results, and automatically-generated annotations. None of the query tags are in NUS-WIDE, and most (m

# Image Validation – *CONTAINS* task

Employed annotators via the Mechanical Turk (MTurk) crowd-sourcing platform.

Annotators were presented with its class description and a grid of candidate images.

Select all images in the grid that contained an object of that class.

Only the images that received a “convincing majority” of votes were included in the ImageNet.

Annotators were presented with its class description (along with links to the relevant Wikipedia pages) and a grid of candidate images.



# Revisiting the ImageNet Labels



Resulting data set might not accurately capture the ground truth.



The above discussed pipeline design itself can lead to systematic errors in dataset



The root cause for many of these errors is that the image validation stage (i.e., the *CONTAINS* task) asks annotators only to verify if a specific proposed label is valid for a given image.



Crucially, annotators are never asked to choose among different possible labels for the image and, in fact, have no knowledge of what the other classes even are.

# Images with Multiple Objects

- Annotators are instructed to ignore the presence of other objects when validating a particular ImageNet label for an image.



IN label:  
Model T

Objects: 3  
car wheel  
Model T  
grille



IN label:  
Afghan hound

Objects: 2  
malinois  
Afghan hound



IN label:  
cab

Objects: 3  
cab  
car wheel  
palace



IN label:  
pot

Objects: 2  
bucket  
pot



IN label:  
toyshop

Objects: 2  
teddy  
toyshop



IN label:  
maypole

Objects: 2  
maypole  
pole



IN label:  
Siamese cat

Objects: 2  
quilt  
Siamese cat



IN label:  
castle

Objects: 2  
castle  
seashore



IN label:  
hamper

Objects: 2  
hamper  
wine bottle



IN label:  
china cabinet

Objects: 4  
goblet  
vase  
china cabinet  
tray



IN label:  
Model T

Objects: 4  
car wheel  
Model T  
grille  
convertible




IN label:  
airliner

Objects: 2  
airliner  
wing

# Biases in Image Filtering

Annotators (non-experts) have no knowledge of what the other classes are, they do not have a sense of the granularity of image features they should pay attention to.



Implies that potential errors in the collection process are unlikely to be corrected by during validation



Thus propagate to the final dataset

# Proposed Work

Develop methodology for obtaining fine-grained data annotations via large-scale human studies

Address short fall of object recognition benchmarks

Current standard model evaluation is insufficient

Introducing Human-based performance evaluation

# Framework - Label Validation to Image Classification


Authors would like annotators to classify the image, selecting all the relevant labels for it.

There are two phases in this step.

- First, they obtain a small set of (potentially) relevant candidate labels for each image.
- Second, they present these labels to annotators and ask them to select one of them for each distinct object using what they call the *CLASSIFY* task.

# Obtaining Candidate Labels

Obtain potential labels for each image by combining the top-5 predictions of 10 models from different parts of the accuracy spectrum with the existing ImageNet label.



Reuse the ImageNet *CONTAINS* task—asking annotators whether an image contains a particular class but for all potential labels



Outcome of this experiment is *Selection Frequency* for each image-label pair



Restricting potential labels to this smaller set of candidate labels



# Obtaining Candidate Labels

Which of these images contain at least one object of type

**Lhasa or Lhasa apso**

**Definition:** a breed of terrier having a long heavy coat raised in Tibet as watchdogs

If you are unsure about the object meaning, please also consult the following Wikipedia page(s): [https://en.wikipedia.org/wiki/Lhasa\\_Apso](https://en.wikipedia.org/wiki/Lhasa_Apso)




**Task:**

For each of the following images, check the box next to an image if it contains at least one object of type *Lhasa or Lhasa apso*.

Select an image if it contains the object **regardless of occlusions, other objects, and clutter or text** in the scene. Only select images that are photographs (**no drawings or paintings**).

**Please make accurate selections!**

If it is impossible to complete a HIT due to missing data or other problems, please return the HIT. Blatantly incorrect answers might cause the HIT to be rejected.



# Image Classification via the CLASSIFY Task



## Asking annotators to identify

All labels that correspond to objects in the image.

The label for the main object (according to their judgment).

Select only one label per distinct object except mutually exclusive objects.



## Identifying the main label and number of objects

From each annotator's response, authors learn what they consider to be the label of the main object, as well as how many objects they think are present in the image



# Image Classification via the CLASSIFY Task

Select which labels appear in the image

(Please read the instructions carefully as they are somewhat unusual)

Task:




**1. Valid labels: select ALL labels that correspond to DISTINCT objects in the image.** If for a single thing you cannot decide between multiple labels (which cannot all be true at the same time---e.g, different animal breeds), select the one that seems most likely.

**Example:** Select ONLY ONE dog breed for a single dog and ONE shoe type for a single shoe (even if you are unsure about the correct breed/type---just pick one). BUT select BOTH "car" and "car wheel" for a car with visible wheels, BOTH "fur" and "coat" for a fur coat, BOTH "grocery store" and "orange" for oranges inside a grocery store (as these correspond to distinct things in the image).

**2. Main object: from the chosen labels, select the one corresponding to the MAIN OBJECT in the image by clicking the appropriate radio button.** (If you cannot decide which object is the main one, pick your best guess.)

If unsure about what a label means, you can consult the corresponding Wikipedia pages.

Examples:

Image	Main object	Valid labels
	<input checked="" type="radio"/> <input type="radio"/> <input type="radio"/>	<input checked="" type="checkbox"/> Car <input checked="" type="checkbox"/> Car wheel <input type="checkbox"/> Truck
	<input type="radio"/> <input type="radio"/> <input checked="" type="radio"/>	<input checked="" type="checkbox"/> Fur <input type="checkbox"/> Wool <input checked="" type="checkbox"/> Fur coat
	<input checked="" type="radio"/> <input type="radio"/>	<input checked="" type="checkbox"/> Collie <input type="checkbox"/> Terrier

Image

Main object

Valid Labels

☐

☐ **pedestal or plinth or footstall**

Definition: an architectural support or base (as for a column or statue)

Wikipedia: <https://en.wikipedia.org/wiki/Pedestal>

☐

☐ **obelisk**

Definition: a stone pillar having a rectangular cross section tapering towards a pyramidal top

Wikipedia: <https://en.wikipedia.org/wiki/Obelisk>

☐

☐ **pirate or pirate ship**

Definition: a ship that is manned by pirates

Wikipedia: <https://en.wikipedia.org/wiki/Piracy>


Submit

# Quantifying the Benchmark-Task Alignment of ImageNet


- Multi-object images
  - More than 1/5 of the ImageNet dataset contains at least two objects.
  - Models perform significantly worse on multi-label images based on top-1 accuracy (measured w.r.t. ImageNet labels): accuracy drops by more than 10% across all models.
  - There are pairs of classes which consistently co-occur.
  - Model accuracy is especially low on certain classes that systematically co-occur.
  - A more natural notion of accuracy for multi-object images would be, to consider a model prediction to be correct if it matches the label of any object in the image.




# Multi-Object Images



(a)



(b)



IN label:  
monastery  
  
Objects: 3  
valley  
church  
monastery



IN label:  
mosquito net  
  
Objects: 2  
quilt  
mosquito net



IN label:  
wall clock  
  
Objects: 5  
studio couch  
wall clock  
pillow  
table lamp  
lampshade



IN label:  
cannon  
  
Objects: 2  
tank  
cannon

(c)

Figure 3: (a) Number of objects per image—more than a fifth of the images contains two or more objects from ImageNet classes. (b) Pairs of classes which consistently co-occur as distinct objects. Here, we visualize the top 15 ImageNet classes based on how often their images contain another *fixed* object (“Other label”). (c) Random examples of multi-label ImageNet images (cf. Appendix Figure 17 for additional samples).

# Multi-Object Images: Human-label disagreement




Although models suffer a sizeable accuracy drop on multi-object images, they are still relatively good at predicting the ImageNet label.



This bias could be justified whenever there is a distinct main object in the image, and it corresponds to the ImageNet label.



For nearly a third of the multi-object images, the ImageNet label does not denote the most likely main object as judged by human annotators.



(a)



ImageNet label:  
feather boa  
Main label:  
sunglasses  
Objects: 3  
sunglasses  
sunglass  
feather boa



ImageNet label:  
wooden spoon  
Main label:  
mixing bowl  
Objects: 2  
wooden spoon  
mixing bowl



ImageNet label:  
ladle  
Main label:  
fountain  
Objects: 2  
ladle  
fountain



ImageNet label:  
bulletproof vest  
Main label:  
assault rifle  
Objects: 2  
assault rifle  
bulletproof vest

(b)



# Human-Label disagreement



IN label:  
caldron

Main label:  
street sign

Objects: 2  
street sign  
caldron



IN label:  
assault rifle

Main label:  
military uniform

Objects: 3  
assault rifle  
military uniform  
rifle



IN label:  
Windsor tie

Main label:  
suit

Objects: 2  
Windsor tie  
suit



IN label:  
cleaver

Main label:  
gown

Objects: 2  
cleaver  
gown



IN label:  
bearskin

Main label:  
trombone

Objects: 2  
bearskin  
trombone



IN label:  
water bottle

Main label:  
restaurant

Objects: 3  
goblet  
restaurant  
water bottle



IN label:  
plate

Main label:  
soup bowl

Objects: 2  
plate  
soup bowl



IN label:  
coffeepot

Main label:  
teapot

Objects: 3  
teapot  
cup  
pot



IN label:  
bonnet

Main label:  
wool

Objects: 2  
wool  
bonnet



IN label:  
consomme

Main label:  
plate

Objects: 2  
consomme  
soup bowl



IN label:  
banana

Main label:  
orange

Objects: 2  
orange  
banana



IN label:  
vault

Main label:  
church

Objects: 2  
altar  
church



IN label:  
picket fence

Main label:  
seashore

Objects: 2  
picket fence  
seashore



IN label:  
shoji

Main label:  
sliding door

Objects: 4  
sliding door  
shoji  
dining table  
window shade



IN label:  
sock

Main label:  
Loafer

Objects: 2  
sock  
Loafer



IN label:  
ping-pong ball

Main label:  
upright

Objects: 2  
ping-pong ball  
upright

# Quantifying the Benchmark-Task Alignment of ImageNet

- Bias in label validation
  - Recall that annotators are asked a somewhat leading question, of whether a specific label is present in the image, making them prone to answering positively even for images of a different, yet similar, class.
  - Under the original task setup (i.e., the CONTAIN task), annotators consistently select multiple labels, for nearly 40% of the images, another label is selected at least as often as the ImageNet label.
  - Even when annotators perceive a single object, they often select as many as 10 classes.
  - If instead of asking annotators to judge the validity of a specific label(s) in isolation, asking them to choose the main object among several possible labels simultaneously (i.e., via the CLASSIFY task), they select substantially fewer labels.

# Bias in Label Validation




Figure 8: (a) Number of labels selected in the CONTAINS task: the y-axis measures the number of labels that were selected by at least two annotators; the x-axis measures the average number of objects indicated to be present in the image during the CLASSIFY task; the dot size represents the number of images in each 2D bin. Even when annotators perceive an images as depicting a single object, they often select multiple labels as valid. (b) Number of labels that at least two annotators selected for the main image object (in the CLASSIFY task; cf. Section 3.2) as a function of the number of labels presented to them. Annotator confusion decreases significantly when the task setup explicitly involves choosing between multiple labels *simultaneously*.



# Bias in Label Validation

- Confusing class pairs
  - There are several pairs of ImageNet classes that annotators have trouble telling apart—they consistently select both labels as valid for images of either class.
  - On some of these pairs we see that models still perform well.
  - However, for other pairs, even state-of-the-art models have poor accuracy (below 40%).
  - If that is indeed the case, it is natural to wonder whether accuracy on ambiguous classes can be improved without overfitting to the ImageNet test set.
  - The annotators' inability to remedy overlaps in the case of ambiguous class pairs could be due to the presence of classes that are semantically quite similar, e.g., “rifle” and “assault rifle”.
  - In some cases, there also were errors in the task setup. For instance, there were occasional overlaps in the class names (e.g., “maillot” and “maillot, tank suit”) and Wikipedia links (e.g., “laptop computer” and “notebook computer”) presented to the annotators.






Figure 9: (a) ImageNet class pairs for which annotators often deem both classes as valid. We visualize the top 10 pairs split based on the accuracy of EfficientNet B7 on these pairs being high (*top*) or low (*bottom*). (b) Model progress on ambiguous class pairs (from (a) *bottom*) has been largely stagnant—possibly due to substantial overlap in the class distributions. In fact, models are unable to distinguish between these pairs better than chance (cf. pairwise accuracy).

# Model Evaluation -Beyond Test Accuracy

Human assessment of model predictions

- Selection frequency of the prediction
  - How often annotators select the predicted label as being present in the image (determined using the *CONTAINS* task).
- Accuracy based on main label annotation
  - How frequently the prediction matches the main label for the image, as obtained using our *CLASSIFY* task.





# Human Assessment of Model Predictions – Incorrect Predictions





Figure 11: Distribution of annotator selection frequencies (cf. Section 3.1) for model predictions deemed incorrect w.r.t. the ImageNet label. Models that are more accurate also seem to make fewer mistakes that have low human selection frequency (for the corresponding image-prediction pair).

# Human Assessment of Model Predictions



The predictions of state-of-the-art models have gotten, on average, quite close to ImageNet labels.



That is, annotators are almost equally likely to select the predicted label as being present in the image (or being the main object) as the ImageNet label.



This indicates that model predictions might be closer to what non-expert annotators can recognize as the ground truth.



This also means, we are at a point where we may no longer be able to easily identify (e.g., using crowd-sourcing) the extent to which further gains in accuracy correspond to such improvements.

# Confusion Matrix




Figure 12: Characterizing similarity between model and human predictions (indicated by main object selection in the CONTAINS task): (a) Model (ResNet-50) and human confusion matrices on 11 ImageNet superclasses (cf. Section A.1.1). (b) Superclass co-occurrence matrix: how likely a specific pair of superclasses is to occur together (based on annotation from Section 3.2).

# Conclusion

- There are many images with multiple valid labels, and ambiguous classes in ImageNet.
- Top-1 accuracy often underestimates the performance of models by unduly penalizing them for predicting the label of a different, but also valid, image object.
- Taking a step towards evaluation metrics that overcome these issues, authors utilize human annotators to directly judge the correctness of model predictions.
- On the positive side, they find that models that are more accurate on ImageNet also tend to be more human-aligned in their errors.
- While this might be reassuring, it also indicates that we are at a point where we cannot easily gauge (e.g., via simple crowd-sourcing) whether further progress on the ImageNet benchmark is meaningful, or is simply a result of overfitting to this benchmark's particular characteristics.