

Assisted project 3:

Create a Java program to demonstrate JDBC and Spring Integration:

Pom.xml:

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/maven-v4_0_0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <groupId>SpringSetup</groupId>
  <artifactId>SpringSetup</artifactId>
  <packaging>war</packaging>
  <version>0.0.1-SNAPSHOT</version>
  <name>SpringSetup Maven Webapp</name>
  <url>http://maven.apache.org</url>

  <properties>
    <org.springframework.version>5.1.6.RELEASE</org.springframework.version>
  </properties>

  <dependencies>
    <dependency>
      <groupId>junit</groupId>
      <artifactId>junit</artifactId>
      <version>3.8.1</version>
      <scope>test</scope>
    </dependency>

    <dependency>
      <groupId>org.springframework</groupId>
      <artifactId>spring-core</artifactId>
      <version>${org.springframework.version}</version>
    </dependency>

    <dependency>
      <groupId>org.springframework</groupId>
      <artifactId>spring-expression</artifactId>
      <version>${org.springframework.version}</version>
    </dependency>

    <dependency>
      <groupId>org.springframework</groupId>
      <artifactId>spring-beans</artifactId>
      <version>${org.springframework.version}</version>
    </dependency>

    <dependency>
```

```
<groupId>org.springframework</groupId>
<artifactId>spring-context</artifactId>
<version>${org.springframework.version}</version>
</dependency>
```

```
<dependency>
<groupId>org.springframework</groupId>
<artifactId>spring-context-support</artifactId>
<version>${org.springframework.version}</version>
</dependency>
```

```
<dependency>
<groupId>org.springframework</groupId>
<artifactId>spring-jdbc</artifactId>
<version>${org.springframework.version}</version>
</dependency>
```

```
<dependency>
<groupId>org.springframework</groupId>
<artifactId>spring-orm</artifactId>
<version>${org.springframework.version}</version>
</dependency>
```

```
<dependency>
<groupId>org.springframework</groupId>
<artifactId>spring-web</artifactId>
<version>${org.springframework.version}</version>
</dependency>
```

```
<dependency>
<groupId>org.springframework</groupId>
<artifactId>spring-webmvc</artifactId>
<version>${org.springframework.version}</version>
</dependency>
```

```
<dependency>
<groupId>log4j</groupId>
<artifactId>log4j</artifactId>
<version>1.2.16</version>
<scope>runtime</scope>
</dependency>
```

```
<dependency>
<groupId>javassist</groupId>
<artifactId>javassist</artifactId>
<version>3.12.1.GA</version>
</dependency>
```

USE ecommerce:

```
--
-- Table structure for table `eproduct`
--
```

```

DROP TABLE IF EXISTS `eproduct`;
/*!40101 SET @saved_cs_client = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;
CREATE TABLE `eproduct` (
  `ID` bigint(20) NOT NULL AUTO INCREMENT,
  `name` varchar(100) DEFAULT NULL,
  `price` decimal(10,2) DEFAULT NULL,
  `date added` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP,
  PRIMARY KEY (`ID`)
) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=latin1;
/*!40101 SET character_set_client = @saved_cs_client */;

--
-- Dumping data for table `eproduct`
--

LOCK TABLES `eproduct` WRITE;
/*!40000 ALTER TABLE `eproduct` DISABLE KEYS */;
INSERT INTO `eproduct` VALUES (1, 'HP Laptop ABC', 21900.00, '2019-06-04 07:18:57'), (2, 'Acer Laptop ABC', 23300.00, '2019-06-04 07:19:07'), (3, 'Lenovo Laptop ABC', 33322.00, '2019-06-04 07:19:19');
/*!40000 ALTER TABLE `eproduct` ENABLE KEYS */;
UNLOCK TABLES;

```

EProduct:

```

package com.ecommerce.entity;

import java.math.BigDecimal;
import java.util.Date;
import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.Id;
import javax.persistence.Table;

public class EProductEntity {

    private long ID;
    private String name;
    private BigDecimal price;
    private Date dateAdded;

    public long getID() {return this.ID; }
    public String getName() { return this.name;}
    public BigDecimal getPrice() { return this.price;}
    public Date getDateAdded() { return this.dateAdded;}

    public void setID(long id) { this.ID = id;}
    public void setName(String name) { this.name = name;}
    public void setPrice(BigDecimal price) { this.price = price;}
    public void setDateAdded(Date date) { this.dateAdded = date;}
}

```

```
}
```

EProductDAO:

```
package com.ecommerce.entity;

import java.math.BigDecimal;
import java.util.Date;
import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.Id;
import javax.persistence.Table;

public class EProductEntity {

    private long ID;
    private String name;
    private BigDecimal price;
    private Date dateAdded;

    public long getID() {return this.ID; }
    public String getName() { return this.name;}
    public BigDecimal getPrice() { return this.price;}
    public Date getDateAdded() { return this.dateAdded;}

    public void setID(long id) { this.ID = id;}
    public void setName(String name) { this.name = name;}
    public void setPrice(BigDecimal price) { this.price = price;}
    public void setDateAdded(Date date) { this.dateAdded = date;}
}
```

MainController:

```
package com.ecommerce.controller;

import org.apache.log4j.Logger;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Controller;
import org.springframework.ui.ModelMap;
import org.springframework.validation.BindingResult;
import org.springframework.web.bind.annotation.ModelAttribute;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;
import org.springframework.web.bind.annotation.RequestParam;

import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

import com.ecommerce.entity.EProduct;
```

```

import com.ecommerce.dao.EProductDAO;

@Controller
public class MainController {

    @Autowired
    EProductDAO eproductDAO;

    @RequestMapping(value = "/listProducts", method = RequestMethod.GET)
    public String listProducts(ModelMap map)
    {
        List<EProduct> list= eproductDAO.getProducts();
        model.addAttribute("list",list);
        return "listProducts";
    }
}

```

main-servlet.xml:

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:aop="http://www.springframework.org/schema/aop"
    xmlns:context="http://www.springframework.org/schema/context"
    xmlns:jee="http://www.springframework.org/schema/jee"
    xmlns:lang="http://www.springframework.org/schema/lang"
    xmlns:p="http://www.springframework.org/schema/p"
    xmlns:tx="http://www.springframework.org/schema/tx"
    xmlns:util="http://www.springframework.org/schema/util"
    xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans-2.5.xsd
http://www.springframework.org/schema/aop
http://www.springframework.org/schema/aop/spring-aop-2.5.xsd
http://www.springframework.org/schema/context
http://www.springframework.org/schema/context/spring-context-2.5.xsd
http://www.springframework.org/schema/tx
http://www.springframework.org/schema/tx/spring-tx-2.5.xsd">
    <context:annotation-config />
    <context:component-scan base-package="com.ecommerce.controller" />
    <bean id="jspViewResolver"
        class="org.springframework.web.servlet.view.InternalResourceViewResolver">
        <property name="viewClass"
            value="org.springframework.web.servlet.view.JstlView"></property>
        <property name="prefix" value="/WEB-INF/view/"></property>
        <property name="suffix" value=".jsp"></property>
    </bean>
    <bean id="messageSource"
        class="org.springframework.context.support.ReloadableResourceBundleMessageSource">
        <property name="basename" value="classpath:messages"></property>
        <property name="defaultEncoding" value="UTF-8"></property>
    </bean>

```

```

<bean id="dataSource"
    <u>class</u>="org.apache.commons.dbcp.BasicDataSource" destroy-method="close"
    p:driverClassName="`${jdbc.driverClassName}`"
    p:url="`${jdbc.databaseurl}`" p:username="`${jdbc.username}`"
    p:password="`${jdbc.password}`"></bean>

    <bean id="ds"
    <u>class</u>="org.springframework.jdbc.datasource.DriverManagerDataSource">
        <property name="driverClassName"
    value="com.mysql.jdbc.Driver"></property>
        <property name="url"
    value="jdbc:mysql://localhost:3306/ecommerce"></property>
        <property name="username" value="root"></property>
        <property name="password" value="master"></property>
    </bean>

    <bean id="jt" class="org.springframework.jdbc.core.JdbcTemplate">
        <property name="dataSource" ref="ds"></property>
    </bean>

    <bean id="dao" class="com.ecommerce.dao.EProductDAO">
        <property name="template" ref="jt"></property>
    </bean>

    <tx:annotation-driven />
    <bean id="transactionManager"
        <u>class</u>="org.springframework.orm.hibernate3.HibernateTransactionManager">
        <property name="sessionFactory" ref="sessionFactory"></property>
    </bean>
</beans>

```

Index.jsp:

```

<html>
<body>
<h2>Spring Application</h2>

<a href="listProducts">List Products</a>
</body>
</html>

```

Listproducts.jsp:

```

<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
    <%@ taglib uri="http://www.springframework.org/tags/form" prefix="form"%>
    <%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>

<!DOCTYPE html>
<html>

```

```

<head>
<meta charset="UTF-8">
<title>List Products</title>
</head>
<body>
  <c:forEach var="product" items="${list}">
    ${product.name}, ${product.price}, ${product.dateAdded}<br>
  </c:forEach>

</body>
</html>

```

Web.xml:

```

<?xml version="1.0" encoding="UTF-8"?>
<web-app xmlns="http://java.sun.com/xml/ns/javaee"
version="2.5"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://java.sun.com/xml/ns/javaee
http://java.sun.com/xml/ns/javaee/web-app_2_5.xsd">

  <display-name>Archetype Created Web Application</display-name>

  <welcome-file-list>
    <welcome-file>/WEB-INF/view/index.jsp</welcome-file>
  </welcome-file-list>
  <servlet>
    <servlet-name>main</servlet-name>
    <servlet-class>
      org.springframework.web.servlet.DispatcherServlet
    </servlet-class>
    <load-on-startup>1</load-on-startup>
  </servlet>
  <servlet-mapping>
    <servlet-name>main</servlet-name>
    <url-pattern>/</url-pattern>
  </servlet-mapping>
  <context-param>
    <param-name>contextConfigLocation</param-name>
    <param-value>/WEB-INF/main-servlet.xml</param-value>
  </context-param>
  <listener>
    <listener-
class>org.springframework.web.context.ContextLoaderListener</listener-class>
    </listener>
  </web-app>

```