

Assisted Project 1: Configure Hibernate in Eclipse IDE.

Index.html:

```
<?xml version="1.0" encoding="UTF-8"?>
<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://xmlns.jcp.org/xml/ns/javaee"
xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/javaee http://xmlns.jcp.org/xml/ns/javaee/web-
app_3_1.xsd" id="WebApp_ID" version="3.1">
  <display-name>phasehibernatedemo</display-name>
  <welcome-file-list>
    <welcome-file>index.html</welcome-file>
    <welcome-file>index.jsp</welcome-file>
    <welcome-file>index.htm</welcome-file>
    <welcome-file>default.html</welcome-file>
    <welcome-file>default.jsp</welcome-file>
    <welcome-file>default.htm</welcome-file>
  </welcome-file-list>
</web-app>
```

Hibernate.cfg.xml:

```
<?xml version='1.0' encoding='utf-8'?>
<!DOCTYPE hibernate-configuration PUBLIC
"-//Hibernate/Hibernate Configuration DTD 3.0//EN"
"http://www.hibernate.org/dtd/hibernate-configuration-3.0.dtd">
<hibernate-configuration>
  <session-factory>
    <!-- Database connection settings -->
    <property name="connection.driver_class">com.mysql.cj.jdbc.Driver</property>
    <property name="connection.url">jdbc:mysql://localhost:3306/ecommerce</property>
    <property name="connection.username">root</property>
    <property name="connection.password">Vinny@123</property>

  </session-factory>
</hibernate-configuration>
```

InitDemo.java:

```
package com.simpli;
import java.io.IOException;
import java.io.PrintWriter;

import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
```

```

import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;

import org.hibernate.Session;
import org.hibernate.SessionFactory;

@WebServlet("/init")
public class InitDemo extends HttpServlet {
    private static final long serialVersionUID = 1L;

    protected void doGet(HttpServletRequest request, HttpServletResponse response)
        throws ServletException, IOException {

        PrintWriter out = response.getWriter();
        out.println("<html><body>");

        // STEP 1: Get a Session (connection) from the Session Factory class
        SessionFactory factory = HibernateUtil.getSessionFactory();

        Session session = factory.openSession();

        out.println("Hibernate Session opened.<br>");

        session.close();

        out.println("Hibernate Session closed.<br>");

        // STEP 2 execute the HQL commands
        // for now we will only test if the connection is established with MySQL server.

        out.println("</body></html>");

    }
}

```

HibernateUtil.Java:
package com.simpli;

```

import org.hibernate.SessionFactory;
import org.hibernate.boot.*;
import org.hibernate.boot.registry.*;

```

```

public class HibernateUtil {

    private static final SessionFactory sessionFactory;

    static {
        try {
            StandardServiceRegistry standardRegistry = new StandardServiceRegistryBuilder()
                .configure("hibernate.cfg.xml").build();

            Metadata metaData = new MetadataSources(standardRegistry).getMetadataBuilder().build();
            sessionFactory = metaData.getSessionFactoryBuilder().build();

        } catch (Throwable th) {
            throw new ExceptionInInitializerError(th);
        }
    }

    public static SessionFactory getSessionFactory() {
        return sessionFactory;
    }
}

```

