1. Write a program to demonstrate the differences between GET and POST using servlet.

Index.html:

```
<!DOCTYPE html>
<html>
<head>
<meta charset="ISO-8859-1">
<title>Insert title here</title>
</head>
<body>
<a href="GetHandler?name=John+Doe&address=145+Lake+Avenue">Do a Servlet
GET</a><br><br><
<form name=frm method="post" action="PostHandler">
  Name <input name="name" id="name" maxlength=50><br>
  Address <input name="address" id="address" maxlength=100><br>
  <button>Submit
</form>
</body>
</html>
GetHandler.java
import java.io.IOException;
```

```
import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
 * <u>Servlet</u> implementation class GetHandler
@WebServlet("/GetHandler")
public class GetHandler extends HttpServlet {
      private static final long serialVersionUID = 1L;
    /**
     * @see HttpServlet#HttpServlet()
    public GetHandler() {
        super();
        // TODO Auto-generated constructor stub
    }
       * @see HttpServlet#doGet(HttpServletRequest request, HttpServletResponse
response)
```

```
*/
      protected void doGet(HttpServletRequest request, HttpServletResponse response)
throws ServletException, IOException {
             // TODO Auto-generated method stub
             response.getWriter().append("Served at:
").append(request.getContextPath());
      }
       * @see HttpServlet#doPost(HttpServletRequest request, HttpServletResponse
response)
      protected void doPost(HttpServletRequest request, HttpServletResponse
response) throws ServletException, IOException {
             // TODO Auto-generated method stub
             doGet(request, response);
      }
}
PostHandler:
import java.io.IOException;
import java.io.PrintWriter;
import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
/**
* Servlet implementation class PostHandler
@WebServlet("/PostHandler")
public class PostHandler extends HttpServlet {
        private static final long serialVersionUID = 1L;
    /**
* @see HttpServlet#HttpServlet()
    public PostHandler() {
        super();
        // TODO Auto-generated constructor stub
    }
        * @see HttpServlet#doGet(HttpServletRequest request, HttpServletResponse
response)
        protected void doGet(HttpServletRequest request, HttpServletResponse
response) throws ServletException, IOException {
                // TODO Auto-generated method stub
```

```
}
        /**
         * @see HttpServlet#doPost(HttpServletRequest request, HttpServletResponse
response)
        protected void doPost(HttpServletRequest request, HttpServletResponse
response) throws ServletException, IOException {
                // TODO Auto-generated method stub
                  PrintWriter out = response.getWriter();
                    out.println("<html><body>");
                    String name = request.getParameter("name");
                    String address = request.getParameter("address");
                    out.println("Name=" + name + "<br>Address=" + address);
                    out.println("</body></html>");
        }
}
Web.xml:
<?xml version="1.0" encoding="UTF-8"?>
<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"</pre>
xmlns="http://xmlns.jcp.org/xml/ns/javaee"
xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/javaee
http://xmlns.jcp.org/xml/ns/javaee/web-app_3_1.xsd" id="WebApp_ID" version="3.1">
  <display-name>assisted1</display-name>
  <welcome-file-list>
    <welcome-file>index.html</welcome-file>
    <welcome-file>index.jsp</welcome-file>
    <welcome-file>index.htm</welcome-file>
    <welcome-file>default.html</welcome-file>
    <welcome-file>default.jsp</welcome-file>
    <welcome-file>default.htm</welcome-file>
  </welcome-file-list>
</web-app>
```

Output:



