

1.3 Weitere Listenmethoden

Neben `add(DataElement data)`, `size()`, `print()` und `remove(DataElement compare)` verfügen Listen noch über weitere Methoden. Besprechen Sie mit ihrem Nachbarn wie die Methoden umgesetzt werden können. Notieren Sie Pseudocode und markieren / notieren Sie Schwierigkeiten bei der Umsetzung. Notieren Sie während der Implementierung auch Ihren Java Code.

0. removeHead() { //in der Klasse List

[illegible]

1. removeTail() { //in der Klasse Node

A blank sheet of graph paper featuring a uniform grid of small squares. A vertical column of squares, located approximately one-third of the way from the left edge, is shaded gray, extending across all rows of the page. The rest of the grid consists of unshaded white squares.

2. addHead(DataElement data) { //in der Klasse List

[illegible]

3. `addBefore(_____, _____) { //in Node`

[illegible]

[illegible]A full-page sheet of white graph paper with a light gray grid. The grid consists of small squares, approximately 10 units wide by 10 units high. A vertical column of squares, located roughly in the center of the page, is shaded gray from top to bottom, serving as a margin or reference line.[illegible]A blank grid of 20 columns and 10 rows. A vertical gray line is positioned between the 10th and 11th columns, dividing the grid into two equal halves of 10 columns each. The grid is composed of small squares, and the vertical line is a solid gray bar.