RESEARCH PAPER SUMMARY

PCA and Elastic Net vs Double Descent

How dimensionality reduction and structured regularization change instability in high-degree polynomial regression.

100	1-129	80 / 20	2
SYNTHETIC SAMPLES	POLYNOMIAL DEGREES	TRAIN / TEST SPLIT	STABILIZATION METHODS

Central finding. PCA and Elastic Net both control the instability associated with double descent, but they do so differently. PCA removes low-variance directions and can eliminate the sharp test-error spike. Elastic Net shrinks and sparsifies coefficients, producing a heavily smoothed curve that may prevent the model from reaching the overfitting regime.

AUTHORS

Mourad Gad
Iliyas Shaizada

Menoufia National University, Egypt
Cardiff University Kazakhstan, Kazakhstan

SUPERVISOR

Dr. Ahmed Elsayed

Menoufia National University
Faculty of Engineering, Menoufia University, Egypt
ahmed.elsayed.melegy.nassar@gmail.com

1. Research problem and core ideas

The paper investigates double descent: a non-monotonic relationship between model complexity and generalization error. Instead of test error following only the classical U-shaped bias-variance curve, error can rise sharply near the interpolation threshold and then fall again as the model becomes even more over-parameterized.

1. Classical descent

Increasing complexity reduces bias, so test error falls.

2. Interpolation peak

Near parameters = samples, the model can fit noise and test error spikes.

3. Second descent

Beyond interpolation, some over-parameterized solutions can generalize better again.

Why the interpolation region becomes unstable

When the number of effective parameters approaches the number of training samples, some eigenvalues of the Gram matrix become very small. The fitted coefficients can then react strongly to small perturbations and noise, producing large variance and a spike in test mean squared error.

Research question: Can PCA or Elastic Net control the unstable directions and coefficients that produce this behavior in polynomial regression?

PCA: change the feature space

Action	Mechanism	Expected effect
Center and rotate the polynomial features	Produces orthogonal principal components ordered by captured variance	Removes correlation between transformed predictors
Retain only leading components	Drops directions with very small variance	Reduces effective dimensionality and variance amplification
Retain nearly all components	Keeps unstable low-variance directions	Repeated or sharp test-error spikes can remain

Elastic Net: constrain the coefficients

Elastic Net combines L1 regularization, which promotes sparse coefficients, with L2 regularization, which shrinks coefficients and stabilizes groups of correlated predictors. In this paper it acts more strongly than PCA: rather than merely reshaping the peak, it heavily smooths the regression path and prevents large high-degree error spikes.

Difference in mechanism: PCA removes unstable directions before regression; Elastic Net keeps the expanded feature space but limits how strongly the fitted model can use it.

2. Experimental methodology

The experiments use a deliberately small synthetic nonlinear regression problem so that model complexity can be increased beyond the number of available samples. This makes the interpolation and over-parameterized regimes visible.

100	1	1-129	MSE
SAMPLES	INPUT VARIABLE	DEGREE RANGE	EVALUATION METRIC

Dataset and target

Inputs are sampled uniformly from -1 to 1. The target is **y = sin(2*pi*X) + noise**, where the added Gaussian noise has standard deviation 1. A fixed random seed is used for an 80% training and 20% test split.

Compared configurations

Configuration	Exact setting	Purpose
Polynomial regression baseline	Degrees 1 through 129; regression on the full polynomial basis	Reveal instability as effective parameter count increases
PCA plus regression	Several retained-variance levels, ranging from almost 100% down to 95%	Measure how discarding low-variance directions changes the curve
Elastic Net	alpha = 0.02; L1 ratios 0.2, 0.4, 0.5, 0.7, and 0.9	Compare different mixtures of sparsity and L2 shrinkage

Data journey

Generate noisy sine data	Create polynomial features	Apply PCA or Elastic Net	Record train/test MSE
100 samples one input variable	Degree 1 to 129	Vary retained variance or L1 ratio	Plot error against degree

Evaluation

For every polynomial degree, training and test mean squared error are calculated. MSE averages the squared difference between observed and predicted targets, so large unstable predictions are penalized heavily. The implementation uses Python, NumPy, scikit-learn, and Matplotlib in a CPU-only environment.

This design makes the comparison interpretable: polynomial degree changes model complexity, PCA changes effective dimensionality, Elastic Net changes coefficient freedom, and train/test MSE shows the resulting stability or instability.

3. PCA findings

PCA changes the double-descent curve by controlling the effective number and geometry of the polynomial features. The paper's strongest contrast is between retaining almost every principal component and retaining only enough components to explain 95% of the variance.




Figure 2 from the paper. With nearly 100% retained variance, test MSE becomes extremely unstable at high polynomial degrees, while training error sometimes approaches zero.




Figure 4 from the paper. At 95% retained variance, both curves remain smooth; the sharp high-degree test-error spikes disappear.

Interpretation

Observation	Interpretation
Nearly full variance retention preserves repeated spikes	Orthogonalization alone does not guarantee stability when low-variance directions remain
Lower retention reduces the effective parameter count	The model moves away from the most unstable near-singular regime
The 95% curve becomes nearly flat	Discarding low-variance components suppresses variance amplification, but also limits the complexity the model can express

4. Elastic Net findings and overall conclusion

Elastic Net produces a different form of stabilization. With alpha fixed at 0.02, the combined L1 and L2 penalty keeps the fitted polynomial from developing large coefficients as degree increases. Train and test MSE therefore change only slightly after the first few degrees.




Figure 5. Elastic Net train and test MSE remain smooth across degrees.




Figure 6. Degree-129 fits for five L1 ratios are similar and strongly regularized.

PCA and Elastic Net compared

Method	What it controls	Effect reported in the paper	Main trade-off
PCA	Number and variance of retained feature directions	Progressively removes spikes; at 95% retention the curve is stable	Too much reduction may prevent interpolation and remove useful detail
Elastic Net	Magnitude and sparsity of fitted coefficients	Heavily smooths high-degree regression across all tested L1 ratios	Regularization may be strong enough to prevent the double-descent regime entirely

Overall conclusion

The paper concludes that low-variance directions are a major source of instability in this synthetic polynomial-regression setting. PCA can eliminate the sharp interpolation spike by discarding those directions. Elastic Net reaches stability through coefficient shrinkage and sparsity, producing a smoother but more strongly constrained model.

Scope and limitations

The evidence comes from one synthetic dataset with 100 samples, one 80/20 split, one noise level, and a single Elastic Net alpha. The results demonstrate mechanisms clearly, but they should not yet be generalized to large real-world datasets without repeated seeds, confidence intervals, wider hyperparameter searches, and additional datasets.

Reference foundation

The paper builds on work by Gedon, Ribeiro, and Schon on principal-component regression and double descent; Nakkiran et al. on deep double descent; Zou and Hastie on Elastic Net; Bach on random projections; Pezeshki et al. on multi-scale feature learning; and Yilmaz and Heckel on regularization-wise double descent.