

SPEC® CFP2006 Result

Copyright 2006-2026 Standard Performance Evaluation Corporation

Microsoft Corporation

(Test Sponsor: Kenji Mouri)

Azure Standard D64as v7

SPECfp®2006 =

Not Run

SPECfp_base2006 =

88.6

CPU2006 license: 3939


Test sponsor: Kenji Mouri

Tested by: Misaki

Test date: Feb-2026

Hardware Availability: Feb-2026

Software Availability: Jan-2026



Hardware

CPU Name: AMD EPYC 9V45 96-Core
CPU Characteristics: AMD EPYC 9V45 96-Core @ 4.6GHz
CPU MHz: 4600
FPU: Integrated
CPU(s) enabled: 32 cores, 1 chip, 32 cores/chip, 2 threads/core
CPU(s) orderable: 1 chips
Primary Cache: 1 MB I + 1.5 MB D on chip per core
Secondary Cache: 32 MB I+D on chip per core

Continued on next page

Software

Operating System: Debian GNU/Linux 12 (bookworm)
6.1.0-43-cloud-amd64
Compiler: C/C++/Fortran: Version 12.2.0 of GCC, the GNU Compiler Collection
Auto Parallel: No
File System: ext4
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2026 Standard Performance Evaluation Corporation

Microsoft Corporation
(Test Sponsor: Kenji Mouri)

Azure Standard D64as v7

SPECfp2006 = Not Run

SPECfp_base2006 = 88.6

CPU2006 license: 3939

Test sponsor: Kenji Mouri

Tested by: Misaki

Test date: Feb-2026

Hardware Availability: Feb-2026

Software Availability: Jan-2026

L3 Cache: 512 MB
Other Cache: None
Memory: 256 GB
Disk Subsystem: 256 GB Premium SSD
Other Hardware: None

Peak Pointers: Not Applicable
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	80.4	169	80.6	169	80.3	169						
416.gamess	232	84.5	231	84.8	231	84.9						
433.milc	143	64.2	144	63.8	145	63.2						
434.zeusmp	99.5	91.4	99.6	91.4	99.7	91.3						
435.gromacs	122	58.5	122	58.5	122	58.4						
436.cactusADM	124	96.6	125	95.7	125	95.9						
437.leslie3d	95.2	98.8	95.7	98.2	99.6	94.3						
444.namd	134	59.7	135	59.6	134	59.8						
447.dealII	108	106	108	106	108	106						
450.soplex	86.4	96.6	88.8	94.0	87.0	95.8						
453.povray	49.7	107	49.8	107	49.8	107						
454.calculix	262	31.5	262	31.5	261	31.6						
459.GemsFDTD	104	102	105	101	105	101						
465.tonto	135	72.7	136	72.2	135	72.7						
470.lbm	75.3	182	75.5	182	75.6	182						
481.wrf	124	89.9	125	89.2	125	89.3						
482.sphinx3	170	115	169	115	170	115						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

Sysinfo program /home/misaki/Library/cpu2006/Docs/sysinfo.new
Revision 6993 of 2015-11-06 (b5e8d4b4eb51ed28d7f98696cbe290c1)
running on HimiMisakiBenchmarkAMD64 Wed Feb 18 05:30:14 2026

This section contains SUT (System Under Test) info as seen by
some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo
model name : AMD EPYC 9V45 96-Core Processor
1 "physical id"s (chips)
64 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2026 Standard Performance Evaluation Corporation

Microsoft Corporation
(Test Sponsor: Kenji Mouri)

SPECfp2006 = Not Run

Azure Standard D64as v7

SPECfp_base2006 = 88.6

CPU2006 license: 3939

Test sponsor: Kenji Mouri

Tested by: Misaki

Test date: Feb-2026

Hardware Availability: Feb-2026

Software Availability: Jan-2026

Platform Notes (Continued)

```
caution.)
cpu cores : 32
siblings : 64
physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21
                22 23 24 25 26 27 28 29 30 31
cache size : 1024 KB
```

```
From /proc/meminfo
MemTotal:      263921476 kB
HugePages_Total:    0
Hugepagesize:    2048 kB
```

```
/usr/bin/lsb_release -d
Debian GNU/Linux 12 (bookworm)
```

```
From /etc/*release* /etc/*version*
cloud-release:
ID=azure
VERSION="20260210-2384"
debian_version: 12.13
os-release:
PRETTY_NAME="Debian GNU/Linux 12 (bookworm)"
NAME="Debian GNU/Linux"
VERSION_ID="12"
VERSION="12 (bookworm)"
VERSION_CODENAME=bookworm
ID=debian
HOME_URL="https://www.debian.org/"
SUPPORT_URL="https://www.debian.org/support"
```

```
uname -a:
Linux HimiMisakiBenchmarkAMD64 6.1.0-43-cloud-amd64 #1 SMP PREEMPT_DYNAMIC
Debian 6.1.162-1 (2026-02-08) x86_64 GNU/Linux
```

```
run-level 5 Feb 17 04:26
```

```
SPEC is set to: /home/misaki/Library/cpu2006
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/nvme0n1p1 ext4  252G   8.2G  233G   4% /
```

(End of data from sysinfo program)

Base Compiler Invocation

C benchmarks:
gcc

C++ benchmarks:
g++

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2026 Standard Performance Evaluation Corporation

Microsoft Corporation

(Test Sponsor: Kenji Mouri)

Azure Standard D64as v7

SPECfp2006 =

Not Run

SPECfp_base2006 =

88.6

CPU2006 license: 3939

Test sponsor: Kenji Mouri

Tested by: Misaki

Test date: Feb-2026

Hardware Availability: Feb-2026

Software Availability: Jan-2026

Base Compiler Invocation (Continued)

Fortran benchmarks:

gfortran

Benchmarks using both Fortran and C:

gcc gfortran

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64 -fsigned-char

Base Optimization Flags

C benchmarks:

-std=gnu89 -m64 -march=native -mprefer-vector-width=512 -O2 -flto
-fno-strict-aliasing

C++ benchmarks:

-std=c++03 -m64 -march=native -mprefer-vector-width=512 -O2 -flto
-fno-strict-aliasing

Fortran benchmarks:

-std=legacy -m64 -march=native -mprefer-vector-width=512 -O2 -flto
-fno-strict-aliasing

Benchmarks using both Fortran and C:

-std=gnu89 -m64 -std=legacy -march=native -mprefer-vector-width=512
-O2 -flto -fno-strict-aliasing

SPEC CFP2006 Result

Copyright 2006-2026 Standard Performance Evaluation Corporation

Microsoft Corporation

(Test Sponsor: Kenji Mouri)

Azure Standard D64as v7

SPECfp2006 =

Not Run

SPECfp_base2006 =

88.6

CPU2006 license: 3939

Test sponsor: Kenji Mouri

Tested by: Misaki

Test date: Feb-2026

Hardware Availability: Feb-2026

Software Availability: Jan-2026

Base Other Flags

Fortran benchmarks:

416.gamess: -funconstrained-commons

Benchmarks using both Fortran and C:

481.wrf: -fallow-argument-mismatch

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Wed Feb 18 07:36:58 2026 by SPEC CPU2006 PS/PDF formatter v6401.