

Shiv Nadar University Chennai

CS3807 – Deep Learning Laboratory

Experiment 3

Implementation of Convolutional Neural Networks (CNNs) for Image Classification

Degree & Branch	B.Tech Artificial Intelligence & Data Science	Semester V
Subject Code & Name	CS3807 – Deep Learning Laboratory	AY: 2026– 27

1. Objective

To understand the working principle of Convolutional Neural Networks by implementing convolution, pooling, feature map visualization, and image classification using TensorFlow/Keras.

2. Learning Outcomes

Students will be able to

1. Explain the convolution operation.
2. Compute output dimensions using stride and padding.
3. Visualize feature maps.
4. Implement max pooling and average pooling.
5. Calculate CNN parameters.
6. Build a CNN for image classification.
7. Evaluate CNN performance.

3. Background Theory

A Convolutional Neural Network consists of

- Convolution Layer
- Activation Layer
- Pooling Layer
- Fully Connected Layer

The convolution operation is

$$Y(i, j) = \sum_m \sum_n X(i + m, j + n) K(m, n)$$

where

- X : Input Image
- K : Kernel (Filter)
- Y : Feature Map

The output feature map size is

$$\frac{N - F + 2P}{S} + 1$$

where

N Input Size

F Filter Size

P Padding

S Stride

3.1 Common Convolution Kernels

A **kernel** (or **filter**) is a small matrix that slides over an input image to extract important visual features such as edges, textures, corners, and smooth regions. During convolution, the kernel is multiplied element-wise with the corresponding image pixels, and the results are summed to produce a single value in the output feature map. Different kernels highlight different image characteristics.

1. Identity Kernel

The identity kernel preserves the original image without modifying its pixel values.

$$\begin{bmatrix} 0 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Purpose:

- Preserves the original image.
- Used for understanding the convolution operation.

2. Sobel-X Kernel (Vertical Edge Detection)

The Sobel-X kernel detects **vertical edges** by measuring intensity changes along the horizontal direction.

$$\begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}$$

Applications:

- Object detection
- Lane detection
- Face recognition

3. Sobel-Y Kernel (Horizontal Edge Detection)

The Sobel-Y kernel detects **horizontal edges** by measuring intensity changes along the vertical direction.

$$\begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix}$$

Applications:

- Text detection
- Boundary extraction
- Medical image analysis

4. Laplacian Kernel

The Laplacian kernel detects edges in all directions using the second-order derivative of image intensity.

$$\begin{bmatrix} 0 & -1 & 0 \\ -1 & 4 & -1 \\ 0 & -1 & 0 \end{bmatrix}$$

Applications:

- Edge enhancement
- Satellite image analysis
- Medical imaging

5. Sharpening Kernel

This kernel enhances fine details by emphasizing high-frequency components.

$$\begin{bmatrix} 0 & -1 & 0 \\ -1 & 5 & -1 \\ 0 & -1 & 0 \end{bmatrix}$$

Applications:

- Image enhancement
- Optical Character Recognition (OCR)
- Face recognition

6. Box Blur Kernel

The Box Blur kernel smooths an image by replacing each pixel with the average of its neighboring pixels.

$$\frac{1}{9} \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$$

Applications:

- Noise removal
- Image smoothing
- Image preprocessing

7. Gaussian Blur Kernel

Gaussian blur smooths the image while preserving the overall structure better than a simple average filter.

$$\frac{1}{16} \begin{bmatrix} 1 & 2 & 1 \\ 2 & 4 & 2 \\ 1 & 2 & 1 \end{bmatrix}$$

Applications:

- Noise reduction
- Computer vision preprocessing
- Feature extraction

8. Emboss Kernel

The Emboss kernel creates a three-dimensional appearance by emphasizing directional changes in intensity.

$$\begin{bmatrix} -2 & -1 & 0 \\ -1 & 1 & 1 \\ 0 & 1 & 2 \end{bmatrix}$$

Applications:

- Texture analysis
- Artistic image effects

9. Outline Detection Kernel

This kernel highlights object boundaries by emphasizing regions with rapid intensity changes.

$$\begin{bmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{bmatrix}$$

Applications:

- Image segmentation
- Boundary detection
- Shape extraction

10. Motion Blur Kernel

This kernel simulates motion blur along the diagonal direction.

$$\frac{1}{5} \begin{bmatrix} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 & 1 \end{bmatrix}$$

Applications:

- Motion simulation
- Image restoration
- Video processing

Summary of Common Kernels

Kernel	Size	Purpose	Applications
Identity	3×3	Preserve original image	Baseline comparison
Sobel-X	3×3	Detect vertical edges	Object detection
Sobel-Y	3×3	Detect horizontal edges	Boundary detection
Laplacian	3×3	Detect edges in all directions	Medical imaging
Sharpen	3×3	Enhance details	Image enhancement
Box Blur	3×3	Smooth image	Noise removal
Gaussian Blur	3×3	Reduce noise	Computer vision
Emboss	3×3	3D effect	Artistic filtering
Outline	3×3	Boundary extraction	Segmentation
Motion Blur	5×5	Simulate motion	Video processing

4. Numerical Example 1: Convolution

Consider the following input image.

$$X = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

Kernel

$$K = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

Output

First position

$$1(1) + 2(0) + 4(0) + 5(1) = 6$$

Second position

$$2(1) + 3(0) + 5(0) + 6(1) = 8$$

Third position

$$4(1) + 5(0) + 7(0) + 8(1) = 12$$

Fourth position

$$5(1) + 6(0) + 8(0) + 9(1) = 14$$

Feature Map

$$\begin{bmatrix} 6 & 8 \\ 12 & 14 \end{bmatrix}$$

5. Numerical Example 2: Max Pooling

Feature map

$$\begin{bmatrix} 1 & 5 & 2 & 3 \\ 7 & 8 & 1 & 0 \\ 4 & 6 & 9 & 5 \\ 2 & 3 & 1 & 8 \end{bmatrix}$$

Using a 2×2 max pooling filter,
Window 1

$$\begin{bmatrix} 1 & 5 \\ 7 & 8 \end{bmatrix} \rightarrow 8$$

Window 2

$$\begin{bmatrix} 2 & 3 \\ 1 & 0 \end{bmatrix} \rightarrow 3$$

Window 3

$$\begin{bmatrix} 4 & 6 \\ 2 & 3 \end{bmatrix} \rightarrow 6$$

Window 4

$$\begin{bmatrix} 9 & 5 \\ 1 & 8 \end{bmatrix} \rightarrow 9$$

Output

$$\begin{bmatrix} 8 & 3 \\ 6 & 9 \end{bmatrix}$$

6. Numerical Example 3: Parameter Calculation

Suppose

Input Image

$$32 \times 32 \times 3$$

Convolution Layer

- Filters = 16
- Kernel = 3×3

Parameters

$$(3 \times 3 \times 3 + 1) \times 16$$

$$= (27 + 1) \times 16$$

$$= 448$$

Therefore,
Total trainable parameters = 448.

7. Dataset

Dataset: CIFAR-10

- Training Images : 50,000
- Testing Images : 10,000
- Classes : 10
- Image Size : $32 \times 32 \times 3$

8. Experimental Procedure

Task 1

Load CIFAR-10.

- Display ten sample images.
- Print dataset dimensions.
- Plot class distribution.

Task 2

Implement a convolution layer.

Compare

- Kernel = 3×3
- Kernel = 5×5
- Kernel = 7×7

Record feature map sizes.

Task 3

Study hyperparameters.

Compare

- Stride = 1
- Stride = 2
- Padding = Same
- Padding = Valid

Compute output dimensions.

Task 4

Visualize feature maps after the first convolution layer.

Display at least eight feature maps.

Task 5

Compare

- Max Pooling
- Average Pooling

Compare output size and accuracy.

Task 6

Construct the following CNN.

Input $\rightarrow$ *Conv* $\rightarrow$ *ReLU* $\rightarrow$ *MaxPool* $\rightarrow$ *Conv* $\rightarrow$ *ReLU* $\rightarrow$ *MaxPool* $\rightarrow$ *Flatten* $\rightarrow$ *Dense* $\rightarrow$ *Softmax*

Train for

- Optimizer : Adam
- Epochs : 20
- Batch Size : 32

Task 7

Evaluate

- Accuracy
- Precision
- Recall
- F1-score
- Confusion Matrix
- Classification Report

9. Mandatory Plots

Generate

1. Sample Images
2. Class Distribution
3. Training Accuracy
4. Validation Accuracy
5. Training Loss
6. Validation Loss
7. Feature Maps
8. Confusion Matrix

Write a 2–3 line inference for each plot.

10. Additional Exercises

1. Calculate the output size for a 64×64 image using a 5×5 kernel with stride 2 and padding 2.
2. Compute the trainable parameters of a convolution layer having 64 filters of size 3×3 and an RGB input.
3. Compare ReLU and Sigmoid activation functions.
4. Replace Max Pooling with Average Pooling and compare the results.
5. Increase the number of convolution filters from 16 to 64 and analyze the effect on accuracy and computation time.

11. Results

Record

- Training Accuracy
- Testing Accuracy
- Precision
- Recall
- F1-score
- Number of Parameters

12. Discussion

Answer the following.

1. Why is convolution preferred over fully connected layers for images?
2. How does stride affect the feature map size?
3. What is the role of padding?
4. Why is pooling used?
5. How do feature maps represent image characteristics?
6. Why do CNNs require fewer parameters than MLPs?

13. References

1. Goodfellow et al., *Deep Learning*.
2. Bishop, *Pattern Recognition and Machine Learning*.
3. Haykin, *Neural Networks and Learning Machines*.
4. TensorFlow Documentation.
5. CIFAR-10 Dataset Documentation.