

[Control Variables]

Function

- Changes the value stored in a variable.

Settings

The screenshot shows the 'Control Variables' dialog box. It has three main sections: 'Variable', 'Operation', and 'Operand'.
- In the 'Variable' section, the 'Single' radio button is selected, and the text box contains '0001:Original'.
- In the 'Operation' section, the 'Set' radio button is selected.
- In the 'Operand' section, the 'Random' radio button is selected, and the two text boxes contain '0' and '0' respectively.
At the bottom of the dialog are three buttons: 'OK', 'Cancel', and 'Help'.

- Carries out [Operation] using the values and options specified under [Operand] on the variable specified under [Variable].
- Under [Variable], specify the variable to operate on using one of the 3 following methods.
 - Single** Operates on a single variable. Click the [...] button to display the [Variables] window, and specify the variable to operate.
 - Batch** Enter the start and end points of the range of variables to modify. All variables within this range will be operated upon.
The variable with the same number as the value stored in the given variable will be operated on.
For example, if variable no. 2 is specified which contains “5” at the time the command is processed, variable no. 5 will become the target of this command.
 - Variable** The variable to be used can be specified by clicking the [...] button to open the [Variables] window, from which the number of the variable can be chosen.
- Under [Operation], choose one of the following operations to perform on the variable specified in [Variable].
 - Set** Sets the variable's value to the value specified as the operand.
 - Add** Adds the operand value to the variable's original value and stores it in the variable.
 - Subtract** Subtracts the operand value from the variable's original value and stores it in the variable.
 - Multiply** Multiplies the operand value by the variable's original value and stores it in the variable.
 - Divide** Divides the variable's original value by the operand and stores it in the variable.
 - Modulus** Divides the variable's original value by the operand and stores the remainder in the variable.
- Under [Operand], specify the value to use in the variable calculation using one of the following methods.
 - Constant** Uses the given constant value.
 - Variable** The value stored in the given variable will be used.
For example, if variable no. 5 is specified which contains “2” at the time the command is processed, 2 will be used.

Variable ID (Number of the Variable)	The variable to be used can be specified by clicking the [...] button to open the [Variables] window, from which the number of the variable can be chosen. Refers to the value in the specified variable and uses the variable that corresponds to that value. For example, if variable no. 5 is specified which contains “2” at the time the command is processed, variable no. 2's value will be used. The variable to be used can be specified by clicking the [...] button to open the [Variables] window, from which the number of the variable can be chosen.
Random	Uses a number randomized within a given range. Random numbers are values that are randomized during the game. For example, if the range “0~100” is specified, the value used will be a random number above 0 but below 100.
Item	Uses the number of a possessed or equipped item. From the dropdown menu, choose the item name, and specify whether inventory items or equipped items should be counted.
Actor	Uses an actor's stat, or the item ID of an equipped item. From the dropdown menu, choose the actor's name, as well as the option to take the value of.
Enemies (Battle Events Only)	Uses an enemy stat value. From the dropdown menu, choose the enemy's name, as well as the stat to take the value of.
Other (Map/Common Events Only)	Uses the location information of characters or events on the map. Specify the target character (a) and location information type (b) using the dropdown menus.

Targets

Player	The walking player.
Boat	The boat vehicle.
Ship	The ship vehicle.
Airship	The airship vehicle.
This Event	The current event. If used in a common event, it refers to the last map event on the call stack instead.
Event Name	Other events.

Location Information

Map ID	Uses the ID number of the map the target is on.
X Coordinate	Uses the horizontal coordinate of the target's location on the map.
Y Coordinate	Uses the vertical coordinate of the target's location on the map.
Direction	Uses the facing direction of the target. North (Up) will be 8 East (Right) will be 6 West (Left) will be 4 South (Down) will be 2
Screen X	Uses the horizontal coordinate of the target with respect to the screen.
Screen Y	Uses the vertical coordinate of the target with respect to the screen.

Others

- Use one of the following 8 options. Specify the option from the dropdown menu.

Money	Uses the amount of money currently possessed by the player.
Timer n Remaining Time	Uses the remaining number of seconds on the current timer (n = 1 or 2).
Party Size	Uses the number of members in the player's party.
Save Count	Uses the number of times the player has saved the game data up until the current moment.
Battle Count	Uses the number of times enemies have been battled up until the current moment.
Win Count	Uses the number of times battles have been won up until the current moment.
Loss Count	Uses the number of times battles have been lost up until the current moment.
Escape Count	Uses the number of times battles have been escaped from until the current moment.
MIDI Play Location (Tick)	Uses the current data position of the MIDI file that is being played.