



SAPIENZA  
UNIVERSITÀ DI ROMA

# Artificial Intelligence I

2017/2018 Prof: Daniele Nardi

## Exercises 2: Search in the State Space\* Solutions

Francesco Riccio  
email: [riccio@diag.uniroma1.it](mailto:riccio@diag.uniroma1.it)

\*The slides have been prepared using the textbook material available on the web, and the slides of the previous editions of the course by Prof. Luigia Carlucci Aiello, Prof. Daniele Nardi, Dott. Fabio Previtali and Andrea Vanzo.


October 9th 2016

# Example: Crossing the river

A man has a **wolf**, a **sheep** and a **cabbage**. He is on a river bench with a **boat**, whose maximum **load** for a single trip is the man **plus one of his 3 goods**. The man wants to cross the river with his goods, but he must avoid that - when he is far away - **the wolf eats the sheep** and that, **the sheep eats the cabbage**. How can the man reach his goal?

1. Characterize the **state space**
2. Specify the **operators**
3. Find a minimal sequence of moves to **solve the problem**
4. Find a good **heuristics** to be used by A\*
5. Draw the **search tree generated by A\***. For each node indicate: the number (state),  $f$ ,  $g$ , and  $h$  and an integer indicating the expansion order

**WOLF  
SHEEP  
CABBAGE**



# State space


A man has a **wolf**, a **sheep** and a **cabbage**. He is on a river bench with a **boat**, whose maximum **load** for a single trip is the man **plus one of his 3 goods**. The man wants to cross the river with his goods, but he must avoid that - when he is far away - **the wolf eats the sheep** and that, **the sheep eats the cabbage**. How can the man reach his goal?



## 1. Characterize the **state space**

- Let  $S = D \times D \times D \times D$  where  $D = \{0,1\}$  and  $0$  and  $1$  represent the river benches
- $\langle M, W, S, C \rangle \in S$  represents the position of the man, the wolf, the sheep and the cabbage
- **Initial state**:  $\langle 0,0,0,0 \rangle$ , and **Goal state**:  $\langle 1,1,1,1 \rangle$


# Possible solution



# Operators




Name	Conditions	from State	to State
carryNothing (cn)	$W \neq S, S \neq C$	$\langle M, W, S, C \rangle$	$\langle \bar{M}, W, S, C \rangle$
carryWolf (cw)	$M = W, S \neq C$	$\langle M, W, S, C \rangle$	$\langle \bar{M}, \bar{W}, S, C \rangle$
carrySheep (cs)	$M = S$	$\langle M, W, S, C \rangle$	$\langle \bar{M}, W, \bar{S}, C \rangle$
carryCabbage (cc)	$M = C, W \neq S$	$\langle M, W, S, C \rangle$	$\langle \bar{M}, W, S, \bar{C} \rangle$



# Heuristics & A\*

cost = 1 for each trip,  $h(s) = |4 - M - W - S - C|$



**Continue...**