

1. Which of the following are some common RDBMS in use?

- a) Oracle
- b) MySQL
- c) HeidiSQL
- d) All of the above

2. What command is used to create a new table in SQL?

- a) CREATE TABLE
- b) BUILD TABLE
- c) GENERATE TABLE
- d) None of the above

3. What does the following statement in SQL do?

`DROP TABLE student;`

- a) Deletes a table called student.
- b) Creates a table called student.
- c) Check if there is a table called student.
- d) None of the above.

4. Which of the following are types of Unicode character string types in SQL?

- a) nchar
- b) ntext
- c) Both A and B
- d) None of the above

5. What does BLOB in SQL stand for?

- a) Binary Large Objects
- b) Big Large Objects
- c) Binary Language for Objects
- d) None of the above

6. Which of the following datatype is most appropriate for storing a string of up to 255 characters?

- a) TEXT
- b) TINY TEXT
- c) BLOB
- d) BINARY

7. What happens when no value is inserted in an ENUM list?

- a) Nothing happens
- b) The code will crash
- c) A blank value is inserted in that case
- d) None of the above

8. What is the range of integers that can be held in the MEDIUMINT datatype of SQL?

- a) Signed numbers in the range of -8388608 to 8388607.
- b) Unsigned numbers in the range of 0 to 16777215.
- c) Both A and B.
- d) None of the above.

9. What does the following code snippet do?

```
ALTER TABLE STUDENT ADD(ADDRESS VARCHAR2(20));
```

- a) Adds a column called ADDRESS in the table student.
- b) Checks if a column called ADDRESS is present in the table student.
- c) Invalid Syntax
- d) None of the above

10. Which of the following commands is used to delete all rows and free up space from a table?

- a) TRUNCATE
- b) DROP

- c) DELETE
- d) ALTER

11. Which of the following commands are a part of Data Control Language?

- a) Revoke
- b) Grant
- c) Both A and B
- d) None of the above

12. What does the following code snippet do?

```
DELETE FROM STUDENTS WHERE AGE = 16;  
ROLLBACK;
```

- a) Performs an undo operation on the delete operation.
- b) Deletes the rows from the table where AGE = 16
- c) Deletes the entire table
- d) None of the above

13. When is the wildcard in WHERE clause used?

- a) An exact match is necessary for a CREATE statement.
- b) An exact match is not possible in a SELECT statement.
- c) An exact match is necessary for a SELECT statement.
- d) None of the above.

14. Which of the following is the full form of DDL?

- a) Data definition language
- b) Data derivation language
- c) Dynamic data language
- d) Detailed data language

15. Which SQL constraint do we use to set some value to a field whose value has not been added explicitly?

- a) UNIQUE
- b) NOT NULL
- c) DEFAULT
- d) CHECK

16. What are rows of a relation known as?

- a) Degree
- b) Entity
- c) Tuple
- d) None

17. During transaction before commit which of the following statements is done automatically in case of shutdown?

- a) Rollback
- b) Commit
- c) View
- d) Flashback

18. Which of the following allows you to uniquely identify a tuple?

- a) Schema
- b) Attribute
- c) Super key
- d) Domain

19. How many operations are considered to be the most basic SQL operations?

- a) 4
- b) 3
- c) 2
- d) 1

20. Which of the following is not a SQL command?

- a) DELETE

- b) ORDER BY
- c) SELECT
- d) WHERE

21. What does the following code snippet do?

```
SELECT TOP 5 * FROM students;
```

- a) Select the top 5 entries for all the columns in the students' table.
- b) Select all the entries from the students' table other than the top 5 entries
- c) Selects all entries from the student table except 5 random rows
- d) None of the above

22. Which of the following matches the definition given below: It is an artificial key that aims to uniquely identify each record.

- a) Primary Key
- b) Foreign Key
- c) Surrogate Key
- d) Composite Key

23. Which of the following commands are used to put a restriction on the number of rows returned from a query?

- a) LIMIT
- b) LIKE
- c) WHERE
- d) GROUP BY

24. Which of the following are valid logical operators in SQL?

- a) SOME
- b) ALL
- c) AND
- d) All of the above

25. Which of the following SQL functions compares the similarities of 2 strings and returns the result as a 4 character code?

- a) SOUNDEX
- b) DIFFERENCE
- c) CONCAT
- d) None of the above

26. To select some particular columns, which of the following commands is used?

- a) PROJECTION
- b) SELECTION
- c) JOIN
- d) UNION

27. Primary key can be?

- a) NULL
- b) NOT NULL
- c) Both NULL and NOT NULL
- d) Depends on situation

28. Select the valid SQL type.

- a) NUMERIC
- b) CHARACTER
- c) FLOAT
- d) All of the above

29. Which of the following functions do we use to get a specified day of the month for a given date?

- a) DAY
- b) DATEPART
- c) GETDATE
- d) CURRENT_TIMESTAMP

30. Which of the following operators is used to compare a value to a list of literal values that have been specified?

- a) ANY
- b) BETWEEN
- c) IN
- d) ALL

31) In the database table, data types describe the kind of ____ that it can contain.

- A. Table
- B. Data
- C. Number
- D. None of the above

32) Name of the data type categories are,

- A. String Data types
- B. Numeric Data types
- C. Date and time Data types
- D. All of the above

33) How MySQL determines which one to use, FLOAT or DOUBLE, using the p parameter?

- A. If p comes between 0 to 25, data type becomes FLOAT(). If p comes between 26 to 54, data type becomes DOUBLE().
- B. If p comes between 26 to 54, data type becomes FLOAT(). If p comes between 0 to 25, data type becomes DOUBLE().
- C. If p comes between 25 to 53, data type becomes FLOAT(). If p comes between 0 to 24, data type becomes DOUBLE().
- D. If p comes between 0 to 24, data type becomes FLOAT(). If p comes between 25 to 53, data type becomes DOUBLE().

34) What does BOOL mean in MySQL Numeric Data Types?

- A. A Boolean value is specified by this variable. When a value is nonzero, it is considered false, and zero is considered true.
- B. A Boolean value is specified by this variable. When a value is nonzero, it is considered true, and zero is considered false.
- C. A Boolean value is specified by this variable. When a value is nonzero, it is considered true, and zero is also considered true.

D. A Boolean value is specified by this variable. When a value is nonzero, it is considered true, and zero is also considered false.

35) What can be the maximum size of char(n) in SQL Server String Data Type?

- A. 7000
- B. 8000
- C. 9000
- D. 10000

36) In SQL, Like is a _____ operator.

- A. Relational
- B. Logical
- C. Additional
- D. Unique

37) The character(s) which are used independently or in conjunction with SQL Like Operator:

- A. %
- B. _
- C. Both A. and B.
- D. None of the above

38) Which of the following is/are transaction control commands in SQL?

- A. Commit
- B. Rollback
- C. Both A. and B.
- D. None of the above

39) In order to start the transaction, the command used is –

- A. Mysql > START COMMIT;
- B. Mysql > START TRANSACTION;
- C. Mysql > START ROLLBACK;
- D. None of the above

40) GROUP BY clause is placed before which clause in SQL?

- A. HAVING
- B. WHERE

- C. ORDER BY
- D. FROM

41) What is the default length of any data type in the CAST function?

- A. 10
- B. 20
- C. 30
- D. 40

42) What will be the output of the below SQL statement?

```
SELECT CAST(25.65 AS int);
```

- A. 25
- B. 26

43) The scalar functions operate on each record _____ in SQL.

- A. Dependently
- B. Independently
- C. Interdependently
- D. Intradependently

44) Which function is used to extract substrings from the column of the table –

- A. ROUND()
- B. MID()
- C. FORMAT()
- D. NOW()

45) In order to format, how the column should be displayed, which function is used?

- A. FORM()
- B. DISPLAY()
- C. COL()
- D. FORMAT()

46) What is the symbol of Concatenation Operator?

- A. |
- B. ||
- C. //
- D. \\\

47) _____ variables are not supported by SQL Script.

- A. Bind
- B. Dynamic
- C. Both A) and B)
- D. None of the above

48) Which of the following is TRUE about UNIQUE constraint?

- A. In columns that are subject to the UNIQUE constraint, duplicate values are not allowed.
- B. Unique values will always be present in the column containing the unique constraint.
- C. A single table can have more than one unique constraint, since it can be applied to more than one column.
- D. All of the above

49) _____ and _____ constraints form the core of the PRIMARY KEY constraint.

- A. NOT NULL , CHECK
- B. NOT NULL , DEFAULT
- C. NOT NULL , FOREIGN KEY
- D. NOT NULL , UNIQUE

50) _____ integrity is achieved by using a foreign key.

- A. Referential Integrity
- B. Domain Integrity
- C. User-defined Integrity
- D. Entity Integrity

51) Which type of join returns all the rows from the left table and the matching rows from the right table in SQL?

- a) INNER JOIN
- b) OUTER JOIN
- c) LEFT JOIN
- d) RIGHT JOIN

52) Which function is used to return the current date and time in SQL?

- a) CURRENT_TIMESTAMP
- b) NOW

- c) SYSDATE
- d) GETDATE

53) Which of the following SQL query is correct for selecting the name of the staffs from “staffinfo” table where salary is 10,000 or 25,000?

- A. SELECT name FROM staffinfo WHERE salary BETWEEN 10000 AND 25000;
- B. SELECT name FROM staffinfo WHERE salary IN (10000, 25000);
- C. Both A and B

54) ‘AS’ clause is used in SQL for

- A. Selection operation
- B. Rename Operation
- C. Join Operation
- D. Projection Operation

55) The wildcard in a WHERE clause is useful when?

- A. An exact match is necessary in a CREATE statement.
- B. An exact match is necessary in a SELECT statement.
- C. An exact match is not possible in a SELECT statement
- D. An exact match is not possible in a CREATE statement

56) Which of the following is not a valid SQL type?

- a. FLOAT
- b. NUMERIC
- c. DECIMAL
- d. CHARACTER

57) Which of the following is not a DDL command?

- a. TRUNCATE
- b. ALTER
- c. CREATE
- d. UPDATE

58) Which of the following are TCL commands?

- a. COMMIT and ROLLBACK
- b. UPDATE and TRUNCATE
- c. SELECT and INSERT
- d. GRANT and REVOKE

59) Which statement is used to delete all rows in a table without having the action logged?

- a. DELETE
- b. REMOVE
- c. DROP
- d. TRUNCATE

60) SQL Views are also known as

- a. Simple tables
- b. Virtual tables
- c. Complex tables
- d. Actual Tables

61) How many Primary keys can have in a table?

- a. Only 1
- b. Only 2
- c. Depends on no of Columns
- d. Depends on DBA

62) Which datatype can store unstructured data in a column?

- a. CHAR
- b. RAW
- c. NUMERIC
- d. VARCHAR

63) Which of the following is not Constraint in SQL?

- a. Primary Key
- b. Not Null
- c. Check

d. Union

64) Which of the following is not a valid aggregate function?

- a. COUNT
- b. COMPUTE
- c. SUM
- d. MAX

65) Which data manipulation command is used to combines the records from one or more tables?

- a. SELECT
- b. PROJECT
- c. JOIN
- d. PRODUCT

66) Which operator is used to compare a value to a specified list of values?

- a. ANY
- b. BETWEEN
- c. ALL
- d. IN

67) What operator tests column for absence of data

- a. NOT Operator
- b. Exists Operator
- c. IS NULL Operator
- d. None of the above

68) In which of the following cases a DML statement is not executed?

- a. When existing rows are modified.
- b. When a table is deleted.
- c. When some rows are deleted.
- d. All of the above

69) If we have not specified ASC or DESC after a SQL ORDER BY clause, the following is used by default

- a. DESC
- b. ASC
- c. There is no default value
- d. None of the mentioned

70) Which of the following statement is true?

- a. TRUNCATE free the table space while DELETE does not.
- b. Both TRUNCATE and DELETE statements free the table's space.
- c. Both TRUNCATE and DELETE statement does not free the table's space.
- d. DELETE free the table space while TRUNCATE does not.

71) What is returned by INSTR ('JAVAT POINT', 'P')?

- a. 6
- b. 7
- c. POINT
- d. JAVAT

72) A command that lets you change one or more field in a table is:

- a. INSERT
- b. MODIFY
- c. LOOK-UP
- d. All of the above

73) Which of the following is also called an INNER JOIN?

- a. SELF JOIN
- b. EQUI JOIN
- c. NON-EQUI JOIN
- d. None of the above

74) Which of the following is true about the HAVING clause?

- a. Similar to the WHERE clause but is used for columns rather than groups.
- b. Similar to WHERE clause but is used for rows rather than columns.
- c. Similar to WHERE clause but is used for groups rather than rows.
- d. Acts exactly like a WHERE clause.

75) _____ clause creates temporary relation for the query on which it is defined.

- a. WITH
- b. FROM
- c. WHERE
- d. SELECT

76) The SQL statement:

1. SELECT ROUND (65.726, -1) FROM DUAL;

Prints:

- a. is illegal
- b. garbage
- c. 726
- d. 70

77) Which of the following is true about the SQL AS clause?

- a. The AS clause in SQL is used to change the column name in the output or assign a name to a derived column.
- b. The SQL AS clause can only be used with the JOIN clause.
- c. The AS clause in SQL is used to defines a search condition.
- d. All of the mentioned

78) _____ command makes the updates performed by the transaction permanent in the database?

- a. ROLLBACK
- b. COMMIT
- c. TRUNCATE
- d. DELETE

79) How can you change "Thomas" into "Michel" in the "LastName" column in the Users table?

- a. UPDATE User SET LastName = 'Thomas' INTO LastName = 'Michel'
- b. MODIFY Users SET LastName = 'Michel' WHERE LastName = 'Thomas'

- c. `MODIFY Users SET LastName = 'Thomas' INTO LastName = 'Michel'`
- d. `UPDATE Users SET LastName = 'Michel' WHERE LastName = 'Thomas'`

80) Which command is used to change the definition of a table in SQL?

- a. `CREATE`
- b. `UPDATE`
- c. `ALTER`
- d. `SELECT`

81) Which type of JOIN is used to returns rows that do not have matching values?

- a. Natural JOIN
- b. Outer JOIN
- c. EQUI JOIN
- d. All of the above

82) A CASE SQL statement is _____?

- a. A way to establish a loop in SQL.
- b. A way to establish an IF-THEN-ELSE in SQL
- c. A way to establish a data definition in SQL
- d. All of the above.

83) Which statement is true regarding routines and triggers?

- a. Both run automatically.
- b. Both are stored in the database.
- c. Both consist of procedural code.
- d. Both have to be called to operate.

84) Which statement is true regarding procedures?

- a. They include procedural and SQL statements.
- b. They work similarly to the functions.
- c. It does not need unique names.
- d. It cannot be created with SQL statements.

85) Which of the following is the basic approaches for joining tables?

- a. Union JOIN
- b. Natural JOIN
- c. Subqueries
- d. All of the above

86) Why we need to create an index if the primary key is already present in a table?

- a. Index improves the speed of data retrieval operations on a table.
- b. Indexes are special lookup tables that will be used by the database search engine.
- c. Indexes are synonyms of a column in a table.
- d. All of the above

87) Group of operations that form a single logical unit of work is known as

- a. View
- b. Network
- c. Unit
- d. Transaction

88) Shared locks are applied while performing

- a. Read operations
- b. Write operations
- c. A & B both
- d. None of the above

89) Sequence can generate

- a. Numeric value
- b. Alphanumeric value
- c. A & B both
- d. None of the above

90) A sequence in SQL can generate a maximum number:

- a. 39 digits
- b. 38 digits
- c. 40 digits

d. 37 digits

91) Which of the following is the correct order of a SQL statement?

- a. SELECT, GROUP BY, WHERE, HAVING
- b. SELECT, WHERE, GROUP BY, HAVING
- c. SELECT, HAVING, WHERE, GROUP BY
- d. SELECT, WHERE, HAVING, GROUP BY

92) What is the difference between a PRIMARY KEY and a UNIQUE KEY?

- a. Primary key can store null value, whereas a unique key cannot store null value.
- b. We can have only one primary key in a table while we can have multiple unique keys
- c. Primary key cannot be a date variable whereas unique key can be
- d. None of these

93) Which of the following are the synonyms for Column and ROW of a table?

- 1. Row = [Tuple, Record]
 - 2. Column = [Field, Attribute]
 - 3. Row = [Tuple, Attribute]
 - 4. Columns = [Field, Record]
- a. 1 and 2
 - b. 3 and 4
 - c. Only 1
 - d. Only 2

94) Which operator is used to compare the NULL values in SQL?

- a. Equal
- b. IN
- c. IS
- d. None of Above

95) Which of the following statement is correct regarding the difference between TRUNCATE, DELETE and DROP command?

- I. DELETE operation can be rolled back but TRUNCATE and DROP operations cannot be rolled back.
II. TRUNCATE and DROP operations can be rolled back but DELETE operations cannot be rolled back.
III. DELETE is an example of DML, but TRUNCATE and DROP are examples of DDL.
IV. All are an example of DDL.

- a. I and III
- b. II and III
- c. II and IV
- d. II and IV

96) When the wildcard in a WHERE clause is useful?

- a. When an exact match is required in a SELECT statement.
- b. When an exact match is not possible in a SELECT statement.
- c. When an exact match is required in a CREATE statement.
- d. When an exact match is not possible in a CREATE statement.

97) _____ is NOT a type of constraint in SQL language?

- a. FOREIGN KEY
- b. PRIMARY KEY
- c. UNIQUE
- d. ALTERNATE KEY

98) Which of the following statement is correct to display all the cities with the condition, temperature, and humidity whose humidity is in the range of 60 to 75 from the 'whether' table?

- a. SELECT * FROM weather WHERE humidity IN (60 to 75)
- b. SELECT * FROM weather WHERE humidity BETWEEN 60 AND 75
- c. SELECT * FROM weather WHERE humidity NOT IN (60 AND 75)
- d. SELECT * FROM weather WHERE humidity NOT BETWEEN 60 AND 75

99) _____ is a program that performs some common action on database data and also stored in the database.

- a. Stored Procedure
- b. Trigger

- c. Stored Function
- d. None of the above

100) What is the advantage of the clustered index?

- a. It is fast to update the records.
- b. It does not need extra work for SQL queries.
- c. It minimizes the page transfer and maximizes the cache hits.
- d. None of the above is correct.

Answers :

1) d. All of the above 2) a. CREATE TABLE 3) a. Deletes a table called student.

4) c. Both A and B 5) a. Binary Large Objects. 6) b. TINY TEXT
7) c. A blank value is

inserted in that case. 8) c. Both A and B 9) a. Adds a column called ADDRESS in the table

student . 10) a. TRUNCATE 11) c. Both A and B 12) a.
Performs an undo operation on

the delete operation. 13) b. An exact match is not possible in select statement 14) a. data

definition language 15) c. default 16) c. tuple 17) a. rollback
18) c. super key

19) a. 4 20) a. delete 21) a. select the top 5 entries for all the columns in the student's

table 22) c. surrogate key 23) a. Limit 24) d. All of the above
25) a. soundex

26) a. projection 27) b. NOT NULL 28) d. All of the above 29) a.
DAY 30) b. between

31) b-data

32) d-all of the above

33) d- If p comes between 0 to 24, data type becomes FLOAT(). If p comes between 25 to 53, data type becomes DOUBLE().

34) B) A Boolean value is specified by this variable. When a value is nonzero, it is considered true, and zero is considered false.

35) B-8000

- 36) B- logical
- 37) c- both a and b
- 38) c- both a and b
- 39) b- Mysql > START TRANSACTION;
- 40) C) ORDER BY
- 41) C) 30
- 42) A) 25
- 43) b-independently
- 44) b-mid()
- 45) d- FORMAT()
- 46) ||
- 47) C) Both A) and B)
- 48) d) all of the above
- 49) d) NOT NULL, UNIQUE
- 50) A) Referential Integrity
- 51) c) left join
- 52) a) CURRENT_TIMESTAMP
- 53) b) SELECT name FROM staffinfo WHERE salary IN (10000, 25000);
- 54) b) Rename Operation
- 55) c) An exact match is not possible in a SELECT statement
- 56) c) decimal
- 57) d) update
- 58) a) COMMIT and ROLLBACK
- 59) d) TRUNCATE
- 60) b) Virtual tables
- 61) a) Only 1
- 62) b) RAW
- 63) d) Union
- 64) b) COMPUTE
- 65) c) JOIN
- 66) d) IN
- 67) c) IS NULL Operator
- 68) b) When a table is deleted.

- 69) b) ASC
- 70) a) TRUNCATE free the table space while DELETE does not.
- 71) b) 7
- 72) b) MODIFY
- 73) b) Equi Join
- 74) c) Similar to WHERE clause but is used for groups rather than rows.
- 75) a) With
- 76) d) 70
- 77) a) The AS clause in SQL is used to change the column name in the output or assign a name to a derived column.
- 78) b) COMMIT
- 79) d) UPDATE Users SET LastName = 'Michel' WHERE LastName = 'Thomas'
- 80) c) ALTER
- 81) b) Outer JOIN
- 82) b) A way to establish an IF-THEN-ELSE in SQL
- 83) c) Both consist of procedural code
- 84) a) They include procedural and SQL statements.
- 85) d) All of the above
- 86) a) Index improves the speed of data retrieval operations on a table.
- 87) d) Transaction
- 88) a) Read operations
- 89) c) A & B both
- 90) b) 38 digits
- 91) b) SELECT, WHERE, GROUP BY, HAVING

- 92) b) We can have only one primary key in a table while we can have multiple unique keys
- 93) a) 1 and 2
- 94) c) IS
- 95) a) I and III
- 96) b) When an exact match is not possible in a SELECT statement.
- 97) d) ALTERNATE KEY
- 98) b) SELECT * FROM weather WHERE humidity BETWEEN 60 AND 75
- 99) a) Stored Procedure
- 100) c) It minimizes the page transfer and maximizes the cache hits.

