

C Programming MCQ

1.what is the output of the following code?

```
#include "stdio.h"
int main()
{

    int x, y = 5, z = 5;
    x = y == z;
    printf("%d", x);
    return 0;
```

- ```
}
```
- a)0
  - b)1
  - c)5
  - d)Compiler Error

2.what is the output of the following code?

```
include <stdio.h>
// Assume base address of "GeeksQuiz" to be 1000
int main()
{
 printf(5 + "GeeksQuiz");
 return 0;
```

- ```
}
```
- a)GeeksQuiz
 - b)Quiz
 - c)1005
 - d)Compiler Error

3.What is the output of the above program?

```
#include <stdio.h>
int main(){
    int i = 3;
    printf("%d", (++i)++)
    return 0;
}
```

- a)3 b)4 c)5 d)Compiler Error

4. What is the output of the above program?

```
#include <stdio.h>

int main()
{
    int y = 10000;
    int y = 34;
    printf("Hello World! %d\n", y);
    return 0;
}
```

- a) Compile time error
- b) Hello World! 34
- c) Hello World! 1000
- d) Hello World! followed by a junk value

5 What will be the output of the following C function?

```
#include <stdio.h>

enum birds {SPARROW, PEACOCK, PARROT};
enum animals {TIGER = 8, LION, RABBIT, ZEBRA};

int main()
{
    enum birds m = TIGER;
    int k;
    k = m;
    printf("%d\n", k);
    return 0;
}
```

- a) 0
- b) Compile time error
- c) 1
- d) 8

6. What will be the output of the following C code considering the size of a short int is 2, char is 1 and int is 4 bytes?

```
#include <stdio.h>

int main()
{
    short int i = 20;
    char c = 97;
    printf("%d, %d, %d\n", sizeof(i), sizeof(c), sizeof(c + i));
    return 0;
}
```

- a) 2, 1, 2
- b) 2, 1, 1
- c) 2, 1, 4
- d) 2, 2, 8

7. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int i = 0;
5.      do
6.      {
7.          i++;
8.          if (i == 2)
9.              continue;
10.         printf("In while loop ");
11.     } while (i < 2);
12.     printf("%d\n", i);
13. }
```

- a) In while loop 2
- b) In while loop in while loop 3
- c) In while loop 3
- d) Infinite loop

8. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int x = 0;
5.      if (x == 0)
6.          printf("hi");
7.      else
8.          printf("how are u");
9.          printf("hello");
10. }
```

- a) hi
- b) how are you
- c) hello
- d) hihello

9. What will be the output of the following C code? (Assuming that we have entered the value 1 in the standard input)

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int ch;
5.      printf("enter a value between 1 to 2:");
6.      scanf("%d", &ch);
7.      switch (ch)
8.      {
9.          case 1:
10.             printf("1\n");
11.             default:
12.             printf("2\n");
13.     }
14. }
```

- a) 1
- b) 2
- c) 1 2
- d) Run time error

10. What will be the output of the following C code? (Assuming that we have entered the value 2 in the standard input)

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int ch;
5.      printf("enter a value between 1 to 2:");
6.      scanf("%d", &ch);
7.      switch (ch)
8.      {
9.          case 1:
10.             printf("1\n");
11.             break;
12.             printf("Hi");
13.             default:
14.                 printf("2\n");
15.         }
16.     }
```

- a) 1
- b) Hi 2
- c) Run time error
- d) 2

11. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int x = 0;
5.      if (x++)
6.          printf("true\n");
7.      else if (x == 1)
8.          printf("false\n");
9.  }
```

- a) true
- b) false
- c) compile time error
- d) undefined behavior

12. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int x = 0;
5.      if (x == 1)
6.          if (x == 0)
7.              printf("inside if\n");
8.          else
9.              printf("inside else if\n");
10.     else
11.         printf("inside else\n");
12. }
```

- a) inside if
- b) inside else if
- c) inside else
- d) compile time error

13. What will be the output of the following C code?

```
#include <stdio.h>
```

```
1.  int main()
2.  {
3.      int x = 0;
4.      if (x == 0)
5.          printf("true, ");
6.      else if (x = 10)
7.          printf("false, ");
8.      printf("%d\n", x);
9.  }
```

- a) false, 0
- b) true, 0
- c) true, 10
- d) compile time error

14. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int x = 0;
5.      if (x == 1)
```

```

6.      if (x >= 0)
7.          printf("true\n");
8.      else
9.          printf("false\n");
10.     }

```

- a) true
- b) false
- c) Depends on the compiler
- d) No print statement

15. How many times CppBuzz.com is printed?

```

int main(){
while(1){
    printf("CppBuzz.com");
}
return 0;
}

```

- (A) 1 time
- (B) Compilation Error
- (C) Infinite times
- (D) Runtime Error

16. What is output of below program?

```

int main()
{
int i,j,count;count=0;
for(i=0; i<5; i++){
{
for(j=0;j<5;j++){
{
count++;
}
}
}
printf("%d",count);
return 0;
}

```

- (A) 55
- (B) 54
- (C) 1
- (D) 0

17. What is output of below program?

```
int main()
{
    int i;
    for(i=0; i<5; i++);
    {
        printf("cppbuzz");
    }

    return 0;
}
```

- (A) cppbuzz is printed 5 times
- (B) Compilation Error
- (C) cppbuzz is printed 1 times
- (D) Nothing is printed

18. What is output of below program?

```
int main()
{
    int i,j,k,count;
    count=0;
    for(i=0;i<5;i++)
    {
        for(j=0;j<5;j++)
        {
            count++;
        }
    }
    printf("%d",count);
    return 0;
}
```

- (A) 5
- (B) 10
- (C) 25
- (D) 50

19. What is output of the below program?

```
int main()
{
    int i,j;
    for(i = 0,j=0;j<5;j++)
```

```

{
    printf("%d%d--",i,j);
}
return 0;
}

```

(A) 0--01--12--23--34--
 (B) 00--10--20--30--40--
 (C) Compilation Error
 (D) 00--01--02--03--04--

20. What is output of below program?

```

int main()
{
    for( ; );
    for( ; );
    printf("Hello");
    return 0;
}

```

- (A) Compilation Error
- (B) Runtime Error
- (C) Nothing is printed
- (D) Hello is printed infinite times

21. What is the output of the below program?

```

int main()
{
    for( ; )
    for( ; )
        printf("Hello..");

    return 0;
}

```

- (A) Compilation Error
- (B) Runtime Error
- (C) Hello is printed one time
- (D) Hello is printed infinite times

22. What is output of below code?

```
int main()
{
char name[]="Cppbuz";
int len;
int size;
len = strlen(name);
size = sizeof(name);
printf("%d,%d",len,size);
return 0;
}
```

(A) 6,6
(B) 6,7
(C) 7,7
(D) 0,0

23. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      printf("%d ", 1);
5.      goto l1;
6.      printf("%d ", 2);
7.      l1:goto l2;
8.      printf("%d ", 3);
9.      l2:printf("%d ", 4);
10. }
```

- a) 1 4
- b) Compilation error
- c) 1 2 4
- d) 1 3 4

24. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int i = 0, k;
5.      label: printf("%d", i);
6.      if (i == 0)
7.          goto label;
8.  }
```

- a) 0
- b) Infinite 0
- c) Nothing
- d) Error

25. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int c = 2 ^ 3;
5.      printf("%d\n", c);
6.  }
```

- a) 1
- b) 8
- c) 9
- d) 0

26. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      unsigned int a = -10;
5.      a = ~a;
6.      printf("%d\n", a);
7.  }
```

- a) 9
- b) -10
- c) -11
- d) 10

27. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      if (7 & 8)
5.          printf("Honesty");
6.          if ((~7 & 0x000f) == 8)
7.              printf("is the best policy\n");
8.  }
```

- a) Honesty is the best policy
- b) Honesty
- c) is the best policy
- d) No output

28. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int a = 2;
5.      if (a >> 1)
6.          printf("%d\n", a);
7.  }
```

- a) 0
- b) 1
- c) 2
- d) No Output

29. Comment on the output of the following C code.

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int i, n, a = 4;
5.      scanf("%d", &n);
6.      for (i = 0; i < n; i++)
7.          a = a * 2;
8.  }
```

- a) Logical Shift left
- b) No output
- c) Arithmetic Shift right
- d) Bitwise exclusive OR

30. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int x = 97;
5.      int y = sizeof(x++);
6.      printf("x is %d", x);
7.  }
```

- a) x is 97
- b) x is 98
- c) x is 99
- d) Run time error

31. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int x = 4, y, z;
5.      y = --x;
6.      z = x--;
7.      printf("%d%d%d", x, y, z);
8.  }
```

- a) 3 2 3
- b) 2 2 3
- c) 3 2 2
- d) 2 3 3

32. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int x = 4;
5.      int *p = &x;
6.      int *k = p++;
7.      int r = p - k;
8.      printf("%d", r);
9.  }
```

- a) 4
- b) 8
- c) 1
- d) Run time error

33. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int a = 5, b = -7, c = 0, d;
5.      d = ++a && ++b || ++c;
6.      printf("\n%d%d%d%d", a, b, c, d);
7.  }
```

- a) 6 -6 0 0
- b) 6 -5 0 1
- c) -6 -6 0 1
- d) 6 -6 0 1

34. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int a = -5;
5.      int k = (a++, ++a);
6.      printf("%d\n", k);
7.  }
```

- a) -3
- b) -5
- c) 4
- d) Undefined

35. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int x = 3;
5.      x = x << 1;
6.      printf("%d\n", x);
7.  }
```

- a) 6
- b) 1
- c) Depends on the compiler
- d) Depends on the endianness of the machine

36. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int x = -2;
5.      x = x >> 1;
6.      printf("%d\n", x);
7.  }
```

- a) 1
- b) -1
- c) 2 31 – 1 considering int to be 4 bytes
- d) Either -1 or 1

37. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      if (~0 == 1)
5.          printf("yes\n");
6.      else
7.          printf("no\n");
8.  }
```

- a) yes
- b) no
- c) compile time error
- d) undefined

38. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
```

```

4.    int x = -2;
5.    if (!0 == 1)
6.        printf("yes\n");
7.    else
8.        printf("no\n");
9.    }

```

- a) yes
- b) no
- c) run time error
- d) undefined

39. What will be the output of the following C code?

```

1.    #include <stdio.h>
2.    int main()
3.    {
4.        int y = 0;
5.        if (1 |(y = 1))
6.            printf("y is %d\n", y);
7.        else
8.            printf("%d\n", y);
9.
10.   }

```

- a) y is 1
- b) 1
- c) run time error
- d) undefined

40. What will be the output of the following C code?

```

1.    #include <stdio.h>
2.    int main()
3.    {
4.        int y = 1;
5.        if (y & (y = 2))
6.            printf("true %d\n", y);
7.        else
8.            printf("false %d\n", y);}
9.

```

- a) true 2
- b) false 2
- c) either true 2 or false 2
- d) true 1

41. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      m();
5.      printf("%d", x);
6.  }
7.  int x;
8.  void m()
9.  {
10.     x = 4;
11. }
```

- a) 4
- b) Compile time error
- c) 0
- d) Undefined

42. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int x;
3.  void main()
4.  {
5.      printf("%d", x);
6.  }
```

- a) Junk value
- b) Run time error
- c) 0
- d) Undefined

43. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int x = 5;
3.  void main()
```

```

4.  {
5.    int x = 3;
6.    printf("%d", x);
7.    {
8.        x = 4;
9.    }
10.   printf("%d", x);
11. }

```

- a) Run time error
- b) 3 3
- c) 3 5
- d) 3 4

44. What will be the output of the following C code?

```

1.  #include <stdio.h>
2.  int x = 5;
3.  void main()
4.  {
5.    int x = 3;
6.    printf("%d", x);
7.    {
8.        int x = 4;
9.    }
10.   printf("%d", x);
11. }

```

- a) 3 3
- b) 3 4
- c) 3 5
- d) Run time error

45. Which of the following is an external variable in the following C code?

```

1.  #include <stdio.h>
2.  int func (int a)
3.  {
4.    int b;
5.    return b;
6.  }
7.  int main()
8.  {

```

```
9.     int c;  
10.    func (c);  
11.    }  
12.    int d;
```

- a) a
- b) b
- c) c
- d) d

46. What will be the output of the following C code?

```
1.    #include <stdio.h>  
2.    int main()  
3.    {  
4.        printf("%d", d++);  
5.    }  
6.    int d = 10;
```

- a) 9
- b) 10
- c) 11
- d) Compile time error

47. What will be the output of the following C code?

```
1.    #include <stdio.h>  
2.    double var = 8;  
3.    int main()  
4.    {  
5.        int var = 5;  
6.        printf("%d", var);  
7.    }
```

- a) 5
- b) 8
- c) Compile time error due to wrong format identifier for double
- d) Compile time error due to redeclaration of variable with same name

48. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int i = 10, j = 2;
5.      printf("%d\n", printf("%d %d ", i, j));
6.  }
```

- a) Compile time error
- b) 10 2 4
- c) 10 2 2
- d) 10 2 5

49. What will be the output of the following C code?

```
#include <stdio.h>
```

```
1.  int main()
2.  {
3.      int i = 10, j = 3;
4.      printf("%d %d %d", i, j);
5.  }
```

- a) Compile time error
- b) 10 3
- c) 10 3 some garbage value
- d) Undefined behavior

50. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      char *s = "myworld";
5.      int i = 9;
6.      printf("%*s", i, s);
7.  }
```

- a) myworld
- b) myworld(note: spaces to the left of myworld)
- c) myworld (note: followed by two spaces after myworld)
- d) Undefined

51. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main(int argc, char** argv)
3.  {
4.      char *s = "myworld";
5.      int i = 3;
6.      printf("%10.*s", i, s);
7.  }
```

- a) myw(note:7 spaces before myw)
- b) myworld(note:2 spaces before myworld)
- c) myworld (note:2 spaces after myworld)
- d) myw(note:6 spaces after myw)

52. What is the purpose of sprintf?

- a) It prints the data into stdout
- b) It writes the formatted data into a string
- c) It writes the formatted data into a file
- d) None of the mentioned

53. The syntax to print a % using printf statement can be done by _____

- a) %
- b) \%
- c) ‘%’
- d) %%

54. fgetc, getc, getchar are all declared in _____

- a) stdio. h
- b) ctype. h
- c) assert. h
- d) stdarg. h

55. isalpha() function is used to detect characters both in uppercase and lowercase.

- a) true
- b) false

56. What will be the output of the following C code?

```
int ch= ' ';
if(isgraph(ch))
printf("ch = %c can be printed \n",ch);
```

```
else
    printf("ch=%c cannot be printed \n",ch);
```

- a) ch = ' ' can be printed
- b) ch = ' ' cannot be printed
- c) compile error
- d) run-time error

57. The C library function checks whether the passed character is printable.

- a) isgraph()
- b) isalpha()
- c) isprint()
- d) ispunct()

58. What will be the output of the following C code?

```
char ch[ ] = "0xC";
if(isxdigit(ch[ ]))
    printf("ch = %s is hexadecimal character \n",ch);
else
    printf("ch = %s is not hexadecimal character \n",ch);
```

- a) ch = 0xC is hexadecimal character
- b) ch = 0xC is not hexadecimal character
- c) compile error
- d) run-time error

59. Which among the following option is the full set of character class Hexadecimal digits?

- a) { 0 1 2 3 4 5 6 7 8 9 A B C D E F }
- b) { 0 1 2 3 4 5 6 7 8 9 a b c d e f }
- c) { 0 1 2 3 4 5 6 7 8 9 A B C D E F a b c d e f }
- d) { 0 1 2 3 4 5 6 7 8 9 }

60. What will be the output of the following C code?

```
int i = 0;
char c;
char str[ ] = "Little Star";
while(str[i])
{
    putchar (toupper(str[i]));
```

```
i++;  
}
```

- a) little star
- b) lITTL E sTAR
- c) LITTLE STAR
- d) Little Star

61. What will be the output of the following C code?

```
int ch = '\t';  
if(isprint(ch))  
printf("ch = |%c| printable \n", ch);  
else  
printf("ch = |%c| not printable \n", ch);
```

- a) ch = |\t| printable
- b) ch = |\t| not printable
- c) ch = | | printable
- d) ch = | | not printable

62. What will be returned in the following C code?

```
size_t strlen(const char *s)  
const char *sc;  
for(sc = s; *sc != '\0'; ++sc)  
return(sc - s);
```

- a) number of characters equal in sc
- b) length of string s
- c) doesn't return any value
- d) displays string s

63. The function strstr() is the complement of strchr().

- a) true
- b) false

.

64. What will the following C code do?

```
char * strchr(const char *s, int c )  
char ch = c;  
char *sc;  
for(sc = s; *sc != '\0'; ++sc)
```

```

if(*s == ch)
SC = 9;
i f (*s == '\0' )
return (( char *) s);

```

- a) find last occurrence of c in char s[].
- b) find first occurrence of c in char s[].
- c) find the current location of c in char s[].
- d) There is error in the given code

65. This function offers the quickest way to determine whether two character sequences of the same known length match character for the character up to and including any null character in both.

- a) strcmp()
- b) memcmp()
- c) strncmp()
- d) no such function

66. What will be the output of the following C code?

```

char str1[15];
char str2[15];
int mat;
strcpy(str1, "abcdef");
strcpy(str2, "ABCDEF");
mat= strncmp(str1, str2, 4);
if(mat< 0)
printf("str1 is not greater than str2");
else if(mat> 0)
printf("str2 is is not greater than str1");
else
printf("both are equal");

```

- a) str1 is not greater than str2
- b) str2 is not greater than str1
- c) both are equal
- d) error in given code

67. What will be the output of the following C code?

```
void *memset(void *c, int c, size_t n)
unsigned char ch = c;
unsigned char *su;
for (su = s; 0 < n; ++su, --n)
<br>
*su = ch;
<br>
a) store c throughout unsigned char s[n]
b) store c throughout signed char s[n]
c) find first occurrence of c in s[n]
d) find last occurrence of c in s[n]
```

68. Use _____ to determine the null-terminated message string that corresponds to the error code `errcode`.

- a) `strerror()`
- b) `strstr()`
- c) `strxfrm()`
- d) `memset()`

69. What will be the output of the following C code?

```
const char str1[10]="Helloworld";
const char str2[10] = "world";
char *mat;
mat = strstr(str1, str2);
printf("The substring is:%s\n", mat);
```

- a) The substring is:world
- b) The substring is:Hello
- c) The substring is:Helloworld
- d) error in the code

70. What will the given C code do?

```
int memcmp(const void *str1, const void *str2, size_t n)
```

- a) compares the first n bytes of str1 and str2
- b) copies the first n bytes of str1 to str2
- c) copies the first n bytes of str2 to str1
- d) invalid function

71. Which of the following is the variable type defined in header string. h?

- a) sizet
- b) size
- c) size_t
- d) size-t

72. NULL is the macro defined in the header string. h.

- a) true
- b) false

73. What will be the output of the following C code?

```
const char pla[] = "string1";
const char src[] = "string2";
printf("Before memmove place= %s, src = %s\n", pla, src);
memmove(pla, src, 7);
printf("After memmove place = %s, src = %s\n", pla, src);
```

- a) Before memmove place= string1, src = string2 After memmove place = string2, src = string2
- b) Before memmove place = string2, src = string2 After memmove place= string1, src = string2
- c) Before memmove place = string2, src = string1 After memmove place= string2, src =string2
- d) Before memmove place= string1, src = string2 After memmove place=string1, src = string1

74. What will be the output of the following C code?

```
const char str1[]="ABCDEF1234567";
const char str2[] = "269";
len = strcspn(str1, str2);
printf("First matching character is at %d\n", len + 1);
```

- a) First matching character is at 8
- b) First matching character is at 7
- c) First matching character is at 9
- d) First matching character is at 12

75. What will be the output of the program ?

```
#include<stdio.h>
```

```
int main()
{
    int a[5] = {5, 1, 15, 20, 25};
    int i, j, m;
```

```

    i = ++a[1];
    j = a[1]++;
    m = a[i++];
    printf("%d, %d, %d", i, j, m);
    return 0;
}

```

a) 2, 1, 15

b) 1, 2, 5

c) 3, 2, 15

d) 2, 3, 20

76. What will be the output of the program ?

```
#include<stdio.h>
```

```

int main()
{
    void fun(int, int[]);
    int arr[] = {1, 2, 3, 4};
    int i;
    fun(4, arr);
    for(i=0; i<4; i++)
        printf("%d,", arr[i]);
    return 0;
}

void fun(int n, int arr[])
{
    int *p=0;
    int i=0;
    while(i++ < n)
        p = &arr[i];
    *p=0;
}

```

a) 2, 3, 4, 5

b) 1, 2, 3, 4

c) 0, 1, 2, 3

d) 3, 2, 1 0

77. What will be the output of the program ?

```
#include<stdio.h>
void fun(int **p);
int main()
{
    int a[3][4] = {1, 2, 3, 4, 4, 3, 2, 8, 7, 8, 9, 0};
    int *ptr;
    ptr = &a[0][0];
    fun(&ptr);
    return 0;
}
void fun(int **p)
{
    printf("%d\n", **p);
}
```

a)1 b)2 c)3 d)4

78. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      char *s = "hello";
5.      char *p = s * 3;
6.      printf("%c\t%c", *p, s[1]);
7.  }
```

a) h e
b) l e
c) Compile time error
d) l h

79. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      char *s= "hello";
5.      char *p = s + 2;
6.      printf("%c\t%c", *p, s[1]);
7.  }
```

- a) l e
- b) h e
- c) l l
- d) h l

80. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      void *p;
5.      int a[4] = {1, 2, 3, 8};
6.      p = &a[3];
7.      int *ptr = &a[2];
8.      int n = p - ptr;
9.      printf("%d\n", n);
10. }
```

- a) 1
- b) Compile time error
- c) Segmentation fault
- d) 4

81. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      void *p;
5.      int a[4] = {1, 2, 3, 4};
6.      p = &a[3];
7.      int *ptr = &a[2];
8.      int n = (int*)p - ptr;
9.      printf("%d\n", n);
10. }
```

- a) 1
- b) Compile time error
- c) Segmentation fault
- d) 4

82.. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int a[4] = {1, 2, 3, 4};
5.      int b[4] = {1, 2, 3, 4};
6.      int n = &b[3] - &a[2];
7.      printf("%d\n", n);
8.  }
```

- a) -3
- b) 5
- c) 4
- d) Compile time error

83. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int a[4] = {1, 2, 3, 4};
5.      int *p = &a[1];
6.      int *ptr = &a[2];
7.      ptr = ptr * 1;
8.      printf("%d\n", *ptr);
9.  }
```

- a) 2
- b) 1
- c) Compile time error
- d) Undefined behavior

84. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int a[4] = {1, 2, 3, 4};
5.      int *ptr = &a[2];
6.      float n = 1;
7.      ptr = ptr + n;
8.      printf("%d\n", *ptr);}
```

- a) 4
- b) 3
- c) Compile time error
- d) Undefined behavior

85. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      int a[4] = {1, 2, 3, 4};
5.      void *p = &a[1];
6.      void *ptr = &a[2];
7.      int n = 1;
8.      n = ptr - p;
9.      printf("%d\n", n);
10. }
```

- a) 1
- b) 4
- c) Compile time error
- d) Depends on the compiler

86. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      char *str = "hello, world\n";
5.      char *strc = "good morning\n";
6.      strcpy(strc, str);
7.      printf("%s\n", strc);
8.      return 0;
9.  }
```

- a) hello, world
- b) Crash/segmentation fault
- c) Undefined behavior
- d) Run time error

87.. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      char *str = "hello world";
5.      char strc[] = "good morning india\n";
6.      strcpy(strc, str);
7.      printf("%s\n", strc);
8.      return 0;
9.  }
```

- a) hello world
- b) hello worldg india
- c) Compile time error
- d) Undefined behaviour

88. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      char *str = "hello, world!!\n";
5.      char strc[] = "good morning\n";
6.      strcpy(strc, str);
7.      printf("%s\n", strc);
8.      return 0;
9.  }
```

- a) hello, world!!
- b) Compile time error
- c) Undefined behaviour
- d) Segmentation fault

89. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      char *str = "hello, world\n";
5.      str[5] = '!';
```

```
6.    printf("%s\n", str);
7.    return 0;
8.    }
```

- a) hello. world
- b) hello, world
- c) Compile error
- d) Segmentation fault

90. What will be the output of the following C code?

```
1.    #include <stdio.h>
2.    int main()
3.    {
4.        char str[] = "hello, world";
5.        str[5] = '.';
6.        printf("%s\n", str);
7.        return 0;
8.    }
```

- a) hello. world
- b) hello, world
- c) Compile error
- d) Segmentation fault

91. What will be the output of the following C code?

```
1.    #include <stdio.h>
2.    int main()
3.    {
4.        char *str = "hello world";
5.        char strary[] = "hello world";
6.        printf("%d %d\n", sizeof(str), sizeof(strary));
7.        return 0;
8.    }
```

- a) 11 11
- b) 12 12
- c) 4 12
- d) 4 11

92. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  int main()
3.  {
4.      char *str = "hello world";
5.      char strary[] = "hello world";
6.      printf("%d %d\n", strlen(str), strlen(strary));
7.      return 0;
8.  }
```

- a) 11 11
- b) 12 11
- c) 11 12
- d) x 11 where x can be any positive integer.

93. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void f(char *k)
3.  {
4.      k++;
5.      k[2] = 'm';
6.      printf("%c\n", *k);
7.  }
8.  void main()
9.  {
10.     char s[] = "hello";
11.     f(s);
12. }
```

- a) l
- b) e
- c) h
- d) o

94. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void fun(char *k)
3.  {
4.      printf("%s", k);
5.  }
6.  void main()
7.  {
```

```
8.     char s[] = "hello";
9.     fun(s);
10. }
```

- a) hello
- b) Run time error
- c) Nothing
- d) h

95. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int k = 5;
5.      int *p = &k;
6.      int **m = &p;
7.      printf("%d%d%d\n", k, *p, **m);
8.  }
```

- a) 5 5 5
- b) 5 5 junk value
- c) 5 junk junk
- d) Run time error

96. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int k = 5;
5.      int *p = &k;
6.      int **m = &p;
7.      printf("%d%d%d\n", k, *p, **p);
8.  }
```

- a) 5 5 5
- b) 5 5 junk value
- c) 5 junk junk
- d) Compile time error

97. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int k = 5;
5.      int *p = &k;
6.      int **m = &p;
7.      **m = 6;
8.      printf("%d\n", k);
9.  }
```

- a) 5
- b) Compile time error
- c) 6
- d) Junk

98. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int a[3] = {1, 2, 3};
5.      int *p = a;
6.      int *r = &p;
7.      printf("%d", (**r));
8.  }
```

- a) 1
- b) Compile time error
- c) Address of a
- d) Junk value

99.. What will be the output of the following C code?

```
1.  #include <stdio.h>
2.  void main()
3.  {
4.      int a[3] = {1, 2, 3};
5.      int *p = a;
6.      int **r = &p;
7.      printf("%p %p", *r, a);
8.  }
```

- a) Different address is printed
- b) 1 2
- c) Same address is printed
- d) 1 1

100. What will be the output of the following C code?

```

1.  #include <stdio.h>
2.  void main()
3.  {
4.      int a[3] = {1, 2, 3};
5.      int *p = a;
6.      int *r = &p;
7.      printf("%d", (**r));
8.  }
```

- a) 1
- b) Compile time error
- c) Address of a
- d) Junk value

Answer ;

1- B 2-B 3-D 4-A 5-D 6-C 7-A 8-D 9-C 10-D

11-B 12-C 13-B 14-D 15-C 16-C 17-C 18-C 19-D 20-C

21-D 22-B 23-A 24-B 25-A 26-A 27-C 28-C 29-B 30-A

31-D 32-C 33-D 34-A 35-A 36-B 37-B 38-A 39-A 40-A

41-B 42-C 43-D 44-A 45-D 46-D 47- A 48-D 49- C 50-B

51-A 52- B 53-D 54-A 55-A 56-B 57-C 58-A 59- C 60-C

61-D 62-B 63-A 64-A 65-C 66-B 67-A 68-A 69-A 70-A

71-C 72-A 73-A 74-A 75-C 76-B 77-A 78-C 79-A 80-B

81-A 82-A 83-C 84-C 85- B 86-B 87-A 88-C 89-D 90-A

91-C 92-A 93-B 94-A 95- A 96-D 97-D 98-B 99-C 100-

