

B 3.1.5 Encapsulation Python



B3.1.5 Explain and apply the concepts of encapsulation and information hiding in OOP.

This section explains encapsulation and information hiding in OOP. It covers principles, access modifiers (private, public), controlling class member access, and the importance of limiting access for object integrity and security.

Object-Oriented Programming - Encapsulation and Information Hiding (Python)

This section explores the crucial Object-Oriented Programming (OOP) concepts of **encapsulation** and **information hiding** in Python. Understanding and applying these principles is vital for creating robust, maintainable, and secure software.

The Principles of Encapsulation and Information Hiding

Encapsulation and information hiding are fundamental to managing the complexity of code and ensuring the integrity of objects.

Encapsulation can be thought of as bundling together the **data** (attributes or instance variables) and the **methods** (functions) that operate on that data within a single unit, the **class**. It's like wrapping a gift—the contents (data and methods) are contained within the wrapping (the class). This bundling helps organise your code logically and makes it easier to understand and maintain.

Information Hiding, which is closely related to encapsulation, takes this a step further. It's the principle of restricting access to the internal implementation details of an object and exposing only what is necessary for the outside world to interact with it. Think of a television remote control. You can use the buttons (public interface) to change channels or volume. Still, you don't need to know or have access to the intricate electronic circuitry inside (private implementation) for it to work.

The goal of information hiding is to protect an object's internal state from direct, uncontrolled external modification. By controlling how data is accessed and modified, we can ensure that the object remains valid and consistent. This also allows us to change a class's internal implementation without breaking the code that uses it, as long as the public interface remains the same.

Applying Access Modifiers: **private** and **public** in Python

Python has a slightly different access control approach than languages like Java. While it doesn't have explicit **private** and **public** keywords in the same way, it employs conventions to indicate the intended visibility of class members (attributes and methods).

- **public**: By default, all attributes and methods in Python are considered **public**. This means they can be accessed and modified from outside the class.
- **"private" (by convention)**: Python uses a naming convention to suggest that an attribute or method should be treated as private and not accessed directly from outside the class. This convention involves prefixing the name with **two underscores** (e.g., `__attribute`). This is known as **name mangling**. When Python encounters such a name, it internally changes the name to make it harder (but not impossible) to access from outside the class. This is more of a strong suggestion to other developers that the attribute is intended for internal use.
- **"protected" (by convention)**: Another convention, using a **single underscore** prefix (e.g., `_attribute`), suggests that an attribute or method should be treated as protected. This typically means it's intended for use within the class and its subclasses, but it can still be accessed from outside the class (it's more of a hint that you should do so cautiously).

Controlling Access to Class Members in Python

To implement encapsulation and information hiding effectively in Python, you will typically use the double underscore naming convention for attributes you want to treat as private and provide public methods to access and modify these attributes in a controlled way. These public methods serve a similar purpose to getter and setter methods in other languages.

Here's an example in Python:

```

class Car:
    def __init__(self, model, color):
        self._model = model # Protected attribute (by convention)
        self.__color = color # "Private" attribute (by convention - name mangling)
        self._current_speed = 0 # Protected attribute (by convention)
    # Public getter method for model
    def get_model(self):
        return self._model
    # Public getter method for color
    def get_color(self):
        return self.__color
    # Public getter method for current_speed
    def get_current_speed(self):
        return self._current_speed
    # Public setter method for color with validation
    def set_color(self, new_color):
        if new_color and not new_color.strip() == "":
            self.__color = new_color
        else:
            print("Invalid color provided.")
    # Public method to accelerate the car
    def accelerate(self, increment):
        if increment > 0:
            self._current_speed += increment
            print(f"Accelerating. Current speed: {self._current_speed}")
        else:
            print("Increment must be positive.")
    # Public method to brake the car
    def brake(self, decrement):
        if decrement > 0 and self._current_speed >= decrement:
            self._current_speed -= decrement
            print(f"Braking. Current speed: {self._current_speed}")
        elif decrement <= 0:
            print("Decrement must be positive.")
        else:
            self._current_speed = 0
            print("Braked to a stop.")

# Creating a Car object
my_car = Car("Sedan", "Red")
# Accessing attributes using public getter methods
print(f"Model: {my_car.get_model()}") # Output: Model: Sedan
print(f"Color: {my_car.get_color()}") # Output: Color: Red
# Attempting to directly access a name-mangled attribute (discouraged but possible)
# print(my_car.__color) # This will raise an AttributeError
print(f"Color (mangled): {my_car._Car__color}") # Accessing using the mangled name
# Modifying attribute using a public setter method with validation
my_car.set_color("Blue")
print(f"New Color: {my_car.get_color()}") # Output: New Color: Blue

```

```
my_car.set_color("") # Output: Invalid color provided.  
# Interacting with the object through public methods  
my_car.accelerate(20) # Output: Accelerating. Current speed: 20  
my_car.brake(10)      # Output: Braking. Current speed: 10
```

In this `Car` class:

- `_model` and `_current_speed` are prefixed with a single underscore, indicating they are intended for internal use or within subclasses (protected by convention).
- `__color` is prefixed with a double underscore, triggering name mangling. Python changes its name to something like `_Car__color` internally. While you *can* still access it using this mangled name, it strongly signals that this attribute is intended to be private and should not be accessed directly from outside the class.
- `public` getter methods (`get_model()`, `get_color()`, `get_current_speed()`) are provided to allow controlled read access to the attributes.
- A `public` setter method (`set_color()`) is provided to allow controlled modification of the `__color` attribute, including validation.
- `accelerate()` and `brake()` are `public` methods that modify the `_current_speed` attribute in a controlled manner, also including some basic validation.

The Importance of Limiting Access

Even though Python's enforcement of information hiding through the double underscore convention is not as strict as the `private` keyword in Java, the principle and the benefits remain the same for maintaining the integrity and security of your software:

- **Data Integrity:** By controlling access to attributes through public methods, you can ensure that the data is always in a valid state. Setter methods can include validation logic to prevent invalid values from being assigned to attributes, as seen in the `set_color()` example.
- **Reduced Complexity:** Information hiding simplifies the interaction with objects. Users of the `Car` object only need to know about its public methods (`accelerate()`, `brake()`, `get_color()`, etc.) and don't need to worry about the internal details of how the speed is stored or how the braking mechanism works. This reduces cognitive load and makes the code easier to understand and use.
- **Increased Flexibility and Maintainability:** You can change the internal implementation of a class (e.g., how `_current_speed` is calculated or the underlying data structures used) without affecting the code that uses the class, as long as the public interface (the public methods) remains the same. This makes your code more flexible and easier to maintain over time.

- **Enhanced Security:** By using the double underscore convention, you signal to other developers that an attribute is intended to be private and should not be modified directly. While not a strict security feature, it encourages responsible use of the class and reduces the risk of accidental or unintended modification of internal data.
- **Abstraction:** Encapsulation and information hiding are key aspects of abstraction, one of the four fundamental principles of OOP. They allow you to focus on what an object *does* rather than *how* it does it, leading to more abstract and high-level program design.

In summary, encapsulation and information hiding are essential OOP principles that promote code organization, data integrity, flexibility, maintainability, and a degree of intended privacy in Python. By following the naming conventions (single and double underscores) and providing controlled access through public methods, you can effectively manage how objects are used and enhance the robustness of your Python software.

Try it out

Try instantiating another car and changing its state through the accessors and mutators.

3

_Code

Run

Share

Python3

Remix

All materials on this website are for the exclusive use of teachers and students at subscribing schools for the period of their subscription. Any unauthorised copying or posting of materials on other websites is an infringement of our copyright and could result in your account being blocked and legal action being taken against you.

 [Report a problem](#)