

Overloaded operators

Object-Oriented Programming with C++

Overloading operators

- Allows user-defined types to act like built-in types
- Another way to make a function call.

Overloaded operators

Unary and binary operators can be overloaded:

+ - * / % ^ & | ~

= < > += -= *= /= %=

^= &= |= << >> >>= <<= ==

!= <= >= ! && || ++ --

, ->* -> () []

operator new operator delete

operator new[] operator delete[]

Operators you can't overload

`.` `.*` `::` `?:`

`sizeof` `typeid`

`static_cast` `dynamic_cast` `const_cast`

`reinterpret_cast`

Restrictions

- Only existing operators can be overloaded (you can't create a `**` operator for exponentiation)
- Operators must be overloaded on a class or enumeration type
- Overloaded operators must
 - Preserve number of operands
 - Preserve precedence

C++ overloaded operator

- Just a function with an operator name!
 - Use the `operator` keyword as a prefix to name
`operator * (...)`

C++ overloaded operator

- Just a function with an operator name!
 - Use the `operator` keyword as a prefix to name
`operator * (...)`
- Can be a member function
 - Implicit first argument
`String String::operator+ (const String& that);`

C++ overloaded operator

- Just a function with an operator name!
 - Use the `operator` keyword as a prefix to name

`operator * (...)`

- Can be a member function

- Implicit first argument

`String String::operator+ (const String& that);`

- Can be a global (free) function

- Both arguments explicit

`String operator+ (const String& l, const String& r);`

How to overload

- As member function
 - Implicit first argument
 - No type conversion performed on receiver

Operators as member functions

```
class Integer {  
public:  
    Integer( int n = 0 ) : i(n) {}  
    Integer operator+(const Integer& n) const {  
        return Integer(i + n.i);  
    }  
    ...  
private:  
    int i;  
};
```

Member functions

```
Integer x(1), y(5), z;
```

```
x + y; ====> x.operator+(y);
```

- Implicit first argument
- Developer must have access to class definition
- Members have full access to all data in class
- No type conversion performed on receiver

```
z = x + y;
```

```
z = x + 3;
```

```
z = 3 + y;
```

Member functions

```
Integer x(1), y(5), z;
```

```
x + y; ====> x.operator+(y);
```

- Implicit first argument
- Developer must have access to class definition
- Members have full access to all data in class
- No type conversion performed on receiver

```
z = x + y; ✓
```

```
z = x + 3;
```

```
z = 3 + y;
```

Member functions

```
Integer x(1), y(5), z;
```

```
x + y; ====> x.operator+(y);
```

- Implicit first argument
- Developer must have access to class definition
- Members have full access to all data in class
- No type conversion performed on receiver

```
z = x + y; ✓
```

```
z = x + 3; ✓
```

```
z = 3 + y;
```

Member functions

`Integer x(1), y(5), z;`

`x + y; ==> x.operator+(y);`

- Implicit first argument
- Developer must have access to class definition
- Members have full access to all data in class
- No type conversion performed on receiver

`z = x + y; ✓`

`z = x + 3; ✓`

~~`z = 3 + y;`~~

Member functions...

- For binary operators (+, -, *, etc) member functions require one argument.
- For unary operators (unary -, !, etc) member functions require no arguments:

```
Integer operator-() const {  
    return Integer(-i);  
}
```

...

```
z = -x;
```

Member functions...

- For binary operators (+, -, *, etc) member functions require one argument.
- For unary operators (unary -, !, etc) member functions require no arguments:

```
Integer operator-() const {  
    return Integer(-i);  
}
```

...

```
z = -x; // ???
```


Member functions...

- For binary operators (+, -, *, etc) member functions require one argument.
- For unary operators (unary -, !, etc) member functions require no arguments:

```
Integer operator-() const {  
    return Integer(-i);  
}
```

...

```
z = -x; // z.operator=(x.operator-());
```

How to overload

- As a global function
 - Explicit first argument
 - Type conversions performed on both arguments
 - Can be made a friend

Operator as a global function

```
Integer operator+(  
    const Integer& lhs,  
    const Integer& rhs);
```

```
Integer x, y;
```

```
x + y      ====> operator+(x, y);
```

- Explicit first argument
- Developer does not need special access to classes
- May need to be a friend
- Type conversions performed on both arguments

Global operators (friend)

```
class Integer {  
public:  
    friend Integer operator+(const Integer&, const Integer&);  
    ...  
private:  
    int i;  
};  
  
Integer operator+(const Integer& lhs, const Integer& rhs)  
{  
    return Integer( lhs.i + rhs.i );  
}
```

Global operators

- Binary operators require two arguments
- Unary operators require one argument

- Conversion:

`z = x + y;`

`z = x + 3;`

`z = 3 + y;`

`z = 3 + 7;`

- If you don't have access to private data members, then the global function must use the public interface (e.g. accessors)

Global operators

- Binary operators require two arguments
- Unary operators require one argument
- Conversion:

```
z = x + y; // operator+(x, y)
```

```
z = x + 3;
```

```
z = 3 + y;
```

```
z = 3 + 7;
```

- If you don't have access to private data members, then the global function must use the public interface (e.g. accessors)

Global operators

- Binary operators require two arguments
- Unary operators require one argument
- Conversion:

```
z = x + y; // operator+(x, y)
```

```
z = x + 3; // operator+(x, Integer(3))
```

```
z = 3 + y;
```

```
z = 3 + 7;
```

- If you don't have access to private data members, then the global function must use the public interface (e.g. accessors)

Global operators

- Binary operators require two arguments
- Unary operators require one argument
- Conversion:

```
z = x + y; // operator+(x, y)
```

```
z = x + 3; // operator+(x, Integer(3))
```

```
z = 3 + y; // operator+(Integer(3), y)
```

```
z = 3 + 7;
```

- If you don't have access to private data members, then the global function must use the public interface (e.g. accessors)

Global operators

- Binary operators require two arguments
- Unary operators require one argument
- Conversion:

```
z = x + y; // operator+(x, y)
```

```
z = x + 3; // operator+(x, Integer(3))
```

```
z = 3 + y; // operator+(Integer(3), y)
```

```
z = 3 + 7; // Integer(10)
```

- If you don't have access to private data members, then the global function must use the public interface (e.g. accessors)

Tips: Members vs. Free functions

- Unary operators should be members
- `=` `()` `[]` `->` `->*` must be members
- All other binary operators as non-members

Argument passing

- If it is read-only pass it in as a const reference (except built-ins)
- Make member functions const that don't change the class (boolean operators, +, -, etc)
- For global functions, if the left-hand side changes pass as a reference (stream inserters)

Return values

- Select the return type depending on the expected meaning of the operator. For example,
 - For `operator+` you need to generate a new object.
Return the created object.
 - Logical operators should return `bool` (or `int` for older compilers).

The prototypes of operators

- `+ - * / % ^ & | ~`

The prototypes of operators

- `+ - * / % ^ & | ~`

- `T operator X(const T& l, const T& r);`

The prototypes of operators

- `+ - * / % ^ & | ~`

- T operator `X(const T& l, const T& r);`

- `! && || < <= == >= >`

The prototypes of operators

- `+ - * / % ^ & | ~`
 - T operator `X(const T& l, const T& r);`
- `! && || < <= == >= >`
 - bool operator `X(const T& l, const T& r);`

The prototypes of operators

- `+ - * / % ^ & | ~`
 - T operator `X(const T& l, const T& r);`
- `! && || < <= == >= >`
 - bool operator `X(const T& l, const T& r);`
- `[]`

The prototypes of operators

- `+ - * / % ^ & | ~`
 - `T operator X(const T& l, const T& r);`
- `! && || < <= == >= >`
 - `bool operator X(const T& l, const T& r);`
- `[]`
 - `E& T::operator [](int index);`

Operators ++ and --

- How to distinguish postfix from prefix?
 - `i++` or `++i`

Operators ++ and --

- How to distinguish postfix from prefix?
 - `i++` or `++i`
- Postfix forms take an int argument -- compiler will pass in 0 as that int

```
class Integer {  
public:  
    ...  
    Integer& operator++();    //prefix++  
    Integer operator++(int); //postfix++  
    Integer& operator--();    //prefix--  
    Integer operator--(int); //postfix--  
    ...  
};
```

Operators ++ and --

```
Integer& Integer::operator++() {  
    this->i += 1;          // increment  
    return *this;         // fetch  
}  
  
// int argument not used so leave unnamed so  
// won't get compiler warnings  
Integer Integer::operator++( int ){  
    Integer old( *this );  // fetch  
    ++(*this);             // increment  
    return old;            // return  
}
```

Operators ++ and --

```
Integer& Integer::operator++() {  
    this->i += 1;          // increment  
    return *this;         // fetch  
}  
  
// int argument not used so leave unnamed so  
// won't get compiler warnings  
Integer Integer::operator++( int ){  
    Integer old( *this );    // fetch  
    ++(*this);              // increment  
    return old;              // return  
}
```

Operators **++** and **--**

```
Integer& Integer::operator++() {  
    *this += 1;           // increment  
    return *this;         // fetch  
}  
  
// int argument not used so leave unnamed so  
// won't get compiler warnings  
Integer Integer::operator++( int ){  
    Integer old( *this );   // fetch  
    ++(*this);             // increment  
    return old;             // return  
}
```

Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);
```


Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);  
++x;
```

Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);
```

```
++x;
```

```
    // calls x.operator++();
```

Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);
```

```
++x;
```

```
    // calls x.operator++();
```

```
x++;
```

Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);
```

```
++x;
```

```
    // calls x.operator++();
```

```
x++;
```

```
    // calls x.operator++(0);
```

Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);
```

```
++x;
```

```
    // calls x.operator++();
```

```
x++;
```

```
    // calls x.operator++(0);
```

```
--x;
```

Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);
```

```
++x;
```

```
    // calls x.operator++();
```

```
x++;
```

```
    // calls x.operator++(0);
```

```
--x;
```

```
    // calls x.operator--();
```

Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);
```

```
++x;
```

```
    // calls x.operator++();
```

```
x++;
```

```
    // calls x.operator++(0);
```

```
--x;
```

```
    // calls x.operator--();
```

```
x--;
```

Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);  
++x;  
    // calls x.operator++();  
x++;  
    // calls x.operator++(0);  
--x;  
    // calls x.operator--();  
x--;  
    // calls x.operator--(0);
```


Using the overloaded ++ and --

```
// decrement operators similar to increment
```

```
Integer x(5);  
++x;  
    // calls x.operator++();  
x++;  
    // calls x.operator++(0);  
--x;  
    // calls x.operator--();  
x--;  
    // calls x.operator--(0);
```

- User-defined prefix is more efficient than postfix.

Relational operators

- implement `!=` in terms of `==`
- implement `>`, `>=`, `<=` in terms of `<`

```
class Integer {  
public:  
    ...  
    bool operator==( const Integer& rhs ) const;  
    bool operator!=( const Integer& rhs ) const;  
  
    bool operator<( const Integer& rhs ) const;  
    bool operator>( const Integer& rhs ) const;  
    bool operator<=( const Integer& rhs ) const;  
    bool operator>=( const Integer& rhs ) const;  
}
```

Relational operators

```
bool Integer::operator==( const Integer& rhs ) const {  
    return i == rhs.i;  
}  
  
// implement lhs != rhs in terms of !(lhs == rhs)  
bool Integer::operator!=( const Integer& rhs ) const {  
    return !(*this == rhs);  
}  
  
bool Integer::operator<( const Integer& rhs ) const {  
    return i < rhs.i;  
}
```

Relational operators...

```
// implement lhs > rhs in terms of lhs < rhs
bool Integer::operator>( const Integer& rhs ) const {
    return rhs < *this;
}

// implement lhs <= rhs in terms of !(rhs < lhs)
bool Integer::operator<=( const Integer& rhs ) const {
    return !(rhs < *this);
}

// implement lhs >= rhs in terms of !(lhs < rhs)
bool Integer::operator>=( const Integer& rhs ) const {
    return !(*this < rhs);
}
```

Operator []

- Must be a member function
- Single argument
- Implies that the object acts like an array, so it should return a reference

```
Vector v(100);    // create a vector of size 100  
v[10] = 45;
```

Note: if returned a pointer you would need to do:

```
*v[10] = 45;
```

See: vector.h, vector.cpp

Copying vs. Initialization

```
MyType b;
```

```
MyType a = b;
```

```
a = b;
```

Example: CopyingVsInitialization.cpp

Automatic operator= creation

- The compiler will automatically create one if it's not explicitly provided.
- *memberwise assignment*
- Example: AutomaticOperatorEquals.cpp

Assignment operator

- Must be a member function
- Return a reference to `*this`

```
A = B = C;
```

```
// executed as A = (B = C);
```


Assignment operator

- Must be a member function
- Return a reference to `*this`

```
A = B = C;
```

```
// executed as A = (B = C);
```

- Be sure to assign to all data members: pointers...

Assignment operator

- Must be a member function
- Return a reference to `*this`
`A = B = C;`
`// executed as A = (B = C);`
- Be sure to assign to all data members: pointers...
- Check for self-assignment

Assignment operator skeleton

```
T& T::operator=( const T& rhs ) {  
    // check for self assignment  
    if ( this != &rhs ) {  
        // perform assignment  
    }  
    return *this;  
}
```

//This checks address, not value (*this != rhs)

Assignment operator

- For classes with *dynamically* allocated memory declare an assignment operator (and a copy constructor)
- To prevent assignment, explicitly declare `operator=` as `private`, or use `=delete;`

Value classes

- Appear to be primitive data types

Value classes

- Appear to be primitive data types
- Passed to and returned from functions

Value classes

- Appear to be primitive data types
- Passed to and returned from functions
- Have overloaded operators (often)

Value classes

- Appear to be primitive data types
- Passed to and returned from functions
- Have overloaded operators (often)
- Can be converted to and from other types

Value classes

- Appear to be primitive data types
- Passed to and returned from functions
- Have overloaded operators (often)
- Can be converted to and from other types
- Examples: Complex, Date, ...

User-defined type conversions

- A conversion operator can be used to convert an object of one class into
 - an object of another class
 - a built-in type
- Compilers perform implicit conversions using:
 - Single-argument constructors
 - implicit type conversion operators

Single argument constructors

```
class PathName {  
    string name;  
public:  
    // or could be multi-argument with defaults  
    PathName(const string&);  
    ~ PathName();  
};  
...  
string abc("abc");  
PathName xyz(abc); // OK!  
xyz = abc;          // OK abc => PathName
```

Example: AutomaticTypeConversion.cpp

Prevent implicit conversions

- New keyword: *explicit*

```
class PathName {  
    string name;  
public:  
    explicit PathName(const string&);  
    ~ PathName();  
};  
...  
string abc("abc");  
PathName xyz(abc); // OK!  
xyz = abc;          // error!
```

Example: ExplicitKeyword.cpp

Conversion operations

- Operator conversion
 - Function will be called automatically
 - Return type is same as function name

```
class Rational {  
public:  
    ...  
    operator double() const;    // Rational to double  
}  
Rational::operator double() const {  
    return numerator_ / (double)denominator_;  
}  
Rational r(1,3); double d = 1.3 * r; // r=>double
```

General form of conversion ops

- $X::\text{operator } T()$
 - Operator name is any type descriptor
 - No explicit arguments
 - No return type
 - Compiler will use it as a type conversion from $X \Rightarrow T$

C++ type conversions

- Built-in conversions

- Primitive

`char \Rightarrow short \Rightarrow int \Rightarrow float \Rightarrow double`
 `\Rightarrow int \Rightarrow long`

- Any type `T`

`T \Rightarrow T&`

`T& \Rightarrow T`

`T* \Rightarrow void*`

`T[] \Rightarrow T*`

`T* \Rightarrow T[]`

`T \Rightarrow const T`

C++ type conversions

- Built-in conversions

- Primitive

`char \Rightarrow short \Rightarrow int \Rightarrow float \Rightarrow double
 \Rightarrow int \Rightarrow long`

- Any type `T`

`T \Rightarrow T&`

`T& \Rightarrow T`

`T* \Rightarrow void*`

`T[] \Rightarrow T*`

`T* \Rightarrow T[]`

`T \Rightarrow const T`

- User-defined `T \Rightarrow C`

- if `C(T)` is a valid constructor call for `C`

- if `operator C()` is defined for `T`

C++ type conversions

- Built-in conversions

- Primitive

`char \Rightarrow short \Rightarrow int \Rightarrow float \Rightarrow double
 \Rightarrow int \Rightarrow long`

- Any type `T`

`T \Rightarrow T&`

`T& \Rightarrow T`

`T* \Rightarrow void*`

`T[] \Rightarrow T*`

`T* \Rightarrow T[]`

`T \Rightarrow const T`

- User-defined `T \Rightarrow C`

- if `C(T)` is a valid constructor call for `C`

- if `operator C()` is defined for `T`

- BUT

- See: `TypeConversionAmbiguity.cpp`

Do you want to use them?

- In general, be careful!
 - Cause lots of problems when functions are called unexpectedly.
- Use explicit conversion functions. Instead of using the conversion operator, declare a member function in `class Rational`:

```
double to_double() const;
```

Overloading and type conversion

- C++ checks each argument for a "best match"
- Best match means cheapest
 - Exact match is cost-free
 - Matches involving built-in conversions
 - User-defined type conversions

Overloading

- Just because you can overload an operator doesn't mean you should.
- Overload operators when it makes the code easier to read and maintain.