Kodewala Academy(25th Aug, 2026) - Java Backend Test # 3

Sagar Patil
Oct. 5, 2026, 2:57 p.m.

You've survived the test. The results will arrive soon. 😎

Your score: 97% 43.75/45
Duration: 0:12:29

1. Which statement is true about JDK? 1 / 1 point

Your Answer: ✓ Correct
- ○ Contains only JVM
- ○ Contains only JRE
- ○ Contains only compiler
- ✓ ● Contains JRE, JVM, and development tools

2. Why is Java called platform independent? 1 / 1 point

Your Answer: ✓ Correct
- ○ Java code is interpreted directly by OS
- ✓ ● Bytecode can run on any JVM
- ○ Java programs require no OS
- ○ JVM is platform independent

3. What is the output? 1 / 1 point

```
int i = 1;
while(i <= 3){
   System.out.print(i++);
}
```

Your Answer: ✓ Correct
- ○ 0123
- ✓ ● 123
- ○ 1234
- ○ Infinite loop

4. Which loop executes at least once? 1 / 1 point

Your Answer: ✓ Correct
- ○ for
- ○ while
- ✓ ● do-while
- ○ enhanced for loop

5. Which operator short-circuits evaluation? 1 / 1 point

Your Answer: ✓ Correct
- ○ &
- ✓ ● Both || and &&
- ○ ||
- ○ &&

6. What is stored in args[0]? 1 / 1 point

```
java Test Hello
```

Your Answer: ✓ Correct
- ○ Test
- ○ java
- ✓ ● Hello
- ○ args

7. Which member belongs to the class rather than an object? 1 / 1 point

Your Answer: ✓ Correct
- ○ Instance Variable
- ✓ ● Static Variable
- ○ Local
- ○ None of the above

8. Which method signature is valid? 1 / 1 point

Your Answer: ✓ Correct
- ○ void test(int a)
- ○ int test()
- ○ public static void main(String[] args)
- ✓ ● All of the above

9. Can two methods have the same name? 1 / 1 point

Your Answer: ✓ Correct
- ○ Never
- ○ Only in different classes
- ✓ ● Yes, through method overloading
- ○ No

10. Which access modifier gives the widest accessibility? 1 / 1 point

Your Answer: ✓ Correct
- ○ protected
- ○ private
- ✓ ● public
- ○ default

11. Which access modifier restricts access within the same class only? 1 / 1 point

Your Answer: ✓ Correct
- ○ protected
- ✓ ● private
- ○ public
- ○ default

12. **What is the output?** 1 / 1 point

```
for(int i=1;i<=5;i++){
  if(i==3)
 {
    continue;
}
  System.out.print(i);
}
```

Your Answer: ✓ Correct
- ○ 12345
- ✓ ● 1245
- ○ 345
- ○ 12

13. **What is the output?** 1 / 1 point

```
for(int i=1;i<=5;i++){
  if(i==3)
    {
      break;
    }
  System.out.print(i);
}
```

Your Answer: ✓ Correct
- ○ 12345
- ○ 1245
- ○ 345
- ✓ ● 12

14. Which statement immediately exits a method? 1 / 1 point

Your Answer: ✓ Correct
- ○ break
- ○ continue
- ○ exit
- ✓ ● return

15. Which package is automatically imported? 1 / 1 point

Your Answer: ✓ Correct
- ○ java.util
- ○ java.io
- ✓ ● java.lang
- ○ java.sql

16. Which statement about packages is correct? 1 / 1 point

Your Answer: ✓ Correct
- ○ Package names must start with capital letters
- ✓ ● Packages help avoid naming conflicts
- ○ Package names can contain spaces
- ○ Packages are optional folders

17. What is the size of the array? 1 / 1 point

```
int[] arr = new int[5];
```

Your Answer: ✓ Correct
- ○ 4
- ✓ ● 5
- ○ 6
- ○ Depends on JVM

18. What is the default value of an int array element? 1 / 1 point

Your Answer: ✓ Correct
- ○ null
- ○ 1
- ✓ ● 0
- ○ Undefined

19. What happens? 1 / 1 point

```
int[] arr = new int[3];
System.out.println(arr[3]);
```

Your Answer: ✓ Correct
- ○ 0
- ○ null
- ✓ ● ArrayIndexOutOfBoundsException
- ○ Compilation Error

20. Which is NOT a JVM memory area? 1 / 1 point

Your Answer: ✓ Correct
- ○ Heap
- ○ stack
- ○ metaspace
- ✓ ● Database Area

21. What is the output? 1 / 1 point

```
public class Test{
  static int count;
  public static void main(String[] args){
    System.out.println(count);
  }
}
```

Your Answer: ✓ Correct
- ○ null
- ✓ ● 0
- ○ 1
- ○ Compilation Error

22. Coupon Validation 1 / 1 point

```
boolean isPremium = false;
boolean couponValid = true;
if(isPremium || couponValid)
{
   System.out.println("Discount Applied");
}
```

Your Answer: ✓ Correct
- ○ No Output
- ✓ ● Discount Applied
- ○ Compilation Error
- ○ Runtime Error

23. 1 / 1 point

```
public class Inventory{
   private int stock = 10;
}
```

Which class can access stock directly?

Your Answer: ✓ Correct
- ○ Any class
- ○ Same package
- ○ Subclass
- ✓ ● Inventory class only

24. 1 / 1 point

```
int[] ids = {101,102,103};
System.out.println(ids[3]);
```

Your Answer: ✓ Correct
- ○ 103
- ○ null
- ✓ ● ArrayIndexOutOfBoundsException
- ○ 0

25. A customer can get a discount if they are a premium member OR they have a valid coupon. 1 / 1 point

```
boolean premiumMember = true;
boolean validCoupon = false;
if(premiumMember || validCoupon)
{
   System.out.println("Discount Applied");
}
```

Why is validCoupon not evaluated?

Your Answer: ✓ Correct
- ○ JVM Optimization
- ○ Compiler Error
- ✓ ● Short-Circuit Evaluation of ||
- ○ Both variables are boolean

26. Consider: 1 / 1 point

```
public static void main(String[] args)
 {
   int result = add(10, 20);
   System.out.println(result);
}
public static int add(int a, int b)
{
   return a + b;
}
```

Debugger is stopped at:

```
int result = add(10, 20);
```

Which key should be used if you want to see the execution of:

```
return a + b;
```

Your Answer: ✓ Correct
- ○ F8
- ○ F7
- ○ F6
- ✓ ● F5

27. You are debugging: -0.25 / 1 point

```
int result = add(10,20);
System.out.println(result);
```

You don't want to enter add() method.

Which key should you use?

Your Answer: ✗ Incorrect
- ✗ ● F8
- ○ F7
- ✓ ○ F6
- ○ F5

28. What does F8 do? 1 / 1 point

Your Answer: ✓ Correct
- ○ Enter method
- ○ Execute current line only
- ✓ ● Run till next breakpoint or program completion
- ○ Exit JVM

29. Consider the following code: 1 / 1 point

```
class Product {
   static int gst = 18;
   int price = 1000;
   public void calculate() {
      int discount = 100;
   }
}
```

Which variable is stored in Stack Memory during execution?

Your Answer: ✓ Correct
- ○ gst
- ○ price
- ✓ ● discount
- ○ Product object

30. An inventory system stores 10,000 product IDs in an array. 1 / 1 point

Which characteristic of arrays allows quick retrieval of any element using its index?

Your Answer: ✓ Correct
- ○ Elements are sorted automatically.
- ✓ ● Elements are stored in contiguous memory locations.
- ○ Arrays use HashMap internally.
- ○ Arrays store data in Method Area.

31. If arrays require contiguous memory, what happens when we need a larger array? 1 / 1 point

Your Answer: ✓ Correct
- ○ JVM automatically increases the same memory block.
- ✓ ● A new larger array is created and data is copied.
- ○ Existing array size changes.
- ○ Array moves to Stack.

32. When should for loop be preferred over while loop? 1 / 1 point

Your Answer: ✓ Correct
- ○ When the number of iterations is unknown
- ○ Only for arrays
- ○ Only for strings
- ✓ ● When the number of iterations is known in advance

33. Which loop is generally preferred for reading user input until the user enters a specific value? 1 / 1 point

Your Answer: ✓ Correct
- ○ for loop
- ✓ ● while loop
- ○ do-while
- ○ none

34. 1 / 1 point

```
for( ; ; )
{
System.out.println("Java");
}
```

What happens?

Your Answer: ✓ Correct
- ○ Prints once
- ○ Compilation Error
- ✓ ● Infinite Loop
- ○ Runtime Exception

35. Which statement is TRUE? 1 / 1 point

Your Answer: ✓ Correct
- ○ for loop cannot become an infinite loop.
- ○ while loop cannot become an infinite loop.
- ✓ ● Both for and while can become infinite loops.
- ○ Neither can become an infinite loop.

36. An ATM application keeps asking for a PIN until the correct PIN is entered. 1 / 1 point

Which loop is more suitable?

Your Answer: ✓ Correct
- ○ for
- ✓ ● while
- ○ do-while
- ○ switch

37. An inventory system needs to scan exactly 500 products. 1 / 1 point

Which loop should be preferred?

Your Answer: ✓ Correct
- ○ while loop because it is faster
- ✓ ● for loop because the number of iterations is known
- ○ switch case
- ○ do-while

38. An inventory system needs to scan exactly 500 products. 1 / 1 point

Which loop should be preferred?

Your Answer: ✓ Correct
- ○ while loop because it is faster
- ✓ ● for loop because the number of iterations is known
- ○ switch case
- ○ do-while

39. What is the output? 1 / 1 point

```
class A {
   A() {
      System.out.println("A");
   }
   A(int x) {
      this();
      System.out.println("A-int");
   }
}
class B extends A {
   B() {
      this(10);
      System.out.println("B");
   }
   B(int x) {
      super(x);
      System.out.println("B-int");
   }
}
public class Test {
   public static void main(String[] args) {
      new B();
   }
}
```

Your Answer: ✓ Correct
- ✓ ● A → A-int → B-int → B
- ○ A-int → A → B-int → B
- ○ A → B-int → A-int → B
- ○ Compilation error

40. 1 / 1 point

```
int total = 0;
for (int i = 1; i <= 5; i++)
{
   if (i % 2 == 0)
   {
      continue;
   }
   total += i;
   if (total > 4)
   {
      break;
   }
}
System.out.println(total);
```

Your Answer: ✓ Correct
- ○ 1
- ○ 4
- ○ 5
- ✓ ● 9

41. 1 / 1 point

```
class Parent {
   Parent() {
      System.out.println("Parent");
   }
}

class Child extends Parent {
   Child() {
      this(10);
      System.out.println("Child");
   }

   Child(int x) {
      System.out.println("Child-int");
   }
}

public class Test {
   public static void main(String[] args) {
      new Child();
   }
}
```

Output?

Your Answer: ✓ Correct
- ○ Child → Child-int → Parent
- ✓ ● Parent → Child-int → Child
- ○ Child-int → Parent → Child
- ○ Compilation error

42. Which statement about this() and super() is correct? 1 / 1 point

Your Answer: ✓ Correct
- ○ Both can be used together in the same constructor
- ○ this() must always be the last statement
- ✓ ● this() or super() must be the first statement of a constructor
- ○ super() can be called from any method

43. 1 / 1 point

```
class A {
   A() {
      this(10);
   }
   A(int x) {
      this();
   }
}
```

Your Answer: ✓ Correct
- ○ Executes successfully
- ○ Runtime exception
- ✓ ● Compile-time error due to recursive constructor invocation
- ○ StackOverflowError at runtime

44. 1 / 1 point

```
class A {
   A(int x) {
      System.out.println("A");
   }
}
class B extends A {
   B() {
      System.out.println("B");
   }
}
```

Your Answer: ✓ Correct
- ○ A → B
- ○ B only
- ✓ ● Compilation error
- ○ Runtime exception

45. You are designing an e-commerce application where every Order must have a default status of "NEW". 1 / 1 point

A developer has written:

```
class Order {
   int orderId;
   String status;
   Order() {
      this(0);
      System.out.println("Default Order");
   }
   Order(int orderId) {
      this(orderId, "NEW");
      System.out.println("Order with ID");
   }
   Order(int orderId, String status) {
      this.orderId = orderId;
      this.status = status;
      System.out.println("Order Created");
   }
}
public class Test {
   public static void main(String[] args) {
      Order order = new Order();
   }
}
```

What will be printed, and what will be the final values of orderId and status?

Your Answer: ✓ Correct
- ✓ ● Order Created
  Order with ID
  Default Order
  orderId = 0
  status = "NEW"
- ○ Default Order
  Order with ID
  Order Created
  orderId = 0
  status = "NEW"
- ○ Order Created
  Default Order
  Order with ID
  orderId = 0
  status = null
- ○ Compilation error because constructors cannot call another constructor.

Logout