Kodewala Academy(25th Aug, 2026) - Java Backend Test # 4

Sudarshan Patil
Oct. 12, 2026, 10:10 a.m.

You've survived the test. The results will arrive soon. 😎

Your score: 68% 21/31
Duration: 0:19:52

1.

```
String s1 = new String("Java");

String s2 = new String("Java");

System.out.println(s1 == s2);
```

1 / 1 point

Your Answer: ✓ Correct

○ true
✓ ● false
○ 0
○ 1

2.

```
String s1 = "Java";

String s2 = new String("java");

System.out.println(s1.equals(s2));
```

-0.25 / 1 point

Your Answer: ✗ Incorrect

✗ ● true
○ Compilation Error
✓ ○ false
○ 1

3.

```
String s = "Hello";

s.concat(" World");

System.out.println(s);
```

1 / 1 point

Your Answer: ✓ Correct

○ Hello World
○ Compilation Error
○ Runtime Error
✓ ● Hello

4. Which method compares String contents?

1 / 1 point

Your Answer: ✓ Correct

○ ==
✓ ● equals()
○ hashCode()
○ compare()

5. Which statement is TRUE?

1 / 1 point

Your Answer: ✓ Correct

○ String is mutable
○ StringBuilder is immutable
✓ ● String is immutable
○ StringBuffer is immutable

6. Which method is inherited by every Java class?

1 / 1 point

Your Answer: ✓ Correct

○ None
✓ ● Both - equals() and hashCode()
○ hashCode()
○ equals()

7. What happens if equals() is not overridden?

1 / 1 point

Your Answer: ✓ Correct

○ Compares content
✓ ● Uses == internally
○ Compilation Error
○ Runtime Exception

8. Which class is final?

1 / 1 point

Your Answer: ✓ Correct

○ Object
○ Thread
✓ ● String
○ Exception

9. When is constructor called?

-0.25 / 1 point

Your Answer: ✗ Incorrect

○ Method call
✓ ○ Object creation
✗ ● Compilation
○ Garbage collection

10. If no constructor is written

1 / 1 point

Your Answer: ✓ Correct

○ Compilation Error
○ JVM creates
✓ ● Compiler provides default constructor
○ None

11. First statement inside constructor can be

1 / 1 point

Your Answer: ✓ Correct

○ super()
○ this()
✓ ● either super() or this()
○ anything

12. Which keyword invokes parent constructor?

1 / 1 point

Your Answer: ✓ Correct

○ parent()
○ this()
✓ ● super()
○ extends()

13. Object class is

1 / 1 point

Your Answer: ✓ Correct

✓ ● Parent of all classes
○ Interface
○ Final class
○ Abstract class

14. Instance variable is created

-0.25 / 1 point

Your Answer: ✗ Incorrect

○ Once
○ During class loading
✓ ○ With every object
✗ ● During compilation

15. A Java application receives thousands of requests simultaneously. Each request builds a large string by appending multiple values. The same string object is shared by multiple threads.

-0.25 / 1 point

Your Answer: ✗ Incorrect

○ String
✗ ● StringBuilder
✓ ○ StringBuffer
○ Thread

16.

```
public class Demo {

    public static void main(String[] args) {

        StringBuilder sb = new StringBuilder();



        for (int i = 0; i < 100000; i++) {

            sb.append(i);

        }



        System.out.println(sb.length());

    }

}
```

-0.25 / 1 point

Why is StringBuilder preferred over StringBuffer in this program?

Your Answer: ✗ Incorrect

○ StringBuilder uses less memory
✗ ● StringBuilder is immutable.
○ StringBuffer cannot append integers.
✓ ○ The program is single-threaded, so synchronization overhead is unnecessary.

17. A developer accidentally loses the source code (.java files), but the compiled .class files are still available.

1 / 1 point

Which statement is correct?

Your Answer: ✓ Correct

○ It is impossible to recover the Java code.
✓ ● A Java decompiler can generate readable Java source code from the .class files, although comments and original formatting are usually lost.
○ The JVM can automatically recreate the original source code with comments.
○ The .class file contains only machine code, so decompilation is impossible.

18.

```
Employee e1 = new Employee(101);

Employee e2 = new Employee(101);

System.out.println(e1.equals(e2));
```

1 / 1 point

Employee does NOT override equals().

What happens?

Your Answer: ✓ Correct

○ true
✓ ● false
○ Compilation Error
○ Runtime Exception

19. A banking application updates a shared transaction log using multiple threads simultaneously.

1 / 1 point

Which class should be used?

Your Answer: ✓ Correct

○ String
○ StringBuilder
✓ ● StringBuffer
○ char[]

20. An e-commerce application caches products using product IDs as String keys.

1 / 1 point

```
String id1 = new String("P101");

String id2 = new String("P101");

if(id1 == id2){

    System.out.println("Cache Hit");

}else{

    System.out.println("Cache Miss");

}
```

What will be printed?

Your Answer: ✓ Correct

○ Cache Hit
✓ ● Cache Miss
○ Compilation Error
○ Depends on JVM

21.

```
String s = "Java" + "Backend";
```

1 / 1 point

How many String objects are created at runtime?

Your Answer: ✓ Correct

○ 0
✓ ● 1
○ 2
○ 3

22.

```
public class Utility {

    private Utility()

  {

    }

}
```

1 / 1 point

Why is the constructor made private?

Your Answer: ✓ Correct

○ To improve performance.
✓ ● To prevent object creation because the class contains only utility/static methods.
○ To support inheritance.
○ To reduce memory usage.

23. Output ?

1 / 1 point

```
String s1 = "Java";

String s2 = new String("Java");

String s3 = s2.intern();

System.out.println(s1 == s2);

System.out.println(s1 == s3);

System.out.println(s2 == s3);
```

Your Answer: ✓ Correct

○ true, true, true
✓ ● false, true, false
○ false, false, true
○ true, false, false

24. You are working on a Java-based Order Management System.

1 / 1 point

A developer creates the following class:

```
public class Order {

    private String orderId;

    public Order(String orderId)

  {

        this.orderId = orderId;

    }

}
```

Later, another developer writes:

```
Order o1 = new Order("ORD101");

Order o2 = new Order("ORD101");

if (o1.equals(o2)) {

    System.out.println("Duplicate Order");

} else {

    System.out.println("New Order");

}
```

During testing, the application prints: **New Order**

However, the business requirement is that two orders with the same orderId should be considered equal.

What is the best solution?

Your Answer: ✓ Correct

○ Compare o1 == o2
○ Override only hashCode().
✓ ● Override both equals() and hashCode() based on orderId.
○ Make orderId static.

25.

```
String s1 = "Ja" + "va";

String s2 = "Java";

System.out.println(s1 == s2);
```

1 / 1 point

Your Answer: ✓ Correct

✓ ● true
○ false
○ Compilation error
○ Runtime Error

26.

```
String a = "Java";

String b = "Ja";

String c = b + "va";

System.out.println(a == c);

System.out.println(a == c.intern());
```

1 / 1 point

Your Answer: ✓ Correct

○ true, true
✓ ● false, true
○ false, false
○ true, false

27.

```
String s1 = new String("Spring");

String s2 = s1.intern();

System.out.println(s1 == s2);

System.out.println(s2 == "Spring");
```

-0.25 / 1 point

Your Answer: ✗ Incorrect

○ true, true
✗ ● false, false
✓ ○ false, true
○ true, false

28.

```
final String x = "Ja";

String s1 = x + "va";

String s2 = "Java";

System.out.println(s1 == s2);
```

-0.25 / 1 point

Your Answer: ✗ Incorrect

✓ ○ true
○ false
✗ ● Compilation error
○ Depends on garbage collection

29. Which approach is generally best for repeated string concatenation inside a loop?

1 / 1 point

Your Answer: ✓ Correct

○ Use result.intern() on every iteration.
○ Use new String(result) on every iteration.
○ Use final String result.
✓ ● Use StringBuilder and append each value.

30.

```
String s = new String("Ja") + new String("va");

s.intern();

String s1 = "Java";

System.out.println(s == s1);
```

-0.25 / 1 point

Your Answer: ✗ Incorrect

✓ ○ true
✗ ● false
○ Compilation error
○ Runtime exception

31.

```
public class Test {

    public static void main(String[] args) {

        String s1 = "Java";

        String s2 = new String("Java");

        s2.intern();

        System.out.println(s1 == s2);

    }

}
```

1 / 1 point

Your Answer: ✓ Correct

○ true
✓ ● false
○ Compilation error
○ Runtime exception

Logout