

Electric motors data analysis

Group 8:
Viktor Snesarevskii
Edoardo Belli
Guendalina Biava
Ozrenka Dragić
Madina Kalenova


March-April 2018



Dataset

- ▶ Measurements of torque and current from electric motors
- ▶ Time-series data with frequency 20KHz (downsampled by a factor $M=100$ for real use cases/ease of computation)
- ▶ Data taken from 5 distinct motors in AC and DC modes
- ▶ Each data sample is one recorded operation
- ▶ Operations are recorded while the motor is working properly, then a fault is induced and the same operations are recorded again
- ▶ 1066 AC samples, 924 DC samples (focusing on the DC for now)

The Dataset



Exploratory Analysis: First Approach


- ▶ Feature Extraction

Choose a set of features and check if they are statistically significant for the underlying problem —> to be used later in classification


- ▶ Our set of features is:

Mean, Standard Deviation, Mode, Median


Scatterplot — Currents, Binary




Scatterplot — Torques, Binary



Scatterplot — Currents, Multiclass




Scatterplot — Torques, Multiclass




Exploratory Analysis: Second Approach

- ▶ Principal Component Analysis (time-series data, $p=1524$)
Identify the measurement times where we have maximum variability —>
to be used later for classification/prediction

Principal Component Analysis: Currents, $p=1524$, $N=924$



Principal Component Analysis: Torques, $p=1524$, $N=924$



Final Goals

ABB is interested in three main applications:

- ▶ Motor Classification
Can we identify a motor by a recorded operation?
- ▶ Fault Classification
Can we group motors by their state (working/faulty)?
- ▶ Fault Prediction
Can we predict the state of a motor by measuring current and torque during an operation?

Conclusions

- ▶ First Approach
Further improvements can be made by adding different features and/or transforming the input data, the current feature set doesn't show a clear separation between faulty and working motors.
- ▶ Second Approach
Most of the variability can be captured with a relatively low number of components (10/20 vs $p=1524$).