

max 250g limit) | ALL COMPONENTS DIRECT FIT – ZERO MODIFICATIONS
Solder all rails before battery | Verify in Betaflight Configurator | CG <1mm
MANDATORY before first power | Props OFF for motor direction test

=== SAFETY ===

Connect VTX to VTX | JST-GH 1.25mm: GPS, I2C | XT30: Battery | Heat shrink all
Solder ND, 5V rail | 26AWG: UART signals, ESC PWM | 28AWG: I2C sensors

=== WIRING ===

Power: 1S 11.1V HV (7.6V 75C) XT30 | 30x18x15mm | 4-5min flight | LVC 3.5V/cell
Receiver: UBLOX M10 (optional) | QMC5883L | JST-GH 1.25mm 6-pin | 5Hz default
Antennas: 14mm 1.1g | Dual SX1280 | CRSF@420k | ANT1 vert L ANT2 horiz top
Frame: L 14x14 | 19x19 adapter included | JST-SH 1.0mm 4-pin | 1.8mm F1.6
Motors: 16x16->20x20 | PIT/25/100/200/350mW | SmartAudio | SMA | Foxeer Lollipop
Propellers: 2 3in tri-blade | 5mm hub+1.5mm adapter | 22.8mm tip clearance
ESC: Specter 1804 3500KV | 13.3g | 12x12mm M2 | 1.5mm shaft | 22.68x13.2mm
Servos: 10x20 DShot600 Bidirectional ON | 25x25x4.5mm | 3-6S | 5V/3A BEC
FC: 5 Mini 20x20 ICM42688 DPS310 | 25x25x6.5mm | 4 UARTs | USB-C
Standoffs: 1.8mm carbon | Twin 20x20 tower | 8x M3x25mm alu standoffs | ~45g bare

== BUILD SPECIFICATIONS ==

=== ESC & MOTORS ===

== FLIGHT CONTROLLER ==

== POWER DISTRIBUTION ==

=== MOTOR OUTPUTS (DShot600) ===

=== GPS (optional) ===

=== RECEIVER ===

=== VIDEO SYSTEM ===

